



# RF EXPOSURE REPORT

**REPORT NO.:** SA960213H01

**MODEL NO.:** AWLH6080

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Alpha Networks Inc.

**ADDRESS:** No.8 Li-shing 7th Rd., Science-based Industrial  
Partk, Hsinchu, Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.



# RF Exposure Measurement

## 1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

## 2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A) Limits For Occupational / Control Exposures</b>				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
<b>(B) Limits For General Population / Uncontrolled Exposure</b>				
300-1500	...	...	F/1500	6
1500-100,000	...	...	1.0	30

F = Frequency in MHz



### 3. Friis Formula

Friis transmission formula :  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in  $\text{mW}$

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in  $\text{cm}$

$P_d$  is the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,  
Page 640, Eq. (11-133).

### 4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**



## 6. Test Results

### 6.1 Antenna Gain

There are three antennas provided to this EUT, please refer to the following table:

<b>Antenna 1( With bracket )</b>				
Model No.	Antenna Type	Antenna Connector	Net Gain(dBi)	Note
C664-540089-A	Dipole	SMA Plug Reverse	1.3dB (include Cable loss 2.6dB)	Omni-directional
<b>Antenna 2( With bracket )</b>				
Model No.	Antenna Type	Antenna Connector	Net Gain(dBi)	Note
C037-510810-A	Dipole	SMA Plug Reverse	1.7dB (include Cable loss)	Omni-directional
<b>Antenna 3( Without bracket )</b>				
Model No.	Antenna Type	Antenna Connector	Net Gain(dBi)	Note
C037-510695-A	Dipole	SMA Plug Reverse	1.94dB	Omni-directional

From the above antennas, the worst cases were found in antenna 3.

### 6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

#### For Part 802.11b:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	54.954	0.017	1.0
6	2437	89.125	0.028	1.0
11	2462	57.544	0.018	1.0

#### For Part 802.11g:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	64.565	0.020	1.0
6	2437	95.499	0.030	1.0
11	2462	57.544	0.018	1.0

**DRAFT 802.11n (20MHz) OFDM modulation:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2412	86.584	0.027	1.0
6	2437	184.624	0.057	1.0
11	2462	63.397	0.020	1.0

**DRAFT 802.11n (20MHz) OFDM modulation:**

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )
1	2422	36.481	0.011	1.0
4	2437	112.277	0.035	1.0
7	2452	31.337	0.010	1.0