

FCC TEST REPORT

REPORT NO.: RF130124E04

MODEL NO.: VGP-WAR100

FCC ID: RRK-VGPWAR100

RECEIVED: Jan. 24, 2013

TESTED: Feb. 04 to 06, 2013

ISSUED: Mar. 05, 2013

APPLICANT: Alpha Networks Inc.

ADDRESS: No.8 Li-shing 7th Rd., Science-based Industrial Park,
Hsinchu, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by TAF
or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Table of Contents

RELEASE CONTROL RECORD.....	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT.....	8
3.2 DESCRIPTION OF TEST MODES.....	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4 DESCRIPTION OF SUPPORT UNITS.....	15
3.5 CONFIGURATION OF SYSTEM UNDER TEST	16
4. TEST TYPES AND RESULTS.....	17
4.1 CONDUCTED EMISSION MEASUREMENT	17
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	17
4.1.2 TEST INSTRUMENTS	17
4.1.3 TEST PROCEDURES.....	18
4.1.4 DEVIATION FROM TEST STANDARD	18
4.1.5 TEST SETUP	19
4.1.6 EUT OPERATING CONDITIONS.....	19
4.1.7 TEST RESULTS.....	20
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	22
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT ...	22
4.2.2 TEST INSTRUMENTS	23
4.2.3 TEST PROCEDURES.....	25
4.2.4 DEVIATION FROM TEST STANDARD	25
4.2.5 TEST SETUP	26
4.2.6 EUT OPERATING CONDITIONS.....	26
4.2.7 TEST RESULTS.....	27
4.3 6dB BANDWIDTH MEASUREMENT	40
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	40
4.3.2 TEST INSTRUMENTS	40
4.3.3 TEST PROCEDURE	40
4.3.4 DEVIATION FROM TEST STANDARD	40
4.3.5 TEST SETUP	40
4.3.6 EUT OPERATING CONDITIONS.....	40
4.3.7 TEST RESULTS.....	41
4.4 CONDUCTED OUTPUT POWER MEASUREMENT	42



A D T

4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	42
4.4.2	INSTRUMENTS	42
4.4.3	TEST PROCEDURES	42
4.4.4	DEVIATION FROM TEST STANDARD	42
4.4.5	TEST SETUP	42
4.4.6	EUT OPERATING CONDITIONS	42
4.4.7	TEST RESULTS	43
4.5	POWER SPECTRAL DENSITY MEASUREMENT	44
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	44
4.5.2	TEST INSTRUMENTS	44
4.5.3	TEST PROCEDURE	44
4.5.4	DEVIATION FROM TEST STANDARD	44
4.5.5	TEST SETUP	44
4.5.6	EUT OPERATING CONDITION	44
4.5.7	TEST RESULTS	45
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	46
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	46
4.6.2	TEST INSTRUMENTS	46
4.6.3	TEST PROCEDURE	46
4.6.4	DEVIATION FROM TEST STANDARD	47
4.6.5	TEST SETUP	47
4.6.6	EUT OPERATING CONDITION	47
4.6.7	TEST RESULTS	47
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	52
6.	INFORMATION ON THE TESTING LABORATORIES	53
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	54



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130124E04	Original release	Mar. 05, 2013



A D T

1. CERTIFICATION

PRODUCT: Wireless Router
BRAND NAME: Sony
MODEL NO.: VGP-WAR100
TEST SAMPLE: R&D SAMPLE
APPLICANT: Alpha Networks Inc.
TESTED: Feb. 04 to 06, 2013
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (Model: VGP-WAR100) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Mar. 05, 2013
(Elsie Hsu, Specialist)

APPROVED BY :  , **DATE:** Mar. 05, 2013
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -13.53dB at 0.16562MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.6dB at 2390.00MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 dB
Radiated emissions (30MHz-1GHz)	5.63 dB
Radiated emissions (1GHz -6GHz)	3.54 dB
Radiated emissions (6GHz -18GHz)	4.08 dB
Radiated emissions (18GHz -40GHz)	4.11 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Router
MODEL NO.	VGP-WAR100
POWER SUPPLY	DC 5V from adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: Up to 11Mbps 802.11g: Up to 54Mbps 802.11n: Up to 150Mbps
OPERATING FREQUENCY	2.412 ~ 2.462GHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
MAXIMUM OUTPUT POWER	802.11b: 239.883mW 802.11g: 251.189mW 802.11n (HT20): 245.471mW 802.11n (HT40): 218.776mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

1. The antenna provided to the EUT, please refer to the following table:

Brand	Model	Antenna Type	Connector Type	Gain(dBi)
HL Technology	260-27030	PIFA	NA	1.69

2. The EUT incorporates a SISO function without beam forming.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n (HT20)	1TX/1RX
802.11n (HT40)	1TX/1RX

3. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.
4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ³ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE 1: “-” means no effect.

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	25deg. C, 67%RH	120Vac, 60Hz	Timmy Hu
RE<1G	23deg. C, 68%RH	120Vac, 60Hz	Amos Chuang
RE ³ 1G	24deg. C, 65%RH	120Vac, 60Hz	Amos Chuang
APCM	25deg. C, 60%RH	120Vac, 60Hz	James Chan
OB	25deg. C, 60%RH	120Vac, 60Hz	James Chan

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	Adapter	SONY	VGP-AC10V10	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP cable (10m)
2	AC input cable (0.8m) / DC output cable (1.9m)

NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100287	Feb. 29, 2012	Feb. 28, 2013
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK 8127	8127-523	Sep. 19, 2012	Sep. 20, 2013
Line-Impedance Stabilization Network (for Peripheral) ROHDE & SCHWARZ	ESH3-Z5	848773/004	Oct. 29, 2012	Oct. 28, 2013
RF Cable (JYEBAO)	5DFB	COACAB-002	Aug. 05, 2012	Aug. 04, 2013
50 ohms Terminator	50	3	Oct. 23, 2012	Oct. 22, 2013
Software ADT	BV ADT_Cond_V7.3.7 .3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. Tested Date: Feb. 05, 2013

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

NOTE: The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of EUT.
2. The communication partner run test program “MP TEST.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.10	43.20	41.55	43.30	41.65	65.18	55.18	-21.88	-13.53
2	0.20859	0.11	32.21	18.16	32.32	18.27	63.26	53.26	-30.94	-34.99
3	0.98594	0.18	23.01	20.81	23.19	20.99	56.00	46.00	-32.81	-25.01
4	2.39453	0.25	23.73	17.50	23.98	17.75	56.00	46.00	-32.02	-28.25
5	15.25000	0.79	26.23	24.03	27.02	24.82	60.00	50.00	-32.98	-25.18
6	23.12891	1.12	32.76	29.89	33.88	31.01	60.00	50.00	-26.12	-18.99

REMARKS:

- Q.P. and AV. are abbreviations of quasi-peak and average individually.
- The emission levels of other frequencies were very low against the limit.
- Margin value = Emission level - Limit value
- Correction factor = Insertion loss + Cable loss
- Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.15	43.14	41.47	43.29	41.62	65.38	55.38	-22.09	-13.76
2	0.19687	0.15	33.85	25.94	34.00	26.09	63.74	53.74	-29.74	-27.65
3	0.27891	0.17	25.71	13.72	25.88	13.89	60.85	50.85	-34.97	-36.96
4	0.98594	0.22	23.07	20.91	23.29	21.13	56.00	46.00	-32.71	-24.87
5	2.39063	0.29	22.72	17.13	23.01	17.42	56.00	46.00	-32.99	-28.58
6	23.12891	0.86	32.72	29.79	33.58	30.65	60.00	50.00	-26.42	-19.35

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

Below 1GHz test

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	July 09, 2012	July 08, 2013
Pre-Selector Agilent	N9039A	MY46520311	July 09, 2012	July 08, 2013
Signal Generator Agilent	N5181A	MY49060517	July 09, 2012	July 08, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02578	June 26, 2012	June 25, 2013
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Apr. 09, 2012	Apr. 08, 2013
Horn_Antenna AISI	AIH.8018	0000320091110	Nov. 19, 2012	Nov. 18, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 25, 2012	Dec. 24, 2013
RF Cable	NA	CHGCAB_001	Oct. 06, 2012	Oct. 05, 2013
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Tested Date: Feb. 04, 2013

**A D T****Above 1GHz test**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
Pre-Selector Agilent	N9039A	MY46520310	Sep. 03, 2012	Sep. 02, 2013
Signal Generator Agilent	N5181A	MY49060347	July 24, 2012	July 23, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02465	Feb. 27, 2012	Feb. 26, 2013
SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Apr. 06, 2012	Apr. 05, 2013
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 22, 2012	Nov. 21, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
RF Cable	NA	CHHCAB_001	Oct. 07, 2012	Oct. 06, 2013
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: Feb. 04, 2013

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

1. Place the EUT on testing table.
2. The communication partner run test program “MP TEST.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	106.74	31.7 QP	43.5	-11.8	1.50 H	94	20.88	10.79
2	143.33	32.9 QP	43.5	-10.6	1.50 H	280	18.60	14.29
3	250.03	33.6 QP	46.0	-12.4	1.50 H	360	20.24	13.35
4	314.81	37.2 QP	46.0	-8.8	1.00 H	70	21.53	15.67
5	500.02	34.7 QP	46.0	-11.3	1.50 H	50	14.27	20.39
6	944.58	31.0 QP	46.0	-15.0	1.50 H	214	3.11	27.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	39.71	36.3 QP	40.0	-3.7	1.00 V	238	22.49	13.80
2	50.49	33.7 QP	40.0	-6.3	1.00 V	177	19.67	14.07
3	143.33	31.9 QP	43.5	-11.6	1.00 V	192	17.63	14.29
4	310.19	36.5 QP	46.0	-9.5	1.00 V	151	20.95	15.55
5	500.02	32.1 QP	46.0	-13.9	1.00 V	180	11.72	20.39
6	944.46	31.1 QP	46.0	-14.9	1.00 V	0	3.22	27.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.5 PK	74.0	-12.5	1.12 H	167	29.52	31.98
2	2390.00	51.7 AV	54.0	-2.3	1.12 H	167	19.72	31.98
3	*2412.00	106.5 PK			1.12 H	13	74.45	32.05
4	*2412.00	104.0 AV			1.12 H	13	71.95	32.05
5	2500.00	58.1 PK	74.0	-15.9	1.12 H	167	25.82	32.28
6	2500.00	47.7 AV	54.0	-6.3	1.12 H	167	15.42	32.28
7	4824.00	50.1 PK	74.0	-23.9	1.44 H	189	10.52	39.58
8	4824.00	41.1 AV	54.0	-12.9	1.44 H	189	1.52	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.2 PK	74.0	-13.8	1.00 V	268	28.22	31.98
2	2390.00	47.0 AV	54.0	-7.0	1.00 V	268	15.02	31.98
3	*2412.00	100.7 PK			1.00 V	68	68.65	32.05
4	*2412.00	97.1 AV			1.00 V	68	65.05	32.05
5	2500.00	58.6 PK	74.0	-15.4	1.10 V	171	26.32	32.28
6	2500.00	48.0 AV	54.0	-6.0	1.10 V	171	15.72	32.28
7	4824.00	48.6 PK	74.0	-25.4	1.00 V	329	9.02	39.58
8	4824.00	39.6 AV	54.0	-14.4	1.00 V	329	0.02	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2356.28	58.8 PK	74.0	-15.2	1.14 H	14	26.95	31.85
2	2356.28	47.6 AV	54.0	-6.4	1.14 H	14	15.75	31.85
3	2390.00	56.7 PK	74.0	-17.3	1.14 H	165	24.72	31.98
4	2390.00	45.7 AV	54.0	-8.3	1.14 H	165	13.72	31.98
5	*2437.00	107.3 PK			1.11 H	14	75.18	32.12
6	*2437.00	104.7 AV			1.11 H	14	72.58	32.12
7	2483.50	60.4 PK	74.0	-13.6	1.07 H	170	28.16	32.24
8	2483.50	46.6 AV	54.0	-7.4	1.07 H	170	14.36	32.24
9	2500.00	60.8 PK	74.0	-13.2	1.07 H	169	28.52	32.28
10	2500.00	49.4 AV	54.0	-4.6	1.07 H	169	17.12	32.28
11	4874.00	52.3 PK	74.0	-21.7	1.49 H	214	12.60	39.70
12	4874.00	47.4 AV	54.0	-6.6	1.49 H	214	7.70	39.70
13	7311.00	63.6 PK	74.0	-10.4	1.02 H	314	16.01	47.59
14	7311.00	50.5 AV	54.0	-3.5	1.02 H	314	2.91	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2356.28	57.7 PK	74.0	-16.3	1.00 V	285	25.85	31.85
2	2356.28	44.5 AV	54.0	-9.5	1.00 V	285	12.65	31.85
3	2390.00	58.2 PK	74.0	-15.8	1.00 V	295	26.22	31.98
4	2390.00	44.6 AV	54.0	-9.4	1.00 V	295	12.62	31.98
5	*2437.00	100.1 PK			1.00 V	295	67.98	32.12
6	*2437.00	97.5 AV			1.00 V	295	65.38	32.12
7	2483.50	58.1 PK	74.0	-15.9	1.00 V	295	25.86	32.24
8	2483.50	44.7 AV	54.0	-9.3	1.00 V	295	12.46	32.24
9	2500.00	58.4 PK	74.0	-15.6	1.00 V	301	26.12	32.28
10	2500.00	44.9 AV	54.0	-9.1	1.00 V	301	12.62	32.28
11	4874.00	48.6 PK	74.0	-25.4	1.04 V	338	8.90	39.70
12	4874.00	39.4 AV	54.0	-14.6	1.04 V	338	-0.30	39.70
13	7311.00	63.3 PK	74.0	-10.7	1.00 V	330	15.71	47.59
14	7311.00	50.3 AV	54.0	-3.7	1.00 V	330	2.71	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.0 PK			1.09 H	360	72.82	32.18
2	*2462.00	102.5 AV			1.09 H	360	70.32	32.18
3	2483.50	62.6 PK	74.0	-11.4	1.23 H	279	30.36	32.24
4	2483.50	49.4 AV	54.0	-4.6	1.23 H	279	17.16	32.24
5	4924.00	52.1 PK	74.0	-21.9	1.48 H	221	12.26	39.84
6	4924.00	47.4 AV	54.0	-6.6	1.48 H	221	7.56	39.84
7	7386.00	63.7 PK	74.0	-10.3	1.00 H	345	16.18	47.52
8	7386.00	50.6 AV	54.0	-3.4	1.00 H	345	3.08	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.2 PK			1.30 V	19	70.02	32.18
2	*2462.00	99.8 AV			1.30 V	19	67.62	32.18
3	2483.50	62.8 PK	74.0	-11.2	1.30 V	19	30.56	32.24
4	2483.50	46.8 AV	54.0	-7.2	1.30 V	19	14.56	32.24
5	4924.00	48.5 PK	74.0	-25.5	1.00 V	327	8.66	39.84
6	4924.00	39.3 AV	54.0	-14.7	1.00 V	327	-0.54	39.84
7	7386.00	63.6 PK	74.0	-10.4	1.00 V	337	16.08	47.52
8	7386.00	50.6 AV	54.0	-3.4	1.00 V	337	3.08	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.5 PK	74.0	-3.5	1.13 H	166	38.52	31.98
2	2390.00	51.8 AV	54.0	-2.2	1.13 H	166	19.82	31.98
3	*2412.00	107.0 PK			1.69 H	166	74.95	32.05
4	*2412.00	97.6 AV			1.69 H	166	65.55	32.05
5	2500.00	61.7 PK	74.0	-12.3	1.07 H	170	29.42	32.28
6	2500.00	50.2 AV	54.0	-3.8	1.07 H	170	17.92	32.28
7	4824.00	48.3 PK	74.0	-25.7	1.06 H	350	8.72	39.58
8	4824.00	39.1 AV	54.0	-14.9	1.06 H	350	-0.48	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.2 PK	74.0	-3.8	1.30 V	20	38.22	31.98
2	2390.00	50.4 AV	54.0	-3.6	1.30 V	20	18.42	31.98
3	*2412.00	105.2 PK			1.30 V	20	73.15	32.05
4	*2412.00	95.9 AV			1.30 V	20	63.85	32.05
5	2500.00	58.5 PK	74.0	-15.5	1.30 V	20	26.22	32.28
6	2500.00	46.2 AV	54.0	-7.8	1.30 V	20	13.92	32.28
7	4824.00	49.2 PK	74.0	-24.8	1.03 V	351	9.62	39.58
8	4824.00	39.7 AV	54.0	-14.3	1.03 V	351	0.12	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.3 PK	74.0	-8.7	1.13 H	165	33.32	31.98
2	2390.00	53.4 AV	54.0	-0.6	1.13 H	165	21.42	31.98
3	*2437.00	110.7 PK			1.12 H	169	78.58	32.12
4	*2437.00	101.4 AV			1.12 H	169	69.28	32.12
5	2483.50	68.2 PK	74.0	-5.8	1.08 H	168	35.96	32.24
6	2483.50	53.0 AV	54.0	-1.0	1.08 H	168	20.76	32.24
7	2500.00	66.5 PK	74.0	-7.5	1.08 H	169	34.22	32.28
8	2500.00	52.1 AV	54.0	-1.9	1.08 H	169	19.82	32.28
9	4874.00	48.9 PK	74.0	-25.1	1.02 H	325	9.20	39.70
10	4874.00	39.8 AV	54.0	-14.2	1.02 H	325	0.10	39.70
11	7311.00	63.1 PK	74.0	-10.9	1.00 H	325	15.51	47.59
12	7311.00	49.9 AV	54.0	-4.1	1.00 H	325	2.31	47.59

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.4 PK	74.0	-11.6	1.28 V	19	30.42	31.98
2	2390.00	47.3 AV	54.0	-6.7	1.28 V	19	15.32	31.98
3	*2437.00	106.4 PK			1.28 V	19	74.28	32.12
4	*2437.00	97.1 AV			1.28 V	19	64.98	32.12
5	2483.50	64.9 PK	74.0	-9.1	1.28 V	19	32.66	32.24
6	2483.50	48.4 AV	54.0	-5.6	1.28 V	19	16.16	32.24
7	2500.00	62.3 PK	74.0	-11.7	1.28 V	19	30.02	32.28
8	2500.00	47.8 AV	54.0	-6.2	1.28 V	19	15.52	32.28
9	4874.00	51.7 PK	74.0	-22.3	1.00 V	355	12.00	39.70
10	4874.00	39.1 AV	54.0	-14.9	1.00 V	355	-0.60	39.70
11	7311.00	63.3 PK	74.0	-10.7	1.00 V	330	15.71	47.59
12	7311.00	50.3 AV	54.0	-3.7	1.00 V	330	2.71	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.8 PK			1.11 H	169	73.62	32.18
2	*2462.00	96.6 AV			1.11 H	169	64.42	32.18
3	2483.50	73.2 PK	74.0	-0.8	1.07 H	168	40.96	32.24
4	2483.50	49.5 AV	54.0	-4.5	1.07 H	168	17.26	32.24
5	2500.00	69.0 PK	74.0	-5.0	1.09 H	171	36.72	32.28
6	2500.00	51.1 AV	54.0	-2.9	1.09 H	171	18.82	32.28
7	4924.00	48.8 PK	74.0	-25.2	1.07 H	342	8.96	39.84
8	4924.00	39.6 AV	54.0	-14.4	1.07 H	342	-0.24	39.84
9	7386.00	63.9 PK	74.0	-10.1	1.03 H	339	16.38	47.52
10	7386.00	50.7 AV	54.0	-3.3	1.03 H	339	3.18	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.5 PK			1.08 V	337	72.32	32.18
2	*2462.00	93.2 AV			1.08 V	337	61.02	32.18
3	2483.50	72.6 PK	74.0	-1.4	1.08 V	337	40.36	32.24
4	2483.50	48.6 AV	54.0	-5.4	1.08 V	337	16.36	32.24
5	2500.00	66.5 PK	74.0	-7.5	1.08 V	337	34.22	32.28
6	2500.00	48.8 AV	54.0	-5.2	1.08 V	337	16.52	32.28
7	4924.00	48.8 PK	74.0	-25.2	1.05 V	322	8.96	39.84
8	4924.00	39.5 AV	54.0	-14.5	1.05 V	322	-0.34	39.84
9	7386.00	63.5 PK	74.0	-10.5	1.01 V	328	15.98	47.52
10	7386.00	50.5 AV	54.0	-3.5	1.01 V	328	2.98	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.0 PK	74.0	-2.0	1.13 H	165	40.02	31.98
2	2390.00	51.0 AV	54.0	-3.0	1.13 H	165	19.02	31.98
3	*2412.00	106.3 PK			1.69 H	166	74.25	32.05
4	*2412.00	97.3 AV			1.69 H	166	65.25	32.05
5	2500.00	62.0 PK	74.0	-12.0	1.07 H	169	29.72	32.28
6	2500.00	50.4 AV	54.0	-3.6	1.07 H	169	18.12	32.28
7	4824.00	48.9 PK	74.0	-25.1	1.00 H	341	9.32	39.58
8	4824.00	39.4 AV	54.0	-14.6	1.00 H	341	-0.18	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.8 PK	74.0	-2.2	1.07 V	338	39.82	31.98
2	2390.00	50.6 AV	54.0	-3.4	1.07 V	338	18.62	31.98
3	*2412.00	106.9 PK			1.07 V	338	74.85	32.05
4	*2412.00	94.5 AV			1.07 V	338	62.45	32.05
5	2500.00	60.0 PK	74.0	-14.0	1.07 V	338	27.72	32.28
6	2500.00	48.2 AV	54.0	-5.8	1.07 V	338	15.92	32.28
7	4824.00	48.4 PK	74.0	-25.6	1.05 V	345	8.82	39.58
8	4824.00	39.0 AV	54.0	-15.0	1.05 V	345	-0.58	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.3 PK	74.0	-11.7	1.12 H	165	30.32	31.98
2	2390.00	47.6 AV	54.0	-6.4	1.12 H	165	15.62	31.98
3	*2437.00	110.5 PK			1.12 H	170	78.38	32.12
4	*2437.00	101.2 AV			1.12 H	170	69.08	32.12
5	2483.50	68.0 PK	74.0	-6.0	1.07 H	169	35.76	32.24
6	2483.50	52.8 AV	54.0	-1.2	1.07 H	169	20.56	32.24
7	2500.00	68.0 PK	74.0	-6.0	1.08 H	168	35.72	32.28
8	2500.00	52.4 AV	54.0	-1.6	1.08 H	168	20.12	32.28
9	4874.00	48.7 PK	74.0	-25.3	1.07 H	326	9.00	39.70
10	4874.00	39.5 AV	54.0	-14.5	1.07 H	326	-0.20	39.70
11	7311.00	63.3 PK	74.0	-10.7	1.00 H	336	15.71	47.59
12	7311.00	50.2 AV	54.0	-3.8	1.00 H	336	2.61	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.1 PK	74.0	-7.9	1.09 V	338	34.12	31.98
2	2390.00	48.2 AV	54.0	-5.8	1.09 V	338	16.22	31.98
3	*2437.00	108.4 PK			1.09 V	338	76.28	32.12
4	*2437.00	96.0 AV			1.09 V	338	63.88	32.12
5	2483.50	68.4 PK	74.0	-5.6	1.09 V	338	36.16	32.24
6	2483.50	50.2 AV	54.0	-3.8	1.09 V	338	17.96	32.24
7	2500.00	64.7 PK	74.0	-9.3	1.09 V	338	32.42	32.28
8	2500.00	49.4 AV	54.0	-4.6	1.09 V	338	17.12	32.28
9	4874.00	48.9 PK	74.0	-25.1	1.07 V	351	9.20	39.70
10	4874.00	39.6 AV	54.0	-14.4	1.07 V	351	-0.10	39.70
11	7311.00	63.2 PK	74.0	-10.8	1.00 V	324	15.61	47.59
12	7311.00	49.9 AV	54.0	-4.1	1.00 V	324	2.31	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.5 PK			1.10 H	169	74.32	32.18
2	*2462.00	96.9 AV			1.10 H	169	64.72	32.18
3	2483.50	72.0 PK	74.0	-2.0	1.09 H	169	39.76	32.24
4	2483.50	48.7 AV	54.0	-5.3	1.09 H	169	16.46	32.24
5	2500.00	69.0 PK	74.0	-5.0	1.09 H	171	36.72	32.28
6	2500.00	50.9 AV	54.0	-3.1	1.09 H	171	18.62	32.28
7	4924.00	48.6 PK	74.0	-25.4	1.07 H	335	8.76	39.84
8	4924.00	39.5 AV	54.0	-14.5	1.07 H	335	-0.34	39.84
9	7386.00	63.9 PK	74.0	-10.1	1.00 H	322	16.38	47.52
10	7386.00	50.8 AV	54.0	-3.2	1.00 H	322	3.28	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.3 PK			1.07 V	338	72.12	32.18
2	*2462.00	93.3 AV			1.07 V	338	61.12	32.18
3	2483.50	71.5 PK	74.0	-2.5	1.07 V	338	39.26	32.24
4	2483.50	47.8 AV	54.0	-6.2	1.07 V	338	15.56	32.24
5	2500.00	66.0 PK	74.0	-8.0	1.07 V	338	33.72	32.28
6	2500.00	48.6 AV	54.0	-5.4	1.07 V	338	16.32	32.28
7	4924.00	48.6 PK	74.0	-25.4	1.05 V	350	8.76	39.84
8	4924.00	39.4 AV	54.0	-14.6	1.05 V	350	-0.44	39.84
9	7386.00	62.9 PK	74.0	-11.1	1.00 V	335	15.38	47.52
10	7386.00	50.1 AV	54.0	-3.9	1.00 V	335	2.58	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.4 PK	74.0	-1.6	1.14 H	165	40.42	31.98
2	2390.00	52.8 AV	54.0	-1.2	1.14 H	165	20.82	31.98
3	*2422.00	104.5 PK			1.13 H	166	72.42	32.08
4	*2422.00	94.5 AV			1.13 H	166	62.42	32.08
5	2500.00	65.9 PK	74.0	-8.1	1.08 H	170	33.62	32.28
6	2500.00	51.4 AV	54.0	-2.6	1.08 H	170	19.12	32.28
7	4844.00	48.7 PK	74.0	-25.3	1.00 H	322	9.07	39.63
8	4844.00	39.6 AV	54.0	-14.4	1.00 H	322	-0.03	39.63
9	7266.00	62.8 PK	74.0	-11.2	1.00 H	316	15.20	47.60
10	7266.00	49.9 AV	54.0	-4.1	1.00 H	316	2.30	47.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.6 PK	74.0	-2.4	1.07 V	337	39.62	31.98
2	2390.00	51.9 AV	54.0	-2.1	1.07 V	337	19.92	31.98
3	*2422.00	103.8 PK			1.07 V	337	71.72	32.08
4	*2422.00	90.8 AV			1.07 V	337	58.72	32.08
5	2500.00	62.7 PK	74.0	-11.3	1.07 V	337	30.42	32.28
6	2500.00	49.0 AV	54.0	-5.0	1.07 V	337	16.72	32.28
7	4844.00	48.5 PK	74.0	-25.5	1.00 V	333	8.87	39.63
8	4844.00	39.4 AV	54.0	-14.6	1.00 V	333	-0.23	39.63
9	7266.00	63.5 PK	74.0	-10.5	1.01 V	344	15.90	47.60
10	7266.00	50.4 AV	54.0	-3.6	1.01 V	344	2.80	47.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.8 PK			1.11 H	167	71.68	32.12
2	*2437.00	94.1 AV			1.11 H	167	61.98	32.12
3	2483.50	69.9 PK	74.0	-4.1	1.07 H	169	37.66	32.24
4	2483.50	52.8 AV	54.0	-1.2	1.07 H	169	20.56	32.24
5	2500.00	68.4 PK	74.0	-5.6	1.09 H	169	36.12	32.28
6	2500.00	51.5 AV	54.0	-2.5	1.09 H	169	19.22	32.28
7	4874.00	48.8 PK	74.0	-25.2	1.05 H	337	9.10	39.70
8	4874.00	39.7 AV	54.0	-14.3	1.05 H	337	0.00	39.70
9	7311.00	63.4 PK	74.0	-10.6	1.00 H	334	15.81	47.59
10	7311.00	50.5 AV	54.0	-3.5	1.00 H	334	2.91	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.4 PK			1.07 V	338	71.28	32.12
2	*2437.00	90.7 AV			1.07 V	338	58.58	32.12
3	2483.50	68.2 PK	74.0	-5.8	1.07 V	338	35.96	32.24
4	2483.50	50.4 AV	54.0	-3.6	1.07 V	338	18.16	32.24
5	2500.00	69.0 PK	74.0	-5.0	1.07 V	338	36.72	32.28
6	2500.00	50.4 AV	54.0	-3.6	1.07 V	338	18.12	32.28
7	4874.00	48.5 PK	74.0	-25.5	1.07 V	339	8.80	39.70
8	4874.00	39.5 AV	54.0	-14.5	1.07 V	339	-0.20	39.70
9	7311.00	63.0 PK	74.0	-11.0	1.00 V	328	15.41	47.59
10	7311.00	50.0 AV	54.0	-4.0	1.00 V	328	2.41	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.9 PK			1.10 H	169	70.74	32.16
2	*2452.00	93.1 AV			1.10 H	169	60.94	32.16
3	2483.50	67.5 PK	74.0	-6.5	1.07 H	168	35.26	32.24
4	2483.50	52.6 AV	54.0	-1.4	1.07 H	168	20.36	32.24
5	4904.00	48.2 PK	74.0	-25.8	1.08 H	350	8.43	39.77
6	4904.00	39.2 AV	54.0	-14.8	1.08 H	350	-0.57	39.77
7	7356.00	63.5 PK	74.0	-10.5	1.02 H	314	15.95	47.55
8	7356.00	50.4 AV	54.0	-3.6	1.02 H	314	2.85	47.55
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	101.5 PK			1.07 V	338	69.34	32.16
2	*2452.00	89.1 AV			1.07 V	338	56.98	32.16
3	2483.50	64.2 PK	74.0	-9.8	1.07 V	338	31.96	32.24
4	2483.50	50.2 AV	54.0	-3.8	1.07 V	338	17.96	32.24
5	4904.00	48.2 PK	74.0	-25.8	1.05 V	341	8.43	39.77
6	4904.00	39.2 AV	54.0	-14.8	1.05 V	341	-0.57	39.77
7	7356.00	63.2 PK	74.0	-10.8	1.04 V	327	15.65	47.55
8	7356.00	50.5 AV	54.0	-3.5	1.04 V	327	2.95	47.55

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Nov. 01, 2012	Oct. 31, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Feb. 05, 2013


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	10.14	0.5	PASS
6	2437	9.70	0.5	PASS
11	2462	10.14	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.62	0.5	PASS
6	2437	16.61	0.5	PASS
11	2462	16.62	0.5	PASS

802.11n (HT20)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.88	0.5	PASS
6	2437	17.89	0.5	PASS
11	2462	17.87	0.5	PASS

802.11n (HT40)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.48	0.5	PASS
6	2437	36.49	0.5	PASS
9	2452	36.49	0.5	PASS

4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 10, 2012	May 09, 2013
Power Sensor	MA2411B	0738172	May 10, 2012	May 09, 2013

- Note:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. Tested date : Feb. 05, 2013


4.4.3 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	239.883	23.8	30	PASS
6	2437	208.930	23.2	30	PASS
11	2462	186.209	22.7	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	239.883	23.8	30	PASS
6	2437	251.189	24.0	30	PASS
11	2462	199.526	23.0	30	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	239.883	23.8	30	PASS
6	2437	245.471	23.9	30	PASS
11	2462	177.828	22.5	30	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
3	2422	218.776	23.4	30	PASS
6	2437	208.930	23.2	30	PASS
9	2452	154.882	21.9	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP40	100037	Nov. 01, 2012	Oct. 31, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Feb. 05, 2013


4.5.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-8.52	8	PASS
6	2437	-7.90	8	PASS
11	2462	-7.76	8	PASS

802.11g

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.86	8	PASS
6	2437	-10.26	8	PASS
11	2462	-14.14	8	PASS

802.11n (HT20)

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.69	8	PASS
6	2437	-10.38	8	PASS
11	2462	-14.52	8	PASS

802.11n (HT40)

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-14.13	8	PASS
6	2437	-14.10	8	PASS
9	2452	-14.96	8	PASS

4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP40	100037	Nov. 01, 2012	Oct. 31, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Feb. 05, 2013

4.6.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement





A D T

802.11b:



CH 1



CH 6



CH 11









A D T

802.11g:



CH 1



CH 6



CH 11







A D T

802.11n (HT20):


CH 1



CH 6



CH 11







A D T

802.11n (HT40):


CH 3



CH 6



CH 9



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---