



RF EXPOSURE REPORT

REPORT NO.: SA990203H11

MODEL NO.: WMP-A01

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Alpha Networks Inc.

ADDRESS: No.8 Li-shing 7th Rd., Science-based Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

LAB LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan



A D T

RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in our lab, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B) Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz



3. Friis Formula

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



A D T

6. TEST RESULTS

6.1 Antenna Gain

There are two antennas provided to this EUT, please refer to the following table:

Chain	Manufacture	Model	Gain (dBi)	Cable Loss(dB)	Net Gain (dBi)	Cable Length (cm)	Antenna Type	Connector
Chain (0) Antenna (1)	Grand-Tek	R-SA64G7210180C	7	1) 3 2) 2.4	1) 4 2) 4.6	1) 20 2) 20	Dipole	RP-N plug
Chain (1) Antenna (2)	Grand-Tek	R-SA64G7210380C	7	1) 3.3 2) 3.0	1) 3.7 2) 4	1) 40 2) 40	Dipole	RP-N plug

The EUT was pre-tested with above antennas, the worse case was found in antenna gain <2)4.6dBi> and gain <2)4dBi>.

Note: 11a gain is 7.3 dBi as calculated in EMC report.



A D T

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For 15.247(5GHz):

802.11a: Max Gain=7.3dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
149	5745	729.2	0.779	1.0
157	5785	670.0	0.716	1.0
165	5825	677.7	0.724	1.0

802.11n (20MHz): Max Gain=4.6dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
149	5745	973.5	0.559	1.0
157	5785	883.2	0.507	1.0
165	5825	957.5	0.549	1.0

802.11n (40MHz): Max Gain=4.6dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
151	5755	901.2	0.517	1.0
159	5795	905.0	0.519	1.0



A D T

For 15.407(5GHz):

802.11a: Max Gain=7.3dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
36	5180	21.5	0.023	1.0
40	5200	21.2	0.023	1.0
48	5240	22.3	0.024	1.0

802.11n (20MHz): Max Gain=4.6dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
36	5180	41.2	0.024	1.0
40	5200	40.8	0.023	1.0
48	5240	42.8	0.025	1.0

802.11n (40MHz): Max Gain=4.6dBi

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
38	5190	22.2	0.013	1.0
46	5230	42.9	0.025	1.0