

# Cellphone-Mate, Inc.

## TEST REPORT FOR

### Dual Band Cellphone Signal Booster Model: Dual Force

#### Tested To The Following Standards:

#### FCC Part 24E

Report No.: 95115-9

Date of issue: January 17, 2014



This test report bears the accreditation symbol indicating that the testing performed herein meets the test and reporting requirements of ISO/IEC 17025 under the applicable scope of EMC testing for CKC Laboratories, Inc.

We strive to create long-term, trust based relationships by providing sound, adaptive, customer first testing services. We embrace each of our customers' unique EMC challenges, not as an interruption to set processes, but rather as the reason we are in business.

## TABLE OF CONTENTS

Administrative Information .....	3
Test Report Information .....	3
Report Authorization .....	3
Test Facility Information .....	4
Software Versions .....	4
Site Registration & Accreditation Information .....	4
Summary of Results .....	5
Conditions During Testing .....	5
Equipment Under Test .....	6
Peripheral Devices .....	6
FCC Part 24E .....	7
2.1046 RF Power Output .....	7
2.1047 Modulation Characteristics .....	7
2.1049 Occupied Bandwidth .....	8
2.1051 / Spurious Emissions at Antenna Terminals .....	16
2.1053 / Field Strength of Spurious Radiation .....	19
2.1055 Frequency Stability .....	26
Supplemental Information .....	27
Measurement Uncertainty .....	27
Emissions Test Details .....	27

## ADMINISTRATIVE INFORMATION

### Test Report Information

**REPORT PREPARED FOR:**

Cellphone-Mate, Inc.  
48346 Milmont Ave.  
Fremont, CA 94538

Representative: Hongtao Zhan  
Customer Reference Number: CKC20131113

**REPORT PREPARED BY:**

Dianne Dudley  
CKC Laboratories, Inc.  
5046 Sierra Pines Drive  
Mariposa, CA 95338

Project Number: 95115

**DATE OF EQUIPMENT RECEIPT:**

November 9, 2013

**DATE(S) OF TESTING:**

November 9-December 18, 2013

### Report Authorization

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.



*Steve Behm*  
Director of Quality Assurance & Engineering Services  
CKC Laboratories, Inc.

## Test Facility Information



Our laboratories are configured to effectively test a wide variety of product types. CKC utilizes first class test equipment, anechoic chambers, data acquisition and information services to create accurate, repeatable and affordable test results.

TEST LOCATION(S):  
CKC Laboratories, Inc.  
110 Olinda Place  
Brea, CA 92823

## Software Versions

CKC Laboratories Proprietary Software	Version
EMITest Emissions	5.00.14
Immunity	5.00.07

## Site Registration & Accreditation Information

Location	CB #	TAIWAN	CANADA	FCC	JAPAN
Brea A	US0060	SL2-IN-E-1146R	3082D-1	90473	A-0147

## SUMMARY OF RESULTS

### Standard / Specification: FCC Part 2 / 24E

Test Procedure/Method	Description	Results
2.1046	RF Power Output	NA
2.1047	Modulation Characteristics	NA
2.1049	Occupied Bandwidth	Pass
2.1051 / 24.238	Spurious Emissions at Antenna Terminals	Pass
2.1053 / 24.238	Field Strength of Spurious Radiation	Pass
2.1055	Frequency Stability	NA

NA = Not applicable.

## Conditions During Testing

This list is a summary of the conditions noted for or modifications made to the equipment during testing.

Summary of Conditions
None

## EQUIPMENT UNDER TEST (EUT)

### EQUIPMENT UNDER TEST

#### Dual Band Cellphone Signal Booster

Manuf: Cellphone-Mate, Inc.

Model: Dual Force

Serial: 2

### PERIPHERAL DEVICES

The EUT was tested with the following peripheral device(s):

#### Signal Generator

Manuf: Agilent

Model: E4438C

Serial: MY42082260

#### Power Supply

Manuf: SureCall

Model: GFP451DA-0945-1

Serial: 1211-0000323

## FCC PART 24E

This report contains EMC emissions test results under United States Federal Communications Commission (FCC) 47 CFR 24E requirements for personal communications services authorized in the 1850-1915 and 1930-1995 MHz bands.

### 2.1046 RF Power Output

Not applicable because the power requirements are contained in FCC Part 20.

### 2.1047 Modulation Characteristics

Not applicable because the EUT does not employ modulation characteristics.

## 2.1049 Occupied Bandwidth

### Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 110 North Olinda Place • Brea, CA 92823• 714-993-6112

Customer: **Cellphone-Mate, Inc.**  
 Specification: **Occupied Bandwidth**  
 Work Order #: **95115** Date: 12/18/2013, 01/02/2014  
 Test Type: **Conducted Emissions**  
 Equipment: Dual Band Cellphone Signal Booster Sequence#: 1  
 Manufacturer: Cellphone-Mate, Inc. Tested By: E. Wong, S. Yamamoto  
 Model: Dual Force 110V 60Hz  
 S/N: 2

#### **Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN02869	Spectrum Analyzer	E4440A	2/6/2013	2/6/2015
T2	AN03430	Attenuator	75A-10-12	9/5/2013	9/5/2015
T3	AN02946	Cable	32022-2-2909K-36TC	7/31/2013	7/31/2015

#### **Equipment Under Test (\* = EUT):**

Function	Manufacturer	Model #	S/N
Dual Band Cellphone Signal Booster *	Cellphone-Mate, Inc.	Dual Force	2

#### **Support Devices:**

Function	Manufacturer	Model #	S/N
Power Supply	SureCall	GFP451DA-0945-1	1211-0000323

#### **Test Conditions / Notes:**

The EUT is placed on the test bench. Cellular -800 gain is set at Max gain and PCS-1900 Gain is set at max gain. All dip switches are set to Off position, i.e. toward the 1 2 4 8 16 direction. Evaluation performed at the Outside (Donor) and Inside (Server) antenna port.

CMRS band.

UL: 824-849MHz, 1850-1915MHz

DL: 869-894MHz, 1930-1995MHz

The booster operates in the following frequency band.


UL: 824-849, 1850-1915 MHz

DL: 869-894, 1930-1995 MHz


Test procedure: The test was performed in accordance with section 7.10 of the FCC document: 935210 D03 Wideband Consumer Signal Booster Measurement Guidance DR04-41516 August 7, 2013.

Test environment conditions: 23.9°C, 37% Relative Humidity, 100kPa


### Test Data




UL 1850-1915MHz, CDMA Input




UL 1850-1915MHz, CDMA Output




UL 1850-1915MHz, GSM Input




UL 1850-1915MHz, GSM Output




UL 1850-1915MHz, LTE Input




UL 1850-1915MHz, LTE Output




DL 1930-1995MHz, CDMA Input




DL 1930-1995MHz, CDMA Output




DL 1930-1995MHz, GSM Input



DL 1930-1995MHz, GSM Output




DL 1930-1995MHz, LTE Input



DL 1930-1995MHz, LTE Output

**Test Setup Photos**



## 2.1051 / Spurious Emissions at Antenna Terminals

### Test Data Sheet

Test Location: CKC Laboratories, Inc. • 110 North Olinda Place • Brea, CA 92823• 714-993-6112

Customer: **Cellphone-Mate, Inc.**  
 Specification: **47 CFR §24.238 Spurious Emissions**  
 Work Order #: **94297** Date: 11/9/2013  
 Test Type: **Conducted Emissions** Time: 10:07:44  
 Equipment: **Dual Band Cellphone Signal Booster** Sequence#: 1  
 Manufacturer: Cellphone-Mate, Inc. Tested By: E. Wong  
 Model: Dual Force 110V 60Hz  
 S/N: 2

#### **Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN02869	Spectrum Analyzer	E4440A	2/6/2013	2/6/2015
T2	AN03430	Attenuator	75A-10-12	9/5/2013	9/5/2015
T3	AN02946	Cable	32022-2-2909K-36TC	7/31/2013	7/31/2015

#### **Equipment Under Test (\* = EUT):**

Function	Manufacturer	Model #	S/N
Dual Band Cellphone	Cellphone-Mate, Inc.	Dual Force	2
Signal Booster*			

#### **Support Devices:**

Function	Manufacturer	Model #	S/N
Signal Generator	Agilent	E4438C	MY42082260
Power Supply	SureCall	GFP451DA-0945-1	1211-0000323

#### **Test Conditions / Notes:**

The EUT is placed on the test bench. Cellular -800 gain is set at Max gain and PCS-1900 Gain is set at max gain. All dip switches are set to Off position, i.e. toward the 1 2 4 8 16 direction.

Evaluation performed at the Outside (Donor) and Inside (Server) antenna port.

UL: 1850-1915 MHz

DL: 1930-1995 MHz

TX Freq: UL 1877MHz, DL 1980MHz

Modulation: 4.1 MHz AWGN

Frequency range of measurement = 9 kHz- 20 GHz.

9kHz -150 kHz; RBW=200 Hz, VBW=200 Hz; 150 kHz-30 MHz; RBW=9 kHz, VBW=9 kHz; 30 MHz-1000 MHz; RBW=120 kHz, VBW=120 kHz, 1000 MHz-20000 MHz; RBW=1 MHz, VBW=1 MHz.

Test environment conditions: 23.9°C, 7% Relative Humidity, 100kPa

Ext Attn: 0 dB

<b>Measurement Data:</b>				Reading listed by margin.				Test Lead: Ant Port			
#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	Dist Table	Corr dB $\mu$ V	Spec dB $\mu$ V	Margin dB	Polar Ant	
1	3753.300M	51.0	+0.0	+9.7	+0.8	+0.0	61.5	94.0	-32.5	Ant P	
								UL_1877MHz			
2	3960.000M	38.2	+0.0	+9.8	+1.0	+0.0	49.0	94.0	-45.0	Ant P	
								DL_1980MHz			

### LIMIT LINE FOR SPURIOUS CONDUCTED EMISSION

$$\text{REQUIRED ATTENUATION} = 43 + 10 \log P \text{ dB}$$


$$\text{Limit line (dBuV)} = V_{\text{dBuV}} - \text{Attenuation}$$

$$\begin{aligned} V_{\text{dBuV}} &= 20 \log \frac{V}{1 \times 10^{-6}} \\ &= 20(\log V - \log 1 \times 10^{-6}) \\ &= 20 \log V - 20 \log 1 \times 10^{-6} \\ &= 20 \log V - 20(-6) \\ &= 20 \log V + 120 \end{aligned}$$

$$\begin{aligned} \text{Attenuation} &= 43 + 10 \log P \\ &= 43 + 10 \log \frac{V^2}{R} \\ &= 43 + 10(\log V^2 - \log R) \\ &= 43 + 10(2 \log V - \log R) \\ &= 43 + 20 \log V - 10 \log R \end{aligned}$$

$$\begin{aligned} \text{Limit line} &= V_{\text{dBuV}} - \text{Attenuation} \\ &= 20 \log V + 120 - (43 + 20 \log V - 10 \log R) \\ &= 20 \log V + 120 - 43 - 20 \log V + 10 \log R \\ &= 20 \log V + 120 - 43 - 20 \log V + 10 \log R \\ &= 120 - 43 + 10 \log 50 \quad \text{Note: } R = 50 \Omega \\ &= 120 - 43 + 16.897 \\ &= 94 \text{ dBuV at any power level} \end{aligned}$$

**Test Setup Photos**



## 2.1053 / Field Strength of Spurious Radiation

### Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 110 North Olinda Place • Brea, CA 92823• 714-993-6112

Customer: **Cellphone-Mate, Inc.**  
 Specification: **24.238 Radiated Spurious Emission**  
 Work Order #: **94297** Date: **11/9/2013**  
 Test Type: **Radiated Scan** Time: **14:09:17**  
 Equipment: **Dual Band Cellphone Signal Booster** Sequence#: **2**  
 Manufacturer: Cellphone-Mate, Inc. Tested By: **E. Wong**  
 Model: Dual Force  
 S/N: **2**

#### ***Test Equipment:***

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02869	Spectrum Analyzer	E4440A	2/6/2013	2/6/2015
	AN00314	Loop Antenna	6502	6/29/2012	6/29/2014
	AN01995	Biconilog Antenna	CBL6111C	5/16/2012	5/16/2014
	AN00309	Preamp	8447D	3/29/2012	3/29/2014
	ANP05198	Cable-Amplitude 15 to 45degC (dB)	8268	12/11/2012	12/11/2014
	ANP05050	Cable	RG223/U	1/21/2013	1/21/2015
T1	AN00849	Horn Antenna	3115	4/13/2012	4/13/2014
T2	AN00786	Preamp	83017A	6/20/2012	6/20/2014
T3	ANP05988	Cable	LDF1-50	3/12/2012	3/12/2014
T4	AN02945	Cable	32022-2-2909K-36TC	10/30/2013	10/30/2015
	AN01413	Horn Antenna-ANSI C63.5 (dB/m)	84125-80008	11/9/2012	11/9/2014

#### ***Equipment Under Test (\* = EUT):***

Function	Manufacturer	Model #	S/N
Dual Band Cellphone	Cellphone-Mate, Inc.	Dual Force	2
Signal Booster*			

#### ***Support Devices:***

Function	Manufacturer	Model #	S/N
Signal Generator	Agilent	E4438C	MY42082260
Power Supply	SureCall	GFP451DA-0945-1	1211-0000323
Signal Generator	Agilent	E4433B	US40053164

***Test Conditions / Notes:***

The EUT is placed on the Styrofoam block. Cellular -800 gain is set at Max gain and PCS-1900 Gain is set at max gain. All DIP switches are set to Off position, i.e. towards the 1 2 4 8 16 direction. Evaluation of DL path was performed with signal fed into the Outside (Donor) antenna port while Inside (Server) antenna port terminated with 50 Ohm load. Evaluation of UL path was performed with signal fed into the Inside (Server) antenna port while Outside (Donor) antenna port terminated with 50 Ohm load. Part 22 and Part 24 tested simultaneously. A combiner was used to inject signal in two frequency band into the booster.

CMRS band.

UL: 824-849MHz, 1850-1915MHz

DL: 869-894MHz, 1930-1995MHz

The booster operates in the following frequency band.

UL: 824-849, 1850-1915 MHz

DL: 869-894, 1930-1995 MHz

TX Freq = UL 1877MHz, DL 1980MHz

Modulation: CW

Frequency range of measurement = 9 kHz- 20 GHz.

9kHz -150 kHz; RBW=200 Hz, VBW=200 Hz; 150 kHz-30 MHz; RBW=9 kHz, VBW=9 kHz; 30 MHz-1000 MHz; RBW=120 kHz, VBW=120 kHz, 1000 MHz-10000 MHz; RBW=1 MHz, VBW=1 MHz.

Test environment conditions: 23.9°C, 7% Relative Humidity, 100kPa

Test Location: CKC Laboratories, Inc. • 110 North Olinda Place • Brea, CA 92823• 714-993-6112

Customer: **Cellphone-Mate, Inc.**  
 Specification: **24.238 Radiated Spurious Emission**  
 Work Order #: **94297** Date: 11/9/2013  
 Test Type: **Conducted Emissions** Time: 10:07:44  
 Equipment: **Cellphone Booster/amplifier** Sequence#: 1  
 Manufacturer: Cellphone-Mate, Inc. Tested By: E. Wong  
 Model: CM2020 110V 60Hz  
 S/N: 2

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN02869	Spectrum Analyzer	E4440A	2/6/2013	2/6/2015
T2	AN03430	Attenuator	75A-10-12	9/5/2013	9/5/2015
T3	AN02946	Cable	32022-2-2909K-36TC	7/31/2013	7/31/2015

**Equipment Under Test (\* = EUT):**

Function	Manufacturer	Model #	S/N
Cellphone Booster/amplifier*	Cellphone-Mate, Inc.	CM2020	2

**Support Devices:**

Function	Manufacturer	Model #	S/N
Signal Generator	Agilent	E4438C	MY42082260
Power Supply	SureCall	GFP451DA-0945-1	1211-0000323

**Test Conditions / Notes:**

The EUT is placed on the test bench. Cellular -800 gain is set at Max gain and PCS-1900 Gain is set at max gain. All dip switches are set to Off position, i.e. toward the 1 2 4 8 16 direction. Evaluation performed at the Outside (Donor) and Inside (Server) antenna port. CMRS band.

UL: 824-849MHz, 1850-1915MHz  
 DL: 869-894MHz, 1930-1995MHz

The booster operates in the following frequency band.

UL: 824-849, 1850-1915 MHz  
 DL: 869-894, 1930-1995 MHz

Test environment conditions: 23.9°C, 7% Relative Humidity, 100kPa

1850-  
 Operating Frequency: 1915MHz  
 Channels: GSM  
 Highest Measured Output Power: 18.60 (dBm)= 0.0724 (Watts)  
 Distance: 3 meters  
 Limit:  $43+10\log(P)=$  31.60 dBc

Freq. (MHz)	Reference Level (dBm)	Antenna Polarity (H/V)	dBc
3,758.00	-57.89738566	Horiz	76.50

Operating Frequency: 1930-1995  
 Channels: GSM  
 Highest Measured Output Power: 0.90 (dBm)= 0.0012 (Watts)  
 Distance: 3 meters  
 Limit:  $43+10\log(P)=$  13.79 dBc

Freq. (MHz)	Reference Level (dBm)	Antenna Polarity (H/V)	dBc
3,960.00	-58.39181246	Horiz	59.29
3,960.00	-58.69181246	Vert	59.59

## LIMIT LINE FOR SPURIOUS RADIATED EMISSION

$$\text{REQUIRED ATTENUATION} = 43 + 10 \log P \text{ (dB)}$$

For radiated spurious emission measured at 3 meter test distance,

$$\begin{aligned} \text{Required attenuation} &= 43 + 10 \log P_t \text{ at 3 meter dB} \\ \text{Limit line (dBuV)} &= E_{\text{dBuV}} - \text{Attenuation} \end{aligned}$$

$E_{\text{dBuV}}$  = Measured field strength at 3 meter in dBuV/m

### Power Density (Isotropic)

$$P_D = \frac{P_t}{4\pi r^2}$$

$P_D$  = Power Density in Watts /m<sup>2</sup>

$P_t$  = Average Transmit Power

$r$  = Test distance

### Field Intensity E (V/m)

$$E = \sqrt{P_D \times 377}$$

$$E = \frac{\sqrt{P_t \times 377}}{4\pi r^2}$$

$$E = \sqrt{\frac{P_t \times 30}{r^2}}$$

$$P_t = \left( \frac{E^2 \times r^2}{30} \right)$$

$$10 \log P_t = 10 \log E^2 \text{ (V/m)} + 10 \log r^2 - 10 \log 30$$

$$10 \log P_t = 20 \log E \text{ (V/m)} + 20 \log r - 10 \log 30$$

At 3 meter,  $r = 3$  m

$$10 \log P_t = 20 \log E \text{ (V/m)} + 20 \log 3 - 10 \log 30$$

$$10 \log P_t = 20 \log E \text{ (V/m)} + 9.54 - 14.77$$

$$10 \log P_t = 20 \log E \text{ (V/m)} - 5.23$$

Since  $20 \log E \text{ (V/m)} = 20 \log E \text{ (uV/m)} - 120$

$$10 \log P_t = 20 \log E \text{ (uV/m)} - 120 - 5.23$$

$$10 \log P_t = 20 \log E \text{ (uV/m)} - 125.23$$

$$\begin{aligned}
 \text{Limit line (dBuV) at 3 meter} &= E_{\text{dBuV}} - \text{Attenuation} \\
 &= E_{\text{dBuV}} - (43 + 10 \log P_t \text{ at 3 meter}) \\
 &= E_{\text{dBuV}} - 43 - 10 \log P_t \text{ at 3 meter} \\
 &= E_{\text{dBuV}} - 43 - (20 \log E \text{ (uV/m)} - 125.23) \\
 &= E_{\text{dBuV}} - 43 - 20 \log E \text{ (uV/m)} + 125.23 \\
 &= E_{\text{dBuV}} - 20 \log E \text{ (uV/m)} + 82.23
 \end{aligned}$$

$$\begin{aligned}
 \text{Since } 20 \log E \text{ (uV/m)} &= E \text{ in dBuV/m} \\
 &= E_{\text{dBuV}} - E_{\text{dBuV}} + 82.23
 \end{aligned}$$

$$\text{Radiated Emission limit 3 meter} = 82.23 \text{ dBuV at any power level measured in dBuV}$$

**Test Setup Photos**



## 2.1055 Frequency Stability

Frequency stability does not apply to this type of equipment.

## SUPPLEMENTAL INFORMATION

### Measurement Uncertainty

Uncertainty Value	Parameter
4.73 dB	Radiated Emissions
3.34 dB	Mains Conducted Emissions
3.30 dB	Disturbance Power

The reported measurement uncertainties are calculated based on the worst case of all laboratory environments from CKC Laboratories, Inc. test sites. Only those parameters which require estimation of measurement uncertainty are reported. The reported worst case measurement uncertainty is less than the maximum values derived in CISPR 16-4-2. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ . Compliance is deemed to occur provided measurements are below the specified limits.

### Emissions Test Details

#### TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

#### CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in  $\text{dB}\mu\text{V}/\text{m}$ , the spectrum analyzer reading in  $\text{dB}\mu\text{V}$  was corrected by using the following formula. This reading was then compared to the applicable specification limit.

<b>SAMPLE CALCULATIONS</b>	
Meter reading	(dB $\mu$ V)
+ Antenna Factor	(dB)
+ Cable Loss	(dB)
- Distance Correction	(dB)
- Preamplifier Gain	(dB)
= Corrected Reading	(dB $\mu$ V/m)

#### TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

<b>MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE</b>			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
CONDUCTED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	9 kHz	150 kHz	200 Hz
RADIATED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz
RADIATED EMISSIONS	1000 MHz	>1 GHz	1 MHz

#### SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or carrot ("") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

##### Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

##### Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

##### Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.