

FCC ID: RSQ-BH300

Operational Description of the equipment

1. Turn the BH-300 on

Plug in the BH-300 to cigar port to turn it on, and LCD will display -----ON-----, and then LCD display -----.

2. Turn the BH-300 off

Press Ending key to turn off BH-300, and LCD will display -----OFF----- first, and then nothing display on the LCD.

3. Pairing procedure:

1. Plug BH-300 into the cigar power port of the car.
2. Press Ending key to turn the BH-300 off first.
3. Press and hold Ending key again, until you can hear the tones come from the speaker. And LCD display -----P-----
4. BH-300 is under the pairing mode now, then you can start to pair the BH-300 with your mobile phone now, and the pairing device name is **BH-300**, and password is **1234**.

4. Answer the call:

Press the Answer key to answer the incoming phone call, and the LCD will display the caller's ID. **Note : Some of the mobile phones don't support this function.**

PRODUCT	Bluetooth LCD Plug-in Carkit
MODEL NO.	BH-300
POWER SUPPLY	DC 10~24 V, 1 A
FREQUENCY BAND	ISM 2.4GHz
CARRIER FREQUENCY	2.4GHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1MHz
RATED RF OUTPUT POWER	-6~+4 dBm=1 m
MODULATION TYPE	GFSK
MODE OF OPERATION	duplex
BIT RATE OF TRANSMISSION	700K
ANTENNA TYPE	PCB pattern
ANTENNA GAIN	-3 dBi
OPERATING TEMPERATURE	-5~80°C
CHANNEL BANDWIDTH	1MHz