



FCC RF Test Report

APPLICANT : Gosafe Company Limited
EQUIPMENT : GPS Tracker
BRAND NAME : Gosafe
MODEL NAME : G6S
FCC ID : RSRG-6S-3S
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jan. 10, 2014 and testing was completed on Jun. 05, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards. The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.
No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard.....	5
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.7 Testing Location	7
1.8 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	9
2.3 Support Unit used in test configuration	9
2.4 Measurement Results Explanation Example	10
3 TEST RESULT.....	11
3.1 Conducted Output Power Measurement.....	11
3.2 Peak-to-Average Ratio	13
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	17
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	21
3.5 Band Edge Measurement.....	29
3.6 Conducted Spurious Emission Measurement.....	34
3.7 Field Strength of Spurious Radiation Measurement	40
3.8 Frequency Stability Measurement.....	46
4 LIST OF MEASURING EQUIPMENT.....	50
5 UNCERTAINTY OF EVALUATION.....	51

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< $43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 23.78 dB at 1672.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

Gosafe Company Limited

B301, No. 69 Guangpu West Road, Science City, Guangzhou

1.2 Manufacturer

Gosafe Company Limited

B301, No. 69 Guangpu West Road, Science City, Guangzhou

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GPS Tracker
Brand Name	Gosafe
Model Name	G6S
FCC ID	RSRG-6S-3S
EUT supports Radios application	GPRS
HW Version	V1.0.6
SW Version	V2.04
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz
Maximum Output Power to Antenna	GSM850 : 32.74 dBm GSM1900 : 28.50 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GPRS: GMSK



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.37	0.05 ppm	247KGXW
Part 24	GSM1900 GPRS class 8	GMSK	1.13	0.03 ppm	247KGXW



1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. C. TEL: +86-755- 3320-2398		
Test Site No.	Sportun Site No.		FCC Registration No.
	TH01-SZ	03CH01-SZ	831040

Note: The test site complies with ANSI C63.4 2003 requirement

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power

Meas. License Digital Systems v02r01 with maximum output power.

Frequency range investigated for radiated emission: 30MHz to 10th harmonic.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link


Note:

The maximum power levels are chosen to test as the worst case configuration as follows:
GPRS multi-slot class 8 mode for GMSK modulation,
only these modes were used for all tests.

Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.74	32.66	32.55	28.50	28.05	28.05
GPRS class 10	32.72	32.65	32.54	28.41	28.04	28.04

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 7 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 7 + 10 = 17 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

Cellular Band			
Modes	GSM850 (GPRS class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.74	32.66	32.55
Conducted Power (Watts)	1.88	1.85	1.80

PCS Band			
Modes	GSM1900 (GPRS class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	28.50	28.05	28.05
Conducted Power (Watts)	0.71	0.64	0.64

Note: maximum burst average power for GSM.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. For GPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
3. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup






3.2.5 Test Result of Peak-to-Average Ratio

PCS Band			
Modes	GSM1900 (GPRS class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.31	0.30	0.30


3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 4.JUN.2014 10:25:24



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
2. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = Ps + Et - Es + Gs = Ps + Rt - Rs + Gs$
 Ps (dBm) : Input power to substitution antenna.
 Gs (dBi or dBd) : Substitution antenna Gain.
 $Et = Rt + AF$
 $Es = Rs + AF$
 AF (dB/m) : Receive antenna factor
 Rt : The highest received signal in spectrum analyzer for EUT.
 Rs : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup





3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-21.63	-48.12	0.00	-1.08	25.41	0.35
836.40	-22.51	-48.28	0.00	-0.93	24.84	0.30
848.80	-21.89	-48.35	0.00	-0.76	25.70	0.37

Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-22.77	-47.97	0.00	-1.08	24.12	0.26
836.40	-23.26	-48.01	0.00	-0.93	23.82	0.24
848.80	-21.95	-48.05	0.00	-0.76	25.34	0.34



3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.64	-51.88	0.00	1.96	28.20	0.66
1880.00	-24.90	-52.99	0.00	2.00	30.09	1.02
1909.80	-25.74	-54.28	0.00	1.98	30.52	1.13
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.59	-52.13	0.00	1.96	27.50	0.56
1880.00	-26.98	-53.17	0.00	2.00	28.19	0.66
1909.80	-27.91	-54.13	0.00	1.98	28.20	0.66

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup





3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth


Cellular Band			
Modes	GSM850 (GPRS class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
99% OBW (kHz)	247.47	244.57	246.02
26dB BW (kHz)	309.70	309.70	311.10

PCS Band			
Modes	GSM1900 (GPRS class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
99% OBW (kHz)	247.47	244.57	244.57
26dB BW (kHz)	308.20	309.70	306.80

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
---------------	---------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 3.JUN.2014 19:41:24


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 3.JUN.2014 19:35:04




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 3.JUN.2014 19:40:14


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 3.JUN.2014 19:36:20

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 3.JUN.2014 19:39:13

26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 3.JUN.2014 19:37:32



Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------



99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 3.JUN.2014 20:27:42

03.06.2014
20:27:42**26dB Bandwidth Plot on Channel 512 (1850.2 MHz)**


Date: 3.JUN.2014 20:16:05

03.06.2014
20:16:05

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)


99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 3.JUN.2014 20:20:08

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 3.JUN.2014 20:18:05

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.

3.5.4 Test Setup


<Conducted Band Edge >



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-16.06dBm	Measurement Value :	-16.22dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)




Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.16dB	Maximum 26dB Bandwidth :	0.311MHz
Band Edge :	-16.23dBm	Measurement Value :	-16.39dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)




Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-19.71dBm	Measurement Value :	-19.85dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW}/\text{RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.14dB	Maximum 26dB Bandwidth :	0.310MHz
Band Edge :	-18.40dBm	Measurement Value :	-18.54dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)

Date: 5.JUN.2014 04:25:45

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW}/\text{RBW})$

2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.


3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Conducted Spurious Emission Plot between 1GHz ~ 3GHz






Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Conducted Spurious Emission Plot between 7GHz ~ 9GHz






Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 3.JUN.2014 20:50:13


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 3.JUN.2014 20:43:44




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 3.JUN.2014 21:06:20


Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 3.JUN.2014 21:10:15



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz





3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz






3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850		Temperature :	24~25°C					
Test Mode :	GPRS class 8 Link (GMSK)		Relative Humidity :	48~49%					
Test Engineer :	Leo Liao		Polarization :	Horizontal					
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
 Date: 2014-04-30									
Site	: 03CH01-SZ								
Condition	: -13dBm HF_EIRP_H_130101 HORIZONTAL								
Frequency	ERP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-36.78	-13	-23.78	-53.62	-39.75	0.88	6.00	H	Pass
2510	-36.86	-13	-23.86	-61.62	-39.47	1.08	5.84	H	Pass
3346	-56.61	-13	-43.61	-67.21	-60.98	1.14	7.66	H	Pass



Band :	GSM850	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ
Condition : -13DBM HF_EIRP_V_130101 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA (dBm)	S.G. (dBm)	TX Cable (dBm)	TX Antenna (dBi)	Polarization (H/V)	Result	
									Power (dBm)	loss (dB)
1672	-39.12	-13	-26.12	-52.69	-42.09	0.88	6.00	V	Pass	
2510	-44.16	-13	-31.16	-65.56	-46.77	1.08	5.84	V	Pass	
3346	-55.20	-13	-42.20	-67.03	-59.57	1.14	7.66	V	Pass	



Band :	GSM1900	Temperature :	24~25°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	48~49%
Test Engineer :	Leo Liao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result	
									Reading (dBm)	Result
3760	-48.22	-13	-35.22	-62.29	-54.96	1.28	8.02	H	Pass	
5640	-50.16	-13	-37.16	-68.15	-58.58	1.58	10.00	H	Pass	
7520	-46.15	-13	-33.15	-68.09	-56.47	1.78	12.10	H	Pass	



Band :	GSM1900		Temperature :	24~25°C					
Test Mode :	GPRS class 8 Link (GMSK)		Relative Humidity :	48~49%					
Test Engineer :	Leo Liao		Polarization :	Vertical					
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
<p>Level (dBm)</p> <p>Date: 2014-04-30</p> <p>-13DBM</p> <p>Frequency (MHz)</p>									
Site	: 03CH01-SZ								
Condition	: -13DBM HF_EIRP_V_130101 VERTICAL								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-48.91	-13	-35.91	-63.94	-55.65	1.28	8.02	V	Pass
5640	-51.84	-13	-38.84	-68.92	-60.26	1.58	10	V	Pass
7520	-46.38	-13	-33.38	-68.63	-56.70	1.78	12.1	V	Pass



3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^\circ\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup





3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-40	-0.05	PASS
-20	-38	-0.04	
-10	-33	-0.04	
0	-29	-0.03	
10	-28	-0.03	
20	-35	-0.04	
30	-33	-0.04	
40	-36	-0.04	
50	-39	-0.05	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-48	-0.03	PASS
-20	43	+0.02	
-10	44	+0.02	
0	-47	-0.02	
10	-41	-0.02	
20	45	+0.02	
30	39	+0.02	
40	38	+0.02	
50	42	+0.02	



3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	12	-38	-0.04	2.5	PASS
		BEP	-42	-0.05		
		32	-41	-0.05		
GSM 1900 CH661	GPRS class 8	12	-41	-0.02		
		BEP	43	+0.02		
		32	45	+0.02		

Note:

1. Normal Voltage = 12V.
2. Battery End Point (BEP) = 8 V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 03, 2014	Jun. 03, 2014~Jun. 05, 2014	Mar. 02, 2015	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	13dBm~20dBm	Mar. 03, 2014	Jun. 03, 2014~Jun. 05, 2014	Mar. 02, 2015	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	0.3GHz~40GHz	Mar. 03, 2014	Jun. 03, 2014~Jun. 05, 2014	Mar. 02, 2015	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	-40°C~150°C	Feb. 21, 2014	Jun. 03, 2014~Jun. 05, 2014	Feb. 20, 2015	Conducted (TH01-SZ)
ESClO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Apr. 30, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 27, 2013	Apr. 30, 2014	May 26, 2014	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	23188	30MHz~2GHz	Oct. 26, 2013	Apr. 30, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	Apr. 30, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101073	18GHz~40GHz	Jan. 27, 2014	Apr. 30, 2014	Jan. 26, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Feb. 21, 2014	Apr. 30, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Amplifier	Agilent	83017A	MY39501302	3Hz~26.5GHz	Mar. 03, 2014	Apr. 30, 2014	Mar. 02, 2015	Radiation (03CH01-SZ)
AC Source(AVR)	Chroma	61601	61601000198 5	100Vac~250Vac	Mar. 25, 2014	Apr. 30, 2014	Mar. 24, 2015	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Apr. 30, 2014	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Apr. 30, 2014	NCR	Radiation (03CH01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.90
--	-------------