



Products



Table 4: General Technical Data

Operating Temperature	10 - 32 °C
Storage Temperature	-10 - 40 °C
Operating Humidity	15 - 85 % Rel. humidity
Storage Humidity	10 - 90 % Rel. humidity

Table 5: 433.92 MHz Europe

Maximum output power	10 mW
Frequency	
Minimum	433.38 MHz
Typical	433.92 MHz
Maximum	434.46 MHz
Range	30 - 80 m
Complies to the following standard	ETSI/EN300220, EN301489

Table 6: 433.92 MHz USA

Maximum output power	1 mW
Frequency	
Minimum	433.38 MHz
Typical	433.92 MHz
Maximum	434.46 MHz
Range	20 - 60 m
Complies to the following standard	FCC15.231
FCC ID:RT2-10320201	
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.	

Products

**Table 7: 315.00 MHz**

Maximum output power	1 mW
Frequency	
Minimum	314.60 MHz
Typical	315.00 MHz
Maximum	315.39 MHz
Range	20 - 60 m
Complies to the following standard FCC ID:RT2-10320205	FCC15.231
This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.	