

RF Exposure Evaluation Declaration

Product Name : WIFI Gateway
Trade Name : BOSCH
Model No. : 8738714760 (WIFI Dongle UART 3.3V)
FCC ID. : RTG8738714765

Applicant : BOSCH TERMOTECNOLOGIA S.A.

Address : EN 16 - Km 3.7 3800-533 Cacia Aveiro Portugal

Date of Receipt : Aug. 21, 2017

Date of Declaration : May 16, 2019

Report No. : 1780393R-RF-EXP

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	WIFI Gateway
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	50.3501	0.01551
6	2437	47.4242	0.01461
11	2462	44.6684	0.01376

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	66.2217	0.02040
6	2437	74.3019	0.02289
11	2462	73.1139	0.02253

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	WIFI Gateway
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	66.3743	0.02045
6	2437	73.1139	0.02253
11	2462	70.3072	0.02166

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².