



FCC Part 15 Subpart C Transmitter Class II Permissive Change

Direct Sequence Spread Spectrum Transmitter

Test Report

FCC ID: RTTAB-WLNB

FCC Rule Part: 15.247

ACS Report Number: 05-0374-15C

Manufacturer: DPAC Technologies

Model: ABDB-AN-DPxxx

Trade Name: Airborne WLN-B Module

RF Exposure Information

General Information:

Applicant: DPAC Technologies
 ACS Project: 05-0374
 FCC ID: RTTAB-WLNB
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type (Cirronet): Patch
 Antenna Gain: 12dBi
 Transmitter Conducted Power: 15.66dBm
 Maximum System EIRP: 27.66dBm

Antenna Type (Centurion): Patch
 Antenna Gain: 1.5dBi
 Transmitter Conducted Power: 15.66dBm
 Maximum System EIRP: 17.16dBm

Operating Configuration: Mobile
 Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm^2) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm^2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
2412	15.66	1.00	36.81	12	15.849	20	0.116
2412	15.66	1.00	36.81	1.5	1.413	20	0.010

Installation Guidelines

The installation manual contains the following text advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

"RF Exposure (Intentional Radiators Only)

In accordance with FCC requirements of human exposure to radiofrequency fields, the radiating element shall be installed such that a minimum separation distance of 20cm is maintained from the general population."

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.