

FCC CERTIFICATION
On Behalf of
Comat Electronic (Shenzhen) Co., Ltd.

2.4G Wireless Mouse
Model No.: CM9002G

FCC ID: RTX-CM9002G

Prepared for : Comat Electronic (Shenzhen) Co., Ltd.
Address : No.2 Lane 1, Xin'an 3rd 28 District, Baoan, Shenzhen,
China

Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20121914
Date of Test : August 17-31, 2012
Date of Report : September 6, 2012

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	4
1.3. Measurement Uncertainty.....	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. SUMMARY OF TEST RESULTS.....	7
4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A) 8	8
4.1. Block Diagram of Test Setup.....	8
4.2. The Emission Limit	9
4.3. Configuration of EUT on Measurement	9
4.4. Operating Condition of EUT	9
4.5. Test Procedure	10
4.6. The Field Strength of Radiation Emission Measurement Results	11
5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D)	14
5.1. Block Diagram of Test Setup.....	14
5.2. The Emission Limit For Section 15.249(d)	14
5.3. EUT Configuration on Measurement	15
5.4. Operating Condition of EUT	15
5.5. Test Procedure	16
5.6. The Emission Measurement Result	17
6. BAND EDGES	20
6.1. The Requirement	20
6.2. EUT Configuration on Measurement	20
6.3. Operating Condition of EUT	20
6.4. Test Procedure	20
6.5. The Measurement Result	21
7. ANTENNA REQUIREMENT.....	23
7.1. The Requirement	23
7.2. Antenna Construction	23

APPENDIX I (TEST CURVES) (28 pages)

Test Report Certification

Applicant : Comat Electronic (Shenzhen) Co., Ltd.
Manufacturer : Comat Electronic (Shenzhen) Co., Ltd.
EUT Description : 2.4G Wireless Mouse
(A) MODEL NO.: CM9002G
(B) POWER SUPPLY: 1.5V DC ("AA" batteries 1×)

Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.4: 2009

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : August 17-31, 2012

Prepared by :



(Kelly Cheng, Engineer)

Approved & Authorized Signer :



(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	2.4G Wireless Mouse
Model Number	:	CM9002G
Trade Name	:	COMAT
Power Supply	:	1.5V DC ("AA" batteries 1 ×)
Operate Frequency	:	2402.000-2479.000MHz
Applicant	:	Comat Electronic (Shenzhen) Co., Ltd.
Address	:	No.2 Lane 1, Xin'an 3 rd 28 District, Baoan, Shenzhen, China
Manufacturer	:	Comat Electronic (Shenzhen) Co., Ltd.
Address	:	No.2 Lane 1, Xin'an 3 rd 28 District, Baoan, Shenzhen, China
Date of sample received	:	August 17, 2012
Date of Test	:	August 17-31, 2012

1.2. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 8, 2012	Jan. 7, 2013
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 8, 2012	Jan. 7, 2013
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 8, 2012	Jan. 7, 2013
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 8, 2012	Jan. 7, 2013
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 8, 2012	Jan. 7, 2013
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 8, 2012	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 8, 2012	Jan. 7, 2013
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 8, 2012	Jan. 7, 2013
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 8, 2012	Jan. 7, 2013
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 8, 2012	Jan. 7, 2013

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(a)	Fundamental and Harmonics Radiated Emission	Compliant
Section 15.249(d)	Spurious Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: “N/A” means “Not applicable”.

4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION FOR SECTION 15.249(A)


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: 2.4G Wireless Mouse)

4.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: 2.4G Wireless Mouse)

4.2.The Emission Limit

4.2.1.For intentional radiators, According to section 15.249(a), Operation within the frequency band of 2.4 to 2.4835GHz, The fundamental field strength shall not exceed 94 dB μ V/m and the harmonics shall not exceed 54 dB μ V/m.

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

4.2.2.According to section 15.249(e), as shown in section 15.35(b), the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

4.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. 2.4G Wireless Mouse (EUT)

Model Number : CM9002G
 Serial Number : N/A
 Manufacturer : Comat Electronic (Shenzhen) Co., Ltd.

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.000 - 2479.000 MHz. We are select 2402.000MHz, 2439.000MHz, 2479.000MHz TX frequency to transmit.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 25000MHz is checked.

4.6.The Field Strength of Radiation Emission Measurement Results

PASS.

Date of Test:	August 24, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2402.000MHz	Test Engineer:	Bob

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2402.000	99.27	105.78	-7.45	91.82	98.33	94.00	114.00	-2.18	-15.67	Vertical
2402.000	100.25	106.62	-7.45	92.80	99.17	94.00	114.00	-1.20	-14.83	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4804.000	45.70	51.54	-0.30	45.40	51.24	54.00	74.00	-8.60	-22.76	Vertical
4804.000	47.42	52.07	-0.30	47.12	51.77	54.00	74.00	-6.88	-22.23	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	August 24, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2439.000MHz	Test Engineer:	Bob

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2439.000	90.78	96.19	-7.36	83.42	88.83	94.00	114.00	-10.58	-25.17	Vertical
2439.000	91.24	96.36	-7.36	83.88	89.00	94.00	114.00	-10.12	-25.00	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4878.000	43.05	48.74	0.11	43.16	48.85	54.00	74.00	-10.84	-25.15	Vertical
4878.000	41.93	48.74	0.11	42.04	48.85	54.00	74.00	-11.96	-25.15	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	August 24, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2479.000MHz	Test Engineer:	Bob

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2479.000	91.66	96.48	-7.37	84.29	89.11	94.00	114.00	-9.71	-24.89	Vertical
2479.000	91.03	96.64	-7.37	83.66	89.27	94.00	114.00	-10.34	-24.73	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4958.000	41.15	46.81	0.51	41.66	47.32	54.00	74.00	-12.34	-26.68	Vertical
4958.000	44.10	49.94	0.51	44.61	50.45	54.00	74.00	-9.39	-23.55	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

5. SPURIOUS RADIATED EMISSION FOR SECTION 15.249(D)


5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



(EUT: 2.4G Wireless Mouse)

5.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: 2.4G Wireless Mouse)

5.2. The Emission Limit For Section 15.249(d)

5.2.1. Emission radiated outside of the specified frequency bands, except for harmonics, shall be comply with the general radiated emission limits in Section 15.209.

Radiation Emission Measurement Limits According to Section 15.209

Frequency (MHz)	Limit		The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector.
	Field Strength (microvolts/meter)	Measurement Distance (meters)	
0.009 – 0.490	2400/F(kHz)	300	

0.490 – 1.705	24000/F(kHz)	30	Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
1.705 – 30.0	30	30	
30 - 88	100	3	
88 - 216	150	3	
216 - 960	200	3	
Above 960	500	3	

5.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. 2.4G Wireless Mouse (EUT)

Model Number : CM9002G
Serial Number : N/A
Manufacturer : Comat Electronic (Shenzhen) Co., Ltd.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.000 - 2479.000 MHz. We are select 2402.000MHz, 2439.000MHz, 2479.000MHz TX frequency to transmit.

5.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

5.6.The Emission Measurement Result

PASS.

Date of Test:	August 18, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2402.000MHz	Test Engineer:	Bob

Below 30MHz

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	X
-	-	-	-	-	-	Y
-	-	-	-	-	-	Z

30MHz-25GHz

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$
3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	August 18, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2439.000MHz	Test Engineer:	Bob

Below 30MHz

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	X
-	-	-	-	-	-	Y
-	-	-	-	-	-	Z

30MHz-25GH

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$
3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	August 18, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2479.000MHz	Test Engineer:	Bob

Below 30MHz

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	X
-	-	-	-	-	-	Y
-	-	-	-	-	-	Z

30MHz-25GH

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$
3. The spectral diagrams in appendix I display the measurement of peak values.

6. BAND EDGES

6.1.The Requirement

6.1.1.Band Edge from 2400MHz to 2483.5MHz. Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

6.2.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.2.1. 2.4G Wireless Mouse (EUT)

Model Number : CM9002G
Serial Number : N/A
Manufacturer : Comat Electronic (Shenzhen) Co., Ltd.

6.3.Operating Condition of EUT

6.3.1.Setup the EUT and simulator as shown as Section 4.1.

6.3.2.Turn on the power of all equipment.

6.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.000-2479.000MHz MHz. We are select 2402.000MHz, 2479.000MHz TX frequency to transmit.

6.4.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
RBW=1MHz, VBW=1MHz

6.5.The Measurement Result

Pass.

Date of Test:	August 24, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2402.000MHz	Test Engineer:	Bob

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2310.000	41.11	46.23	-7.81	33.30	38.42	54.00	74.00	-20.70	-35.58	Vertical
2369.250	42.36	47.20	-7.66	34.70	39.54	54.00	74.00	-19.30	-34.46	Vertical
2390.000	43.84	48.09	-7.53	36.31	40.56	54.00	74.00	-17.69	-33.44	Vertical
2310.000	40.05	45.53	-7.81	32.24	37.72	54.00	74.00	-21.76	-36.28	Horizontal
2369.667	41.79	46.56	-7.66	34.13	38.90	54.00	74.00	-19.87	-35.10	Horizontal
2390.099	45.52	50.86	-7.53	37.99	73.33	54.00	74.00	-16.01	-30.67	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

3. The spectral diagrams in appendix I display the measurement of peak values.

Date of Test:	August 24, 2012	Temperature:	25°C
EUT:	2.4G Wireless Mouse	Humidity:	50%
Model No.:	CM9002G	Power Supply:	DC 1.5V
Test Mode:	TX 2479.000MHz	Test Engineer:	Bob

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.869	41.47	46.75	-7.38	34.09	39.37	54.00	74.00	-19.91	-34.63	Vertical
2489.820	40.36	45.16	-7.39	32.97	37.77	54.00	74.00	-21.03	-36.23	Vertical
2500.000	41.77	46.17	-7.40	34.37	38.77	54.00	74.00	-19.63	-35.23	Vertical
2483.000	41.19	46.55	-7.38	33.82	39.18	54.00	74.00	-20.18	-34.82	Horizontal
2489.883	40.05	45.37	-7.39	32.66	37.98	54.00	74.00	-21.34	-36.02	Horizontal
2500.000	40.22	45.86	-7.40	32.82	38.46	54.00	74.00	-21.18	-35.54	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$
3. The spectral diagrams in appendix I display the measurement of peak values.


7. ANTENNA REQUIREMENT

7.1.The Requirement

7.1.1. According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2.Antenna Construction

The antenna is PCB Layout antenna, no consideration of replacement.



Antenna

APPENDIX I (Test Curves)



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2642
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: 2.4G Wireless Mouse
Mode: TX 2402
Model: CM9002G
Manufacturer: COMAT

Polarization: Horizontal
Power Source: DC 1.5V
Date: 12/8/18/
Time: 8/55/36
Engineer Signature:
Distance: 3m

Note: Report NO.: ATE20121914




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2643

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX 2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 12/8/18/

Time: 8/57/19

Engineer Signature:

Distance: 3m

Note: Report NO.: ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3204

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:22:14

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	106.62	-7.45	99.17	114.00	-14.83	peak			
2	2402.000	100.25	-7.45	92.80	94.00	-1.2	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3205

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:24:53

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	105.78	-7.45	98.33	114.00	-15.67	peak			
2	2402.000	99.27	-7.45	91.82	94.00	-2.18	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3208

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:28:01

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4804.000	52.07	-0.30	51.77	74.00	-22.23	peak			
2	4804.000	47.42	-0.30	47.12	54.00	-6.88	AVG			


ACCURATE TECHNOLOGY CO., LTD.


 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

 Job No.: Bob #3206
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 24 C / 48 %
 EUT: 2.4G Wireless Mouse
 Mode: TX2402
 Model: CM9002G
 Manufacturer: COMAT

 Polarization: Vertical
 Power Source: DC 1.5V
 Date: 2012/08/24
 Time: 18:26:22
 Engineer Signature:
 Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4804.000	51.54	-0.30	51.24	74.00	-22.76	peak			
2	4804.000	45.70	-0.30	45.40	54.00	-8.60	AVG			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2648

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: 2.4G Wireless Mouse

Mode: TX 2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/8/18

Time: 11:52:09

Engineer Signature: Bob

Distance: 3m

Note: Report No.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2649

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: 2.4G Wireless Mouse

Mode: TX 2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/8/18

Time: 11:56:43

Engineer Signature: Bob

Distance: 3m

Note: Report No.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2644

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX 2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 12/8/18/

Time: 8/57/38

Engineer Signature:

Distance: 3m

Note: Report NO.: ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2645

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX 2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 12/8/18/

Time: 8/58/13

Engineer Signature:

Distance: 3m

Note: Report NO.: ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3192

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 17:53:53

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	96.36	-7.36	89.00	114.00	-25.00	peak			
2	2439.000	91.24	-7.36	83.88	94.00	-10.12	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3193

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 17:56:35

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2439.000	96.19	-7.36	88.83	114.00	-25.17	peak			
2	2439.000	90.78	-7.36	83.42	94.00	-10.58	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3194

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 17:58:56

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4878.000	48.74	0.11	48.85	74.00	-25.15	peak			
2	4878.000	43.05	0.11	43.16	54.00	-10.84	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3195

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:01:00

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4878.000	48.74	0.11	48.85	74.00	-25.15	peak			
2	4878.000	41.93	0.11	42.04	54.00	-11.96	AVG			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2650	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 2012/8/18
Temp.(C)/Hum.(%) 25 C / 50 %	Time: 12:01:19
EUT: 2.4G Wireless Mouse	Engineer Signature: Bob
Mode: TX 2439	Distance: 3m
Model: CM9002G	
Manufacturer: COMAT	

Note: Report No.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2651

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 50 %

EUT: 2.4G Wireless Mouse

Mode: TX 2439

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/8/18

Time: 12:05:30

Engineer Signature: Bob

Distance: 3m

Note: Report No.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #2646	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 12/8/18/
Temp.(C)/Hum.(%) 24 C / 48 %	Time: 8/58/43
EUT: 2.4G Wireless Mouse	Engineer Signature:
Mode: TX 2479	Distance: 3m
Model: CM9002G	
Manufacturer: COMAT	

Note: Report NO.: ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #2647

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX 2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 12/8/18/

Time: 8/59/12

Engineer Signature:

Distance: 3m

Note: Report NO.: ATE20121914





ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3196

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:04:49

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	96.64	-7.37	89.27	114.00	-24.73	peak			
2	2479.000	91.03	-7.37	83.66	94.00	-10.34	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3197
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 24 C / 48 %
EUT: 2.4G Wireless Mouse
Mode: TX2479
Model: CM9002G
Manufacturer: COMAT

Polarization: Vertical
Power Source: DC 1.5V
Date: 2012/08/24
Time: 18:06:43
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2479.000	96.48	-7.37	89.11	114.00	-24.89	peak			
2	2479.000	91.66	-7.37	84.29	94.00	-9.71	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3198

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:08:12

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4958.000	46.81	0.51	47.32	74.00	-26.68	peak			
2	4958.000	41.15	0.51	41.66	54.00	-12.34	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3199

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:09:49

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	4958.000	49.94	0.51	50.45	74.00	-23.55	peak			
2	4958.000	44.10	0.51	44.61	54.00	-9.39	AVG			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #2652	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 2012/8/18
Temp.(C)/Hum.(%) 25 C / 50 %	Time: 12:10:41
EUT: 2.4G Wireless Mouse	Engineer Signature: Bob
Mode: TX 2479	Distance: 3m
Model: CM9002G	
Manufacturer: COMAT	

Note: Report No.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #2653	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 1.5V
Test item: Radiation Test	Date: 2012/8/18
Temp.(C)/Hum.(%) 25 C / 50 %	Time: 12:15:08
EUT: 2.4G Wireless Mouse	Engineer Signature: Bob
Mode: TX 2479	Distance: 3m
Model: CM9002G	
Manufacturer: COMAT	

Note: Report No.ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3202

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:18:07

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	46.23	-7.81	38.42	74.00	-35.58	peak			
2	2310.000	41.11	-7.81	33.30	54.00	-20.70	AVG			
3	2369.250	47.20	-7.66	39.54	74.00	-34.46	peak			
4	2369.250	42.36	-7.66	34.70	54.00	-19.30	AVG			
5	2390.000	48.09	-7.53	40.56	74.00	-33.44	peak			
6	2390.000	43.84	-7.53	36.31	54.00	-17.69	AVG			


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3203

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2402

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:20:09

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	45.53	-7.81	37.72	74.00	-36.28	peak			
2	2310.000	40.05	-7.81	32.24	54.00	-21.76	AVG			
3	2369.667	46.56	-7.66	38.90	74.00	-35.10	peak			
4	2369.667	41.79	-7.66	34.13	54.00	-19.87	AVG			
5	2390.099	50.86	-7.53	43.33	74.00	-30.67	peak			
6	2390.099	45.52	-7.53	37.99	54.00	-16.01	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Bob #3200

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Horizontal

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:13:01

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.000	46.55	-7.37	39.18	74.00	-34.82	peak			
2	2483.000	41.19	-7.37	33.82	54.00	-20.18	AVG			
3	2489.883	45.37	-7.39	37.98	74.00	-36.02	peak			
4	2489.883	40.05	-7.39	32.66	54.00	-21.34	AVG			
5	2500.000	45.86	-7.40	38.46	74.00	-35.54	peak			
6	2500.000	40.22	-7.40	32.82	54.00	-21.18	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Bob #3201

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 24 C / 48 %

EUT: 2.4G Wireless Mouse

Mode: TX2479

Model: CM9002G

Manufacturer: COMAT

Polarization: Vertical

Power Source: DC 1.5V


Date: 2012/08/24

Time: 18:15:14

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20121914



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.869	46.75	-7.38	39.37	74.00	-34.63	peak			
2	2483.869	41.47	-7.38	34.09	54.00	-19.91	AVG			
3	2489.820	45.16	-7.39	37.77	74.00	-36.23	peak			
4	2489.820	40.36	-7.39	32.97	54.00	-21.03	AVG			
5	2500.000	46.17	-7.40	38.77	74.00	-35.23	peak			
6	2500.000	41.77	-7.40	34.37	54.00	-19.63	AVG			