



RF EXPOSURE REPORT

REPORT NO.: SA941229L01B

MODEL NO.: QBTM400

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Qcom Technology Inc.

ADDRESS: 7F, No. 178, Ming Chuan E. Rd., Sec 3, Taipei
Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)	mW
Low	2.402
High	2.480

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)
Conducted Power	2.34
EIRP Power	1.79

***Note:** PIFA antenna with -0.55dBi gain

Threshold for no SAR evaluation is 24.580mW

Transmitter power is 1.714mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold