

TEST REPORT

REPORT NUMBER: I08GE6990-FCC-EMC

ON


Type of Equipment: GSM/GPRS Mobile Phone (TRI Band
GSM850/1800/1900 handheld Cellular phone)
Type of Designation: VI-3
Manufacturer: Ezze Mobile Tech.,Inc

ACCORDING TO
FCC CFR Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY
MATTERS; GENERAL RULES AND REGULATIONS; e-CFR,
Oct 1,2008
PART 22, PUBLIC MOBILE SERVICES (Oct 1, 2008 Edition)
PART 24, PERSONAL COMMUNICATIONS SERVICES (Oct 1, 2008
Edition)

China Telecommunication Technology Labs.

Month date, year
Feb, 11, 2009

Signature



He Guili
Director

FCC ID: RV2VI3
Report Date: 2009-02-10

Test Firm Name: China Telecommunication Technology Labs
Registration Number: 840587

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22, and 24. The sample tested was found to comply with the requirements defined in the applied rules.

CONTENTS

1 GENERAL INFORMATION	4
1.1 NOTES	4
1.2 TESTERS.....	5
1.3 TESTING LABORATORY INFORMATION	6
1.4 DETAILS OF APPLICANT OR MANUFACTURER	7
2 TEST ITEM	8
2.1 GENERAL INFORMATION	8
2.2 OUTLINE OF EUT.....	8
2.3 MODIFICATIONS INCORPORATED IN EUT	8
2.4 EQUIPMENT CONFIGURATION	8
2.5 OTHER INFORMATION	9
3 SUMMARY OF TEST RESULTS	10
4 TEST RESULTS OF MODE.....	11
4.1 RADIATED SPURIOUS EMISSION.....	11
4.2 RADIATED RF POWER OUTPUT AND ERP	21
4.3 OCCUPIED BANDWIDTH	24
4.4 FREQUENCY STABILITY OVER TEMPERATURE VARIATION	32
4.5 FREQUENCY STABILITY OVER VOLTAGE VARIATION	35
4.6 CONDUCTED RF POWER OUTPUT.....	37
4.7 CONDUCTED SPURIOUS EMISSION	40
4.8 BAND EDGE	45
ANNEX A EXTERNAL PHOTOS	51
ANNEX B INTERNAL PHOTOS.....	54
ANNEX C DEVIATIONS FROM PRESCRIBED TEST METHODS.....	56

1 General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22 and 24.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.

The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex C.

China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTTL Mr. He Guili.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC

1.2 Testers

Name: Yuan Yuan
Position: Engineer
Department: Department of EMC test
Signature: 袁园

Editor of this test report:

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Date: 2009-2-10
Signature: 李国庆

Technical responsibility for area of testing:

Name: Zhang Xia
Position: Manager
Department: Department of EMC test
Date: 2009-2-10
Signature: 张夏

1.3 Testing Laboratory information

1.3.1 Location

Name: China Telecommunication Technology Labs.
Address: No. 11, Yue Tan Nan Jie, Xi Cheng District
BEIJING
P. R. CHINA, 100083
Tel: +86 10 68094053
Fax: +86 10 68011404
Email: emc@chinattl.com

1.3.2 Details of accreditation status

Accredited by: China National Accreditation Service for Conformity
Assessment (CNAS)
Registration number: CNAS Registration No. CNAS L0570
Standard: ISO/IEC 17025:2005

1.3.3 Test location, where different from section 1.3.1

Name: -----
Street: -----
City: -----
Country: -----
Telephone: -----
Fax: -----
Postcode: -----

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name: Ezze Mobile Tech., Inc
Address: 1F, Bubmusa Bldg., 151-31.
Nonhyun-Dong, Kangnam-Ku, Seoul, Korea
Country: Korea
Telephone: +82-2-519-7802
Fax: +82-2-519-7800
Contact: KIM, NAM-SUK
Telephone: +82-2-519-7802
Email: splindid@ezzemobile.com

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: ----
Address: ----

1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: ----
Address: ----

2 Test Item

2.1 General Information

Manufacturer: Ezze Mobile Tech., Inc
 Name: GSM/GPRS Mobile phone (TRI Band GSM850/1800/1900 handheld Cellular phone)
 Model Number: VI-3
 Serial Number: --
 Production Status: Production
 Receipt date of test item: 2008-11-11

2.2 Outline of EUT

E.U.T. is a GSM/GPRS Mobile phone.

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	handset	Ezze Mobile Tech	VI-3	--	None
B	adapter	Yu Feng ELECTRONIC Limited	USB Type charger (YF-0510228)	--	None
C	battery	Zhi-in	Lithium Ion Rechargeable Battery	--	None
D	Earphone	Rich star	Wire Type	--	None

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0 m	No	1	None

2.5 Other Information

(a) Modulation is GMSK.

(b) Emission Designator is 252KGXW.

(c) Version of hardware and software

HW Version: 1.0

SW Version: 1.0

(d) Adaptor information:

Input: 100-240VAC 50-60Hz

Output: 5.0VDC 650mA

(e) Battery information:

3.7VDC 760mAh

Test Report

3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

GSM mode:		
Specification Clause	Name of Test	Result
2.1051, 24.238, 2.1053,22.917	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
22.913(a)	Effective Radiated Power (ERP)	Pass
2.1049,22.917(b), 24.238(b)	Occupied Bandwidth	*Note 1
2.1055,22.355, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055,22.355, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,22.913(a), 24.232(c)	Conducted RF Power Output	Pass
2.1051,22.917,24. 238	Conducted spurious emissions	Pass
Note 1: No applicable performance criteria.		

GPRS mode:		
2.1051, 24.238, 2.1053,22.917	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
22.913(a)	Effective Radiated Power (ERP)	Pass
2.1049,22.917(b), 24.238(b)	Occupied Bandwidth	*Note 2
2.1055,22.355, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055,22.355, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,22.913(a), 24.232(c)	Conducted RF Power Output	Pass
2.1051,22.917,24. 238	Conducted spurious emissions	Pass
Note 2: No applicable performance criteria.		

4 Test Results of mode

4.1 Radiated Spurious Emission

Specifications:	2.1051, 24.238, 2.1053, 22.917					
Date of Tests	2009-1-14					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661 for GSM and GPRS mode					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2010-01-09	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-16	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level / Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

The EUT was placed in an anechoic chamber, see figure SP. The Wireless Communications Test Set was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where all test equipments were controlled by a computer.




Figure SP

Test Method:

The measurement was performed accordance with section 2.2.12 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

1 The maximum spurious emissions were searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.

2 Levels of EUT's transmitter harmonics and suspicious signals were recorded.

3 The recorded levels were corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration was made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.


4 The corrected values of radiated spurious emissions indicated as EIRP are reported.

Note:


1 The investigated ARFCNs are 190 (836.6 MHz) and 661 (1880.0 MHz).

2 The investigated frequency range is 30 MHz ~ 18 GHz.

Test Results for GSM mode:




S190VF for GSM mode




S190HF for GSM mode

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




S190VT for GSM mode




S190HT for GSM mode

FCC Parts 2, 22, 24
Equipment: VI-3


REPORT NO.: I08GE6990-FCC-EMC




S661VF for GSM mode



S661HF for GSM mode



S661VT for GSM mode




S661HT for GSM mode


FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC

Test Results for GPRS mode:




S190VF for GPRS mode




S190HF for GPRS mode

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




S190VT for GPRS mode




S190HT for GPRS mode

FCC Parts 2, 22, 24
Equipment: VI-3


REPORT NO.: I08GE6990-FCC-EMC




S661VF for GPRS mode



S661HF for GPRS mode



S661VT for GPRS mode



S661HT for GPRS mode

4.2 Radiated RF Power Output and ERP

Specifications:	2.1046,24.232,22.913(a)					
Date of Tests	2009-1-14					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 190, 251, 512, 661 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2010-01-09	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-16	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

(a) Radiated RF Power Output

According to Part 24.232(b), i.e., Mobile/portable stations are limited to 2 watts EIRP peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications, so the limit level is 2 W or 33 dBm.

(b) ERP

According to Part 22.913(a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

Limits for Radiated RF Power Output

Frequency range	Limit Level (EIRP) / Resolution Bandwidth
TX channel	33dBm/1MHz

Limits for ERP

Frequency range	Limit Level (ERP)
TX channel	7W

Test Setup:

The EUT was set in an anechoic chamber, which is connected to the Wireless Communications Test Set located outside the chamber over the air. The test was done using an automated test system, where all test equipments were controlled by a computer.

Test Method

The measurement was performed accordance with section 2.2.17 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

1 The maximum power was searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.

2 The measured levels are EIRP values corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration is made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.

3 The corrected maximum levels were reported for EIRP values, and ERP values can be calculated from EIRP values.

Note:

$ERP\text{ dBm} = EIRP\text{ dBm} - 2.15\text{dB}$.

ERP Value for GSM 850 band mode:

ARFCN	Frequency [MHz]	ERP [dBm]
128	824.228457	19.67
190	836.653307	21.36
251	848.877756	22.84

EIRP Value for GSM 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.100200	21.19
661	1879.919840	22.15
810	1909.899800	23.92

ERP Value for GPRS 850 band mode:

ARFCN	Frequency [MHz]	ERP [dBm]
512	824.228457	19.59
661	836.653307	21.37
810	848.877756	22.51

EIRP Value for GPRS 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
128	1850.100200	22.34
190	1880.080160	23.33
251	1909.899800	25.39

4.3 Occupied bandwidth

Specifications:	2.1049,22.917(b),24.238(b)					
Date of Test	2009-1-7					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 190, 251, 512, 661 and 810					
Test Results:	--					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2010-01-09	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-16	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Test Setup

The situation under which maximum EIRP values were found in the measurement of the radiated RF power output was used to determine the 99% occupied bandwidth. The Wireless Communications Test Set was used to set the TX channel, power level and modulation.

Test Method


The 99% occupied bandwidth was calculated from the spectrum analyzer. Markers in the spectrum analyzer were then placed between the calculated frequencies to show the calculated 99% power band.

Note: --

Results data of GSM mode:

EUT channel	99% occupied bandwidth [kHz]
128	244
190	244
251	242
512	244
661	240
810	242


Graphical results for GSM mode:




Channel 128

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




Channel 190



Channel 251


FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Date: 7. JAN. 2009 10:37:46

Channel 512




Date: 7. JAN. 2009 10:37:01

Channel 661

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Channel 810


Results data of GPRS mode:

EUT channel	99% occupied bandwidth [kHz]
128	252
190	252
251	252
512	248
661	252
810	248


Graphical results for GPRS mode:

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




Channel 128




Channel 190

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




Channel 251




Channel 512

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Channel 661



Channel 810

4.4 Frequency Stability over Temperature Variation

Specifications:	2.1055,22.355,24.235					
Date of Test	2009-1-12					
Test conditions:	Ambient Temperature:-30℃-50℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communication s Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
561	Temperature Chamber	Terchy Environmental Technology LTD.	MHU-800SR	84121202	2009-05-06	Normal
111835	Wireless Communication s Test Set	R&S	CMU200	1100000802	--	Normal
Limit						
Frequency deviation [ppm]		±2.5				

Test Setup

The EUT was placed in a temperature chamber, demonstrated as figure T. The wireless communications test set (test simulator) was used to set the TX channel and power levels, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure T: setup for measurement of frequency stability over temperature variation

Test Method

1. The EUT was turned off and placed in the temperature chamber.
2. The temperature of the chamber was set to -30℃ and allowed to stabilize.
3. The EUT temperature was allowed to stabilize for 45 minutes.
4. The EUT was turned on and set to transmit with 8960.
5. The maximum transmit frequency deviation during one minute period was measured by Wireless Communications Test Set.
6. The steps 3-5 were repeated for -20℃, -10℃, 0℃, 10℃, 20℃, 30℃, 40℃ and 50℃.

Test results data for GSM mode:

Channel 190:

Temperature[℃]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-21	-0.025100	Pass
-20	-22	-0.026300	Pass
-10	-21	-0.025100	Pass
0	-23	-0.027490	Pass
10	-25	-0.029880	Pass
20	-26	-0.031080	Pass
30	-25	-0.029880	Pass
40	-20	-0.023910	Pass
50	-21	-0.025100	Pass

Channel 661:

Temperature[℃]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-10	-0.005320	Pass
-20	-11	-0.005850	Pass
-10	-13	-0.006910	Pass
0	-15	-0.007980	Pass
10	-11	-0.005850	Pass
20	-17	-0.009040	Pass
30	-13	-0.006910	Pass
40	-16	-0.008510	Pass
50	-15	-0.007980	Pass

Test results data for GPRS mode:

Channel 190:

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	21	0.025102	Pass
-20	23	0.027492	Pass
-10	19	0.022711	Pass
0	23	0.027492	Pass
10	20	0.023906	Pass
20	28	0.033469	Pass
30	29	0.034664	Pass
40	25	0.029883	Pass
50	25	0.029883	Pass

Channel 661:

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-13	-0.006910	Pass
-20	-11	-0.005850	Pass
-10	-10	-0.005320	Pass
0	-15	-0.007980	Pass
10	-19	-0.010110	Pass
20	-20	-0.010640	Pass
30	-16	-0.008510	Pass
40	-19	-0.010110	Pass
50	-17	-0.009040	Pass

4.5 Frequency Stability over Voltage Variation

Specifications:	2.1055,22.355,24.235					
Date of Test	2009-1-7					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communication s Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communication s Test Set	R&S	CMU200	1100000802	--	Normal
7982	DC Power Source	4NIC	DH1715A-3	004224	--	Normal
Limit						
Frequency deviation [ppm]		±2.5				

Test Setup

The EUT was placed in a shielding chamber and powered by the dummy battery which is connected to a DC power source, demonstrated as figure V. The wireless communications test set was used to set the TX channel and power level, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure V: test setup for measurement of frequency stability over voltage variation

Test Results data for GSM mode:

Channel 190:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	4.2	15	0.017930	Pass
Cut-off point	3.5	16	0.019125	Pass

Channel 661:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	4.2	24	0.012766	Pass
Cut-off point	3.5	26	0.013830	Pass

Test Results data for GPRS mode:

Channel 190:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	4.2	19	0.022711	Pass
Cut-off point	3.5	21	0.025102	Pass

Channel 661:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	4.2	17	0.009043	Pass
Cut-off point	3.5	18	0.009574	Pass


4.6 Conducted RF Power Output

Specifications:	2.1046,22.913(a),24.232(c)					
Date of Tests	2009-1-7					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 190, 251, 512, 661 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2010-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limits for Radiated RF Power Output	
Frequency range	Limit Level (EIRP) /Resolution Bandwidth
TX channel	33dBm/1MHz
Limits for ERP	
Frequency range	Limit Level (ERP)
TX channel	7W

Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

Test Results for GSM mode:

ERP Value for GSM 850 band:

ARFCN	Peak output power [dBm]
128	29.24
190	28.77
251	28.38

EIRP Value for GSM 1900 band:

ARFCN	Peak output power [dBm]
512	27.11
661	27.62
810	27.24

Test Results for GPRS mode:

ERP Value for GPRS 850 band:

ARFCN	Peak output power [dBm]
128	29.25
190	28.76
251	28.27

EIRP Value for GPRS 1900 band:

ARFCN	Peak output power [dBm]
512	26.99
661	27.50
810	27.18

4.7 Conducted Spurious Emission

Specifications:	2.1051,22.917,24.238					
Date of Tests	2009-1-7					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2010-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level / Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26)



Test Method

The measurement was performed accordance with section 2.2.13 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment under test, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Note: --


Test Results for GSM mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
--	--

FCC Parts 2, 22, 24
Equipment: VI-3


REPORT NO.: I08GE6990-FCC-EMC

Graphical results for GSM mode:



Date: 7.JAN.2009 12:40:30

Channel 190



Date: 7.JAN.2009 12:38:31

Channel 661


FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC

Test Results for GPRS mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
--	--


Graphical results for GPRS mode:



Channel 190

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Channel 661

4.8 Band Edge

Specifications:	2.1051, 24.238, 2.1053, 22.917					
Date of Tests	2009-1-7					
Test conditions:	Ambient Temperature:15℃-35℃ Relative Humidity:30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 251, 512 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2010-01-11	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2010-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level / Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

Test Results:

GSM mode:


Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
128 Left band edge	823.978557	-13.06
251 Right band edge	849.019438	-13.47
512 Left band edge	1849.996590	-16.19
810 Right band edge	1910.02144	-17.72

GPRS mode:


Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
128 Left band edge	823.994589	-13.05
251 Right band edge	849.007414	-13.99
512 Left band edge	1849.978560	-16.64
810 Right band edge	1910.021440	-17.39

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




GSM channel 128 Left band edge




GSM channel 251 Right band edge

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




GSM channel 512 Left band edge




GSM channel 810 Right band edge

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC




GPRS channel 128 Left band edge



GPRS channel 251 Right band edge


FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Date: 7.JAN.2009 13:26:40

GPRS channel 512 Left band edge



Date: 7.JAN.2009 13:19:44

GPRS channel 810 Right band edge

Annex A External Photos



Front view



Back view

FCC Parts 2, 22, 24
Equipment: VI-3

REPORT NO.: I08GE6990-FCC-EMC



Adaptor and Cable




Battery




Earphone


Annex B Internal Photos




Main board (face)



Main board (back)



Adaptor (face)



Adaptor (back)

ANNEX C Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

_____ The End of this Report _____

CTL Test Report