

Date: 2004-03-06  
No.: HM112733

## TEST REPORT

Page 1 of 21

### FCC PART 15 SUBPART C CERTIFICATION REPORT FOR LOW POWER TRANSMITTER

#### TEST REPORT No.: HM112733

Equipment Under Test [EUT]: Double Tube 5-in-1 Lantern With Remote Control  
Model Number: 0-889767-117  
Applicant: Overseas Win Limited.  
FCC ID: RWK-889767

Date: 2004-03-06  
No.: HM112733

## TEST REPORT

Page 2 of 21

### CONTENT:

Cover	Page 1 of 21
Content	Page 2-3 of 21
Conclusion	Page 4 of 21

#### **1.0 General Details**

1.1	Test Laboratory	Page 5 of 21
1.2	Applicant Details	Page 5 of 21
	Applicant	
	HKSTC Code Number for Applicant	
	Manufacturer	
1.3	Equipment Under Test [EUT]	Page 6 of 21
	Description of EUT operation	
1.4	Date of Order	Page 6 of 21
1.5	Submitted Sample	Page 6 of 21
1.6	Test Duration	Page 6 of 21
1.7	Country of Origin	Page 6 of 21
1.8	Additional Information of EUT	Page 7 of 21

#### **2.0 Technical Details**

2.1	Investigations Requested	Page 8 of 21
2.2	Test Standards and Results Summary	Page 8 of 21

#### **3.0 Test Results**

3.1	Emission	Page 9-13 of 21
3.2	Bandwidth Measurement	Page 14-15 of 21

Date: 2004-03-06  
No.: HM112733

## **TEST REPORT**

Page 3 of 21

### **Appendix A**

List of Measurement Equipment

Page 16 of 21

### **Appendix B**

Duty Cycle Correction During 100 msec

Page 17-18 of 21

### **Appendix C**

Periodic Operation

Page 19 of 21

### **Appendix D**

Photographs

Page 20-21 of 21

Date: 2004-03-06  
No.: HM112733

## TEST REPORT

Page 4 of 21

### CONCLUSION

The submitted product was deemed to have COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

---

Verified by  
Ivan Toa

---

K C Lee  
for Chief Executive

Date: 2004-03-06

## **TEST REPORT**

Page 5 of 21

No.: HM112733

### **1.0 General Details**

#### **1.1 Test Laboratory**

The Hong Kong Standards and Testing Centre Ltd.  
EMC Laboratory  
10 Dai Wang Street, Taipo Industrial Estate  
New Territories, Hong Kong

Telephone: 852 2666 1888  
Fax: 852 2664 4353

#### **1.2 Applicant Details**

##### **Applicant**

Overseas Win Limited.  
Room 1912, 19/F., Hong Kong Plaza,  
188 Connaught Road West, Hong Kong.

HKSTC Code Number for Applicant

**OVW001**

##### **Manufacturer**

Teng Long Outdoor Implement Co., Ltd.  
Xia Lu Jia Village, Yinjiang Town,  
Yinjiang District, Ningbo City, Zhejiang, China

Date: 2004-03-06

## TEST REPORT

Page 6 of 21

No.: HM112733

### **1.3 Equipment Under Test [EUT]**

#### **Description of Sample**

Product: Double Tube 5-in-1 Lantern With Remote Control  
Manufacturer: Teng Long Outdoor Implement Co., Ltd.  
Brand Name: Northwest Territory  
Model Number: 0-889767-117  
Input Voltage: 12Vd.c ("A23" size battery x 1)

#### **1.3.1 Description of EUT Operation**

The Equipment Under Test (EUT) is an Overseas Win Limited, Double Tube 5-in-1 Lantern With Remote Control. The EUT is to transmit RF signal while each button is being pressed, Modulation by Data Code type is pulses modulation.

### **1.4 Date of Order**

2004-02-13

### **1.5 Submitted Sample(s):**

1 Sample per model

### **1.6 Test Duration**

2004-02-25

### **1.7 Country of Origin**

China

Date: 2004-03-06

## TEST REPORT

Page 7 of 21

No.: HM112733

### 1.8 Additional Information of EUT

	Submitted	Not Available
User Manual	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Part List	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Circuit Diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Printed Circuit Board [PCB] Layout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Block diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>
FCC ID Label	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Date: 2004-03-06

## **TEST REPORT**

Page 8 of 21

No.: HM112733

### **2.0 Technical Details**

#### **2.1 Investigations Requested**

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

#### **2.2 Test Standards and Results Summary Tables**

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.231a	ANSI C63.4:2003	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2003	Class B	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Note: N/A - Not Applicable


**3.0 Test Results****3.1 Emission****3.1.1 Radiated Emissions (30 – 1000MHz)**

Test Requirement:	FCC 47CFR 15.109 Class A
Test Method:	ANSI C63.4:2003
Test Date:	2004-02-25
Mode of Operation:	On mode

**Test Method:**

The sample was placed 0.8m above the ground plane on the OATS \*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

**Test Setup:**

Date: 2004-03-06

**TEST REPORT**

Page 10 of 21

No.: HM112733

**Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.231a]:**

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [ $\mu$ V/m]	Field Strength of Fundamental Emission [Average] [ $\mu$ V/m]
40.66-40.70	1,000	100
70-130	500	50
130-174	500 to 1,500 *	50 to 150 *
174-260	1,500	150
260-470	1,500 to 5,000 *	150 to 500 *
Above 470	5,000	500

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu$ V/m at 3 meters = $56.81818(F)-6136.3636$ ; for the band 260-470 MHz,  $\mu$ V/m at 3 meters = $41.66667(F)-7083.3333$ . The maximum permissitted unwanted emission level is 20dB below the maximum permitted fundamental level.

**Results:**

Field Strength of Fundamental Emissions Peak Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
433.40	55.3	20.7	76.0	6309.6	109,750.1	Horizontal

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
866.80	31.4	29.1	60.5	1059.3	10,975.0	Horizontal
+ 1300.20	29.7	34.3	64.0	1584.9	10,975.0	Vertical
1733.60	< 1.0	32.2	< 33.2	< 45.7	5,000.0	Vertical
2167.00	< 1.0	38.8	< 39.8	< 97.7	5,000.0	Vertical
2600.40	< 1.0	17.4	< 18.4	< 8.3	10,975.0	Vertical
3033.80	< 1.0	17.2	< 18.2	< 8.1	10,975.0	Vertical
3467.20	< 1.0	18.8	< 19.8	< 9.8	10,975.0	Vertical
+ 3900.60	< 1.0	19.7	< 20.7	< 10.8	5,000.0	Vertical
+ 4334.00	< 1.0	20.6	< 21.6	< 12.0	10,975.0	Vertical

Date: 2004-03-06

**TEST REPORT**

Page 11 of 21

No.: HM112733

**Results:**

Field Strength of Fundamental Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
433.40	38.3	20.7	59.0	891.3	10,975.0	Horizontal

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
866.80	14.4	29.1	43.5	149.6	1,097.5	Horizontal
+	1300.20	12.7	34.3	47.0	223.9	1,097.5
	1733.60	< 1.0	32.2	< 33.2	< 45.7	500.0
	2167.00	< 1.0	38.8	< 39.8	< 97.7	500.0
	2600.40	< 1.0	17.4	< 18.4	< 8.3	1,097.5
	3033.80	< 1.0	17.2	< 18.2	< 8.1	1,097.5
	3467.20	< 1.0	18.8	< 19.8	< 9.8	1,097.5
	+	3900.60	< 1.0	19.7	< 20.7	< 10.8
	+	4334.00	< 1.0	20.6	< 21.6	< 12.0

**Remarks:**

\*: Adjusted by Duty Cycle = -17dB

FCC Limit for Average Measurement =  $41.6667(309.98\text{MHz})-7083.3333=5832.5\mu\text{V/m}$ 

+: Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 were not adjusted for averaging and the limit of FCC Rules Part 15 Section 15.209 were applied

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz  $\pm 5.7\text{dB}$

Date: 2004-03-06

## TEST REPORT

Page 12 of 21

No.: HM112733

### Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu$ V/m]
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

### Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
NO EMISSION DETECTED WITHIN 20dB OF THE FCC LIMITS						

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz  $\pm 5.7$ dB

Date: 2004-03-06

## TEST REPORT

Page 13 of 21

No.: HM112733

### 3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.107
Test Method:	ANSI C63.4:2003
Test Date:	2004-02-25
Mode of Operation:	N/A

**Results:** N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.

Date: 2004-03-06

## TEST REPORT

Page 14 of 21

No.: HM112733

### 3.2 20dB Bandwidth of Fundamental Emission

Test Requirement:

FCC 47 CFR 15.231a

Test Method:

ANSI C63.4:2003 (Section 13.1.7)

Test Date:

2004-02-25

Mode of Operation:

On mode

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.

Date: 2004-03-06

## TEST REPORT

Page 15 of 21


No.: HM112733

### Limits for 20 dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20dB Bandwidth [KHz]	FCC Limits * [KHz]
433.1	188	775

\*: FCC Limit for Bandwidth measurement = (0.25%)(Center Frequency)  
=(0.0025)(309.98)  
=775KHz

### 20dB Bandwidth of Fundamental Emission



Date: 2004-03-06

# TEST REPORT

Page 16 of 21

No.: HM112733

## Appendix A

### Test Equipment Audit

#### Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	14/03/03
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	14/03/03
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	14/03/03
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	14/03/03
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	14/03/03
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	14/03/03
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM020	HORN ANTENNA	EMCO	3115	4032	19/07/00
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	04/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/11/02
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	18/12/01
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	02/08/03
EM194	BICONILOG ANTENNA	EMCO	3142B	1795	14/05/02
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

#### Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	18/10/02
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	01/10/02
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	CM
EM142	PULES LIMITER	R & S	ESH3Z2	357.8810.52	03/07/02
EM181	EMI TEST RECEIVER	R & S	ESIB7	100072	28/11/01
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	18/10/02
EM197	LISN	EMCO	4825/2	1193	08/04/03

Remarks:

CM      Corrective Maintenance  
N/A     Not Applicable or Not Available  
TBD    To Be Determined

**Appendix B****Duty Cycle Correction During 100msec**


Each function key sends a different series of characters, but each packet period (27.75msec) never exceeds a series of 39 long (100 $\mu$ sec) or short (50 $\mu$ sec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered  $39 \times 100\mu\text{sec} / 27.75\text{msec} = 14\%$  duty cycle. Figure A through C show the characteristics of the pulses train for one of these functions.

Remarks:

Duty Cycle Correction =  $20\log(0.14) = -17\text{dB}$

The following figures [Figure A to Figure C] showed the characteristics of the pulse train for one of these functions.

**Figure A [Pulse Train]**



Date: 2004-03-06

## TEST REPORT

Page 18 of 21

No.: HM112733

Figure B [Long Pulse]





Figure C [Short Pulse]



Date: 2004-03-06

No.: HM112733

## TEST REPORT

Page 19 of 21

### Appendix C

#### **Periodic Operation [FCC 47CFR 15.231a]**

According to FCC 47CFR15.231a. A transmitter manually activated must automatically deactivate within not more than 5 seconds of being released. The transmitter is a 1 button transmitter. The EUT continues to transmit while the button is being pressed. The EUT ceases transmission almost immediately upon being released and appears to finish the current packet being transmitted. Therefore the longest period of time the transmitter should take to deactivate is a packet length.

Date: 2004-03-06  
No.: HM112733

## TEST REPORT

Page 20 of 21

### Appendix D

#### Photographs of EUT

Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Date: 2004-03-06  
No.: HM112733

## TEST REPORT

Page 21 of 21

### Photographs of EUT

Measurement of Radiated Emission Test Set Up



End of Document