

Test Laboratory: BTL Inc.

Date: 2024/5/22

**W07\_2.4G SRD\_CH36\_Horizontal Up\_5mm****DUT: USB Dongle;**

Communication System: UID 0, BT (0);

Frequency: 2474 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2474$  MHz;  $\sigma = 1.848$  S/m;  $\epsilon_r = 39.553$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.9 °C; Liquid Temperature: 22.2 °C

DASY Configuration:

- Probe: EX3DV4 - SN7693; ConvF(8.33, 8.33, 8.33) @ 2474 MHz; Calibrated: 2023/10/31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn1390; Calibrated: 2023/11/20
- Phantom: ELI v5.0\_Left; Type: QDOVA002AA; Serial: TP:1222
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

**Area Scan (5x9x1):** Measurement grid:  $dx=12$ mm,  $dy=12$ mm

Maximum value of SAR (measured) = 0.147 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 8.918 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.254 W/kg

**SAR(1 g) = 0.112 W/kg; SAR(10 g) = 0.052 W/kg**

Maximum value of SAR (measured) = 0.192 W/kg

