

# FCC RF EXPOSURE REPORT

**FCC ID: RWO-RZ040291**

**Project No.** : 1903C142  
**Equipment** : Gaming Headset  
**Test Model** : RZ04-0291  
**Series Model** : RZ04-0291XXXX-XXXX (X: Can be 0-9, A-Z)  
**Applicant** : Razer Inc.  
**Address** : 201 3rd Street, Suite 900, San Francisco, CA 94103 USA  
  
**According** : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

**REPORT ISSUED HISTORY**

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 19, 2019

## 1. GENERAL SUMMARY

Equipment : Gaming Headset  
Brand Name : RAZER  
Test Model : RZ04-0291  
Series Model : RZ04-0291XXXX-XXXX (X: Can be 0-9, A-Z)  
Applicant : Razer Inc.  
Manufacturer : Razer (Asia-Pacific) Pte.,Ltd.  
Address : 514 Chai Chee Lane, #07-01-06, Singapore 469029  
Factory : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD  
Address : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China  
Date of Test : Apr. 13, 2019 ~ Jun. 26, 2019  
Test Sample : Engineering Sample No.: D190403813  
Standards : KDB447498 D01 General RF Exposure Guidance v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-4-1903C142) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

Table for Filed Antenna:

For WLAN 2.4GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	3.40

For RLAN 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	3.92

## 2. GENERAL CONCLUSION:

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and  $\leq$  50 mm**

MHz	5	10	15	20	25	30	35	40	45	50	mm	SAR Test Exclusion Thresholds (mW)
150	39	77	116	155	194	232	271	310	349	387		
300	27	55	82	110	137	164	192	219	246	274		
450	22	45	67	89	112	134	157	179	201	224		
835	16	33	49	66	82	98	115	131	148	164		
900	16	32	47	63	79	95	111	126	142	158		
1500	12	24	37	49	61	73	86	98	110	122		
1900	11	22	33	44	54	65	76	87	98	109		
2450	10	19	29	38	48	57	67	77	86	96		
3600	8	16	24	32	40	47	55	63	71	79		
5200	7	13	20	26	33	39	46	53	59	66		
5400	6	13	19	26	32	39	45	52	58	65		
5800	6	12	19	25	31	37	44	50	56	62		

Maximum measured transmitter power:

For WLAN 2.4GHz:

Maximum Average Output Power (dBm)	Maximum Average Output Power (mW)	Limit (mW)
3.58	2.28	10

For RLAN 5GHz:

Maximum Output Power (dBm)	Maximum Output Power (mW)	Limit (mW)
1.68	1.47	10

The maximum measured average output power of this EUT is 2.28mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

**End of Test Report**