

FCC Radio Test Report

FCC ID: RWO-RZ0902386

This report concerns (check one): ☒ Original Grant ☐ Class I Change ☐ Class II Change

Project No. : 1803C063
Equipment : Notebook
Test Model : RZ09-02386
Series Model : RZ09-02385
Applicant : Razer Inc.
Address : 201 3rd Street, Suite 900, San Francisco, CA
94103, USA

Date of Receipt : Mar. 08, 2018
Date of Test : Mar. 09, 2018 ~ Apr. 02, 2018
Issued Date : May 22, 2018
Tested by : BTL Inc.

Testing Engineer : Welly Zhou
(Welly Zhou)

Technical Manager : Shawn Xiao
(Shawn Xiao)

Authorized Signatory : Steven Lu
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	11
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.5 DESCRIPTION OF SUPPORT UNITS	12
4 . EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.1.6 EUT TEST CONDITIONS	14
4.1.7 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	15
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 EUT TEST CONDITIONS	18
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	18
4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)	18
4.2.9 TEST RESULTS (ABOVE 1000MHZ)	18
5 . BANDWIDTH TEST	19
5.1 APPLIED PROCEDURES / LIMIT	19
5.1.1 TEST PROCEDURE	19
5.1.2 DEVIATION FROM STANDARD	19
5.1.3 TEST SETUP	19
5.1.4 EUT OPERATION CONDITIONS	19
5.1.5 EUT TEST CONDITIONS	19
5.1.6 TEST RESULTS	19
6 . MAXIMUM OUTPUT POWER TEST	20

Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	20
6.1.1 TEST PROCEDURE	20
6.1.2 DEVIATION FROM STANDARD	20
6.1.3 TEST SETUP	20
6.1.4 EUT OPERATION CONDITIONS	20
6.1.5 EUT TEST CONDITIONS	20
6.1.6 TEST RESULTS	20
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	21
7.1 APPLIED PROCEDURES / LIMIT	21
7.1.1 TEST PROCEDURE	21
7.1.2 DEVIATION FROM STANDARD	21
7.1.3 TEST SETUP	21
7.1.4 EUT OPERATION CONDITIONS	21
7.1.5 EUT OPERATION CONDITIONS	21
7.1.6 TEST RESULTS	21
8 . POWER SPECTRAL DENSITY TEST	22
8.1 APPLIED PROCEDURES / LIMIT	22
8.1.1 TEST PROCEDURE	22
8.1.2 DEVIATION FROM STANDARD	22
8.1.3 TEST SETUP	22
8.1.4 EUT OPERATION CONDITIONS	22
8.1.5 EUT TEST CONDITIONS	22
8.1.6 TEST RESULTS	22
9 . MEASUREMENT INSTRUMENTS LIST	23
APPENDIX A - CONDUCTED EMISSION	25
APPENDIX B - RADIATED EMISSION (9KHZ TO 30MHZ)	30
APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)	39
APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)	52
APPENDIX E - BANDWIDTH	65
APPENDIX F - MAXIMUM OUTPUT POWER TEST	70
APPENDIX G - ANTENNA CONDUCTED SPURIOUS EMISSION	72
APPENDIX H - POWER SPECTRAL DENSITY TEST	80

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-2-1803C063	Original Issue.	May 11, 2018
MDG1805037	Updated Peak Output Power of limit.	May 22, 2018

1. CERTIFICATION

Equipment : Notebook
Brand Name : RAZER
Test Model : RZ09-02386
Series Model : RZ09-02385
Applicant : Razer Inc.
Manufacturer : Razer Inc.
Address : 201 3rd Street, Suite 900, San Francisco, CA 94103, USA
Factory : BYD Precision Manufacture Co., Ltd.
Address : No.3001, Baohe Road, Baolong industrial, Longgang Street , Longgang Zone, Shenzhen
Date of Test : Mar. 09, 2018 ~ Apr. 02, 2018
Test Sample : Engineering Sample NO. D180301983 for conducted, D180302153 for radiated.
Standard(s) : FCC Part15, Subpart C (15.247)
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1803C063) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP according to the ISO-17025 quality assessment standard and technical standard(s).

Test result included in this report is only for the Bluetooth LE part.

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(b)(3)	Peak Output Power	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	
15.247(d)/15.205/15.209	Transmitter Radiated Emissions	PASS	

Note:

(1)" N/A" denotes test is not applicable to this device.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 854385

BTL's designation number for FCC: CN5020

2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) $k=1.96$ or $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)). Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$.

The BTL measurement uncertainty as below table:

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	2.32

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Notebook	
Brand Name	RAZER	
Test Model	RZ09-02386	
Series Model	RZ09-02385	
Model Difference	Please refer to note 2.	
Hardware Version	C1_MB	
Firmware Version	Windows 10	
Product Description	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK
	Bit Rate of Transmitter	
	Output Power (Max.)	3.89 dBm (1Mbps) 3.49 dBm (2Mbps)
Power Source	DC voltage supplied from AC/DC adapter.	
Power Rating	Please refer to note 2.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2.

Model	RZ09-02386	RZ09-02385
Graphics Card	N17E-G2 MAX-Q	N17E-G1 MAX-Q
Adapter	RC30-024801	#1 RC30-024801 #2 RC30-0238
Power Rating	I/P: AC100-240V, 3.6V 50/60Hz O/P: DC 19.5V, 11.8A	#1 I/P: AC100-240V, 3.6V 50/60Hz O/P: DC 19.5V, 11.8A #2 I/P: AC 100-240V, 2.5A 50/60Hz O/P: DC 19.5V/10.26A

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3. Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
2	Molex	N/A	Internal	N/A	3.06

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode NOTE (1)

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX Mode NOTE (1)

Note:

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The Measurement is the worst case.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of BT LE

Test Software Version	DRTU		
Frequency (MHz)	2402	2440	2480
BT LE(1Mbps)	2	0	0
BT LE(2Mbps)	1	-1	-1

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	2m	DC Cable
2	NO	NO	1m	AC Cable

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 EUT TEST CONDITIONS

Temperature: 24°C Relative Humidity: 60% Test Voltage: N/A

4.1.7 TEST RESULTS

Please refer to the Appendix A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform.In this case, a “ * ” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) “ N/A ” denotes test is not applicable to this device.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	RBW 1MHz VBW 3MHz peak detector for Pk value RMS detector for AV value

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.2.6 EUT TEST CONDITIONS

Temperature: 22°C Relative Humidity: 56% Test Voltage: AC 120V/60Hz

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix C.

4.2.9 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 24°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

5.1.6 TEST RESULTS

Please refer to the Appendix E.

6. MAXIMUM OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 24°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

6.1.6 TEST RESULTS

Please refer to the Appendix F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = 10 ms.
- Offset=antenna gain+cable loss

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT OPERATION CONDITIONS

Temperature: 24°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

7.1.6 TEST RESULTS

Please refer to the Appendix G.

8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=3KHz, VBW=10 KHz, Sweep time = auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 EUT TEST CONDITIONS

Temperature: 24°C Relative Humidity: 60% Test Voltage: AC 120V/60Hz

8.1.6 TEST RESULTS

Please refer to the Appendix H.

9. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 11, 2019
2	LISN	EMCO	3816/2	52765	Mar. 11, 2019
3	50Ω Terminator	SHX	TF2-3G-A	8122901	Mar. 11, 2019
4	TWO-LINE V-NETWORK	R&S	ENV216	101447	Mar. 11, 2019
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	Cable	N/A	RG223	12m	Oct. 19, 2018

Radiated Emission Measurement - Below 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 11, 2019
2	Amplifier	HP	8447D	2944A09673	Oct. 19, 2018
3	Receiver	Agilent	N9038A	MY52130039	Aug. 20, 2018
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	Jun. 26, 2018
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Antenna	EM	EM-6876-1	230	Feb. 07, 2019

Radiated Emission Measurement - Above 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	Mar. 11, 2019
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 08, 2018
3	Amplifier	Agilent	8449B	3008A02274	Mar. 11, 2019
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 11, 2019
5	Receiver	Agilent	N9038A	MY52130039	Aug. 20, 2018
6	Controller	CT	SC100	N/A	N/A
7	Controller	MF	MF-7802	MF780208416	N/A
8	Cable	emci	EMC104-SM-SM-1 2000(12m)	N/A	Jun. 26, 2018
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

6dB Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

Peak Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	ANRITSU	ML2495A	1128009	Mar. 26, 2018
2	Pulse Power Sensor	ANRITSU	MA 2411B	1027500	Mar. 26, 2018

Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018


Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

Remark: "N/A" denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

APPENDIX A - CONDUCTED EMISSION

Test Mode : Normal Link_Adapter: RC30-024801


Line



No.	Freq.	Reading	Correct	Measure	Limit	Margin	Detector	Comment
	MHz	Level	Factor	ment				
1 *	0.1545	53.37	9.75	63.12	65.75	-2.63	QP	
2	0.1545	41.70	9.75	51.45	55.75	-4.30	AVG	
3	0.1725	48.80	9.74	58.54	64.84	-6.30	QP	
4	0.1725	35.60	9.74	45.34	54.84	-9.50	AVG	
5	0.2130	50.07	9.72	59.79	63.09	-3.30	QP	
6	0.2130	25.30	9.72	35.02	53.09	-18.07	AVG	
7	0.3480	38.80	9.75	48.55	59.01	-10.46	QP	
8	0.3480	25.80	9.75	35.55	49.01	-13.46	AVG	
9	0.5235	42.20	9.76	51.96	56.00	-4.04	QP	
10	0.5235	20.90	9.76	30.66	46.00	-15.34	AVG	
11	0.9825	33.80	9.77	43.57	56.00	-12.43	QP	
12	0.9825	26.70	9.77	36.47	46.00	-9.53	AVG	

Test Mode : Normal Link_Adapter: RC30-024801


Neutral



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1635	49.80	9.64	59.44	65.28	-5.84	QP	
2	0.1635	37.00	9.64	46.64	55.28	-8.64	AVG	
3	0.3750	39.10	9.65	48.75	58.39	-9.64	QP	
4	0.3750	27.30	9.65	36.95	48.39	-11.44	AVG	
5	0.4605	37.30	9.65	46.95	56.68	-9.73	QP	
6	0.4605	26.70	9.65	36.35	46.68	-10.33	AVG	
7	0.5775	35.60	9.66	45.26	56.00	-10.74	QP	
8 *	0.5775	31.40	9.66	41.06	46.00	-4.94	AVG	
9	0.8205	34.10	9.66	43.76	56.00	-12.24	QP	
10	0.8205	22.40	9.66	32.06	46.00	-13.94	AVG	
11	1.2435	31.90	9.68	41.58	56.00	-14.42	QP	
12	1.2435	20.70	9.68	30.38	46.00	-15.62	AVG	

Test Mode : Normal Link_Adapter: RC30-0238


Line



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1635	52.14	9.78	61.92	65.28	-3.36	Peak	
2	0.1635	26.99	9.78	36.77	55.28	-18.51	AVG	
3	0.1995	48.60	9.76	58.36	63.63	-5.27	Peak	
4	0.1995	25.10	9.76	34.86	53.63	-18.77	AVG	
5	0.4920	44.23	9.72	53.95	56.13	-2.18	Peak	
6	0.4920	20.40	9.72	30.12	46.13	-16.01	AVG	
7 *	0.7483	44.11	9.81	53.92	56.00	-2.08	Peak	
8	0.7483	17.51	9.81	27.32	46.00	-18.68	AVG	
9	0.8924	41.54	9.85	51.39	56.00	-4.61	Peak	
10	0.8924	16.90	9.85	26.75	46.00	-19.25	AVG	
11	1.2074	40.72	9.87	50.59	56.00	-5.41	Peak	
12	1.2074	16.60	9.87	26.47	46.00	-19.53	AVG	

Test Mode : Normal Link_Adapter: RC30-0238

Neutral



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1635	53.06	9.67	62.73	65.28	-2.55	Peak	
2	0.1635	41.80	9.67	51.47	55.28	-3.81	AVG	
3	0.2805	48.05	9.65	57.70	60.80	-3.10	Peak	
4	0.2805	19.40	9.65	29.05	50.80	-21.75	AVG	
5 *	0.5954	44.12	9.66	53.78	56.00	-2.22	Peak	
6	0.5954	15.50	9.66	25.16	46.00	-20.84	AVG	
7	0.7481	43.83	9.71	53.54	56.00	-2.46	Peak	
8	0.7483	17.91	9.71	27.62	46.00	-18.38	AVG	
9	1.0634	42.28	9.75	52.03	56.00	-3.97	Peak	
10	1.0634	14.90	9.75	24.65	46.00	-21.35	AVG	
11	1.4010	41.09	9.77	50.86	56.00	-5.14	Peak	
12	1.4010	14.31	9.77	24.08	46.00	-21.92	AVG	

APPENDIX B - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode:	TX B MODE CHANNEL 01_Adapter: RC30-024801
------------	---


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0128	51.86	20.54	72.40	125.46	-53.06	AVG	
2		0.0323	54.23	19.23	73.46	117.42	-43.96	AVG	
3	*	0.0368	60.28	19.10	79.38	116.29	-36.91	AVG	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-024801


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2040	27.26	16.74	44.00	101.41	-57.41	AVG	
2	*	1.2098	24.33	15.72	40.05	65.95	-25.90	QP	
3		2.3962	18.62	15.28	33.90	69.54	-35.64	QP	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-024801


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0303	45.96	19.29	65.25	117.98	-52.73	AVG	
2	*	0.0366	53.32	19.10	72.42	116.34	-43.92	AVG	
3		0.0697	34.59	18.31	52.90	110.74	-57.84	AVG	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-024801

Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2971	25.69	16.62	42.31	98.15	-55.84	AVG	
2	*	1.2098	24.19	15.81	40.00	65.95	-25.95	QP	
3		2.4218	20.36	15.39	35.75	69.54	-33.79	QP	

Test Mode:	TX B MODE CHANNEL 01_Adapter: RC30-0238
------------	---


Ant 0°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment				
			dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.0128	51.86	20.54	72.40	125.46	-53.06	AVG	
2		0.0323	54.23	19.23	73.46	117.42	-43.96	AVG	
3	*	0.0368	60.28	19.10	79.38	116.29	-36.91	AVG	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-0238


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2040	27.26	16.74	44.00	101.41	-57.41	AVG	
2	*	1.2098	24.33	15.72	40.05	65.95	-25.90	QP	
3		2.3962	18.62	15.28	33.90	69.54	-35.64	QP	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-0238


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0303	45.96	19.29	65.25	117.98	-52.73	AVG	
2	*	0.0366	53.32	19.10	72.42	116.34	-43.92	AVG	
3		0.0697	34.59	18.31	52.90	110.74	-57.84	AVG	

Test Mode: TX B MODE CHANNEL 01_Adapter: RC30-0238

Ant 90°




No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2971	25.69	16.62	42.31	98.15	-55.84	AVG	
2	*	1.2098	24.19	15.81	40.00	65.95	-25.95	QP	
3		2.4218	20.36	15.39	35.75	69.54	-33.79	QP	

APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2402MHz _CH00_1Mbps_Adapter: RC30-024801

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	83.3500	51.84	-18.34	33.50	40.00	-6.50	Peak	
2	180.3500	45.91	-12.07	33.84	43.50	-9.66	Peak	
3	374.3500	38.34	-11.67	26.67	46.00	-19.33	Peak	
4	488.8100	40.98	-8.99	31.99	46.00	-14.01	Peak	
5	636.2500	33.44	-5.73	27.71	46.00	-18.29	Peak	
6	794.3600	30.29	-1.48	28.81	46.00	-17.19	Peak	

Test Mode:

TX 2402MHz _CH00_1Mbps_Adapter: RC30-024801


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	86.2600	49.00	-18.46	30.54	40.00	-9.46	Peak	
2 *	220.1200	50.99	-13.91	37.08	46.00	-8.92	Peak	
3	352.0400	45.83	-11.93	33.90	46.00	-12.10	Peak	
4	379.2000	46.22	-11.61	34.61	46.00	-11.39	Peak	
5	494.6300	38.26	-8.85	29.41	46.00	-16.59	Peak	
6	909.7900	31.39	1.22	32.61	46.00	-13.39	Peak	

Test Mode: TX 2440MHz _CH19_1Mbps_Adapter: RC30-024801


Vertical



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	86.2600	52.55	-18.46	34.09	40.00	-5.91	Peak	
2	184.2300	46.54	-12.38	34.16	43.50	-9.34	Peak	
3	372.4100	38.25	-11.69	26.56	46.00	-19.44	Peak	
4	456.8000	40.27	-9.77	30.50	46.00	-15.50	Peak	
5	643.0400	33.37	-5.61	27.76	46.00	-18.24	Peak	
6	832.1900	31.56	-0.48	31.08	46.00	-14.92	Peak	

Test Mode: TX 2440MHz _CH19_1Mbps_Adapter: RC30-024801

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	150.2800	45.08	-13.51	31.57	43.50	-11.93	Peak	
2 *	221.0900	51.46	-13.93	37.53	46.00	-8.47	Peak	
3	396.6600	42.92	-11.40	31.52	46.00	-14.48	Peak	
4	454.8600	39.96	-9.82	30.14	46.00	-15.86	Peak	
5	741.9800	31.42	-2.68	28.74	46.00	-17.26	Peak	
6	934.0400	29.49	1.69	31.18	46.00	-14.82	Peak	

Test Mode: TX 2480MHz _CH39_1Mbps_Adapter: RC30-024801

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	85.2900	52.49	-18.41	34.08	40.00	-5.92	Peak	
2	184.2300	46.68	-12.38	34.30	43.50	-9.20	Peak	
3	392.7800	41.08	-11.45	29.63	46.00	-16.37	Peak	
4	485.9000	45.21	-9.06	36.15	46.00	-9.85	Peak	
5	553.8000	38.15	-7.62	30.53	46.00	-15.47	Peak	
6	802.1200	32.90	-1.30	31.60	46.00	-14.40	Peak	

Test Mode:	TX 2480MHz _CH39_1Mbps_Adapter: RC30-024801
------------	---


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	116.3300	45.68	-15.69	29.99	43.50	-13.51	Peak	
2 *	215.2700	51.61	-13.94	37.67	43.50	-5.83	Peak	
3	357.8599	46.79	-11.86	34.93	46.00	-11.07	Peak	
4	404.4200	43.14	-11.23	31.91	46.00	-14.09	Peak	
5	468.4400	40.84	-9.49	31.35	46.00	-14.65	Peak	
6	755.5600	30.67	-2.32	28.35	46.00	-17.65	Peak	

Test Mode: TX 2402MHz _CH00_1Mbps_Adapter: RC30-0238

Vertical




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	85.290	52.20	-18.42	33.78	40.00	-6.22	peak	
2	122.150	45.65	-15.24	30.41	43.50	-13.09	peak	
3	195.870	46.02	-13.38	32.64	43.50	-10.86	peak	
4	320.030	36.44	-12.48	23.96	46.00	-22.04	peak	
5	414.120	44.96	-10.97	33.99	46.00	-12.01	peak	
6	499.480	31.15	-8.73	22.42	46.00	-23.58	peak	

Test Mode: TX 2402MHz _CH00_1Mbps_Adapter: RC30-0238

Horizontal

Note:


Radiated Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		85.290	45.50	-18.42	27.08	40.00	-12.92	peak	
2		103.720	42.43	-17.00	25.43	43.50	-18.07	peak	
3		220.120	49.40	-13.90	35.50	46.00	-10.50	peak	
4		326.820	42.14	-12.36	29.78	46.00	-16.22	peak	
5		369.500	48.67	-11.72	36.95	46.00	-9.05	peak	
6	*	395.690	51.64	-11.41	40.23	46.00	-5.77	peak	

Test Mode: TX 2440MHz _CH19_1Mbps_Adapter: RC30-0238


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		55.220	44.77	-13.94	30.83	40.00	-9.17	peak	
2	*	85.290	53.05	-18.42	34.63	40.00	-5.37	peak	
3		155.130	43.76	-13.21	30.55	43.50	-12.95	peak	
4		186.170	43.99	-12.54	31.45	43.50	-12.05	peak	
5		230.790	44.16	-14.14	30.02	46.00	-15.98	peak	
6		424.790	47.94	-10.66	37.28	46.00	-8.72	peak	

Test Mode: TX 2440MHz _CH19_1Mbps_Adapter: RC30-0238

Horizontal




No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin	Detector	Comment
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	88.200	45.80	-18.56	27.24	43.50	-16.26	peak	
2	118.270	42.42	-15.53	26.89	43.50	-16.61	peak	
3 *	222.060	50.69	-13.95	36.74	46.00	-9.26	peak	
4	303.540	43.41	-12.77	30.64	46.00	-15.36	peak	
5	415.090	47.03	-10.93	36.10	46.00	-9.90	peak	
6	444.190	42.99	-10.10	32.89	46.00	-13.11	peak	

Test Mode:

TX 2480MHz _CH39_1Mbps_Adapter: RC30-0238


Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		55.220	43.96	-13.94	30.02	40.00	-9.98	peak	
2		88.200	53.01	-18.56	34.45	43.50	-9.05	peak	
3		156.100	43.54	-13.16	30.38	43.50	-13.12	peak	
4		192.960	45.82	-13.12	32.70	43.50	-10.80	peak	
5		329.730	35.36	-12.31	23.05	46.00	-22.95	peak	
6 *		421.880	51.42	-10.74	40.68	46.00	-5.32	peak	

Test Mode: TX 2480MHz _CH39_1Mbps_Adapter: RC30-0238

Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		87.230	45.33	-18.51	26.82	40.00	-13.18	peak	
2		118.270	42.89	-15.53	27.36	43.50	-16.14	peak	
3		224.970	49.23	-14.02	35.21	46.00	-10.79	peak	
4		325.850	41.60	-12.37	29.23	46.00	-16.77	peak	
5	*	418.000	46.90	-10.85	36.05	46.00	-9.95	peak	
6		435.460	42.90	-10.36	32.54	46.00	-13.46	peak	

APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)

Test Mode : TX 2402MHz _CH00_1Mbps

Vertical

110 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	39.14	9.14	48.28	74.00	-25.72	Peak	
2	2390.0000	30.31	9.14	39.45	54.00	-14.55	AVG	
3 *	2402.0500	82.86	9.18	92.04	54.00	38.04	AVG	No Limit
4	2402.2500	83.54	9.18	92.72	74.00	18.72	Peak	No Limit

Test Mode :	TX 2402MHz _CH00_1Mbps
-------------	------------------------

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4797.8000	37.51	6.56	44.07	74.00	-29.93	Peak	
2 *	4816.4000	26.58	6.63	33.21	54.00	-20.79	AVG	

Test Mode : TX 2402MHz _CH00_1Mbps

Horizontal

110 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	40.12	9.14	49.26	74.00	-24.74	Peak	
2	2390.0000	31.92	9.14	41.06	54.00	-12.94	AVG	
3 *	2402.0000	67.82	9.18	77.00	54.00	23.00	AVG	No Limit
4	2402.2500	69.34	9.18	78.52	74.00	4.52	Peak	No Limit

Test Mode : TX 2402MHz _CH00_1Mbps

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4815.1000	24.55	6.63	31.18	54.00	-22.82	AVG	
2	4830.9000	34.99	6.68	41.67	74.00	-32.33	Peak	

Test Mode : TX 2440MHz _CH19_1Mbps

Vertical

110 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2440.0000	81.43	9.32	90.75	54.00	36.75	AVG	No Limit
2	2440.2500	82.14	9.32	91.46	74.00	17.46	Peak	No Limit

Test Mode : TX 2440MHz _CH19_ 1Mbps

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4882.8000	25.85	6.87	32.72	54.00	-21.28	AVG	
2	4886.9000	36.06	6.88	42.94	74.00	-31.06	Peak	

Test Mode : TX 2440MHz _CH19_ 1Mbps

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2440.0000	64.25	9.32	73.57	54.00	19.57	AVG	No Limit
2	2440.2000	65.75	9.32	75.07	74.00	1.07	Peak	No Limit

Test Mode : TX 2440MHz _CH19_ 1Mbps

Horizontal

80 dBuV/m




No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1	4882.9000	34.37	6.87	41.24	74.00	-32.76	Peak	
2 *	4884.6000	23.94	6.88	30.82	54.00	-23.18	AVG	

Test Mode : TX 2480MHz _CH39_1Mbps

Vertical

110 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2479.7500	80.50	9.47	89.97	74.00	15.97	Peak	No Limit
2 *	2480.0000	79.82	9.47	89.29	54.00	35.29	AVG	No Limit
3	2483.5000	37.59	9.48	47.07	74.00	-26.93	Peak	
4	2483.5000	28.68	9.48	38.16	54.00	-15.84	AVG	

Test Mode :	TX 2480MHz _CH39_ 1Mbps
-------------	-------------------------

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4960.0350	35.55	7.15	42.70	74.00	-31.30	Peak	
2 *	4960.6750	25.95	7.15	33.10	54.00	-20.90	AVG	

Test Mode : TX 2480MHz _CH39_1Mbps

Horizontal

110 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2480.0500	69.55	9.47	79.02	74.00	5.02	Peak	No Limit
2 *	2480.0500	68.81	9.47	78.28	54.00	24.28	AVG	No Limit
3	2483.5000	38.24	9.48	47.72	74.00	-26.28	Peak	
4	2483.5000	29.92	9.48	39.40	54.00	-14.60	AVG	

Test Mode :	TX 2480MHz _CH39_ 1Mbps
-------------	-------------------------

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4960.4950	33.71	7.15	40.86	74.00	-33.14	Peak	
2 *	4960.6200	23.97	7.15	31.12	54.00	-22.88	AVG	

APPENDIX E - BANDWIDTH


Test Mode:	TX Mode_1Mbps
------------	---------------

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2402	0.630	1.056	500	Pass
2440	0.635	1.052	500	Pass
2480	0.656	1.056	500	Pass




Date: 16.MAR.2018 11:12:26

TX CH19



Date: 16.MAR.2018 11:14:27


TX CH39



Date: 16.MAR.2018 11:16:00


Test Mode:	TX Mode_2Mbps
------------	---------------

Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2402	1.210	2.050	500	Pass
2440	1.130	2.050	500	Pass
2480	1.158	2.060	500	Pass




Date: 22.MAY.2018 14:17:28

TX CH19



Date: 22.MAY.2018 14:16:03

TX CH39



Date: 22.MAY.2018 14:14:45

APPENDIX F - MAXIMUM OUTPUT POWER TEST

Test Mode :	CH00, CH19 , CH39 - 1Mbps
-------------	---------------------------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	3.72	0.0024	21.00	1.00	Pass
2440	3.89	0.0024	21.00	1.00	Pass
2480	3.63	0.0023	21.00	1.00	Pass


Test Mode :	CH00, CH19 , CH39 - 2Mbps
-------------	---------------------------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	3.39	0.0022	21.00	1.00	Pass
2440	3.49	0.0022	21.00	1.00	Pass
2480	3.11	0.0021	21.00	1.00	Pass

APPENDIX G - ANTENNA CONDUCTED SPURIOUS EMISSION


Test Mode : CH00, CH19 , CH39 - 1Mbps

CH00 (Lower) - 1Mbps




Date: 16.MAR.2018 11:12:50

CH39 (upper) - 1Mbps




Date: 16.MAR.2018 11:16:24

CH00 (10 Harmonic of the frequency) 1




Date: 16.MAR.2018 11:13:02

CH00 (10 Harmonic of the frequency) 2




Date: 16.MAR.2018 11:13:09

CH00 (10 Harmonic of the frequency) 3




Date: 16.MAR.2018 11:13:16

CH19 (10 Harmonic of the frequency) 1




Date: 16.MAR.2018 11:14:47

CH19 (10 Harmonic of the frequency) 2




Date: 16.MAR.2018 11:14:54

CH19 (10 Harmonic of the frequency) 3




Date: 16.MAR.2018 11:15:01

CH39 (10 Harmonic of the frequency) 1




Date: 16.MAR.2018 11:16:37

CH39 (10 Harmonic of the frequency) 2



Date: 16.MAR.2018 11:16:44

CH39 (10 Harmonic of the frequency) 3




Date: 16.MAR.2018 11:16:51

APPENDIX H - POWER SPECTRAL DENSITY TEST


Test Mode:	CH00, CH19 , CH39 - 1Mbps
------------	---------------------------

Frequency (MHz)	Power Density (dBm/3kHz)	Power Density (mW/3kHz)	Max. Limit (dBm/3kHz)	Test Result
2402	-11.690	0.068	8.00	Pass
2440	-11.460	0.071	8.00	Pass
2480	-11.790	0.066	8.00	Pass




Date: 16.MAR.2018 11:11:46

TX CH19



Date: 16.MAR.2018 11:15:06

TX CH39



Date: 16.MAR.2018 11:16:56