



SAR Exemption Evaluation Report

Product Name : Remote Controller

Model No. : GB346WJSA

FCC ID : RX3-GB346WJSA

Applicant : Hon Hai Precision Industry Co., Ltd.

Address : No.151, Sec. 1, Nankan Rd., Lujhu Taoyuan
County Taiwan 33859

Date of Receipt : Mar. 24, 2020

Issued Date : Aug. 26, 2020

Report No. : 2032140R-RF-US-P20V02

Report Version : V1.0

The test results presented in this report relate only to the object tested.

The measurement result is considered in conformance with the requirement if it is within the prescribed limit.
It is not necessary to account the uncertainty associated with the measurement result, unless the
specification, standard or customer have special requirements

This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing
Laboratory

This report is not used for social proof in China (or Mainland China) market.

Test Report Certification

Issued Date : Aug. 26, 2020
Report No. : 2032140R-RF-US-P20V02




Product Name : Remote Controller
Applicant : Hon Hai Precision Industry Co., Ltd.
Address : No.151, Sec. 1, Nankan Rd., Lujhu Taoyuan County Taiwan 33859
Manufacturer : Yan Tai FuHuaDa Precision Electronics Co., Ltd.
Address : A-7 Section, Yantai Economic & Technological Development Area, Shan Dong
Model No. : GB346WJSA
FCC ID : RX3-GB346WJSA
EUT Voltage : DC 3V
Applicable Standard : KDB 447498 D01v06
Test Result : Complied
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199

Documented By : 

(Project Assistant: Kitty Li)

Reviewed By : 

(Technical Supervisor: Frank He)

Approved By : 

(Supervisor: Jack Zhang)

1. RF Exposure Evaluation

1.1. Limits

According to **KDB 447498 D01 General RF Exposure Guidance v06**

4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq$

3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances $>$ 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:

a) $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz

b) $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at $>$ 1500 MHz and \leq 6 GHz

3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances \leq 50 mm are determined by:

a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances $>$ 50 mm and $<$ 200 mm

b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances \leq 50 mm

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Remote Controller
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Information

Antenna model	N/A			
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX <input type="checkbox"/> 3*TX+3*RX	
Antenna technology	<input checked="" type="checkbox"/>	SISO		
	<input type="checkbox"/>	Basic		
	<input type="checkbox"/>	CDD		
	<input type="checkbox"/>	Beam-forming		
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/> Dipole	
	<input type="checkbox"/>		<input type="checkbox"/> PIFA	
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/> PCB	
	<input type="checkbox"/>		<input type="checkbox"/> Ceramic Chip Antenna	
	<input type="checkbox"/>		<input type="checkbox"/> Stamping Antenna	
	<input type="checkbox"/>		<input type="checkbox"/> Metal plate type F antenna	
	<input type="checkbox"/>		<input type="checkbox"/> Monopole antenna	
Antenna Gain	0.72 dBi			

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

$$\text{SAR test exclusion thresholds} = \sqrt{f(\text{GHz})} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

The Maximum tune-up power is 0.5dB higher than Maximum Measurement power, so the maximum conducted power we used to calculate RF exposure is 5.72dBm.

Band	Exposure Condition	Pmax	Pmax	Distance	f(GHz)	calculation result	Stand-alone Test exclusion threshold	SAR Test
		(dBm)	(mw)	(mm)			3.00	
BT	Body	5.72	3.73	5	2.48	1.18	3.00	No

Conclusion: 2.4GHz SAR was not required.

————— The End —————