

Test Report No.50140126 001

Appendix D: Radiated Spurious Emission Data

(File: 50140126AppendixD)


Contents

Radiated Emissions, Band Edges, 2.35-2.5G	2
Spurious Emissions, TX Mode, 1-18G.....	18
Spurious Emissions, TX Mode, 18-26.5G.....	42
Spurious Emissions, TX Mode, 9k-30M	66
Spurious Emissions, TX Mode, 30M-1G	68
Spurious Emissions, RX Mode, 1-18G	70
Spurious Emissions, RX Mode, 18-26.5G	72
Spurious Emissions, RX Mode, 30M-1G.....	74
Spurious Emissions, RX Mode, 9k-30M.....	76
Mains Emissions, 150k-30M.....	78



Radiated Emissions, Band Edges, 2.35-2.5G

Radiated Bandedge 11b



Low Channel (Hor)





Low Channel (Ver)





High Channel (Hor)





High Channel (Ver)





Radiated Bandedge 11g
Low Channel (Hor)




Low Channel (Ver)




High Channel (Hor)



High Channel (Ver)





Date: 12.APR.2018 01:23:03





Date: 12.APR.2018 01:21:15

Radiated Bandedge 11n_20M



Low Channel (Hor)





Low Channel (Ver)



High Channel (Hor)





High Channel (Ver)





Radiated Bandedge 11n_40M


Low Channel (Hor)




Low Channel (Ver)



High Channel (Hor)





Date: 12.APR.2018 02:19:30



Date: 12.APR.2018 02:17:39

High Channel (Ver)




Spurious Emissions, TX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:09:59
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2412-TX		
Remark:	Power Setting 1D		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	52.47	49.81	74.00	-24.19	peak	100	219	
2	7236.000	5.32	44.82	50.14	74.00	-23.86	peak		0	
3	8684.000	6.40	45.38	51.78	74.00	-22.22	peak	100	130	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:10:52
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2412-TX		
Remark:	Power Setting 1D		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	49.89	47.23	74.00	-26.77	peak			
2	7236.000	5.32	44.19	49.51	74.00	-24.49	peak			
3	9177.000	6.48	45.17	51.65	74.00	-22.35	peak	100	3	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:12:59
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	55.68	53.15	74.00	-20.85	peak	100	167	
2	4874.000	-2.53	53.96	51.43	54.00	-2.57	AVG	100	167	
3	7311.000	5.52	44.67	50.19	74.00	-23.81	peak			
4	8786.000	6.42	45.08	51.50	74.00	-22.50	peak	100	337	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:13:51
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	50.91	48.38	74.00	-25.62	peak			
2	7311.000	5.52	44.82	50.34	74.00	-23.66	peak			
3	9007.000	6.44	45.29	51.73	74.00	-22.27	peak	100	94	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:18:08
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2462-TX		
Remark:	Power Setting 1E		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	55.62	53.23	74.00	-20.77	peak	100	198	
2	4924.000	-2.39	53.61	51.22	54.00	-2.78	AVG	100	198	
3	7386.000	5.70	43.55	49.25	74.00	-24.75	peak			
4	8820.000	6.41	44.89	51.30	74.00	-22.70	peak	100	31	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:19:01
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2462-TX		
Remark:	Power Setting 1E		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	50.17	47.78	74.00	-26.22	peak			
2	7386.000	5.70	44.60	50.30	74.00	-23.70	peak			
3	8922.000	6.42	44.90	51.32	74.00	-22.68	peak	100	302	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:21:56
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2412-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	48.46	45.80	74.00	-28.20	peak			
2	7236.000	5.32	44.35	49.67	74.00	-24.33	peak			
3	8803.000	6.42	44.96	51.38	74.00	-22.62	peak	100	239	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:22:48
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2412-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	47.68	45.02	74.00	-28.98	peak			
2	7236.000	5.32	46.19	51.51	74.00	-22.49	peak			
3	8480.000	6.35	44.94	51.29	74.00	-22.71	peak	100	356	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:24:40
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2437-TX		
Remark:	Power Setting 21		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	51.72	49.19	74.00	-24.81	peak			
2	7311.000	5.52	43.86	49.38	74.00	-24.62	peak			
3	8531.000	6.38	45.19	51.57	74.00	-22.43	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:25:32
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2437-TX		
Remark:	Power Setting 21		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	48.20	45.67	74.00	-28.33	peak			
2	7311.000	5.52	44.16	49.68	74.00	-24.32	peak			
3	8905.000	6.42	45.57	51.99	74.00	-22.01	peak	100	125	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:27:33
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2462-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	50.48	48.09	74.00	-25.91	peak			
2	7386.000	5.70	43.75	49.45	74.00	-24.55	peak			
3	8497.000	6.38	45.41	51.79	74.00	-22.21	peak	100	360	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:28:26
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2462-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	48.58	46.19	74.00	-27.81	peak			
2	7386.000	5.70	44.09	49.79	74.00	-24.21	peak			
3	8565.000	6.39	45.14	51.53	74.00	-22.47	peak	100	264	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:31:23
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2412-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	47.77	45.11	74.00	-28.89	peak			
2	7236.000	5.32	44.88	50.20	74.00	-23.80	peak			
3	8769.000	6.41	45.16	51.57	74.00	-22.43	peak	100	222	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:32:15
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2412-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4824.000	-2.66	49.21	46.55	74.00	-27.45	peak			
2	7236.000	5.32	45.67	50.99	74.00	-23.01	peak			
3	8582.000	6.39	44.84	51.23	74.00	-22.77	peak	100	210	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:34:30
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2437-TX		
Remark:	Power Setting 18 18		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	49.47	46.94	74.00	-27.06	peak			
2	7311.000	5.52	44.72	50.24	74.00	-23.76	peak			
3	8633.000	6.39	44.96	51.35	74.00	-22.65	peak	100	334	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:35:22
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2437-TX		
Remark:	Power Setting 18 18		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	48.21	45.68	74.00	-28.32	peak			
2	7311.000	5.52	43.82	49.34	74.00	-24.66	peak			
3	8463.000	6.34	44.69	51.03	74.00	-22.97	peak	100	29	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:37:29
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2462-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	48.42	46.03	74.00	-27.97	peak			
2	7386.000	5.70	44.30	50.00	74.00	-24.00	peak			
3	8327.000	6.18	44.01	50.19	74.00	-23.81	peak	100	215	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:38:22
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2462-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4924.000	-2.39	49.04	46.65	74.00	-27.35	peak			
2	7386.000	5.70	43.74	49.44	74.00	-24.56	peak			
3	8480.000	6.35	44.64	50.99	74.00	-23.01	peak	100	210	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:40:34
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2422-TX		
Remark:	Power Setting 13 13		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4844.000	-2.61	49.18	46.57	74.00	-27.43	peak			
2	7266.000	5.40	44.86	50.26	74.00	-23.74	peak			
3	8565.000	6.39	45.16	51.55	74.00	-22.45	peak	100	219	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:41:26
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2422-TX		
Remark:	Power Setting 13 13		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4844.000	-2.61	49.78	47.17	74.00	-26.83	peak			
2	7266.000	5.40	44.29	49.69	74.00	-24.31	peak			
3	8191.000	6.03	44.46	50.49	74.00	-23.51	peak	100	101	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:43:47
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2437-TX		
Remark:	Power Setting 16 16		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	49.23	46.70	74.00	-27.30	peak			
2	7311.000	5.52	43.52	49.04	74.00	-24.96	peak			
3	8004.000	5.82	45.06	50.88	74.00	-23.12	peak	100	304	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:44:39
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2437-TX		
Remark:	Power Setting 16 16		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4874.000	-2.53	47.88	45.35	74.00	-28.65	peak			
2	7311.000	5.52	44.96	50.48	74.00	-23.52	peak			
3	8480.000	6.35	44.70	51.05	74.00	-22.95	peak	100	60	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:46:36
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2452-TX		
Remark:	Power Setting 12 12		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4904.000	-2.44	48.45	46.01	74.00	-27.99	peak			
2	7356.000	5.63	45.33	50.96	74.00	-23.04	peak			
3	8531.000	6.38	44.86	51.24	74.00	-22.76	peak	100	358	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:47:28
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2452-TX		
Remark:	Power Setting 12 12		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4904.000	-2.44	50.28	47.84	74.00	-26.16	peak			
2	7356.000	5.63	44.19	49.82	74.00	-24.18	peak			
3	8650.000	6.40	44.55	50.95	74.00	-23.05	peak	100	5	


Spurious Emissions, TX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:00:19
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2412-TX		
Remark:	Power Setting 1D		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21910.000	32.65	17.19	49.84	74.00	-24.16	peak		0	




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:00:25
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2412-TX		
Remark:	Power Setting 1D		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21782.500	32.72	17.41	50.13	74.00	-23.87	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:00:53
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22148.000	32.61	17.87	50.48	74.00	-23.52	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:01:00
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21697.500	32.77	17.74	50.51	74.00	-23.49	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:01:30
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2462-TX		
Remark:	Power Setting 1E		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21825.000	32.69	17.22	49.91	74.00	-24.09	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:01:36
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2462-TX		
Remark:	Power Setting 1E		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21510.500	32.89	17.28	50.17	74.00	-23.83	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:02:03
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2412-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22513.500	32.65	17.60	50.25	74.00	-23.75	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:02:10
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2412-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22743.000	32.72	17.45	50.17	74.00	-23.83	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:02:37
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2437-TX		
Remark:	Power Setting 21		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21128.000	32.55	17.54	50.09	74.00	-23.91	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:02:43
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2437-TX		
Remark:	Power Setting 21		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21561.500	32.85	18.35	51.20	74.00	-22.80	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:03:14
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2462-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23100.000	32.89	17.81	50.70	74.00	-23.30	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:03:20
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	G-2462-TX		
Remark:	Power Setting 1B		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21102.500	32.53	17.91	50.44	74.00	-23.56	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:03:48
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2412-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23117.000	32.91	17.65	50.56	74.00	-23.44	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:03:55
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2412-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21349.000	32.75	17.85	50.60	74.00	-23.40	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:04:20
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2437-TX		
Remark:	Power Setting 18 18		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21323.500	32.73	17.58	50.31	74.00	-23.69	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:04:26
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2437-TX		
Remark:	Power Setting 18 18		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21442.500	32.84	17.60	50.44	74.00	-23.56	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:04:51
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2462-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	23159.500	32.95	17.30	50.25	74.00	-23.75	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:04:57
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N20-2462-TX		
Remark:	Power Setting 15 15		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21757.000	32.73	17.95	50.68	74.00	-23.32	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:05:22
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2422-TX		
Remark:	Power Setting 13 13		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21493.500	32.89	16.85	49.74	74.00	-24.26	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:05:29
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2422-TX		
Remark:	Power Setting 13 13		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22122.500	32.60	17.20	49.80	74.00	-24.20	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:05:54
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2437-TX		
Remark:	Power Setting 16 16		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22377.500	32.63	18.25	50.88	74.00	-23.12	peak			




Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:06:01
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2437-TX		
Remark:	Power Setting 16 16		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22454.000	32.63	17.29	49.92	74.00	-24.08	peak			



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:06:25
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2452-TX		
Remark:	Power Setting 12 12		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21442.500	32.84	17.35	50.19	74.00	-23.81	peak			



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:06:32
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	N40-2452-TX		
Remark:	Power Setting 12 12		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21408.500	32.80	17.87	50.67	74.00	-23.33	peak			


Spurious Emissions, TX Mode, 9k-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC15.209_9k-1G_3m	Ant. Polarization:	
Test item:	Radiation Emission	Test Time:	2018/4/12 04:47:44
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0095	19.73	31.33	51.06	128.03	-76.97	QP	100	322	
2	0.0277	20.11	22.77	42.88	118.74	-75.86	QP	100	191	
3	0.0401	19.78	21.06	40.84	115.53	-74.69	QP	100	103	
4	0.0421	19.71	20.85	40.56	115.11	-74.55	QP	100	274	
5	0.0459	19.57	20.35	39.92	114.36	-74.44	QP	100	103	
6	0.0961	19.15	13.23	32.38	107.94	-75.56	QP	100	40	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC15.209_9k-1G_3m	Ant. Polarization:	
Test item:	Radiation Emission	Test Time:	2018/4/12 04:50:25
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1500	19.08	23.64	42.72	104.08	-61.36	QP	100	78	
2	4.7469	19.60	12.39	31.99	69.50	-37.51	QP	100	121	
3	8.0602	20.04	12.46	32.50	69.50	-37.00	QP	100	242	
4	12.7765	20.71	10.94	31.65	69.50	-37.85	QP	100	223	
5	18.9853	21.81	9.64	31.45	69.50	-38.05	QP	100	78	
6	23.2837	22.21	7.95	30.16	69.50	-39.34	QP	100	13	


Spurious Emissions, TX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:31:10
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	239.5200	-6.85	44.23	37.38	46.00	-8.62	QP	100	121	
2	261.8300	-5.01	40.88	35.87	46.00	-10.13	QP	100	128	
3	359.8000	-3.16	43.12	39.96	46.00	-6.04	QP	100	105	
4	367.5600	-3.03	40.17	37.14	46.00	-8.86	QP	100	288	
5	814.7300	3.05	31.52	34.57	46.00	-11.43	QP	100	190	
6	960.2300	5.54	30.95	36.49	54.00	-17.51	QP	100	292	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:32:04
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-TX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	44.5500	-8.54	39.76	31.22	40.00	-8.78	QP	100	111	
2	119.2400	-7.50	46.39	38.89	43.50	-4.61	QP	100	62	
3	239.5200	-6.85	40.16	33.31	46.00	-12.69	QP	100	151	
4	377.2600	-2.85	37.04	34.19	46.00	-11.81	QP	100	26	
5	720.6400	1.72	35.90	37.62	46.00	-8.38	QP	100	105	
6	960.2300	5.54	34.36	39.90	54.00	-14.10	QP	100	187	


Spurious Emissions, RX Mode, 1-18G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 03:51:34
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4162.000	-5.27	51.44	46.17	74.00	-27.83	peak	100	266	
2	5318.000	-1.70	48.80	47.10	74.00	-26.90	peak	100	174	
3	6508.000	4.31	45.01	49.32	74.00	-24.68	peak	100	37	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 03:52:27
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	4893.000	-3.39	50.62	47.23	74.00	-26.77	peak	100	251	
2	5743.000	0.72	46.63	47.35	74.00	-26.65	peak	100	80	
3	6525.000	4.29	45.27	49.56	74.00	-24.44	peak	100	74	


Spurious Emissions, RX Mode, 18-26.5G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:07:00
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	22122.500	32.60	17.33	49.93	74.00	-24.07	peak			



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Above 1G PEAK	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:07:07
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62 %
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	21332.000	32.74	17.22	49.96	74.00	-24.04	peak			


Spurious Emissions, RX Mode, 30M-1G



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Class B 3M Radiation	Ant. Polarization:	Horizontal
Test item:	Radiation Emission	Test Time:	2018/4/12 04:34:43
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	119.2400	-7.50	40.46	32.96	43.50	-10.54	QP	100	98	
2	239.5200	-6.85	43.45	36.60	46.00	-9.40	QP	100	114	
3	359.8000	-3.16	42.56	39.40	46.00	-6.60	QP	100	282	
4	373.3800	-2.92	36.61	33.69	46.00	-12.31	QP	100	289	
5	720.6400	1.72	32.52	34.24	46.00	-11.76	QP	100	144	
6	960.2300	5.54	31.25	36.79	54.00	-17.21	QP	100	295	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC Class B 3M Radiation	Ant. Polarization:	Vertical
Test item:	Radiation Emission	Test Time:	2018/4/12 04:35:36
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%) :	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	119.2400	-7.50	46.17	38.67	43.50	-4.83	QP	100	121	
2	239.5200	-6.85	39.79	32.94	46.00	-13.06	QP	100	141	
3	359.8000	-3.16	36.65	33.49	46.00	-12.51	QP	100	62	
4	382.1100	-2.76	33.91	31.15	46.00	-14.85	QP	100	39	
5	600.3600	0.08	29.99	30.07	46.00	-15.93	QP	100	124	
6	960.2300	5.54	34.38	39.92	54.00	-14.08	QP	100	184	


Spurious Emissions, RX Mode, 9k-30M



TUV Rheinland Taiwan Ltd.


11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105

Tel:+886-2172-7000 fax:+886-2528-0018



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC15.209_9k-1G_3m	Ant. Polarization:	
Test item:	Radiation Emission	Test Time:	2018/4/12 04:48:37
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%)	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:			

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.0097	19.81	32.32	52.13	127.85	-75.72	QP	100	360	
2	0.0303	20.12	21.84	41.96	117.96	-76.00	QP	100	216	
3	0.0421	19.71	21.22	40.93	115.11	-74.18	QP	100	104	
4	0.0529	19.41	16.55	35.96	113.12	-77.16	QP	100	281	
5	0.0743	19.28	14.29	33.57	110.18	-76.61	QP	100	360	
6	0.0973	19.15	11.41	30.56	107.83	-77.27	QP	100	104	



Service No.:	114076042	Test Distance:	3m
Test Standard:	FCC15.209_9k-1G_3m	Ant. Polarization:	
Test item:	Radiation Emission	Test Time:	2018/4/12 04:51:18
Applicant:	Hon Hai Precision Industry Co., Ltd.	Test Rating:	DC 5V
Product:	802.11 a/b/g/n/ac module	Temp.(°C)/Hum.(%):	22(°C)/62%
Model No.:	WFU033	Test Engineer:	Curry Chen
Test Mode:	B-2437-RX		
Remark:	Power Setting 20		

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (°)	Remark
1	0.1799	19.06	25.17	44.23	102.50	-58.27	QP	100	334	
2	4.6275	19.53	12.35	31.88	69.50	-37.62	QP	100	200	
3	8.5976	20.09	12.33	32.42	69.50	-37.08	QP	100	39	
4	11.3139	20.45	11.81	32.26	69.50	-37.24	QP	100	295	
5	16.6571	21.39	9.53	30.92	69.50	-38.58	QP	100	128	
6	22.4181	22.15	8.95	31.10	69.50	-38.40	QP	100	256	


Mains Emissions, 150k-30M



TUV Rheinland Taiwan Ltd.
11F., No.758, Sec.4 Bade Road. Songshan Dist, Taipei City 105
Tel:+886-2172-7000 Fax:+886-2528-0018

File: C:\EMC\Report\2018\Hon Hai\114076042(WFU033)\114076042(WFU033)_00003.EMI

Date: 2018-04-18 Time: 22:09:02




Trace: 1

Site : Conduction room
Condition : FCC Part15 Class B Conduction(QP) line1
Test Engineer: Colin Lu
Applicant : Hon Hai
Product : 802.11 a/b/g/n/ac module
Model No. : WFU033
Test Rating : 5Vdc
Tmp/Hum : 21 °C / 47 %
Memo : (1) WIFI link

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.156	6.58	9.65	16.23	65.67	-49.44	QP
2	0.156	-2.18	9.65	7.47	55.67	-48.20	Average
3	7.460	1.95	9.77	11.72	60.00	-48.28	QP
4	7.460	-2.89	9.77	6.88	50.00	-43.12	Average
5	12.887	12.34	9.80	22.14	60.00	-37.86	QP
6	12.887	7.06	9.80	16.86	50.00	-33.14	Average
7	17.023	6.36	9.81	16.17	60.00	-43.83	QP
8	17.023	1.82	9.81	11.63	50.00	-38.37	Average
9	18.432	10.51	9.81	20.32	60.00	-39.68	QP
10	18.432	5.48	9.81	15.29	50.00	-34.71	Average
11	29.409	10.43	9.79	20.22	60.00	-39.78	QP
12	29.409	4.38	9.79	14.17	50.00	-35.83	Average

File: C:\EMC\Report\2018\Hon Hai\114076042(WFU033)\114076042(WFU033)_00005.EMI

Date: 2018-04-18 Time: 22:15:29



Trace: 1

Site : Conduction room
Condition : FCC Part15 Class B Conduction(QP) neutral
Test Engineer: Colin Lu
Applicant : Hon Hai
Product : 802.11 a/b/g/n/ac module
Model No. : WFU033
Test Rating : 5Vdc
Tmp/Hum : 21 °C / 47 %
Memo : (1) WIFI link

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.158	5.74	9.66	15.40	65.59	-50.19	QP
2	0.158	-2.15	9.66	7.51	55.59	-48.08	Average
3	6.754	3.53	9.77	13.30	60.00	-46.70	QP
4	6.754	-1.26	9.77	8.51	50.00	-41.49	Average
5	7.460	2.62	9.78	12.40	60.00	-47.60	QP
6	7.460	-2.25	9.78	7.53	50.00	-42.47	Average
7	12.634	8.42	9.83	18.25	60.00	-41.75	QP
8	12.634	2.80	9.83	12.63	50.00	-37.37	Average
9	18.617	10.66	9.87	20.53	60.00	-39.47	QP
10	18.617	5.73	9.87	15.60	50.00	-34.40	Average
11	28.545	9.94	9.89	19.83	60.00	-40.17	QP
12	28.545	4.23	9.89	14.12	50.00	-35.88	Average