

## § 15.247 (e)(i) and § 2.1091 - RF EXPOSURE

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

### Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz)                               | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-----------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3-1.34                                            | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                             | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                              | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                            | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                        | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

### MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 5.93(dBm)

Maximum peak output power at antenna input terminal: 3.92 (mW)

Prediction distance: 20 (cm)

Predication frequency: 915 (MHz)

Antenna Gain (typical): 2.5 (dBi)

antenna gain: 1.78 (numeric)

Power density at predication frequency at 20 cm: 0.0014(mW/cm<sup>2</sup>)

MPE limit for uncontrolled exposure at prediction frequency: 0.61 (mW/cm<sup>2</sup>)

### Test Result

The EUT is a mobile device. The power density level at 20 cm is 0.0014mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit of 0.61mW/cm<sup>2</sup> at 915 MHz.