

RF Exposure / MPE Calculation

No. : 4787971961-E2V2
Applicant : TAIYO YUDEN CO., LTD.
Type of Equipment : Bluetooth Dual-mode Module
Model No. : EYSGCC
FCC ID : RYYEYSGCC

TAIYO YUDEN CO., LTD. declares that Model: EYSGCC complies with FCC radiation exposure requirement specified in the FCC Rule 2.1091 (for mobile).

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “EYSGCC” as calculated from (B) Limits for General Population / Uncontrolled Exposure of TABLE 1- LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) of §1.1310 Radiofrequency radiation exposure limits.

This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = \frac{P \times G}{4 \times \pi \times r^2}$$

Where

$P =$ 15.85 mW (Maximum average output power)

☐ Frame power was used for the above value in consideration of 6-minutes time-averaging

☒ Burst power was used for the above value in consideration of worst condition.

$G =$ 0.832 Numerical Antenna gain; equal to -0.8 dBi

$r =$ 20 cm (Separation distance)

Power Density Result $S = 0.00262 \text{ mW/cm}^2$

Even taking into account the tolerance, this device can be satisfied with the limits.