



**FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E**

**TEST REPORT**

**For**

**Home Monitoring Gateway**

**Model: iHUB-3000**

**Trade Name: iControl**

*Issued to*

**iControl Networks Inc.**  
3045 Park Blvd. 2nd floor  
Palo Alto, CA 94306, U.S.A

*Issued by*

**Compliance Certification Services Inc.**  
No. 11, Wu-Gong 6<sup>th</sup> Rd., Wugu Industrial Park,  
Taipei Hsien 248, Taiwan (R.O.C.)  
<http://www.ccsemc.com.tw>  
[service@tw.ccsemc.com](mailto:service@tw.ccsemc.com)



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



## TABLE OF CONTENTS

<b>1. TEST RESULT CERTIFICATION.....</b>	<b>3</b>
<b>2. EUT DESCRIPTION .....</b>	<b>4</b>
<b>3. TEST METHODOLOGY .....</b>	<b>5</b>
3.1    EUT CONFIGURATION .....	5
3.2    EUT EXERCISE .....	5
3.3    GENERAL TEST PROCEDURES .....	5
3.4    DESCRIPTION OF TEST MODES.....	5
<b>4. INSTRUMENT CALIBRATION.....</b>	<b>6</b>
4.1    MEASURING INSTRUMENT CALIBRATION .....	6
4.2    MEASUREMENT EQUIPMENT USED .....	6
<b>5. FACILITIES AND ACCREDITATIONS.....</b>	<b>8</b>
5.1    FACILITIES .....	8
5.2    EQUIPMENT .....	8
5.3    TABLE OF ACCREDITATIONS AND LISTINGS .....	9
<b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
6.1    SETUP CONFIGURATION OF EUT .....	10
6.2    SUPPORT EQUIPMENT .....	10
<b>7. FCC PART 22 &amp; 24 REQUIREMENTS .....</b>	<b>11</b>
7.1    AVERAGE POWER .....	11
7.2    ERP & EIRP MEASUREMENT .....	13
7.3    OCCUPIED BANDWIDTH MEASUREMENT .....	16
7.4    OUT OF BAND EMISSION AT ANTENNA TERMINALS .....	21
7.5    FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT .....	28
7.6    FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT .....	42
7.7    FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT .....	44
7.8    POWERLINE CONDUCTED EMISSIONS .....	46
<b>APPENDIX I PHOTOGRAPHS OF TEST SETUP.....</b>	<b>49</b>



## 1. TEST RESULT CERTIFICATION

**Applicant:** iControl Networks Inc.  
3045 Park Blvd. 2nd floor  
Palo Alto, CA 94306, U.S.A

**Equipment Under Test:** Home Monitoring Gateway

**Trade Name:** iControl

**Model Number:** iHUB-3000

**Date of Test:** March 26 ~ June 16, 2008

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E	No non-compliance noted

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA/EIA-603-A-2001 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rule FCC PART 22 Subpart H and PART 24 Subpart E.

The test results of this report relate only to the tested sample identified in this report.

*Approved by:*

---

Rex Lai  
Section Manager  
Compliance Certification Services Inc.

*Reviewed by:*

---

Amanda Wu  
Section Manager  
Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	Home Monitoring Gateway
<b>Trade Name</b>	iControl
<b>Model Number</b>	iHUB-3000
<b>Model Discrepancy</b>	N/A
<b>Power Supply</b>	Model Number: DSA-15P-12 US 120150 I/P: AC 100-240V, 0.5A, 50-60Hz O/P: DC 12V, 1.25A
<b>Frequency Range</b>	TX: 824 ~ 849 MHz / 1850 ~ 1910 MHz RX: 869 ~ 894 MHz / 1930 ~ 1989.8 MHz
<b>Transmit Power (ERP &amp; EIRP Power)</b>	GPRS 850 MHz: 18.98 dBm GPRS 1900 MHz: 26.05dBm
<b>Cellular Phone Protocol</b>	GPRS
<b>Type of Emission</b>	GPRS 850 MHz: 243KGXW--- GPRS 1900 MHz: 241KGXW---
<b>Antenna Gain</b>	850 MHz: -7 dBi 1900 MHz: -7 dBi
<b>Antenna Type</b>	Dipole Antenna

**Remark:**

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: S23-IHUB3000 filing to comply with Part 22 and Part 24 of the FCC 47 CFR Rules.



### 3. TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4 and FCC CFR 47, 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057.

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

#### 3.3 GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.

#### 3.4 DESCRIPTION OF TEST MODES

The EUT (model: iHUB-3000) had been tested under operating condition.

EUT staying in continuous transmitting mode was programmed.

GPRS 850: Channel Low (CH128), Channel Mid (CH190) and Channel High (CH251) were chosen for full testing.

GPRS 1900: Channel Low (CH512), Channel Mid (CH661) and Channel High (CH810) were chosen for full testing.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.



## 4. INSTRUMENT CALIBRATION

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 4.2 MEASUREMENT EQUIPMENT USED

#### Equipment Used for Emissions Measurement

*Remark: Each piece of equipment is scheduled for calibration once a year.*

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	02/24/2009
Power Meter	Agilent	E4416A	GB41291611	04/06/2009
Power Sensor	Agilent	E9327A	US40441097	06/06/2009
Temp. / Humidity Chamber	TERCHY	MHG-150LF	930619	08/06/2009
DC Power Source	Agilent	E3640A	MY40001774	01/10/2009

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	09/11/2008
Test Receiver	Rohde&Schwarz	ESCI	100064	11/30/2008
Switch Controller	TRC	Switch Controller	SC94050010	05/03/2009
4 Port Switch	TRC	4 Port Switch	SC94050020	05/03/2009
Horn-Antenna	TRC	HA-0502	06	06/04/2009
Horn-Antenna	TRC	HA-0801	04	06/19/2009
Bilog- Antenna	Sunol Sciences	JB3	A030205	03/28/2009
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC: 965860 IC: IC 6106	09/25/2008
Reject Filter	Micro-Tronics	HPM13194	003	04/24/2009
S.G.	HP	83630B	3844A01022	04/17/2009
Substituted Dipole	SCHWAZBECK	VHAP/UHAP	998+999/ 981+982	12/10/2008
Substituted Horn	EMCO	3115	00022257	12/10/2008
Test S/W	LABVIEW (V 6.1)			

*Remark: The measurement uncertainty is less than +/-3.7046dB (30MHz ~ 1GHz), +/-3.0958dB (Above 1GHz) which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.*



<b>Powerline Conducted Emissions Test Site</b>				
<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Due</b>
EMI TEST RECEIVER 9kHz-30MHz	ROHDE & SCHWARZ	ESHS30	828144/003	11/19/2008
TWO-LINE V-NETWORK 9kHz-30MHz	SCHAFFNER	NNB41	03/10013	06/11/2009
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	04/09/2009
Test S/W		LABVIEW (V 6.1)		

**Remark:** The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



## **5. FACILITIES AND ACCREDITATIONS**

### **5.1 FACILITIES**

No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



### 5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	EN 55011, EN 55014-1/2, CISPR 11, CISPR 14-1/2, EN 55022, EN 55015, CISPR 22, CISPR 15, AS/NZS 3548, VCCI V3 (2001), CFR 47, FCC Part 15/18, CNS 13783-1, CNS 13439, CNS 13438, CNS 13803, CNS 14115, EN 55024, IEC 801-2, IEC 801-3, IEC 801-4, IEC/EN 61000-3-2, EIC/EN 61000-3-3, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 50081-1/EN 61000-6-3, EN 50081-2/EN 61000-6-4, EN 50081-2/EN 61000-6-1: 2001	 ACCREDITED TESTING CERT #0824.01
USA	FCC	3M Semi Anechoic Chamber (965860 and 898658) to perform FCC Part 15/18 measurements	 965860, 898658
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method –47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 6106 & IC 6106A-2) to perform RSS 212 Issue 1	 IC 6106 IC 6106A-2

\* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### 6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
1.	Universal Radio Communication tester (Remote)	R&S	CMU 200	1100.000.8.02	N/A	N/A	Unshielded, 1.8m
2.	USB 2.0 External HDD	Portable	ME-911U2	N/A	FCC DoC	Shielded, 1.8m	N/A
3.	USB 2.0 External HDD	TeraSyS	F12-U	A0100214-2Bq0039	FCC DoC	Shielded, 1.8m	N/A

**Remark:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


## 7. FCC PART 22 & 24 REQUIREMENTS

### 7.1 AVERAGE POWER

#### LIMIT

According to FCC §2.1046.

#### Test Configuration



*Remark: Measurement setup for testing on Antenna connector*

#### TEST PROCEDURE

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a power meter. Transmitter output was read off the power meter in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to the power meter reading.



## TEST RESULTS

*No non-compliance noted.*

### Test Data

Test Mode	CH	Frequency (MHz)	Power Meter Reading (dBm)	Attenuator (dB)	Average Power (dBm)
GPRS 850 (Class 10)	128	824.20	-1.41	29.9	28.49
	190	836.60	-1.21		28.69
	251	848.80	-1.10		28.80

*Remark: The value of factor includes both the loss of cable and external attenuator*

Test Mode	CH	Frequency (MHz)	Power Meter Reading (dBm)	Attenuator (dB)	Average Power (dBm)
GPRS 1900 (Class 10)	512	1850.20	-5.99	35.90	29.91
	661	1880.00	-6.38		29.52
	810	1909.80	-5.70		30.20

*Remark: The value of factor includes both the loss of cable and external attenuator*

## 7.2 ERP & EIRP MEASUREMENT

### LIMIT


According to FCC §2.1046

FCC 22.913(b): The Effective Radiated Power (ERP) of mobile transmitters must not exceed 7 Watts.


FCC 24.232(b): The equivalent Isotropic Radiated Power (EIRP) must not exceed 2 Watts.


### TEST CONFIGURATION

#### Below 1 GHz



#### Above 1 GHz



**For Substituted Method Test Set-UP****TEST PROCEDURE**

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement of the EUT, the resolution bandwidth was set to 3MHz and the average bandwidth was set to 3MHz. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824-849MHz, and EIRP in frequency band 1851.25 –1910MHz were measured using a substitution method. The EUT was replaced by half-wave dipole (824-849MHz) or horn antenna (1851.25-1910MHz) connected to a signal generator. The spectrum analyzer reading was recorded and ERP/EIRP was calculated as follows:

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$



## **TEST RESULTS**

*No non-compliance noted.*

### **GPRS 850 Test Data (Class 10)**

Channel	Frequency (MHz)	Antenna Pol.	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
128	824.20	V	18.19	-3.42	14.77	38.50	-23.73
	824.20	H	22.58	-3.60	18.98	38.50	-19.52
190	836.60	V	17.81	-3.34	14.47	38.50	-24.03
	836.60	H	22.47	-3.50	18.98	38.50	-19.52
251	848.80	V	17.32	-3.23	14.09	38.50	-24.41
	848.80	H	21.95	-3.35	18.60	38.50	-19.90

### **GPRS 1900 Test Data (Class 10)**


Channel	Frequency (MHz)	Antenna Pol.	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
512	1850.20	V	-17.29	42.49	25.20	33.00	-7.80
	1850.20	H	-22.18	42.51	20.33	33.00	-12.67
661	1880.00	V	-17.65	42.49	24.85	33.00	-8.15
	1880.00	H	-22.95	42.53	19.58	33.00	-13.42
810	1909.80	V	-16.44	42.49	26.05	33.00	-6.95
	1909.80	H	-20.18	42.55	22.37	33.00	-10.63

## 7.3 OCCUPIED BANDWIDTH MEASUREMENT

### LIMIT

According to §FCC 2.1049.

### Test Configuration



*Remark: Measurement setup for testing on Antenna connector*

### TEST PROCEDURE

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW was set to about 1% of emission BW, VBW is set to 3 times the RBW, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.



## **TEST RESULTS**

*No non-compliance noted*


### **Test Data**

<b>Test Mode</b>	<b>CH</b>	<b>Frequency (MHz)</b>	<b>Bandwidth (kHz)</b>
GPRS 850 (Class 10)	128	824.18	243.3322
	190	836.60	241.1042
	251	848.79	236.9706

<b>Test Mode</b>	<b>CH</b>	<b>Frequency (MHz)</b>	<b>Bandwidth (kHz)</b>
GPRS 1900 (Class 10)	512	1850.20	241.6313
	661	1880.00	238.3755
	810	1909.80	239.4165


## Test Plot

### GPRS 850 (CH Low)



Transmit Freq Error 20.691 kHz  
x dB Bandwidth 306.916 kHz

### GPRS 850 (CH Mid)




Transmit Freq Error 242.189 Hz  
x dB Bandwidth 314.418 kHz

**GPRS 850(CH High)**

Agilent 18:25:07 Jun 5, 2008

R T




Transmit Freq Error 9.546 kHz  
x dB Bandwidth 300.547 kHz

**GPRS 1900 (CH Low)**

Agilent 18:42:06 Jun 5, 2008

R T




Transmit Freq Error -1.873 kHz  
x dB Bandwidth 310.558 kHz

### GPRS 1900 (CH Mid)

Agilent 18:42:43 Jun 5, 2008

R T




Transmit Freq Error      1.434 kHz  
x dB Bandwidth      313.283 kHz

### GPRS 1900 (CH High)

Agilent 18:43:14 Jun 5, 2008

R T



Transmit Freq Error      683.514 Hz  
x dB Bandwidth      316.388 kHz

## 7.4 OUT OF BAND EMISSION AT ANTENNA TERMINALS

### LIMIT

According to FCC §2.1051, FCC §22.917, FCC §24.238(a).


**Out of Band Emissions:** The mean power of emission must be attenuated below the mean power of the non-modulated carrier (P) on any frequency twice or more than twice the fundamental frequency by at least  $43 + 10 \log P$  dB.

**Mobile Emissions in Base Frequency Range:** The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitters operated must be attenuated to a level not exceed -80 dBm at the transmit antenna connector.

**Band Edge Requirements:** In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the Out of band Emission

### TEST CONFIGURATION

**Out of band emission at antenna terminals:**



### TEST PROCEDURE

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10 th harmonic. Limit = -13dBm

Band Edge Requirements (824 MHz and 849 MHz /1850MHz and 1910MHz): In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.



## **TEST RESULTS**

*No non-compliance noted.*

### **Test Data**

<b>Mode</b>	<b>CH</b>	<b>Location</b>	<b>Description</b>
GPRS 850 (Class 10)	128	Figure 7-1	Conducted spurious emissions, 30MHz - 20GHz
	190	Figure 7-2	Conducted spurious emissions, 30MHz - 20GHz
	251	Figure 7-3	Conducted spurious emissions, 30MHz - 20GHz

<b>Mode</b>	<b>CH</b>	<b>Location</b>	<b>Description</b>
GPRS 1900 (Class 10)	512	Figure 8-1	Conducted spurious emissions, 30MHz - 20GHz
	661	Figure 8-2	Conducted spurious emissions, 30MHz - 20GHz
	810	Figure 8-3	Conducted spurious emissions, 30MHz - 20GHz

<b>Mode</b>	<b>CH</b>	<b>Location</b>	<b>Description</b>
GPRS 850 (Class 10)	128	Figure 9-1	Band Edge emissions
	251	Figure 9-2	Band Edge emissions

<b>Mode</b>	<b>CH</b>	<b>Location</b>	<b>Description</b>
GPRS 1900 (Class 10)	512	Figure 10-1	Band Edge emissions
	810	Figure 10-2	Band Edge emissions

## Test Plot

### GPRS 850

Figure 7-1: Out of Band emission at antenna terminals – GPRS CH Low




Figure 7-2: Out of Band emission at antenna terminals – GPRS CH Mid





Figure 7-3: Out of Band emission at antenna terminals – GPRS CH High



## GPRS 1900

Figure 8-1: Out of Band emission at antenna terminals – GPRS CH Low




Figure 8-2: Out of Band emission at antenna terminals – GPRS CH Mid





Figure 8-3: Out of Band emission at antenna terminals – GPRS CH High



## GPRS 850

Figure 9-1: Band Edge emissions – GPRS CH Low





Figure 9-2: Band Edge emissions –GPRS CH High



## GPRS 1900

Figure 10-1: Band Edge emissions – GPRS CH Low





Figure 10-2: Band Edge emissions – GPRS CH High




## 7.5 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

### LIMIT


According to FCC §2.1053

### Test Configuration


#### Below 1 GHz



#### Above 1 GHz



## Substituted Method Test Set-up



## TEST PROCEDURE

The EUT was placed on a non-conductive, the measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$

## TEST RESULTS

*Refer to the attached tabular data sheets.*

**Radiated Spurious Emission Measurement Result****Below 1GHz****Operation Mode:** GPRS 850 / TX / CH 128**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
60.07	V	-40.83	-15.40	-56.23	-13.00	-43.23
239.52	V	-43.75	-13.19	-56.94	-13.00	-43.94
480.08	V	-50.66	-7.85	-58.51	-13.00	-45.51
531.49	V	-56.69	-7.18	-63.87	-13.00	-50.87
665.35	V	-60.04	-5.47	-65.51	-13.00	-52.51
719.67	V	-59.08	-4.97	-64.05	-13.00	-51.05
<hr/>						
239.52	H	-43.31	-12.81	-56.12	-13.00	-43.12
264.74	H	-47.59	-13.05	-60.64	-13.00	-47.64
294.81	H	-49.13	-12.99	-62.12	-13.00	-49.12
408.30	H	-52.79	-9.96	-62.75	-13.00	-49.75
480.08	H	-51.58	-7.89	-59.47	-13.00	-46.47
719.67	H	-57.68	-5.11	-62.79	-13.00	-49.79

***Remark:***

1. The emission behaviour belongs to narrowband spurious emission.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 850 / TX / CH 190**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
60.07	V	-41.11	-15.40	-56.51	-13.00	-43.51
177.44	V	-40.72	-13.96	-54.67	-13.00	-41.67
239.52	V	-44.35	-13.19	-57.54	-13.00	-44.54
480.08	V	-51.22	-7.85	-59.07	-13.00	-46.07
534.40	V	-57.30	-7.13	-64.43	-13.00	-51.43
719.67	V	-59.69	-4.97	-64.66	-13.00	-51.66
<hr/>						
133.79	H	-46.37	-13.69	-60.06	-13.00	-47.06
164.83	H	-46.13	-12.93	-59.05	-13.00	-46.05
214.30	H	-43.97	-13.76	-57.73	-13.00	-44.73
239.52	H	-45.84	-12.81	-58.65	-13.00	-45.65
480.08	H	-51.49	-7.89	-59.38	-13.00	-46.38
719.67	H	-57.12	-5.11	-62.23	-13.00	-49.23

**Remark:**

1. The emission behaviour belongs to narrowband spurious emission.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 850 / TX / CH 251**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
60.07	V	-41.83	-15.40	-57.23	-13.00	-44.23
134.76	V	-46.70	-11.97	-58.67	-13.00	-45.67
207.51	V	-46.37	-14.27	-60.64	-13.00	-47.64
240.49	V	-43.76	-13.20	-56.96	-13.00	-43.96
480.08	V	-51.30	-7.85	-59.15	-13.00	-46.15
533.43	V	-52.88	-7.15	-60.03	-13.00	-47.03
<hr/>						
60.07	H	-47.62	-15.57	-63.20	-13.00	-50.20
171.62	H	-46.30	-12.81	-59.10	-13.00	-46.10
208.48	H	-42.66	-13.63	-56.30	-13.00	-43.30
239.52	H	-45.56	-12.81	-58.38	-13.00	-45.38
480.08	H	-52.48	-7.89	-60.37	-13.00	-47.37
719.67	H	-57.91	-5.11	-63.02	-13.00	-50.02

**Remark:**

1. The emission behaviour belongs to narrowband spurious emission.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Above 1GHz****Operation Mode:** GPRS 850 / TX / CH 128**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1441.00	V	-56.04	2.45	-53.59	-13.00	-40.59
1651.00	V	-30.21	2.73	-27.48	-13.00	-14.48
2281.00	V	-59.41	4.44	-54.97	-13.00	-41.97
2470.00	V	-42.20	5.47	-36.72	-13.00	-23.72
3296.00	V	-56.10	7.28	-48.82	-13.00	-35.82
4122.00	V	-50.06	7.59	-42.48	-13.00	-29.48
<hr/>						
1441.00	H	-57.79	2.39	-55.40	-13.00	-42.40
1651.00	H	-35.59	2.76	-32.83	-13.00	-19.83
2470.00	H	-56.77	5.36	-51.41	-13.00	-38.41
2659.00	H	-60.54	6.02	-54.52	-13.00	-41.52
3282.00	H	-57.35	7.34	-50.01	-13.00	-37.01
4122.00	H	-59.64	7.43	-52.22	-13.00	-39.22

***Remark:***

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 850 / TX / CH 190**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1672.00	V	-32.57	2.74	-29.83	-13.00	-16.83
2512.00	V	-46.16	5.68	-40.48	-13.00	-27.48
3282.00	V	-58.34	7.28	-51.05	-13.00	-38.05
3345.00	V	-51.84	7.28	-44.56	-13.00	-31.56
4185.00	V	-47.97	7.58	-40.38	-13.00	-27.38
6565.00	V	-58.70	12.42	-46.28	-13.00	-33.28
1371.00	H	-58.47	2.05	-56.42	-13.00	-43.42
1441.00	H	-56.41	2.39	-54.02	-13.00	-41.02
1672.00	H	-39.52	2.78	-36.74	-13.00	-23.74
2512.00	H	-60.61	5.55	-55.07	-13.00	-42.07
3282.00	H	-58.94	7.34	-51.60	-13.00	-38.60
4185.00	H	-56.23	7.43	-48.81	-13.00	-35.81

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 850 / TX / CH 251**Test Date:** May 27, 2008**Temperature:** 25°C**Tested by:** Mark Yang**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1700.00	V	-34.09	2.75	-31.34	-13.00	-18.34
2547.00	V	-46.73	5.80	-40.93	-13.00	-27.93
3394.00	V	-50.19	7.28	-42.92	-13.00	-29.92
4248.00	V	-43.05	7.58	-35.47	-13.00	-22.47
6565.00	V	-57.55	12.42	-45.13	-13.00	-32.13
6789.00	V	-58.41	13.46	-44.95	-13.00	-31.95
<hr/>						
1441.00	H	-55.33	2.39	-52.94	-13.00	-39.94
1700.00	H	-39.54	2.79	-36.74	-13.00	-23.74
2547.00	H	-58.40	5.66	-52.74	-13.00	-39.74
3282.00	H	-55.87	7.34	-48.53	-13.00	-35.53
3394.00	H	-57.92	7.43	-50.50	-13.00	-37.50
4241.00	H	-52.48	7.43	-45.05	-13.00	-32.05

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Below 1GHz****Operation Mode:** GPRS 1900 / TX / CH 512**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
58.13	V	-30.93	-15.55	-46.49	-13.00	-33.49
133.79	V	-38.77	-12.00	-50.77	-13.00	-37.77
203.63	V	-39.29	-13.44	-52.74	-13.00	-39.74
399.57	V	-46.60	-10.60	-57.20	-13.00	-44.20
480.08	V	-50.62	-7.85	-58.48	-13.00	-45.48
799.21	V	-52.90	-3.75	-56.65	-13.00	-43.65
98.87	H	-30.41	-18.46	-48.87	-13.00	-35.87
138.64	H	-37.05	-13.33	-50.39	-13.00	-37.39
202.66	H	-38.01	-12.60	-50.61	-13.00	-37.61
401.51	H	-46.73	-10.28	-57.01	-13.00	-44.01
480.08	H	-45.71	-7.89	-53.60	-13.00	-40.60
720.64	H	-55.28	-5.08	-60.37	-13.00	-47.37

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 1900 / TX / CH 661**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
59.10	V	-30.87	-15.47	-46.34	-13.00	-33.34
137.67	V	-38.04	-11.87	-49.91	-13.00	-36.91
203.63	V	-40.28	-13.44	-53.73	-13.00	-40.73
480.08	V	-50.16	-7.85	-58.01	-13.00	-45.01
546.04	V	-51.13	-6.92	-58.04	-13.00	-45.04
668.26	V	-52.74	-5.46	-58.20	-13.00	-45.20
<hr/>						
98.87	H	-30.20	-18.46	-48.66	-13.00	-35.66
201.69	H	-37.77	-12.43	-50.20	-13.00	-37.20
359.80	H	-45.47	-11.41	-56.88	-13.00	-43.88
480.08	H	-44.03	-7.89	-51.92	-13.00	-38.92
673.11	H	-52.74	-5.42	-58.16	-13.00	-45.16
720.64	H	-55.61	-5.08	-60.69	-13.00	-47.69

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 1900 / TX / CH 810**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization (V/H)	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
59.10	V	-30.64	-15.47	-46.11	-13.00	-33.11
133.79	V	-39.26	-12.00	-51.26	-13.00	-38.26
204.60	V	-39.44	-13.65	-53.09	-13.00	-40.09
480.08	V	-50.45	-7.85	-58.30	-13.00	-45.30
542.16	V	-51.36	-6.99	-58.34	-13.00	-45.34
667.29	V	-50.95	-5.46	-56.42	-13.00	-43.42
98.87	H	-30.17	-18.46	-48.63	-13.00	-35.63
133.79	H	-37.53	-13.69	-51.22	-13.00	-38.22
201.69	H	-37.05	-12.43	-49.48	-13.00	-36.48
398.60	H	-48.36	-10.38	-58.74	-13.00	-45.74
480.08	H	-44.90	-7.89	-52.79	-13.00	-39.79
719.67	H	-55.09	-5.11	-60.21	-13.00	-47.21

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Above 1GHz****Operation Mode:** GPRS 1900 / TX / CH 512**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
2701.00	V	-57.50	6.31	-51.20	-13.00	-38.20
3282.00	V	-57.74	7.28	-50.46	-13.00	-37.46
3758.00	V	-49.03	7.44	-41.59	-13.00	-28.59
4927.00	V	-46.02	8.82	-37.21	-13.00	-24.21
5641.00	V	-58.32	9.16	-49.16	-13.00	-36.16
N/A						
2477.00	H	-53.19	5.39	-47.80	-13.00	-34.80
3072.00	H	-41.56	7.17	-34.39	-13.00	-21.39
3282.00	H	-58.27	7.34	-50.94	-13.00	-37.94
3702.00	H	-58.29	7.48	-50.81	-13.00	-37.81
4927.00	H	-55.66	8.38	-47.29	-13.00	-34.29
N/A						

***Remark:***

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 1900 / TX / CH 661**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3758.00	V	-52.89	7.44	-45.45	-13.00	-32.45
4927.00	V	-46.65	8.82	-37.83	-13.00	-24.83
5641.00	V	-56.19	9.16	-47.03	-13.00	-34.03
7391.00	V	-55.76	15.07	-40.69	-13.00	-27.69
N/A						
3282.00	H	-58.55	7.34	-51.21	-13.00	-38.21
4927.00	H	-39.49	8.38	-31.11	-13.00	-18.11
N/A						

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

**Operation Mode:** GPRS 1900 / TX / CH 810**Test Date:** March 26, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading level (dBuV)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3016.00	V	-42.03	7.30	-34.73	-13.00	-21.73
3282.00	V	-58.98	7.28	-51.70	-13.00	-38.70
3821.00	V	-55.57	7.48	-48.09	-13.00	-35.09
7391.00	V	-59.07	15.07	-44.01	-13.00	-31.01
N/A						
2680.00	H	-58.85	6.09	-52.77	-13.00	-39.77
3282.00	H	-58.37	7.34	-51.04	-13.00	-38.04
3821.00	H	-58.78	7.46	-51.32	-13.00	-38.32
7391.00	H	-49.45	15.06	-34.38	-13.00	-21.38
N/A						

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.


## 7.6 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

### LIMIT

According to FCC §2.1055, FCC §24.235.

Frequency Tolerance: 2.5 ppm

### Test Configuration



**Remark:** Measurement setup for testing on Antenna connector



## TEST PROCEDURE

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

## TEST RESULTS

*No non-compliance noted.*

Reference Frequency: GPRS Mid Channel 836.6 MHz @ 20°C				
Limit: ± 2.5 ppm = 2090 Hz				
Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
12	50	83600015	25	2090
	40	83600011	21	
	30	83600001	11	
	20	83599990	0	
	10	83600005	15	
	0	83600016	26	
	-10	83600005	15	
	-20	83600003	13	
	-30	83599997	7	

Reference Frequency: GPRS Mid Channel 1880 MHz @ 20°C				
Limit: ± 2.5 ppm = 4700 Hz				
Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
12	50	1879999991	4	4700
	40	1880000014	27	
	30	1880000010	23	
	20	1879999987	0	
	10	1879999959	-28	
	0	1880000020	33	
	-10	1879999987	0	
	-20	1879999990	3	
	-30	1879999993	6	


## 7.7 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

### LIMIT

According to FCC §2.1055, FCC §24.235,

Frequency Tolerance: 2.5 ppm.

### Test Configuration



*Remark: Measurement setup for testing on Antenna connector.*



## TEST PROCEDURE

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

## TEST RESULTS

*No non-compliance noted.*

<b>Reference Frequency: GPRS Mid Channel 836.6 MHz @ 20°C</b>				
Limit: $\pm 2.5$ ppm = 2090Hz				
Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
13.2	20	83599991	1	2090
12		83599990	0	
10.8		83600006	16	
9 (End Point)		83599998	-8	

<b>Reference Frequency: GPRS Mid Channel 1880 MHz @ 20°C</b>				
Limit: $\pm 2.5$ ppm = 4700 Hz				
Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
13.2	20	1879999992	5	4700
12		1879999987	0	
10.8		1880000015	28	
9(End Point)		1880000006	19	



## 7.8 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete..



## TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

**Operation Mode:**

Normal Link

**Test Date:**

June 16, 2008

**Temperature:**

22°C

**Tested by:**

Jerry Lin

**Humidity:**

45% RH


Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1600	40.61	13.71	0.19	40.80	13.90	65.46	55.46	-24.66	-41.56	L1
0.1950	41.74	36.74	0.16	41.90	36.90	63.82	53.82	-21.92	-16.92	L1
0.2600	33.67	29.17	0.13	33.80	29.30	61.43	51.43	-27.63	-22.13	L1
0.7200	35.07	34.97	0.03	35.10	35.00	56.00	46.00	-20.90	-11.00	L1
3.0150	32.10	23.90	0.10	32.20	24.00	56.00	46.00	-23.80	-22.00	L1
26.2850	34.07	15.67	0.93	35.00	16.60	60.00	50.00	-25.00	-33.40	L1
0.1750	33.93	9.63	0.17	34.10	9.80	64.72	54.72	-30.62	-44.92	L2
0.2200	29.46	7.86	0.14	29.60	8.00	62.82	52.82	-33.22	-44.82	L2
0.7200	35.57	31.67	0.03	35.60	31.70	56.00	46.00	-20.40	-14.30	L2
2.9400	28.80	22.20	0.10	28.90	22.30	56.00	46.00	-27.10	-23.70	L2
4.9400	22.46	14.76	0.24	22.70	15.00	56.00	46.00	-33.30	-31.00	L2
24.3200	33.20	24.00	0.90	34.10	24.90	60.00	50.00	-25.90	-25.10	L2

**Remark:**

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

## Test Plots

### *Conducted emissions (Line 1)*



### *Conducted emissions (Line 2)*

