



WHA YU INDUSTRIAL CO., LTD. (HEAD OFFICE)
 DONGGUAN AEON TECH CO.,LTD.(CHINA)
 TAI HWA ELECTRONIC CO., LTD.(CHINA)
 SHANGHAI HUA YU ELECTRONIC CO., LTD.(CHINA)
 SU ZHOU AEON TECH CO., LTD. (CHINA)

SPECIFICATION FOR APPROVAL

CUSTOMER: 中磊電子股份有限公司

PART NAME: RF Antenna Cable Assembly

PART NO.:

REVISION:

W. Y. P/NO.: C147-510415-A(SSR-73065)

REV.: X1

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
APPROVED BY :	周東生 	
DATE :	12/6/07 	

WHA YU GROUP

WHA YU INDUSTRIAL CO., LTD.(HEAD OFFICE)

華裕實業股份有限公司

Address: No. 326, Sec. 2, Kung Tao 5 Road, Hsin Chu City, Taiwan, R.O.C.

Tel: +886-3-5714225(REP.) Fax: + 886-3-5713853 · + 886-3-5723600

DONGGUAN AEON TECH CO., LTD.(CHINA)

東莞台霖電子通訊有限公司

Address: Lakeside Industrial Park, Da Ling Shan Town, Dong Guan City, Guangdong, China

Tel: + 86-769-85655858 Fax: + 86-769-85655251

TAI HWA ELECTRONIC FACTORY

台樺電業製品廠

Address: Pak Ho District, Hou Street Town, Dong Guan City, Guangdong, China

Tel: + 86-769-85599375 · + 86-769-85912375 Fax: + 86-769-85599376

HUA HONG INTERNATIONAL LTD.

華弘國際有限公司

Address: Rm.1103A, President Commercial Centre, 608 Nathan Road, Mong Kok, Kowloon, Hong Kong

Tel: + 86-852-27712210 Fax: + 86-852-23843747

SHANGHAI HUA YU ELECTRONIC CO., LTD. (CHINA)

上海華裕電子有限公司

Address: 3586, Wai Qing Song Road, Qing Pu County, Shanghai China

Tel: + 86-21-59741348 · + 86-21-59744101~4 Fax: + 86-21-59741347

SU ZHOU AEON TECH CO., LTD. (CHINA)

蘇州華廣電通有限公司

Address: Limin North Road, LiLi Town, LiLi Industrial Park, LinHu Economic Zone

Wujiang City, Jiangsu Province, China

Tel: + 86-512-63627980 Fax: + 86-512-63627981

Contents

<i>Item</i>	<i>Description</i>	<i>Page</i>
1.	天線規格表	 1
2.	成品圖	 2
3.	測試報告	 3~7

RF Antenna Assembly

Specification

1. Electrical Properties :


- 1.1 Frequency Range..... 824MHz ~ 960MHz/1710MHz ~ 1990MHz
- 1.2 Impedance 50Ω Nominal
- 1.3 VSWR 5 : 1 Max.
- 1.4 Radiation Omni-directional
- 1.5 Gain(peak)..... -0.5dBi (824MHz ~ 960MHz)
1.0dBi (1710MHz ~ 1990MHz)
- 1.6 Polarization..... Linear; Vertical
- 1.7 Admitted Power..... 1W
- 1.8 Cable..... RG-178 Coaxial Cable
- 1.9 Connector..... SMA Plug Reverse

2. Physical Properties :




- 2.1 Antenna Cover..... TPE
- 2.2 Antenna Base..... PC
- 2.3 Antenna Base..... PBT
- 2.4 Operating Temp. -10°C ~ +60°C
- 2.5 Storage Temp. -10°C ~ +70°C
- 2.6 Color White

CG-

REV	DATE	DESCRIPTION
X1	12/4-2007	New Issue



GP標籤貼於外箱兩邊側面左上角共
2PCS Label貼於外箱兩邊側面共2PCS



Packing : 20pcs/Tray

6	Cable	RG-178 , Translucent Brown ; 50 Ω	1	
5	Connector	SMA Straight Plug/Reverse	1	
4	Rivet	POM , White	2	
3	Antenna Base	PBT ; Color:White	1	
2	Antenna Base	PC ; Color:White	1	
1	Antenna Cover	TPE ; Color:White	1	
NO	DESCRIPTION		QTY	REMARK

CUSTOMER'S SIGNATURE

XX.	±5	APPROVED
X.	±3.0	CHECKED
.X	±1.0	DRAWING
.XX	±0.5	
.XXX	±0.1	
96.12.5		


CUSTOMER: 中磊		
PART NO :		
PARTNAME: RF Antenna Assembly		
W.Y P/NO : C147-510415-A		
REV	UNIT	FILE : SSR-73065
X1	m/m	SHEET : 1/1

M.gear Wha Yu Group


THIS DRAWING, AND ITS INHERANT DESIGN CONCEPTS, ARE THE PROPERTY OF WHA YU AND AS SUCH MAY NOT BE COPIED, REPRODUCED, OR GIVEN TO THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF WHA YU.

RF Antenna Assembly


P/NO : C147-510415-A(SSR-73065) SPEC :Dual Band




Far-field Amplitude of Antenna C147-510415-A(SSR-73065)-V.nsi



Far-field Amplitude of Antenna C147-510415-A(SSR-73065)-H.nsi



Far-field Amplitude of Antenna C147-510415-A(SSR-73065)-V.nsi



Far-field Amplitude of Antenna C147-510415-A(SSR-73065)-H.nsi

