

# Ke Mei Ou Laboratory Co., Ltd.

7A, Jiaxiangge, Jiahuixincheng, No.3027, Shennan Rd., Futian, Shenzhen, Guangdong, P.R.China. Zip Code: 518033  
Tel: + 86 755 83642690 Fax: + 86 755 83297077  
www.kmolab.com



FEDERAL COMMUNICATIONS COMMISSION  
Registration Number: 125782  
INDUSTRY CANADA  
Registration Number: IC4986

## FCC TEST REPORT

Under  
FCC 15 Subpart C, Paragraph 15.239

Prepared For :

### Beijing Founder Import & Export Co., Ltd.

Rm 922, 9F, Founder Building Zhongguancun, No.298 Chengfu Road Beijing, China

FCC ID: S2W-KELLANDI

EUT: Car E-Jukebox

Model: KELLAND-I

March 6, 2005

Report Type: Original Report

Test Engineer: Peter Lin

Test Date: February 22, 2005

  
Review By: \_\_\_\_\_

Apollo Liu / Manager

The test report consists 22 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Ke Mei Ou Laboratory Corporation. The test result in the report only applied to the tested sample.

**TABLE OF CONTENTS**

<b>1. General Information.....</b>	<b>3</b>
1. 1 Notes.....	3
1. 2 Testing Laboratory .....	3
1. 3 Details of Applicant .....	3
1. 4 Application Details.....	3
1. 5 Test Item.....	3
1. 6 Test Standards.....	3
<b>2. Technical Test.....</b>	<b>4</b>
2. 1 Summary of Test Results.....	4
2. 2 Antenna Requirement.....	4
<b>3. EUT Modifications.....</b>	<b>4</b>
<b>4. Conducted Power Line Test.....</b>	<b>5</b>
4. 1 Test Equipment .....	5
4. 2 Test Procedure .....	5
4. 3 Test Setup .....	5
4. 4 Configuration of The EUT.....	6
4. 5 EUT Operating Condition.....	7
4. 6 Conducted Power Line Emission Limits .....	7
4. 7 Conducted Power Line Test Result.....	8
<b>5. Radiated Emission Test.....</b>	<b>10</b>
5. 1 Test Equipment .....	10
5. 2 Test Procedure .....	10
5. 3 Radiated Test Setup .....	10
5. 4 Configuration of The EUT.....	11
5. 5 EUT Operating Condition.....	11
5. 6 Radiated Emission Limit .....	11
5. 7 Radiated Emission Test Result.....	12
<b>6. Band Edge.....</b>	<b>13</b>
6. 1 Test Equipment .....	13
6. 2 Test Procedure .....	13
6. 3 Radiated Test Setup .....	13
6. 4 Configuration of The EUT.....	14
6. 5 EUT Operating Condition.....	14
6. 6 Band Edge FCC 15.239 Limit.....	14
6. 7 Band Edge Test Result.....	14
<b>7. Photos of Testing.....</b>	<b>16</b>
7. 1 EUT Test Photographs.....	16
7. 2 EUT Detailed Photographs .....	17
<b>8. FCC ID Label .....</b>	<b>21</b>
<b>9. Test Equipment.....</b>	<b>22</b>

## 1. General Information

### 1. 1 Notes

The test results of this report relate exclusively to the test item specified in 1.5. The KMO Lab does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the KMO Lab.

### 1. 2 Testing Laboratory

#### Ke Mei Ou Laboratory Co., Ltd.

7A, Jiaxiangge, Jiahuixincheng, No.3027, Shennan Rd., Futian, Shenzhen, Guangdong, P.R.China.

Tel: +86 755 83642690 Fax: +86 755 83297077

Email: [kmo@kmolab.com](mailto:kmo@kmolab.com)

Internet: [www.kmolab.com](http://www.kmolab.com)

Site on File with the Federal Communications Commission – United States

Registration Number: 125782

For 3 & 10 meter OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC4986

For 3 & 10 meter OATS

### 1. 3 Details of Applicant

Name : Beijing Founder Import & Export Co., Ltd.

Address : Rm 922, 9F, Founder Building Zhongguancun, No.298 Chengfu Road Beijing, China.

Contact : Kevin Chen / Vice Manager

Tel : +86 10 82529598

Fax : +86 10 82529595

### 1. 4 Application Details

Date of Receipt of Application : January 25, 2005

Date of Receipt of Test Item : January 25, 2005

Date of Test : February 22~March 6, 2005

### 1. 5 Test Item

Manufacturer : Shenzhen Founder Cyber Tech. Co., Ltd.

Address : Peking University Founder Science Park, Shiyan, Bao'an, Shenzhen, China

Brand Name : N/A

Model No. : KELLAND-I

Description : Car E-Jukebox

### Additional Information

Frequency : 88.1MHz~88.9MHz

Number of Channels : 5

Antenna : Internal

Power Supply : DC 9~12V, 200mA

Operation Distance : 3~5m

Resolution : N/A

### 1. 6 Test Standards

FCC 15 Subpart C, Paragraph 15.239

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

## 2. Technical Test

### 2. 1 Summary of Test Results

**The EUT has been tested according to the following specifications:**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	PASS	Complies
FCC Part 15, Paragraph 15.207	Conducted Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.239 Limit	Field Strength of Fundamental	PASS	Minimum passing margin is -19.96 / -2.56 dB at 88.100 MHz Vertical
FCC Part 15, Subpart C Paragraph 15.239 Limit & Paragraph 15.209	Radiated Test	PASS	Meets Class B Limit Minimum passing margin is -3.82 dB at 40.600 MHz Vertical
FCC Part 15 Subpart C Paragraph 15.239 Limit	Measured Bandwidth	PASS	Complies.

### 2. 2 Antenna Requirement

#### A. Regulation

FCC section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

#### B. Result

The EUT has a built in antenna which is a short wire solder on the PCB, this is permanently attached antenna and meets the requirements of this section.

## 3. EUT Modifications

No modification by Ke Mei Ou Laboratory Co., Ltd.

## 4. Conducted Power Line Test


### 4. 1 Test Equipment

Please refer to Section 9 this report.

### 4. 2 Test Procedure

The EUT was tested according to ANSI C63.4 - 2001. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 uHenry as specified by section 5.1 of ANSI C63.4 - 2001. cables and peripherals were moved to find the maximum emission levels for each frequency.

### 4. 3 Test Setup



For the actual test configuration, Please refer to the related items – Photos of Testing.

#### 4. 4 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2001. EUT is the transmitter part of a FM transmitter. According to the specifications of the manufacturer, The EUT has been tested as an independent unit together with other necessary accessories or support units.

Three channels were provided to this EUT.

Channel	Frequency (MHz)
Low	88.1
Middle	88.5
High	88.9

Note: The channel low, middle, high were pre-tested. The channel low, worst case one, was chosen for radiated emission test. Test with a MP3 Player as the sound source for the EUT.

The following support units or accessories were used to form a representative test configuration during the tests.

#### A. EUT

Device	Manufacturer	Model #	FCC ID
Car E-Jukebox	Shenzhen Founder Cyber Tech. Co., Ltd.	KELLAND-I	S2W-KELLANDI

#### B. Internal Devices

Device	Manufacturer	Model #	FCCID / DoC
N/A			


#### C. Peripherals

Device	Manufacturer	Model # Serial #	FCC ID/ DoC	Cable
MP3 Player	Bantam Interactive Technologies, Inc.	M2104	DoC	N/A
N/A				
N/A				

#### 4. 5 EUT Operating Condition

Operating condition is according to ANSI C63.4 - 2001.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



#### 4. 6 Conducted Power Line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHz)	Class A QP/AV	Class B QP/AV
0.15 – 0.5	79/66	66-56/56-46
0.5 – 5.0	73/60	56/46
5.0 - 30	73/60	60/50

**NOTE** : In the above table, the tighter limit applies at the band edges.

#### 4. 7 Conducted Power Line Test Result

Product	: CAR E-Jukebox	Test Mode	: CH1
Test Item	: Conducted Emission Data	Temperature	: 25 °C
Test Voltage	: DC 9V (Power by Class 2 Adaptor)	Humidity	: 56%RH
Test Result	: <b>PASS</b>		

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All readings are quasi -peak values with a resolution bandwidth of 9 KHz.

- Temperature : 26 °C
- Humidity : 53 % RH

**CH1**

FCC Part 15 Paragraph 15.207							
Frequency (MHz)	Emission (dBuV)		LINE/ NEUTRAL	Limit (dBuV)		Margin (dB)	
	QP	AV		QP	AV	QP	AV
NF			LINE				
NF			NEUTRAL				
NF			LINE				
NF			NEUTRAL				
NF			LINE				
NF			NEUTRAL				

**Note:** NF = No Significant Peak was Found.

**Note:**

- Uncertainty in conducted emission measured is <+/ -2dB.
- The emission levels of other frequencies were very low against the limit.
- All Reading Levels are Quasi-Peak and Average value.
- Emission = Meter Reading + Factor; Factor = Insertion Loss + Cable Loss.
- Margin Value = Emission Level - Limit Value.

**Conducted Emission****EN55022**

EUT: Car E-Jukebox M/N: KELLAND-I

Manufacturer: Shenzhen Founder Cyber Tech. Co., Ltd.


Operating Condition: Transmitter

Test Site: Ke Mei Ou Laboratory

Operator: Peter Lin

Test Specification: LINE&amp;NEUTRAL

Comment:



## 5. Radiated Emission Test


### 5. 1 Test Equipment

Please refer to Section 9 this report.

### 5. 2 Test Procedure

1. The EUT was tested according to ANSI C63.4 - 2001. The radiated test was performed at Ke Mei Ou Laboratory. This site is on file with the FCC laboratory division, Registration No. 125782.
2. The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2001.
3. The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
4. The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
5. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
6. The antenna polarization : Vertical polarization and Horizontal polarization.

### 5. 3 Radiated Test Setup



For the actual test configuration , please refer to the related items – Photos of Testing.

## 5. 4 Configuration of The EUT

Same as section 4 . 4 of this report

## 5. 5 EUT Operating Condition

Same as section 4 . 5 of this report.

## 5. 6 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

### A. FCC Part 15 Subpart C Paragraph 15.239 Limit

According to 15.239 the field strength of emission from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (3m)	
	Peak (dBuV/m)	Average (dBuV/m)
88 to 108	67.96	47.96

### B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency (MHz)	Distance (m)	Field Strength (microvolts/m)
0.009 - 0.490	300	2400/F(kHz)
0.490 - 1.705	30	24000/F(kHz)
1.705 – 30.0	30	30
30 - 88	3	100
88 - 216	3	150
216 - 960	3	200
ABOVE 960	3	500

**Note:** As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

## 5. 7 Radiated Emission Test Result

### A. Fundamental Radiated Emission Data

Product	: Car E-Jukebox	Test Mode	: Channel Low
Test Item	: Fundamental Radiated Emission Data	Temperature	: 25 °C
Test Voltage	: DC 12 (Power by Battery)	Humidity	: 56%RH
Test Result	: PASS		

Freq. (MHz)	Emission PK/AV (dBuV/m)	HORIZ / VERT	Limits PK/AV (dBuV/m)	Margin (dB)
88.100	40.6 / 37.9	HORIZ	67.96 / 47.96	-27.36 / -10.06
88.100	48.0 / 45.4	VERT	67.96 / 47.96	-19.96 / -2.56

**Note:** (1) PK= Peak, AV=Average.  
 (2) Emission Level = Reading Level + Probe Factor + Cable Loss.

Product	: Car E-Jukebox	Test Mode	: Channel Middle
Test Item	: Fundamental Radiated Emission Data	Temperature	: 25 °C
Test Voltage	: DC 12 (Power by Battery)	Humidity	: 56%RH
Test Result	: PASS		

Freq. (MHz)	Emission PK/AV (dBuV/m)	HORIZ / VERT	Limits PK/AV (dBuV/m)	Margin (dB)
88.500	39.9 / 36.6	HORIZ	67.96 / 47.96	-28.06 / -11.36
88.500	46.7 / 45.1	VERT	67.96 / 47.96	-21.26 / -2.86

**Note:** (1) PK= Peak, AV=Average.  
 (2) Emission Level = Reading Level + Probe Factor + Cable Loss.

Product	: Car E-Jukebox	Test Mode	: Channel High
Test Item	: Fundamental Radiated Emission Data	Temperature	: 25 °C
Test Voltage	: DC 12 (Power by Battery)	Humidity	: 56%RH
Test Result	: PASS		

Freq. (MHz)	Emission PK/AV (dBuV/m)	HORIZ / VERT	Limits PK/AV (dBuV/m)	Margin (dB)
88.900	34.2 / 30.5	HORIZ	67.96 / 47.96	-33.76 / -17.46
88.900	43.7 / 41.4	VERT	67.96 / 47.96	-24.26 / -6.56

**Note:** (1) PK= Peak, AV=Average.  
 (2) Emission Level = Reading Level + Probe Factor + Cable Loss.

### B. General Radiated Emission Data & Harmonics Radiated Emission Data

Product	: Car E-Jukebox	Test Mode	: Channel Low
Test Item	: General Radiated Emission Data & Harmonics Radiated Emission Data	Temperature	: 25 °C
Test Voltage	: DC 12 (Power by Battery)	Humidity	: 56%RH
Test Result	: PASS		

Freq. (MHz)	Emission (dBuV/m)	HORIZ / VERT	Limits (dBuV/m)	Margin (dB)
36.520	29.63	HORIZ	40.0	-10.37
40.600	36.18	VERT	40.0	-3.82
176.240	32.71	HORIZ	43.5	-10.79

**Note:** (1) All Reading Levels below 1GHz are Quasi-Peak, above are peak and average value.  
 (2) Emission Level = Reading Level + Probe Factor + Cable Loss.

## 6. Band Edge


### 6. 1 Test Equipment

Please refer to Section 9 this report.

### 6. 2 Test Procedure

1. The EUT was tested according to ANSI C63.4 - 2001. The radiated test was performed at Ke Mei Ou Laboratory. This site is on file with the FCC laboratory division, Registration No. 125782.
2. The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2001.
3. The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz , peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
4. The antenna height were varied from 1 m to 4 m high to find the maximum emission for each frequency.
5. The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field strength of harmonics measurement. The bandwidth below 30MHz setting on the field strength meter is 10 kHz, above 1GHz are 1 MHz.
6. Maximizing procedure was performed on the highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
7. The antenna polarization : Vertical polarization and horizontal polarization.

### 6. 3 Radiated Test Setup



For the actual test configuration , please refer to the related items – Photos of Testing

## 6. 4 Configuration of The EUT

Same as section 4 . 4 of this report

## 6. 5 EUT Operating Condition


Same as section 4 . 5 of this report.

## 6. 6 Band Edge FCC 15.239 Limit

Emission from the intentional radiator shall be confined within a bands 200kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88 to 108 MHz.


## 6. 7 Band Edge Test Result

Product	: Car E-Jukebox	Test Mode	: Channel Low
Test Item	: Band Edge Data	Temperature	: 25 °C
Test Voltage	: DC 12 (Power by Battery)	Humidity	: 56%RH
Test Result	: <b>PASS</b>		




Date: 28.FEB.2005 17:07:07

Product : Digital FM Transmitter  
 Test Item : Band Edge Data  
 Test Voltage : DC 3.3V (Power by iPod)  
 Test Result : **PASS**



Date: 28.FEB.2005 17:15:45  
 Product : Digital FM Transmitter  
 Test Item : Band Edge Data  
 Test Voltage : DC 3.3V (Power by iPod)  
 Test Result : **PASS**



Date: 28.FEB.2005 16:35:32

**Note:** (1) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.  
 (2) The average measurement was not performed when the peak measured data under the limit of average detection.

## 7. Photos of Testing

### 7. 1 EUT Test Photographs

Conducted emission test view



Radiated emission test view



## 7.2 EUT Detailed Photographs

EUT top view




EUT bottom view






EUT inside whole view




Main board component side







Main board solder side



## 8. FCC ID Label

FCC ID: S2W-KELLANDI

**This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.**

The Label must not be a stick-on paper label. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

### Proposed Label Location on EUT

EUT Bottom View/Proposed FCC ID Label Location



## 9. Test Equipment

The following test equipments were used during the radiated & conducted emission test:

Equipment/ Facilities	Manufacturer	Model #	Serial No.	Date of Cal.	Due Date
Turntable	KMO	KSZ001T	200306	NCR	NCR
Antenna Tower	KMO	KSZ002AT	200307	NCR	NCR
OATS	KMO	KSZSITE001	N/A	July 06, 2004	July 06, 2005
EMI Test Receiver	Rohde & Schwarz	ESPI3	100180	Oct.18, 2004	Oct.18, 2005
Signal Generator	Rohde & Schwarz	SMT03	100059	Feb.01, 2005	Feb.01, 2006
Signal Generator	FLUKE	PM5418+Y/C	LO747012	Feb 01, 2005	Feb 01, 2006
Signal Generator	FLUKE	PM5418TX	LO738007	Feb 01, 2005	Feb 01, 2006
Biconical Antenna	Rohde & Schwarz	HK116	EMC0502	Dec. 14,2004	Dec. 14,2005
Bilog Antenna	Chase	CBL6111C	2576	Feb.01, 2005	Feb.01, 2006
Ultra Broadband Antenna	Rohde & Schwarz	HL 562	100110	June.05, 2004	June.05, 2005
AMN	Rohde & Schwarz	ESH3-Z5	100196	Oct. 23,2004	Oct. 23, 2005
AMN	Rohde & Schwarz	ESH3-Z5	100197	Oct. 23,2004	Oct. 23, 2005
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
Absorbing Clamp	Rohde & Schwarz	MDS-21	N/A	Oct. 29,2004	Oct. 29,2005
KMO Shielded Room	KMO	KMO-001	N/A	N/A	N/A
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Feb. 27, 2005	Feb.27, 2006
AMN	Rohde & Schwarz	ESH3-Z5	100002	Feb. 01, 2005	Feb.01, 2006
LISN	Kyoritsu	KNW-407	8-1441-8	Feb. 23, 2005	Feb.23, 2006
EMI Test Receiver	Rohde & Schwarz	ESI26	838786/013	Feb. 01, 2005	Feb.01, 2006
Bilog Antenna	Chase	CBL6112B	2591	Feb. 01, 2005	Feb.01, 2006
Horn Antenna	Rohde & Schwarz	HF906	100014	Feb. 01, 2005	Feb.01, 2006
Power Meter	Rohde & Schwarz	NRVD	100041	Feb. 01, 2005	Feb.01, 2006
Radio Communication Test Set	Rohde & Schwarz	CMS 54	846621/024	Feb 01, 2005	Feb 01, 2006
Modulation Analyzer	Hewlett-Packard	8901B	2303A00362	Feb 01, 2005	Feb 01, 2006
Temperature Chamber	TABAI	PSL-4GTW	N/A	Feb 06,2005	Feb 06, 2006
3m Semi-Anechoic Chamber	Albatross Projects	9mX6mX6m	N/A	Feb. 01, 2005	Feb.01, 2006