

## FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Result

#### Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

**Calculated Data:**

For worst case:

Mode	Frequency (MHz)	Antenna Gain <sup>#</sup>		Max Tune-up Power <sup>#</sup>		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
BT	2402-2480	2.50	1.78	2.5	1.78	25	0.0004	1.0
BLE	2402-2480	2.50	1.78	7.0	5.01	25	0.0011	1.0
2.4G Wi-Fi	2412-2462	5.51	3.56	30.0	1000	25	0.4533	1.0
5G Wi-Fi	5150-5250	5.61	3.64	15.5	35.48	25	0.0164	1.0
	5250-5350	5.61	3.64	16.5	44.67	25	0.0207	1.0
	5470-5725	5.61	3.64	16.0	39.81	25	0.0185	1.0
	5725-5850	5.61	3.64	19.0	79.43	25	0.0368	1.0
	5850-5895	5.61	3.64	20.5	112.20	25	0.0520	1.0
6G Wi-Fi	5925-6425	5.61	3.64	12.0	15.85	25	0.0073	1.0
	6425-6525	5.61	3.64	11.0	12.59	25	0.0058	1.0
	6525-6875	5.61	3.64	11.0	12.59	25	0.0058	1.0
	6875-7125	5.61	3.64	11.0	12.59	25	0.0058	1.0

Note:

- 1) The tune up conducted power and antenna gain was declared by the applicant.
- 2) For the Wi-Fi mode, the antenna gain should be the directional gain.
- 3) The BT, 2.4G Wi-Fi, 5G Wi-Fi and 6G Wi-Fi cannot Simultaneous transmitting.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 25cm from nearby persons.

**Result: Compliant.**