

CM91 two way wireless transmitters

User and Installation Guide

Installation: Mount the CM91 master into the socket of the hose handle by pressing it in. secure in place with a dab of silicone glue and attaché the battery to the battery drawer.

Mount the CM91 slave into the power unit of the central vacuum system. Locate its socket and push the module in; finish by securing the module with a dab of silicone glue.

Programming and testing: In order to operate the master and the slave must be paired. Locate the slave “learn” button and hold in depress it for 2 seconds until the green LED turns on. Within 30 seconds press the ON button of the master unit.

The slave will blink once indicating that the pairing was successful and then turn OFF.

Operation: Operate the ON/OFF button of the master several times to acknowledge that the unit functions properly by turning the power unit On and OFF.

Warning: Changes or modifications not expressly approved by Alutron Modules Inc. could void the user’s authority to operate the equipment.

Unauthorized changes or modifications to the equipment could void the user’s authority to operate the equipment.

Federal Communications Commission (FCC) Statement: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced technician for help.

Properly shielded and grounded cables and connectors must be used to meet FCC emission limits. Alutron Modules Inc. is not responsible for any radio or television interference caused by using other than recommended cables or connectors.

These devices comply with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) These devices may not cause harmful interference, and (2) these devices must accept any interference received, including interference that may cause undesired operation.