

## FCC Test Report

**Report No.:** RF160224C17A

**FCC ID:** S4L4AP54

**Test Model:** 4AP54

**Received Date:** Nov. 24, 2016

**Test Date:** (1) Mar. 04, 2016 ~ Mar. 15, 2016  
(2) Dec. 12, 2016

**Issued Date:** Dec. 20, 2016

**Applicant:** TomTom International BV

**Address:** De Ruijterkade 154 Amsterdam, 1011 AC Netherlands

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
( R.O.C )

**Test Location:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan  
Hsien 333, Taiwan, R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

<b>Release Control Record .....</b>	<b>4</b>
<b>1 Certificate of Conformity .....</b>	<b>5</b>
<b>2 Summary of Test Results.....</b>	<b>6</b>
2.1 Measurement Uncertainty.....	6
2.2 Modification Record .....	6
<b>3 General Information .....</b>	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Description of Test Modes.....	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	9
3.3 Description of Support Units .....	10
3.3.1 Configuration of System under Test .....	10
3.4 General Description of Applied Standards.....	11
<b>4 Test Types and Results .....</b>	<b>12</b>
4.1 Radiated Emission and Bandedge Measurement .....	12
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	12
4.1.2 Test Instruments .....	13
4.1.3 Test Procedures.....	15
4.1.4 Deviation from Test Standard .....	15
4.1.5 Test Set Up .....	16
4.1.6 EUT Operating Conditions.....	16
4.1.7 Test Results .....	17
4.2 Number of Hopping Frequency Used .....	23
4.2.1 Limits of Hopping Frequency Used Measurement .....	23
4.2.2 Test Setup.....	23
4.2.3 Test Instruments .....	23
4.2.4 Test Procedure .....	23
4.2.5 Deviation from Test Standard .....	23
4.2.6 Test Results .....	23
4.3 Dwell Time on Each Channel.....	25
4.3.1 Limits of Dwell Time on Each Channel Measurement.....	25
4.3.2 Test Setup.....	25
4.3.3 Test Instruments .....	25
4.3.4 Test Procedures.....	25
4.3.5 Deviation from Test Standard .....	25
4.3.6 Test Results .....	26
4.4 Channel Bandwidth.....	29
4.4.1 Limits of Channel Bandwidth Measurement.....	29
4.4.2 Test Setup.....	29
4.4.3 Test Instruments .....	29
4.4.4 Test Procedure .....	29
4.4.5 Deviation from Test Standard .....	29
4.4.6 EUT Operating Condition .....	29
4.4.7 Test Results .....	30
4.5 Hopping Channel Separation.....	31
4.5.1 Limits of Hopping Channel Separation Measurement.....	31
4.5.2 Test Setup.....	31
4.5.3 Test Instruments .....	31
4.5.4 Test Procedure .....	31
4.5.5 Deviation from Test Standard .....	31
4.5.6 Test Results .....	32
4.6 Maximum Output Power .....	33
4.6.1 Limits of Maximum Output Power Measurement .....	33
4.6.2 Test Setup.....	33

4.6.3 Test Instruments .....	33
4.6.4 Test Procedure .....	33
4.6.5 Deviation from Test Standard .....	33
4.6.6 EUT Operating Condition .....	33
4.6.7 Test Results .....	34
4.7 Conducted Out of Band Emission Measurement .....	35
4.7.1 Limits Of Conducted Out Of Band Emission Measurement .....	35
4.7.2 Test Instruments .....	35
4.7.3 Test Procedure .....	35
4.7.4 Deviation from Test Standard .....	35
4.7.5 EUT Operating Condition .....	35
4.7.6 Test Results .....	35
<b>5 Pictures of Test Arrangements.....</b>	<b>39</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>40</b>

### Release Control Record

Issue No.	Description	Date Issued
RF160224C17A	Original Release	Dec. 20, 2016

## 1 Certificate of Conformity

**Product:** GPS Navigation System

**Brand:** TomTom

**Test Model:** 4AP54

**Sample Status:** Production Unit

**Applicant:** TomTom International BV

**Test Date:** (1) Mar. 04, 2016 ~ Mar. 15, 2016

(2) Dec. 12, 2016


**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Dec. 20, 2016

Evonne Liu / Specialist

**Approved by :**  , **Date:** Dec. 20, 2016

Stanley Wu / Assistant Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Not applicable	Without AC power port of the EUT
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Pass	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -11.75 dB at 54.3 MHz.
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

**NOTE:** If The Frequency Hopping System operating in 2400-2483.5 MHz band and the output power less than 125 mW. The hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of hopping channel whichever is greater.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	GPS Navigation System
<b>Brand</b>	TomTom
<b>Test Model</b>	4AP54
<b>Status of EUT</b>	Production Unit
<b>Power Supply Rating</b>	3.7Vdc (Battery) 5Vdc (Home Charger) 12/24Vdc (Car Battery)
<b>Modulation Type</b>	GFSK, π/4-DQPSK, 8DPSK
<b>Transfer Rate</b>	1/2/3 Mbps
<b>Operating Frequency</b>	2402 ~ 2480 MHz
<b>Number of Channel</b>	79
<b>Output Power</b>	1.738 mW
<b>Antenna Type</b>	Wire antenna with -1.5 dBi gain
<b>Antenna Connector</b>	N/A
<b>Accessory Device</b>	Refer to Note as below
<b>Data Cable Supplied</b>	Refer to Note as below

Note:

1. The details for the models are listed as below.

SKU	Sample	Brand	Model	Difference
1	A	TomTom	4AA53	5" with GPS function only (LCM 1)
	B	TomTom	4AP54	5" plus with GPS and BT function (LCM 1)
2	C	TomTom	4AP54	5" plus with GPS and BT function (LCM 2)

2. The EUT contains following accessory devices.

Product	Brand	Model	Description
Battery	TomTom	AT5	3.7Vdc, 920mAh
Car Charger 1	TomTom	4UUC3Z	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A Type A
Car Charger 2	TomTom	4UUC3Z	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A Type B
Car Charger 3	TomTom	4UUC23	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A
Car Charger 4	TomTom	4UUC23B	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A
Car Charger 5	TomTom	4UUC25	I/P: 12/24 Vdc O/P: 5Vdc, 2.1A
Car Charger 6	TomTom	4UUC5B	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A
Car Charger 7	TomTom	4UUC9	I/P: 12/24 Vdc O/P: 5Vdc, 1.2A / 2.1A 12/24 Vdc, 2.0A
Car Charger 8	TomTom	4UUC26	I/P: 12/24 Vdc O/P: 5Vdc, 2.4A / 1.5A
Home Charger	TomTom	4UUC6B	I/P: 110-240 Vac O/P: 5Vdc, 1.2A

Product	Brand	Model	Description
USB Cable 1	TomTom	4UUC.001.24	1.5m shielded cable w/o core
USB Cable 2	TomTom	4UUC.001.35	1.5m shielded cable w/o core
LCM 1	Samsung	LTR050VP01	5.0" WQVGA resistive LCM
LCM 2	Innolux	ZD050NA-05H	5.0" WQVGA resistive LCM

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Description of Test Modes

79 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To			Description
	RE≥1G	RE<1G	APCM	
A	√	√	√	SKU 1: Sample A+B
B	√	√	-	SKU 2: Sample C

Where **RE≥1G**: Radiated Emission above 1 GHz      **RE<1G**: Radiated Emission below 1 GHz

**APCM**: Antenna Port Conducted Measurement

**NOTE:**

1. For Radiated emission test, pre-tested GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.
2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
3. “-”means no effect.

#### Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
B	0 to 78	39	FHSS	GFSK	DH5

#### Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
A, B	0 to 78	39	FHSS	GFSK	DH5

#### Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	$\pi/4$ -DQPSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**Test Condition:**

Applicable To	Environmental Conditions	Input Power	Tested by
RE $\geq$ 1G	25 deg. C, 65 % RH	DC24V	Karl Lee
RE<1G	25 deg. C, 65 % RH	DC24V	Karl Lee
APCM	25 deg. C, 65 % RH	3.7 Vdc	Luke Chen

**3.3 Description of Support Units**



The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Bluetooth Tester	R&S	CBT	100980	N/A
2.	DC Power Supply	Com Solve	33010D	807748	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A
2.	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items 1 acted as communication partners to transfer data.

**3.3.1 Configuration of System under Test**


### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**FCC Public Notice DA 00-705**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

#### 4.1.2 Test Instruments

(1) Test data: Mar. 04, 2016 ~ Mar. 15, 2016

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2016	Jan. 20, 2017
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep.03, 2015	Sep.02, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 04, 2016	Jan. 03, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Jan. 08, 2016	Jan. 07, 2017
Loop Antenna	EM-6879	269	Jul. 31, 2015	Jul. 30, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 21, 2015	Dec. 20, 2016
Preamplifier EMCI	EMC 184045	980116	Dec. 21, 2015	Dec. 20, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2015	Dec. 27, 2016
Power Meter Anritsu	ML2495A	1232002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor Anritsu	MA2411B	1207325	Sep. 21, 2015	Sep. 20, 2016
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 12, 2015	Oct. 11, 2016
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 12, 2015	Oct. 11, 2016
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 12, 2015	Oct. 11, 2016
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC7450F-10.

(2) Test data: Dec. 12, 2016

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2016	Jan. 20, 2017
Spectrum Analyzer Agilent	N9010A	MY52220314	Nov. 16, 2016	Nov. 15, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 04, 2016	Jan. 03, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Jan. 08, 2016	Jan. 07, 2017
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2016	Jul. 07, 2017
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 19, 2016	Oct. 18, 2017
Loop Antenna	EM-6879	269	Aug. 11, 2016	Aug. 10, 2017
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Preamplifier EMCI	EMC 012645	980115	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 184045	980116	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 330H	980112	Oct. 21, 2016	Oct. 20, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 08, 2016	Sep. 07, 2017
Power Sensor Anritsu	MA2411B	1207325	Sep. 08, 2016	Sep. 07, 2017
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 21, 2016	Oct. 20, 2017
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 21, 2016	Oct. 20, 2017
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 21, 2016	Oct. 20, 2017
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2016	Jul. 07, 2017

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC7450F-10.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle  $\geq 98 \%$ ) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### <Frequency Range below 1 GHz>



##### <Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

##### Mode A

###### ABOVE 1 GHz DATA :

###### GFSK

EUT Test Condition			Measurement Detail						
Channel		Channel 0			Frequency Range		1 GHz ~ 25 GHz		
Input Power		DC24V			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2364	39.8	38.17	54	-14.2	31.76	5.37	35.5	142	233	Average
2364	55.14	53.51	74	-18.86	31.76	5.37	35.5	142	233	Peak
2402	78.44	76.71			31.8	5.4	35.47	142	233	Average
2402	82.12	80.39			31.8	5.4	35.47	142	233	Peak
2498	40.39	38.37	54	-13.61	31.9	5.53	35.41	142	233	Average
2498	56.04	54.02	74	-17.96	31.9	5.53	35.41	142	233	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2326	39.77	38.26	54	-14.23	31.73	5.3	35.52	107	355	Average
2326	55.33	53.82	74	-18.67	31.73	5.3	35.52	107	355	Peak
2402	83.5	81.77			31.8	5.4	35.47	107	355	Average
2402	88.03	86.3			31.8	5.4	35.47	107	355	Peak
2490	40.5	38.49	54	-13.5	31.9	5.53	35.42	107	355	Average
2490	55.69	53.68	74	-18.31	31.9	5.53	35.42	107	355	Peak

###### Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 2402 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 39		Frequency Range		1 GHz ~ 25 GHz
Input Power		DC24V		Detector Function		Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By		Karl Lee

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2368	39.85	38.21	54	-14.15	31.76	5.37	35.49	142	233	Average
2368	55.58	53.94	74	-18.42	31.76	5.37	35.49	142	233	Peak
2441	78.45	76.58			31.85	5.46	35.44	142	233	Average
2441	82.04	80.17			31.85	5.46	35.44	142	233	Peak
2498	40.37	38.35	54	-13.63	31.9	5.53	35.41	142	233	Average
2498	56.12	54.1	74	-17.88	31.9	5.53	35.41	142	233	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2356	39.81	38.18	54	-14.19	31.76	5.37	35.5	185	306	Average
2356	55.38	53.75	74	-18.62	31.76	5.37	35.5	185	306	Peak
2441	84.7	82.83			31.85	5.46	35.44	185	306	Average
2441	88.46	86.59			31.85	5.46	35.44	185	306	Peak
2496	40.51	38.49	54	-13.49	31.9	5.53	35.41	185	306	Average
2496	55.98	53.96	74	-18.02	31.9	5.53	35.41	185	306	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 2441 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
<b>Channel</b>		Channel 78			<b>Frequency Range</b>	
<b>Input Power</b>		DC24V			<b>Detector Function</b>	
<b>Environmental Conditions</b>		25 deg. C, 65 % RH			<b>Tested By</b>	

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2350	39.9	38.33	54	-14.1	31.74	5.33	35.5	142	233	Average
2350	55.61	54.04	74	-18.39	31.74	5.33	35.5	142	233	Peak
2480	78.42	76.46			31.88	5.5	35.42	142	233	Average
2480	82.76	80.8			31.88	5.5	35.42	142	233	Peak
2494	40.44	38.42	54	-13.56	31.9	5.53	35.41	142	233	Average
2494	55.58	53.56	74	-18.42	31.9	5.53	35.41	142	233	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2312	39.65	38.17	54	-14.35	31.71	5.3	35.53	185	306	Average
2312	55.74	54.26	74	-18.26	31.71	5.3	35.53	185	306	Peak
2480	84.25	82.29			31.88	5.5	35.42	185	306	Average
2480	88.81	86.85			31.88	5.5	35.42	185	306	Peak
2494	40.43	38.41	54	-13.57	31.9	5.53	35.41	185	306	Average
2494	55.5	53.48	74	-18.5	31.9	5.53	35.41	185	306	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 2480 MHz: Fundamental frequency.

**9 kHz ~ 30 MHz DATA:**

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

**30 MHz ~ 1 GHz WORST-CASE DATA:**

EUT Test Condition		Measurement Detail					
Channel	Channel 39	Frequency Range				30 MHz ~ 1 GHz	
Input Power	DC24V	Detector Function				Peak (PK) Quasi-peak (QP)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By				Karl Lee	

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
72.66	20.35	43.28	40	-19.65	8.18	1.11	32.22	165	132	Peak
147.99	28.38	49.15	43.5	-15.12	9.98	1.52	32.27	168	124	Peak
204.42	19.59	39.14	43.5	-23.91	11.08	1.65	32.28	142	74	Peak
389.6	27.44	39.94	46	-18.56	17.35	2.34	32.19	187	146	Peak
625.5	22.43	29.57	46	-23.57	22.1	2.93	32.17	134	120	Peak
892.9	26.04	29.11	46	-19.96	24.96	3.49	31.52	181	247	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
54.3	28.25	52.22	40	-11.75	7.36	0.9	32.23	107	224	Peak
138.27	22.25	43.86	43.5	-21.25	9.28	1.38	32.27	153	127	Peak
262.47	12.37	29.17	46	-33.63	13.37	1.94	32.11	139	126	Peak
426	19.81	31.85	46	-26.19	17.73	2.41	32.18	176	231	Peak
542.2	20.37	29.36	46	-25.63	20.43	2.76	32.18	197	126	Peak
851.6	25.29	29.83	46	-20.71	23.8	3.44	31.78	134	121	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

**Mode B**
**ABOVE 1 GHz DATA :**
**GFSK**

EUT Test Condition			Measurement Detail						
<b>Channel</b>		Channel 39			<b>Frequency Range</b>		1 GHz ~ 25 GHz		
<b>Input Power</b>		DC24V			<b>Detector Function</b>		Peak (PK) Average (AV)		
<b>Environmental Conditions</b>		25 deg. C, 65 % RH			<b>Tested By</b>		Karl Lee		

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2357	39.79	38.16	54	-14.21	31.76	5.37	35.5	129	196	Average
2357	55.49	53.86	74	-18.51	31.76	5.37	35.5	129	196	Peak
2441	74.49	72.62			31.85	5.46	35.44	129	196	Average
2441	78.12	76.25			31.85	5.46	35.44	129	196	Peak
2485	40.29	38.3	54	-13.71	31.88	5.53	35.42	129	196	Average
2498	56.26	54.24	74	-17.74	31.9	5.53	35.41	129	196	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2375	39.69	38.03	54	-14.31	31.78	5.37	35.49	199	274	Average
2375	55.42	53.76	74	-18.58	31.78	5.37	35.49	199	274	Peak
2441	76.53	74.66			31.85	5.46	35.44	199	274	Average
2441	80.53	78.66			31.85	5.46	35.44	199	274	Peak
2498	40.45	38.43	54	-13.55	31.9	5.53	35.41	199	274	Average
2498	56.02	54	74	-17.98	31.9	5.53	35.41	199	274	Peak

**Remarks:**

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
2. 2441 MHz: Fundamental frequency.

### 9 kHz ~ 30 MHz DATA:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

### 30 MHz ~ 1 GHz WORST-CASE DATA:

EUT Test Condition		Measurement Detail							
Channel	Channel 39	Frequency Range				30 MHz ~ 1 GHz			
Input Power	DC24V	Detector Function				Peak (PK) Quasi-peak (QP)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By				Karl Lee			

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
123.15	22.99	44.98	43.5	-20.51	8.87	1.38	32.24	157	246	Peak
159.87	23.87	43.82	43.5	-19.63	10.8	1.52	32.27	186	129	Peak
230.88	16.71	34.9	46	-29.29	12.13	1.85	32.17	129	208	Peak
470.8	23.1	33.95	46	-22.9	18.72	2.56	32.13	142	263	Peak
681.5	23.61	29.36	46	-22.39	23.31	3.05	32.11	185	114	Peak
825.7	24.67	29.66	46	-21.33	23.55	3.38	31.92	193	325	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
76.98	21.19	44	40	-18.81	8.3	1.11	32.22	154	118	Peak
154.47	18.36	38.72	43.5	-25.14	10.39	1.52	32.27	196	234	Peak
238.44	12.99	30.8	46	-33.01	12.48	1.85	32.14	152	214	Peak
476.4	19.18	29.84	46	-26.82	18.9	2.56	32.12	134	126	Peak
619.9	22.38	29.67	46	-23.62	21.96	2.93	32.18	129	232	Peak
755.7	24.2	29.87	46	-21.8	23.25	3.22	32.14	187	132	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor


Margin value = Emission level – Limit value

## 4.2 Number of Hopping Frequency Used

### 4.2.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

### 4.2.2 Test Setup



### 4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.2.4 Test Procedure

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.


### 4.2.5 Deviation from Test Standard

No deviation.

### 4.2.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

## GFSK




### 4.3 Dwell Time on Each Channel

#### 4.3.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedures

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.
- .

#### 4.3.5 Deviation from Test Standard

No deviation.


#### 4.3.6 Test Results

##### GFSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.00	432.00	0.14	0.4
DH3	5.20	1695.00	0.28	0.4
DH5	3.40	2955.00	0.32	0.4

##### NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.



**Π/4-DQPSK**

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
2DH1	10.00	450.00	0.14	0.4
2DH3	5.00	1705.00	0.27	0.4
2DH5	3.40	2935.00	0.32	0.4

**NOTE:**

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.




## 8DPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
3DH1	10.00	444.00	0.14	0.4
3DH3	5.20	1705.00	0.28	0.4
3DH5	3.20	2955.00	0.30	0.4

### NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.




## 4.4 Channel Bandwidth

### 4.4.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5 MHz, if the 20 dB bandwidth of hopping channel is greater than 25 kHz, two-thirds 20 dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

### 4.4.5 Deviation from Test Standard


No deviation.

### 4.4.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

#### 4.4.7 Test Results

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)		
		GFSK	$\pi/4$ -DQPSK	8DPSK
0	2402	0.948	1.330	1.270
39	2441	0.951	1.330	1.270
78	2480	0.942	1.330	1.270




## 4.5 Hopping Channel Separation

### 4.5.1 Limits of Hopping Channel Separation Measurement

At least 25 kHz or two-third of 20 dB hopping channel bandwidth (whichever is greater).

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

#### Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

### 4.5.5 Deviation from Test Standard


No deviation.

#### 4.5.6 Test Results

Channel	Freq. (MHz)	Adjacent Channel Separation (MHz)			20 dB Bandwidth (MHz)			Minimum Limit (MHz)			Pass / Fail
		GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK	
0	2402	1.00	1.00	1.00	0.948	1.330	1.270	0.632	0.887	0.847	Pass
39	2441	1.00	1.00	1.00	0.951	1.330	1.270	0.634	0.887	0.847	Pass
78	2480	1.00	1.00	1.00	0.942	1.330	1.270	0.628	0.887	0.847	Pass

**NOTE:**

1. The minimum limit is two-third 20 dB bandwidth.




## 4.6 Maximum Output Power

### 4.6.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125 mW.

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

### 4.6.5 Deviation from Test Standard


No deviation.

### 4.6.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

#### 4.6.7 Test Results

Channel	Frequency (MHz)	Output Power (mW)			Output Power (dBm)			Power Limit (mW)	Pass / Fail
		GFSK	$\pi/4$ -DQPSK	8DPSK	GFSK	$\pi/4$ -DQPSK	8DPSK		
0	2402	1.738	1.268	1.422	2.40	1.03	1.53	125	PASS
39	2441	1.321	1.035	1.172	1.21	0.15	0.69	125	PASS
78	2480	1.089	0.873	0.993	0.37	-0.59	-0.03	125	PASS



## 4.7 Conducted Out of Band Emission Measurement

### 4.7.1 Limits Of Conducted Out Of Band Emission Measurement

Below –20 dB of the highest emission level of operating band (in 100 kHz RBW).

### 4.7.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

### 4.7.4 Deviation from Test Standard





No deviation.

### 4.7.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



### 4.7.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.



**GFSK**
**Hopping disabled\_Low Channel**

**Hopping disabled\_High Channel**

**Hopping enabled\_Low Channel**

**Hopping enabled\_High Channel**


$\pi/4$ -DQPSK


Hopping disabled\_Low Channel




Hopping disabled\_High Channel




Hopping enabled\_Low Channel



Hopping enabled\_High Channel



## 8DPSK



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---