

FCC RF Test Report

APPLICANT : TomTom International BV
EQUIPMENT : GPS Navigation System
BRAND NAME : TomTom
MODEL NAME : 4CT50, 4KN50
FCC ID : S4L4CT50
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Jul. 09, 2010 and completely tested on Jan. 04, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Anderson Chiu / Deputy Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Testing Site	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 RF Output Power	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 RF Utility	9
3 TEST RESULT	10
3.1 Number of Channel Measurement	10
3.2 20dB and 99% Bandwidth Measurement	13
3.3 Hopping Channel Separation Measurement	26
3.4 Dwell Time Measurement	29
3.5 Peak Output Power Measurement	31
3.6 Band Edges Measurement	34
3.7 Spurious Emission Measurement	38
3.8 AC Conducted Emission Measurement	42
3.9 Radiated Emission Measurement	46
3.10 Antenna Requirements	55
4 LIST OF MEASURING EQUIPMENT	56
5 UNCERTAINTY OF EVALUATION	57
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR0D2410	Rev. 01	Initial issue of report	Jan. 13, 2011

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.2	-	Gen 4.4.1	99% Bandwidth	-	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	$\leq 1\text{W}$	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.8	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 17.40 dB at 0.198 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.03 dB at 34.05 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

TomTom International BV

Rembrandtplein 35 1017 CT Amsterdam The Netherlands

1.2 Manufacturer

Tech-Giant (Shanghai) Computer Co., Ltd.

C#, No. 1, South Rongteng Road, Songjiang Export Processing Zone, Shanghai, China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GPS Navigation System
Brand Name	TomTom
Model Name	4CT50, 4KN50
FCC ID	S4L4CT50
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : -2.98 dBm (0.001 W) Bluetooth EDR (2Mbps) : -1.99 dBm (0.001 W) Bluetooth EDR (3Mbps) : -1.85 dBm (0.001 W)
Antenna Type	Chip Antenna with gain 2 dBi
HW Version	1.1
SW Version	10.150
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	Mobile Phone	Nokia	2730classic	QTLRM-578	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	-3.70 dBm	-2.11 dBm	-1.85 dBm
Ch39	2441MHz	-2.98 dBm	-1.99 dBm	-1.87 dBm
Ch78	2480MHz	-4.63 dBm	-3.54 dBm	-3.40 dBm

Remark:

1. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	N/A	N/A	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz
AC Conducted Emission	Mode 1 :GSM850 (GPRS 8) Idle + Bluetooth Link + GPS Rx + Adapter 1		
Remark: For radiated TCs, the data rate was set in 3Mbps due to the highest RF output power; only the data of these modes was reported.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

For Bluetooth function, the RF utility, "PUTTY" was installed in EUT which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for transmitting and receiving signals continuously.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.


3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 7~9	Temperature :	25~27℃
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 16.JUL.2010 03:27:50



Date: 16.JUL.2010 03:31:56

3.2 20dB and 99% Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.000
39	2441	1.000
78	2480	0.996


20 dB Bandwidth Plot on Channel 00



Date: 16.JUL.2010 02:01:14




20 dB Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:00:41


20 dB Bandwidth Plot on Channel 78



Date: 16.JUL.2010 02:02:50

Test Mode :	Mode 4, 5, 6	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.296
39	2441	1.302
78	2480	1.302

20 dB Bandwidth Plot on Channel 00


Date: 16.JUL.2010 02:04:34




20 dB Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:03:53


20 dB Bandwidth Plot on Channel 78



Date: 16.JUL.2010 02:03:23

Test Mode :	Mode 7, 8, 9	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.266

20 dB Bandwidth Plot on Channel 00


Date: 16.JUL.2010 02:05:01




20 dB Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:05:34

20 dB Bandwidth Plot on Channel 78




Date: 16.JUL.2010 02:06:11

3.2.6 Test Result of 99% Occupied Bandwidth


Test Mode :	Mode 1, 2, 3	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.879
39	2441	0.876
78	2480	0.876


99% Bandwidth Plot on Channel 00



Date: 16.JUL.2010 02:11:35

99% Occupied Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:10:48

99% Occupied Bandwidth Plot on Channel 78


Date: 16.JUL.2010 02:10:26

Test Mode :	Mode 4, 5, 6	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.172
39	2441	1.192
78	2480	1.184

99% Bandwidth Plot on Channel 00


Date: 16.JUL.2010 02:08:30




99% Occupied Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:09:03


99% Occupied Bandwidth Plot on Channel 78



Date: 16.JUL.2010 02:09:30

Test Mode :	Mode 7, 8, 9	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.164
39	2441	1.176
78	2480	1.172

99% Bandwidth Plot on Channel 00


Date: 16.JUL.2010 02:07:54




99% Occupied Bandwidth Plot on Channel 39



Date: 16.JUL.2010 02:07:12

99% Occupied Bandwidth Plot on Channel 78



Date: 16.JUL.2010 02:06:47

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup




3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 7, 8, 9	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.844	Pass
39	2441	1.002	0.844	Pass
78	2480	1.002	0.844	Pass


Channel Separation Plot on Channel 00 - 01



Date: 16.JUL.2010 02:20:43




Channel Separation Plot on Channel 39 - 40



Date: 16.JUL.2010 02:18:05

Channel Separation Plot on Channel 77 - 78



Date: 16.JUL.2010 02:17:20

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time

Test Mode :	Mode 8	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
3DH5	3.50	2948.00	0.33	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




3DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 16.JUL.2010 02:44:49

3DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 16.JUL.2010 02:50:59

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1W (30 dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 7, 8, 9	Temperature :	25~27°C
Test Engineer :	Lancelot Chen	Relative Humidity :	47~50%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	-1.85	30	Pass
39	2441	-1.87	30	Pass
78	2480	-3.40	30	Pass




Peak Output Power Plot on Channel 00



Date: 16.JUL.2010 01:27:59


Peak Output Power Plot on Channel 39



Date: 16.JUL.2010 01:28:26



Peak Output Power Plot on Channel 78



Date: 16.JUL.2010 01:28:48

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	43~44%
		Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.42	46.66	-27.34	74	42.03	32.13	6.03	33.53	129	46	Peak
2389.42	35.96	-18.04	54	31.33	32.13	6.03	33.53	129	46	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.85	47.93	-26.07	74	43.3	32.13	6.03	33.53	100	5	Peak
2388.85	33.97	-20.03	54	29.34	32.13	6.03	33.53	100	5	Average

Test Mode :	Mode 3	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	43~44%
		Test Engineer :	David Yang


ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	67.39	-6.61	74	62.5	32.27	6.18	33.56	200	69	Peak
2483.5	35.41	-18.59	54	30.52	32.27	6.18	33.56	200	69	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	65.12	-8.88	74	60.23	32.27	6.18	33.56	125	6	Peak
2483.5	34.18	-19.82	54	29.29	32.27	6.18	33.56	125	6	Average

3.6.6 Test Result of Conducted Band Edges


Test Mode :	Mode 7 and 9	Temperature :	25~27°C
Test Channel :	00 and 78	Relative Humidity :	47~50%
		Test Engineer :	Lancelot Chen

Low Band Edge Plot on Channel 00



Date: 16.JUL.2010 02:31:39

High Band Edge Plot on Channel 78



Date: 16.JUL.2010 02:22:10

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.7.4 Test Setup



3.7.5 Test Result


Test Mode :	Mode 7	Temperature :	25~27°C
Test Channel :	00	Relative Humidity :	47~50%
		Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 16.JUL.2010 03:36:05

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 16.JUL.2010 03:36:40




Test Mode :	Mode 8	Temperature :	25~27°C
Test Channel :	39	Relative Humidity :	47~50%
		Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 16.JUL.2010 03:37:34

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 16.JUL.2010 03:38:16




Test Mode :	Mode 9	Temperature :	25~27°C
Test Channel :	78	Relative Humidity :	47~50%
		Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 16.JUL.2010 03:38:47

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 16.JUL.2010 03:39:31

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.8.4 Test Setup



3.8.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Novic Jiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 (GPRS 8) Idle + Bluetooth Link + GPS Rx + Adapter 1		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	46.0	Off	L1	19.3	17.7	63.7
0.294000	37.3	Off	L1	19.3	23.1	60.4
0.494000	34.5	Off	L1	19.3	21.6	56.1
1.286000	34.1	Off	L1	19.4	21.9	56.0
1.878000	35.3	Off	L1	19.4	20.7	56.0
2.966000	34.4	Off	L1	19.5	21.6	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	34.3	Off	L1	19.3	19.4	53.7
0.294000	27.8	Off	L1	19.3	22.6	50.4
0.494000	25.4	Off	L1	19.3	20.7	46.1
1.286000	24.1	Off	L1	19.4	21.9	46.0
1.878000	25.2	Off	L1	19.4	20.8	46.0
2.966000	23.6	Off	L1	19.5	22.4	46.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Jiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 (GPRS 8) Idle + Bluetooth Link + GPS Rx + Adapter 1		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	46.3	Off	N	19.3	17.4	63.7
0.294000	39.9	Off	N	19.3	20.5	60.4
0.494000	38.2	Off	N	19.3	17.9	56.1
0.790000	35.2	Off	N	19.4	20.8	56.0
1.382000	35.2	Off	N	19.5	20.8	56.0
1.878000	33.9	Off	N	19.4	22.1	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.198000	34.3	Off	N	19.3	19.4	53.7
0.294000	29.7	Off	N	19.3	20.7	50.4
0.494000	27.6	Off	N	19.3	18.5	46.1
0.790000	25.5	Off	N	19.4	20.5	46.0
1.382000	25.9	Off	N	19.5	20.1	46.0
1.878000	22.7	Off	N	19.4	23.3	46.0

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


- The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.9.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	David Yang	Temperature :	24~25°C	
		Relative Humidity :	43~44%	

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.61	28.92	-11.08	40	47	12.8	0.63	31.51	136	275	Peak
106.41	26.86	-16.64	43.5	46.41	10.97	1.03	31.55	-	-	Peak
143.94	25.25	-18.25	43.5	44.08	11.52	1.2	31.55	-	-	Peak
335	29.7	-16.3	46	44.75	14.39	1.87	31.31	-	-	Peak
623.4	23.52	-22.48	46	31.41	20.25	2.76	30.9	-	-	Peak
872.6	25.37	-20.63	46	29.87	22.92	3.3	30.72	-	-	Peak
2389.42	35.96	-18.04	54	31.33	32.13	6.03	33.53	129	46	Average
2389.42	46.66	-27.34	74	42.03	32.13	6.03	33.53	129	46	Peak
2402	99.45	-	-	94.8	32.16	6.03	33.54	129	46	Peak
2402	82.84	-	-	78.21	32.13	6.03	33.53	129	46	Average
2500	33.8	-20.2	54	28.89	32.3	6.18	33.57	129	46	Average
2500	46.66	-27.34	74	41.75	32.3	6.18	33.57	129	46	Peak
8334	56.51	-17.49	74	43.66	36	10.95	34.1	116	89	Peak
8334	43.08	-10.92	54	30.23	36	10.95	34.1	116	89	Average

Test Mode :	Mode 1	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	36.18	-3.82	40	49.79	17.29	0.57	31.47	100	143	Peak
44.85	32.26	-7.74	40	52.19	10.92	0.65	31.5	-	-	Peak
93.18	30.34	-13.16	43.5	51.59	9.32	0.96	31.53	-	-	Peak
335	25.68	-20.32	46	40.73	14.39	1.87	31.31	-	-	Peak
582.1	21.61	-24.39	46	30.19	19.72	2.64	30.94	-	-	Peak
803.3	25.5	-20.5	46	30.78	22.25	3.15	30.68	-	-	Peak
2388.85	33.97	-20.03	54	29.34	32.13	6.03	33.53	100	5	Average
2388.85	47.93	-26.07	74	43.3	32.13	6.03	33.53	100	5	Peak
2402	98.29	-	-	93.64	32.16	6.03	33.54	100	5	Peak
2402	82.39	-	-	77.76	32.13	6.03	33.53	100	5	Average
2500	33.79	-20.21	54	28.88	32.3	6.18	33.57	100	5	Average
2500	45.61	-28.39	74	40.7	32.3	6.18	33.57	100	5	Peak
8370	56.08	-17.92	74	43.22	36	10.95	34.09	100	198	Peak
8370	42.73	-11.27	54	29.87	36	10.95	34.09	100	198	Average

Test Mode :	Mode 2	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
48.9	31.84	-8.16	40	53.73	8.96	0.68	31.53	153	302	Peak
143.94	21.89	-21.61	43.5	40.72	11.52	1.2	31.55	-	-	Peak
240.06	24.5	-21.5	46	42.79	11.6	1.53	31.42	-	-	Peak
335	29.02	-16.98	46	44.07	14.39	1.87	31.31	-	-	Peak
699.7	23.49	-22.51	46	30.54	20.83	2.94	30.82	-	-	Peak
931.4	26.52	-19.48	46	30.07	23.65	3.42	30.62	-	-	Peak
2326	45.97	-28.03	74	41.54	32.02	5.92	33.51	198	135	Peak
2326	33.95	-20.05	54	29.52	32.02	5.92	33.51	198	135	Average
2441	82.78	-	-	78	32.22	6.11	33.55	198	135	Average
2441	99.07	-	-	94.29	32.22	6.11	33.55	198	135	Peak
2500	46.37	-27.63	74	41.46	32.3	6.18	33.57	198	135	Peak
2500	33.84	-20.16	54	28.93	32.3	6.18	33.57	198	135	Average
8397	56.25	-17.75	74	43.38	36	10.96	34.09	133	291	Peak
8397	42.78	-11.22	54	29.91	36	10.96	34.09	133	291	Average

Test Mode :	Mode 2	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	36.97	-3.03	40	50.58	17.29	0.57	31.47	103	175	Peak
119.37	24.02	-19.48	43.5	42.34	12.14	1.1	31.56	-	-	Peak
240.06	22.18	-23.82	46	40.47	11.6	1.53	31.42	-	-	Peak
335	21.78	-24.22	46	36.83	14.39	1.87	31.31	-	-	Peak
623.4	23.99	-22.01	46	31.88	20.25	2.76	30.9	-	-	Peak
788.6	25.31	-20.69	46	30.81	22.06	3.12	30.68	-	-	Peak
2340	44.68	-29.32	74	40.2	32.05	5.95	33.52	101	7	Peak
2340	33.87	-20.13	54	29.39	32.05	5.95	33.52	101	7	Average
2441	99.54	-	-	94.76	32.22	6.11	33.55	101	7	Peak
2441	83.81	-	-	79.03	32.22	6.11	33.55	101	7	Average
2484	45.62	-28.38	74	40.73	32.27	6.18	33.56	101	7	Peak
2484	33.68	-20.32	54	28.79	32.27	6.18	33.56	101	7	Average
8061	56.27	-17.73	74	43.55	36	10.84	34.12	100	313	Peak
8061	42.76	-11.24	54	30.04	36	10.84	34.12	100	313	Average

Test Mode :	Mode 3	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
48.9	32.5	-7.5	40	54.39	8.96	0.68	31.53	125	263	Peak
143.94	22.49	-21.01	43.5	41.32	11.52	1.2	31.55	-	-	Peak
240.06	24.38	-21.62	46	42.67	11.6	1.53	31.42	-	-	Peak
335	28.97	-17.03	46	44.02	14.39	1.87	31.31	-	-	Peak
624.1	22.05	-23.95	46	29.94	20.25	2.76	30.9	-	-	Peak
752.9	24	-22	46	30.08	21.56	3.06	30.7	-	-	Peak
2316	45.99	-28.01	74	41.58	32	5.92	33.51	200	69	Peak
2316	34.18	-19.82	54	29.77	32	5.92	33.51	200	69	Average
2480	100.33	-	-	95.44	32.27	6.18	33.56	200	69	Peak
2480	84.13	-	-	79.24	32.27	6.18	33.56	200	69	Average
2483.5	67.39	-6.61	74	62.5	32.27	6.18	33.56	200	69	Peak
2483.5	35.41	-18.59	54	30.52	32.27	6.18	33.56	200	69	Average
8274	55.89	-18.11	74	43.07	36	10.92	34.1	128	117	Peak
8274	44.05	-9.95	54	31.23	36	10.92	34.1	128	117	Average

Test Mode :	Mode 3	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	43~44%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	36.55	-3.45	40	50.16	17.29	0.57	31.47	102	149	Peak
121.26	23.94	-19.56	43.5	42.24	12.15	1.11	31.56	-	-	Peak
240.06	22.74	-23.26	46	41.03	11.6	1.53	31.42	-	-	Peak
335	22.15	-23.85	46	37.2	14.39	1.87	31.31	-	-	Peak
623.4	23.64	-22.36	46	31.53	20.25	2.76	30.9	-	-	Peak
719.3	23.85	-22.15	46	30.52	21.11	2.99	30.77	-	-	Peak
2356	46.05	-27.95	74	41.54	32.08	5.95	33.52	125	6	Peak
2356	33.8	-20.2	54	29.29	32.08	5.95	33.52	125	6	Average
2480	83.45	-	-	78.56	32.27	6.18	33.56	125	6	Average
2480	98.67	-	-	93.78	32.27	6.18	33.56	125	6	Peak
2483.5	65.12	-8.88	74	60.23	32.27	6.18	33.56	125	6	Peak
2483.5	34.18	-19.82	54	29.29	32.27	6.18	33.56	125	6	Average
8445	56.27	-17.73	74	43.38	36	10.98	34.09	102	312	Peak
8445	43.32	-10.68	54	30.43	36	10.98	34.09	102	312	Average

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is Chip Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101329	9kHz~30GHz	Apr. 26, 2010	Apr. 25, 2011	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9KHz – 30MHz	Dec. 03, 2010	Dec. 02, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9KHz – 30MHz	Dec. 01, 2010	Nov. 30, 2011	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32 dB.GAIN	Mar. 27, 2010	Mar. 26, 2011	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH07-HY)
Bluetooth Base Station	R&S	CBT32	100519	N/A	May 12, 2009	May 11, 2011	-
GPS Station	T&E	GS-50	N/A	N/A	N/A	N/A	-

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP0D2410 as below.