

AW869A

Dual band WiFi6 + BT5.2 Module Spec

拟制 Design	审核 Check	批准 Approve	版本 Version	日期 Date
			V1.1	2023.03.13

更改记录

Reversion History

版本 Version	日期 Date	更改内容 Modification
1.0	2023.02.22	First release
1.1	2023.03.13	Add FCC warnings

目录

Contents

1. Overview.....	1
2. Features.....	1
3. Block Diagram.....	2
4. General Specification.....	2
5. RF Specification.....	3
5.1 2.4 GHz RF Specification.....	3
5.2 5 GHz RF Specification.....	4
5.3 Bluetooth Section.....	5
6. Recommended Operating Rating.....	6
7. Physical Dimensions.....	7
8. Pin Description.....	7
9. Suplier.....	9
10. Physical photo.....	9
11. Layout Recommendation.....	10
12. Baking & Storage Temperature & Recommended Reflow Profile.....	11
12.1 Baking & Storage Temperature.....	11
12.2 Recommended Reflow Profile.....	12
13. Packing information.....	12
13.1 Carrier size Detail:.....	12
13.2 Packaging Detail.....	12

RF Exposure

FCC RF Radiation Exposure Statement:

1. This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
2. This equipment complies with RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1) this device may not cause harmful interference and
- 2) this device must accept any interference received, including interference that may cause undesired operation.

Applicable FCC Rules

This module has been tested and found to comply with the following requirements for Modular Approval.

- Part 15.247 - Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
- Part 15.407 – General technical requirements.

Additional testing, Part 15 Subpart B disclaimer

The modular transmitter is only FCC authorized for the specific rule parts (i.e., FCC transmitter rules) listed on the grant, and that the host product manufacturer is responsible for compliance to any other FCC rules that apply to the host not covered by the modular transmitter grant of certification.

The final host product still requires Part 15 Subpart B compliance testing with the modular transmitter installed.

Test Modes

This device uses various test mode programs for test set up which operate separate from production firmware. Host integrators should contact the grantee for assistance with test modes needed for module/host compliance test requirements.

Antennas

This radio transmitter has been approved by the FCC to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Part 15.21

You are cautioned that changes or modifications not expressly approved by the part responsible for compliance could void the user's authority to operate the equipment.

Wireless devices with WLAN 5GHz

FCC regulations restrict the operation of this device to indoor use only.

Radio	Antenna Type	Freq. (MHz)	Max. Peak Antenna Gain (dBi)
Bluetooth	FPC	2402-2480	0.29
WiFi 2.4GHz	FPC	2412-2462	0.29

Radio	Antenna Type	Freq. (MHz)	Max. Peak Antenna Gain (dBi)
WiFi 5GHz	FPC	5150~5250	0.45
		5250~5350	1.85
		5350~5725	2.78
		5725~5850	1.55


1. Overview

The AW869A is a highly integrated module with Dual band WiFi,BT5.2; combination solution to support 1 × 1 IEEE 802.11a/b/g/n WLAN standards and BT 5.2 enabling seamless integration of WLAN/BT and low-energy technology.

2. Features

- Supports a low-power SDIO 2.0 interface for WLAN and a HS-UART interface for BT
- Provides a highly integrated WLAN system-on-chip (SoC) for 2.4&5.8 GHz 802.11n
- Supports WLAN 2.4&5.8 GHz , 20 MHz/40 MHz
- Supports BT 5.2, BLE, and ANT+ and backward compatibility with BT 1.x and BT 2.x+ Enhanced Data Rate
- Supports a single-ended RF port for cleaner and lower cost design
- Supports STA,AP,WiFi Direct modes concurrently

3. Block Diagram



4. General Specification

Model	AW869A
Product Name	WLAN 802.11a/b/g/n SDIO2.0 1T1R + Bluetooth 5.2 module
Major Chipset	AIC8800D
Standard	802.11a/b/g/n
Modulation Method	BPSK/ QPSK/ 16-QAM/ 64-QAM
Frequency Band	Dual band 2.4&5.8GHz ISM
WiFi Interface	SDIO2.0
BT Interface	UART
Operating Temperature	-20° C ~ 70° C
Storage Temperature	-20° C ~ 125°C
Humidity	5% to 90% maximum
Dimension	12x12x1.7 (LxWxH) ±0.2mm

5. RF Specification

5.1 2.4 GHz RF Specification

Feature	Description
WLAN Standard	IEEE 802.11b/g/n WiFi compliant
Frequency Range	2.400 GHz ~ 2.497 GHz (2.4 GHz ISM Band)
Number of Channels	2.4GHz: Ch1 ~ Ch11 (by software to setting country code) default
	2.4GHz: Ch1 ~ Ch13 (by software to setting country code)
Modulation	802.11b : DQPSK, DBPSK, CCK 802.11 g/n : OFDM /64-QAM,16-QAM, QPSK, BPSK
Output Power	802.11b /11Mbps : 16dBm $\pm$ 2 dB @ EVM $\leq$ -15dB
	802.11g /54Mbps : 15 dBm $\pm$ 2 dB @ EVM $\leq$ -28dB
	802.11n /MCS7 : 14 dBm $\pm$ 2 dB @ EVM $\leq$ -30dB
Receive Sensitivity (11b,20MHz) @8% PER	- 1Mbps PER @ -93 dBm, typical
	- 2Mbps PER @ -90 dBm, typical
	- 5.5Mbps PER @ -88 dBm, typical
	- 11Mbps PER @ -86 dBm, typical
Receive Sensitivity (11g,20MHz) @10% PER	- 6Mbps PER @ -91 dBm, typical
	- 9Mbps PER @ -89 dBm, typical
	- 12Mbps PER @ -86 dBm, typical
	- 18Mbps PER @ -83 dBm, typical
	- 24Mbps PER @ -80 dBm, typical
	- 36Mbps PER @ -77 dBm, typical
	- 48Mbps PER @ -74 dBm, typical
	- 54Mbps PER @ -72 dBm, typical
Receive Sensitivity (11n,20MHz) @10% PER	- MCS=0 PER @ -90 dBm, typical
	- MCS=1 PER @ -87 dBm, typical
	- MCS=2 PER @ -84 dBm, typical
	- MCS=3 PER @ -81 dBm, typical
	- MCS=4 PER @ -78 dBm, typical
	- MCS=5 PER @ -75 dBm, typical
	- MCS=6 PER @ -72 dBm, typical
	- MCS=7 PER @ -70 dBm, typical
	- MCS=0 PER @ -87 dBm, typical

	- MCS=1 PER @ -84 dBm, typical
	- MCS=2 PER @ -81 dBm, typical
	- MCS=3 PER @ -78 dBm, typical
	- MCS=4 PER @ -75 dBm, typical
	- MCS=5 PER @ -72 dBm, typical
	- MCS=6 PER @ -69 dBm, typical
	- MCS=7 PER @ -67 dBm, typical
Maximum Input Level	802.11b : -10 dBm
	802.11g/n/ax : -20 dBm
Antenna Reference	Small antennas with 0~2 dBi peak gain

5.2 5 GHz RF Specification

Feature	Description
WLAN Standard	IEEE 802.11a/n/ac/ax WiFi compliant
Frequency Range	4.900 GHz ~ 5.845 GHz (5.0 GHz ISM Band)
Number of Channels	5.0GHz : Please see the table
Modulation	802.11a : OFDM /64-QAM,16-QAM, QPSK, BPSK 802.11n : OFDM /64-QAM,16-QAM, QPSK, BPSK
Output Power	802.11a /54Mbps : 14 dBm $\pm$ 2 dB @ EVM $\leq$ -25dB
	802.11n HT20 /MCS7 : 13 dBm $\pm$ 2 dB @ EVM $\leq$ -28dB
	802.11n HT40 /MCS7 : 13dBm $\pm$ 2 dB @ EVM $\leq$ -28dB
Receive Sensitivity (11a,20MHz) @10% PER	- 6Mbps PER @ -93dBm, typical
	- 9Mbps PER @ -90 dBm, typical
	- 12Mbps PER @ -87 dBm, typical
	- 18Mbps PER @ -84 dBm, typical
	- 24Mbps PER @ -81 dBm, typical
	- 36Mbps PER @ -78 dBm, typical
	- 48Mbps PER @ -76 dBm, typical
	- 54Mbps PER @ -74 dBm, typical
	- MCS=0 PER @ -92 dBm, typical

	- MCS=1 PER @ -89 dBm, typical
	- MCS=2 PER @ -86 dBm, typical
	- MCS=3 PER @ -83 dBm, typical
	- MCS=4 PER @ -80 dBm, typical
	- MCS=5 PER @ -77 dBm, typical
	- MCS=6 PER @ -74 dBm, typical
	- MCS=7 PER @ -72 dBm, typical
Receive Sensitivity (11n,40MHz) @10% PER	- MCS=0 PER @ -90 dBm, typical
	- MCS=1 PER @ -87 dBm, typical
	- MCS=2 PER @ -84 dBm, typical
	- MCS=3 PER @ -81 dBm, typical
	- MCS=4 PER @ -78 dBm, typical
	- MCS=5 PER @ -75 dBm, typical
	- MCS=6 PER @ -72 dBm, typical
	- MCS=7 PER @ -70 dBm, typical
Maximum Input Level	802.11a/n/ac/ax : -20 dBm
Antenna Reference	Small antennas with 0~2 dBi peak gain

5.3 Bluetooth Section

Feature	Description
General Specification	
Bluetooth Standard	Bluetooth V5.2 of 1, 2 and 3 Mbps.
Host Interface	UART
Antenna Reference	Small antennas with 0~2 dBi peak gain
Frequency Band	2402 MHz ~ 2480 MHz
Number of Channels	BR/EDR :79 channels;BLE:40 channels
Modulation	FHSS, GFSK, DPSK, DQPSK
RF Specification	
Output Power, tolerance±2dBm	
BDR Output Power	7 dBm
EDR Output Power	7 dBm

BLE Output Power	7 dBm
Sensitivity, tolerance ± 2 dBm	
Sensitivity @ BER=0.1% for GFSK(1Mbps)	-96 dBm
Sensitivity @ BER=0.01% for $\pi/4$ -DQPSK(2Mbps)	-91 dBm
Sensitivity @ BER=0.01% for 8DPSK(3Mbps)	-89 dBm
Sensitivity @ BLE=30.8% for LE(1Mbps)	-100 dBm
Sensitivity @ BLE=30.8% for LE(2Mbps)	-90 dBm
Maximum Input Level	GFSK(1Mbps): -20 dBm
	$\pi/4$ -DQPSK(2Mbps): -20 dBm
	8DPSK(3Mbps): -20 dBm


6. Recommended Operating Rating

Symbol	Parameter	Minimum	Typical	Maximum	Units
VDD	3.3V supply voltage	3.0	3.3	3.6	V
VDDIO	I/O supply voltage	1.7	1.8	1.9	V
Current	3.3V rating current	--	--	450	mA


7. Physical Dimensions

注：其它未标的公差为 $\pm 0.1\text{mm}$.

(Unit: mm)



8. Pin Description



NO.	Name	Type	Description
1	GND	—	Ground connections
2	RF	I/O	WL_BT RF I/O port (2.4/5GHz)
3	GND	—	Ground connections
4	BT_ANT	I/O	NC(BT_RF_BT Alone)
5	GND	—	Ground connections
6	Host wake BT	I	Host wake BT(GPIOB5)
7	BT wake host	O	BT wake host (GPIOB3)
8	NC	—	No connect, keep floating
9	VDD	P	3.3V INPUT
10	NC	—	No connect, keep floating
11	NC	—	No connect, keep floating
12	WL_DIS	I	Power key (L=OFF, H=ON)
13	WL_Wake-up host	O	WL Wake-up host (GPIOB2)
14	SD_DAT2	I/O	SDIO DATA2
15	SD_DAT3	I/O	SDIO DATA3
16	SD_CMD	I/O	SDIO command line
17	SD_CLK	I/O	SDIO CLK
18	SD_DAT0	I/O	SDIO DATA0
19	SD_DAT1	I/O	SDIO DATA1
20	GND	—	Ground connections
21	NC	—	No connect, keep floating
22	VDDIO	P	I/O Voltage supply input 1.8V
23	NC	—	No connect, keep floating
24	LPO	—	No connect, keep floating
25	NC	—	No connect, keep floating
26	NC	—	No connect, keep floating
27	NC	—	No connect, keep floating
28	NC	—	No connect, keep floating
29	UART0_TX	—	No connect, keep floating(Debug pin)
30	UART0_RX	—	No connect, keep floating(Debug pin)
31	GND	—	Ground connections
32	NC	—	No connect, keep floating
33	GND	—	Ground connections
34	BT_DIS	—	Reserved (GPIOB7)
35	NC	—	No connect, keep floating
36	GND	—	Ground connections
37	NC	—	No connect, keep floating

38	NC	—	No connect, keep floating
39	NC	—	No connect, keep floating
40	NC	—	No connect, keep floating
41	UART_RTS	O	Bluetooth UART interface
42	UART_TX	O	Bluetooth UART interface
43	UART_RX	I	Bluetooth UART interface
44	UART_CTS	I	Bluetooth UART interface

备注：HFP(蓝牙通话)功能硬件采用 UART 接口

9. Supplier

Supplier list	
Name of material	Material brand
Crystal	JWT/FK/TKD/Murata/TXC
Duplexer	ACX/GLEAD/Sunlord/Walsin
Inductor	Sunlord/ CHILISIN/ SAMWHA/Murata
Wifi chip	Allwinner
RF FEM	Chipbetter
RF switch	Richwave/Qwave/RDA/Maxscend
Capacitance	SAMSUNG /EYANG
Resistance	UniOhm /YAGEO
PCB(12x12x0.5mm)	A,O,I,F


10. Physical Photo



MC 表: Made China
2302 表生产时间, 23 年 02 月
(随模组生产时间变化!!)

说明: PCB 不同供应商, 底部丝印有微小差异

11. Layout Recommendation



(Top view)

12. Baking & Storage Temperature & Recommended Reflow

Profile（烘烤，储存温度和推荐炉温）

12.1 Baking & Storage Temperature

- Storage life: 12 months. Storage conditions: <40°C. Relative humidity: <90%R.H.

(保存期限：12个月，储存环境条件：温度在：<40°C，相对湿度：<90%R.H.)

- After this bag is opened, devices that will be subjected to infrared reflow, vapor-phase reflow, or equivalent processing must be .(模块包装被拆后，SMT 组装之时限)

- ✓ Check the humidity card :stored at $\leq 20\%RH$. If :30%~40%(pink) or greater than 40%(red). Labeling module has moisture absorption.(检查湿度卡：显示值应小于30%（蓝色），如：30%~40%(粉红色)或者大于40%（红色）表示模块已吸湿气.)

- ✓ Mounted within 168 hours at factory conditions of: $t \leq 30^\circ C$, $\leq 60\%R.H$.

(工厂环境温度湿度管制： $\leq 30^\circ C$, $\leq 60\%R.H$, 168小时内。)

- ✓ Once opened, the workshop the preservation of life for 168 hours.

(拆封后，车间的保存寿命为168小时.)

- Module apart packing after 168 hours, If baking is required, devices may be baked for.

(如在拆封后的168个小时内未使用完，需要烘烤，烘烤条件如下：)

- ✓ Modules must be to remove module moisture problem. (模块须重新烘烤，以除去模块吸湿问题.)

- ✓ Baking temperature: $40^\circ C \pm 5^\circ C$, 120 hours. (烘烤温度条件： $40^\circ C \pm 5^\circ C$ ，120小时).

- ✓ After baking, put proper amount of desiccant to seal packages.


(烘烤后，放入适量的干燥剂再密封包装)

12.2 Recommended Reflow Profile

Referred IPC/JEDEC standard.


Peak Temperature : <250°C

Number of Times : 2 times




13. Packing information


13.1 Carrier Size Detail



ITEM	W	A0	B0	K0	P	F	E	D	P0	P2	T
DIM	24	12.5	12.5	2.8	16	13.25	1.75	1.50	4	2	0.3
TOLE	$\begin{smallmatrix} +0.30 \\ -0.30 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.10 \\ -0.10 \end{smallmatrix}$	$\begin{smallmatrix} +0.05 \\ -0.05 \end{smallmatrix}$

13.2 Packaging Detail





ESD CAUTION

The AW869A module is ESD (electrostatic discharge) sensitive device and may be damaged with ESD or spike voltage. Although AW869A module is with built-in ESD protection circuitry, please handle with care to avoid the permanent malfunction or the performance degradation.