

# FCC Test Report

## FCC ID: S5V-D101V3

**Product:** Tablet PC

**Trade Mark:** DRAGON TOUCH

**Model Number:** K8

**Serial Model:** N/A

**Report No.:** SER171215019003E

**Prepared for**

PROEXPRESS DISTRIBUTOR LLC

7668 standish place, STE B, Rockville, Maryland, 20855, United States

**Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen P.R. China  
Tel.: +86-755-6115 6588  
Fax.: +86-755-6115 6599  
Website: <http://www.ntek.org.cn>

## TEST RESULT CERTIFICATION

**Applicant's name** ..... : PROEXPRESS DISTRIBUTOR LLC  
Address ..... : 7668 standish place, STE B, Rockville, Maryland, 20855, United States  
**Manufacturer's Name** ..... : PROEXPRESS DISTRIBUTOR LLC  
Address ..... : 7668 standish place, STE B, Rockville, Maryland, 20855, United States

### Product description

Product name ..... : Tablet PC

Model and/or type reference : K8

FCC Part15B

**Standards** ..... : ANSI C63.4:2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

**Date of Test** ..... :

Date (s) of performance of tests ..... : 15 Dec. 2017 ~ 09 Jan. 2018

Date of Issue ..... : 09 Jan. 2018

Test Result ..... : **Pass**

Testing Engineer : 

(Susan Su)

Technical Manager : 

(Jason Chen)

Authorized Signatory : 

(Sam Chen)

**Table of Contents**

	<b>Page</b>
<b>1 . TEST SUMMARY</b>	<b>4</b>
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
<b>2 . GENERAL INFORMATION</b>	<b>6</b>
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST SETUP	8
2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.4 MEASUREMENT INSTRUMENTS LIST	10
<b>3 . EMC EMISSION TEST</b>	<b>11</b>
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 TEST RESULTS	19
3.2.5 TEST RESULTS(1000~6000MHz)	21

## 1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B ANSI C63.4: 2014	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

### 1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

FCC Registration Number:463705; IC Registration Number:9270A-1

CNAS Registration Number:L5516

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~12.4GHz	5.0	

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet PC						
Trade Mark	DRAGON TOUCH						
Model Name	K8						
Serial Model	N/A						
Model Difference	N/A						
Product Description	<p>The EUT is a Tablet PC.</p> <table border="1"> <tr> <td>Connecting I/O port:</td> <td>USB, Earphone</td> </tr> <tr> <td>Operation Frequency:</td> <td>BT:2402~2480 MHz WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz</td> </tr> <tr> <td>Modulation Type:</td> <td>BT(1Mbps): GFSK BT EDR(2Mbps): <math>\pi/4</math>-DQPSK BT EDR(3Mbps): 8-DPSK IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)</td> </tr> </table>	Connecting I/O port:	USB, Earphone	Operation Frequency:	BT:2402~2480 MHz WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Connecting I/O port:	USB, Earphone						
Operation Frequency:	BT:2402~2480 MHz WIFI:802.11b/g/n20:2412~2462MHz 802.11n40MHz: 2422-2452MHz						
Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)						
Power Source	DC 3.7V/3600mAh from Battery or DC 5V from USB Port.						
Adapter	Model: GS-0500200A Input:AC100~240V 50~60Hz 0.3A Output:DC5V, 2000mA						
Battery	DC 3.7V/3600mAh						
HW Version	F-0321 2817 F-M E351308 94V-0						
Firmware version	V2.1_20160902						
SW Version	A64_A861L11BC_PG_1605061.20170105						

### 2.1.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	charging+WIFI
Mode 2	charging +BT
Mode 3	charging +TF Card
Mode 4	charging +Camera
Mode 5	Connect to PC

For Conducted Test	
Final Test Mode	Description
Mode 1	charging+WIFI
Mode 2	charging +BT
Mode 3	charging +TF Card
Mode 4	charging +Camera
Mode 5	Connect to PC

For Radiated Test	
Final Test Mode	Description
Mode 1	charging+WIFI
Mode 2	charging +BT
Mode 3	charging +TF Card
Mode 4	charging +Camera
Mode 5	Connect to PC

Note: Final Test Mode: Through Pre-scan, find the mode 5 is the worst case.  
Only the worst case mode is recorded in the report.

## 2.2 DESCRIPTION OF TEST SETUP



### 2.3 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Tablet PC	DRAGON TOUCH	K8	N/A	EUT
E-2	PC	DELL	D06S	34531671097	Peripherals
E-3	Monitor	SHARP	LCD-32MS46A	09426089241597	Peripherals
E-4	KB	DELL	SK-8185	OY526KUS	Peripherals
E-5	Mouse	DELL	MS111-P	cn-011d3v-71581-11e-1th 7	Peripherals
E-6	Printer	Canon	L11121E	LBP2900	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	NO	YES	1.5m	
C-2	HDMI Cable	NO	NO	1.0m	
C-3	KB Cable	NO	NO	1.2m	
C-4	Mouse Cable	NO	NO	1.2m	
C-5	USB Cable	NO	NO	1.5m	

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in «Length» column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

## 2.4 MEASUREMENT INSTRUMENTS LIST

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2017.06.06	2018.06.05	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2017.06.06	2018.06.05	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2017.04.09	2018.04.08	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
8	Amplifier	EMC	EMC051835SE	980246	2017.08.09	2018.08.08	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
10	Power Meter	DARE	RPR3006W	15I00041S NO84	2017.08.09	2018.08.08	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2017.07.06	2018.07.05	1 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
13	High Test Cable(1G-40 GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
14	High Test Cable(1G-40 GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.06.06	2018.06.05	1 year
2	LISN	R&S	ENV216	101313	2017.04.19	2018.04.18	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2017.06.06	2018.06.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2017.06.06	2018.06.05	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



**Note: 1. Support units were connected to second LISN.**

**2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


## 3.1.5 TEST RESULTS

EUT:	Tablet PC	Model Name. :	K8
Temperature:	23 °C	Relative Humidity:	37%
Pressure:	1010hPa	Test Date:	2017-12-15
Test Mode:	Mode 5	Phase :	L
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1665	37.88	9.82	47.7	65.13	-17.43	QP
0.1665	20.4	9.82	30.22	55.13	-24.91	AVG
0.4299	29.83	9.83	39.66	57.25	-17.59	QP
0.4299	16.46	9.83	26.29	47.25	-20.96	AVG
0.8497	29.53	9.88	39.41	56	-16.59	QP
0.8497	17.24	9.88	27.12	46	-18.88	AVG
1.1775	28.08	9.91	37.99	56	-18.01	QP
1.1775	14.31	9.91	24.22	46	-21.78	AVG
1.9616	24.62	9.84	34.46	56	-21.54	QP
1.9616	11.25	9.84	21.09	46	-24.91	AVG
22.082	35.28	10.28	45.56	60	-14.44	QP
22.082	24.82	10.28	35.1	50	-14.9	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Tablet PC	Model Name. :	K8
Temperature:	23 °C	Relative Humidity:	37%
Pressure:	1010hPa	Test Date:	2017-12-15
Test Mode:	Mode 5	Phase :	N
Test Voltage:	DC 5V from PC AC120V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1607	36.65	9.92	46.57	65.42	-18.85	QP
0.1607	19.66	9.92	29.58	55.42	-25.84	AVG
0.466	30.06	9.93	39.99	56.58	-16.59	QP
0.466	12.41	9.93	22.34	46.58	-24.24	AVG
0.67	32.49	9.93	42.42	56	-13.58	QP
0.67	22.34	9.93	32.27	46	-13.73	AVG
1.07	30.21	9.93	40.14	56	-15.86	QP
1.07	20.64	9.93	30.57	46	-15.43	AVG
1.4256	29.13	9.93	39.06	56	-16.94	QP
1.4256	19.7	9.93	29.63	46	-16.37	AVG
21.5017	36.78	10.3	47.08	60	-12.92	QP
21.5017	25.08	10.3	35.38	50	-14.62	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Tablet PC	Model Name. :	K8
Temperature:	23 °C	Relative Humidity:	37%
Pressure:	1010hPa	Test Date:	2017-12-15
Test Mode:	Mode 5	Phase :	L
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1665	37.88	9.82	47.7	65.13	-17.43	QP
0.1665	20.4	9.82	30.22	55.13	-24.91	AVG
0.442	28.73	9.83	38.56	57.02	-18.46	QP
0.442	16.9	9.83	26.73	47.02	-20.29	AVG
0.8497	29.53	9.88	39.41	56	-16.59	QP
0.8497	17.24	9.88	27.12	46	-18.88	AVG
1.2096	26.69	9.91	36.6	56	-19.4	QP
1.2096	15.13	9.91	25.04	46	-20.96	AVG
1.542	25.59	9.89	35.48	56	-20.52	QP
1.542	13.86	9.89	23.75	46	-22.25	AVG
19.5699	34.35	10.25	44.6	60	-15.4	QP
19.5699	23.1	10.25	33.35	50	-16.65	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Tablet PC	Model Name. :	K8
Temperature:	23 °C	Relative Humidity:	37%
Pressure:	1010hPa	Test Date:	2017-12-15
Test Mode:	Mode 5	Phase :	N
Test Voltage:	DC 5V from PC AC240V/60Hz		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Correct Factor (dB)	Measure-ment (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Remark
0.1737	33.28	9.92	43.2	64.78	-21.58	QP
0.1737	11.91	9.92	21.83	54.78	-32.95	AVG
0.674	32.01	9.93	41.94	56	-14.06	QP
0.674	20.47	9.93	30.4	46	-15.6	AVG
1.038	29.67	9.93	39.6	56	-16.4	QP
1.038	12.91	9.93	22.84	46	-23.16	AVG
1.6814	28.27	9.94	38.21	56	-17.79	QP
1.6814	7.36	9.94	17.3	46	-28.7	AVG
2.1619	26.73	9.94	36.67	56	-19.33	QP
2.1619	14.33	9.94	24.27	46	-21.73	AVG
18.6935	34.88	10.25	45.13	60	-14.87	QP
18.6935	23.63	10.25	33.88	50	-16.12	AVG

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:

- (1) The limit for radiated test was performed according to as following:  
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### 3.2.2 TEST PROCEDURE

##### Test Arrangement for Radiated Emissions up to 1 GHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency below 1GHz.

##### Test Arrangement for Radiated Emissions above 1 GHz.

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.


Note: For the hand-held device, the EUT should be measured for all 3 axes and only the worst case is recorded in the report

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Avg	1 MHz	10 Hz

### 3.2.3 TEST SETUP

For Radiated Emission 30~1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



## 3.2.4 TEST RESULTS


## TEST RESULTS (30~1000 MHz)

EUT:	Tablet PC	Model Name:	K8
Temperature:	25 °C	Relative Humidity:	41%
Pressure:	1010 hPa	Test Date :	2017-12-15
Test Mode :	Mode 5	Polarization :	Horizontal
Test Power :		DC 5V from PC AC120V/60Hz	

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	55.2207	10.5	12.23	22.73	40	-17.27	QP
H	139.3609	15.87	11.4	27.27	43.5	-16.23	QP
H	199.9856	25.14	13.76	38.9	43.5	-4.6	QP
H	336.035	22.41	14.1	36.51	46	-9.49	QP
H	482.2156	20.51	16.99	37.5	46	-8.5	QP
H	721.7259	16.88	21.63	38.51	46	-7.49	QP

## Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.




EUT:	Tablet PC	Model Name :	K8
Temperature:	25 °C	Relative Humidity:	41%
Pressure:	1010 hPa	Test Date :	2017-12-15
Test Mode :	Mode 5	Polarization :	Vertical
Test Power :	DC 5V from PC AC120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.0704	6.14	20.74	26.88	40	-13.12	QP
V	51.1208	10.63	13.3	23.93	40	-16.07	QP
V	203.5228	22.97	13.85	36.82	43.5	-6.68	QP
V	360.4476	15.14	14.47	29.61	46	-16.39	QP
V	451.1349	15.75	16.18	31.93	46	-14.07	QP
V	599.3211	18.72	18.69	37.41	46	-8.59	QP

Remark:

Factor = Antenna Factor + Cable Loss - Amplifier.



## 3.2.5 TEST RESULTS(1000~6000MHz)

EUT:	Tablet PC	Model Name :	K8
Temperature:	25 °C	Relative Humidity:	41%
Pressure:	1010 hPa	Test Date :	2017-12-15
Test Mode :	Mode 5		
Test Power :	DC 5V from PC AC120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequenc y	Reading	Corre ct	Result	Limit	Over Limit	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
V	1187.5	55.09	-10.1	45.02	74	-28.98	peak
V	1187.5	31.57	-10.1	21.5	54	-32.5	AVG
V	2012.5	46.82	-7.66	39.16	74	-34.84	peak
V	2012.5	30.58	-7.66	22.92	54	-31.08	AVG
V	2912.5	43.57	-5.25	38.32	74	-35.68	peak
V	2912.5	31.12	-5.25	25.87	54	-28.13	AVG
H	1287.5	47.14	-10.6	36.58	74	-37.42	peak
H	1287.5	30.58	-10.6	20.02	54	-33.98	AVG
H	1850	51.34	-8.14	43.2	74	-30.8	peak
H	1850	32.15	-8.14	24.01	54	-29.99	AVG
H	2412.5	46.44	-5.45	40.99	74	-33.01	peak
H	2412.5	30.16	-5.45	24.71	54	-29.29	AVG

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: Only the worst results data points are reported in the report.