

RF Exposure

No. : 25FE0137-YK-1

Applicant	:	Sokkia Co.,Ltd.
Type of Equipment	:	Blue Stick
Model No.	:	BS01
FCC ID	:	S6MBS01

Sokkia Co.,Ltd. declares that Model : Blue Stick
complies with FCC radiation exposure requirement specified in the
FCC Rules 2.1091, 2.1093.

The “BS01” has 1.13 mW of conducted Peak Output power and 1.13 mW of EIRP.

This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List)
so that SAR testing is excluded. The Following calculation is the reference data for 20cm
distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain
antenna provided with the “BS01” as calculated
from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population
/ Uncontrolled Exposure.

This calculation is based on the highest EIRP possible from the system,
considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled
exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P =	1.13 mW (Maximum peak output power)	
G =	1.00 Numerical Antenna gain; equal	0.00 dBi
r =	20.0 cm	

For: BS01

$$S = 0.00022 \text{ mW/cm}^2$$