

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo
315315, China

Manufacturer : Cixi City Yidong Electronic Co., Ltd.
Guanhaiwei Industrial West Zone, Cixi City, Ningbo
315315, China

Product Name : Wi-Fi Smart Adaptor

Type/Model : WFU-1

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Date of issue: June 8, 2015

Prepared by:



Nemo Li (Project engineer)

Approved by:



Daniel Zhao (Reviewer)

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^3)$$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

As we can see from the test report 150500091SHA-001:

Frequency band	Power		Antenna Gain		R	S	Limits
(MHz)	dBm	mW	dB _i	(Numeric)	(cm)	(mW/cm ²)	(mW/cm ²)
2400 -2483.5	12.70	18.62	3.45	2.21	20	0.0082	1

Note: 1 mW/cm² from 1.310 Table 1

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.