


RF PRODUCT INFORMATION

Broad Band LTCC Multi Layer Ceramic Chip Antenna For ISM Band 2.4 GHz Applications

- RFANT5220110A0T Series

Patent Pending



FEATURES

- Surface Mounted Devices with a small dimension of $5.2 \times 2.0 \times 1.1 \text{ mm}^3$ meet future miniaturization trend.
- Embedded and LTCC (Low Temperature Co-fired Ceramic) technology is able to future integrate with system design as well as beautifying the housing of final product.
- High Stability in Temperature / Humidity Change

ELECTRICAL CHARACTERISTICS


Item	Specification
Central frequency	2.450 GHz (Note-1)
Bandwidth	150MHz (typical)
Gain	0 ~ 2 dBi
VSWR	2 max.
Polarization	Linear
Azimuth Beamwidth	Omni-directional
Impedance	50Ω

- Note 1. Central Frequency should be defined after customers' application approval.


APPLICATIONS

- Bluetooth/ Wireless LAN/ HomeRF
- ISM band 2.4GHz applications.


DIMENSION



CONSTRUCTION



Test Board



CONTACT INFORMATION

For more information, please contact with HF Division, Walsin Technology Corporation

Tel : 886-3-475-8711

Fax No. : 886-3-475-5197

E mail : info@passivecomponent.com