



RF EXPOSURE REPORT

REPORT NO.: SA960409L03

MODEL NO.: BT-36

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Wanstonic Electronics Ltd.

ADDRESS: 4F, NO. 540-1, CHUNG CHENG ROAD,
HSINTIEN CITY, TAIPEI HSIEN, TAIWAN

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	10.60	11.482
EIRP Power	12.54	17.947

***Note:** The antenna is printed antenna with 1.94dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 17.947mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold