

# SENA

Dates of Tests: May 26 ~ June 09, 2011

Test Report S/N: LR500111106H

Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID

**S7A-SP01**

IC

**8154A-SP01**

APPLICANT

**Sena Technologies, Inc.**

<b>Equipment Class</b>	:	<b>Part 15 Spread Spectrum Transmitter (DSS)</b>
<b>Manufacturing Description</b>	:	<b>Bluetooth Stereo Motorcycle Headset</b>
<b>Manufacturer</b>	:	<b>Sena Technologies, Inc.</b>
<b>Model name</b>	:	<b>SPH10</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
		<b>RSS-210 and ISSUE No. :8 Date :2010</b>
<b>Frequency Range</b>	:	<b>2402 ~ 2480MHz</b>
<b>RF power</b>	:	<b>Max 11.47dBm - Conducted</b>
<b>Data of issue</b>	:	<b>June 14, 2011</b>

This test report is issued under the authority of:

The test was supervised by:




Hyun-Chae You, Manager

Il-Shin kim, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S	-----	3
2. INFORMATION'S ABOUT TEST ITEM	-----	4
3. TEST REPORT	-----	5
3.1 SUMMARY OF TESTS	-----	5
3.2 TECHNICAL CHARACTERISTICS TEST	-----	6
3.2.1 CARRIER FREQUENCY SEPARATION	-----	6
3.2.2 NUMBER OF HOPPING FREQUENCIES	-----	8
3.2.3 20 dB BANDWIDTH	-----	10
3.2.4 TIME OF OCCUPANCY (Dwell Time)	-----	17
3.2.5 TRANSMITTER OUTPUT POWER	-----	22
3.2.6 BAND – EDGE & SPURIOUS	-----	26
3.2.7 FIELD STRENGTH OF HARMONICS-Transmitter	-----	32
3.2.8 FIELD STRENGTH OF HARMONICS-Receiver	-----	35
3.2.9 AC CONDUCTED EMISSIONS	-----	40

## **APPENDIX**

APPENDIX TEST EQUIPMENT USED FOR TESTS	-----	43
--	-------	----

## 1. General information's

### **1-1 Test Performed**

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### **1-2 Accredited agencies**

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2011-09-30	ECT accredited Lab.
KCC	KOREA	KR0049	2013-04-24	EMC accredited Lab.
FCC	U.S.A	610755	2014-04-27	FCC filing
FCC	U.S.A	649054	2013-04-13	FCC CAB
VCCI	JAPAN	R2133(10m), C2307	2014-06-21	VCCI registration
VCCI	JAPAN	T-2009	2013-12-23	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

## 2. Information's about test item

### 2-1 Client & Manufacturer

Company name : Sena Technologies, Inc.  
 Address : 210 Yangjae-dong Seocho-gu Seoul 137-130 Korea  
 Telephone / Facsimile : +82-2-571-8283/ +82-2-573-7710

### 2-2 Equipment Under Test (EUT)

Trade name : Bluetooth Stereo Motorcycle Headset  
 Model name : SPH10  
 Serial number : Identical prototype  
 Date of receipt : May 20, 2011  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip antenna (M/N: SENA\_009) Max Gain 0.5 dBi  
 Frequency Range : 2402 ~ 2480MHz  
 RF output power : Max. 11.47dBm - Conducted  
 Number of channels : 79  
 Duty cycle : 80.90 %  
 Channel spacing : 1MHz  
 Channel Access Protocol : Frequency Hopping Spread Spectrum (FHSS)  
 Type of Modulation : Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)  
 Power Source : 3.7 Vdc from Internal Battery (Li-Ion Polymer Battery)  
 Firmware Version : V1.0.0

### 2-4 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

### 2-5 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 / 15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies    NC=Not Complies    NT=Not Tested    NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: This device is only operated by DC

#### Note 1: Antenna Requirement

→ The Sena Technologies, Inc. SPH10 unit complies with the requirement of §15.203.

The antenna type is the Chip antenna

**Note 2:** The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

RSS-210 and ISSUE No.: 8 Date: 2010

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

#### The spectrum analyzer is set to:

Span = 2~3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
1.0043	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency SeparationBasic ModeEDR Mode

### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

#### The spectrum analyzer is set to:

Frequency range      Start = 2400.0MHz,   Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more)      Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Span > 40MHz

#### Measurement Data: Complies

<b>Total number of Hopping Channels</b>	79
---	----


- See next pages for actual measured spectrum plots.

#### Minimum Standard:

At least 15 hopes

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Number of Hopping Frequencies

### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW) Detector function = peak

Trace = max hold

#### Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.881	0.873
2441	39	0.842	0.873
2480	78	0.829	0.881

#### Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.324	1.350
2441	39	1.341	1.315
2480	78	1.345	1.337



- See next pages for actual measured spectrum plots.



#### Minimum Standard:


N/A



#### Measurement Setup



Same as the Chapter 3.2.1 (Figure 1)



Channel 1 of basic mode20 dB Bandwidth99% Bandwidth

Channel 2 of basic mode20 dB Bandwidth99% Bandwidth

Channel 3 of basic mode20 dB Bandwidth99% Bandwidth

**Channel 1 at EDR mode****20 dB Bandwidth****99% Bandwidth**

Channel 2 at EDR mode20 dB Bandwidth99% Bandwidth

Channel 3 at EDR mode20 dB Bandwidth99% Bandwidth

### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Mode	Number of transmission in a 31.6s ( 79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	30(Times / 3sec) *10.533 = 315.99	0.521	164.63	400
DH3	15(Times / 3sec) *10.533 = 158.00	1.761	278.23	400
DH5	10(Times / 3sec) *10.533 = 105.33	3.029	319.04	400
EDR 3Mbps DH5	10(Times / 3sec) *10.533 = 105.33	3.043	320.52	400



- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms



#### Minimum Standard:



0.4 seconds within a 30 second period per any frequency



#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

DH1 at basic mode

**DH3 at basic mode**

**DH5 at basic mode**

**DH5 at EDR mode with 3Mbps**

### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW  $\geq$  RBW)      Detector function = peak

Trace = max hold      Sweep = auto

#### Measurement Data: Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>9.77</b>	<b>9.48</b>	Complies
2441	39	<b>10.74</b>	<b>11.86</b>	Complies
2480	78	<b>11.47</b>	<b>14.03</b>	Complies

#### Measurement Data: EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>3.78</b>	<b>2.39</b>	Complies
2441	39	<b>5.05</b>	<b>3.20</b>	Complies
2480	78	<b>5.92</b>	<b>3.91</b>	Complies

- See next pages for actual measured spectrum plots.


<b>Minimum Standard:</b>	< 250 mW
--------------------------	----------

#### Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

### Channel 1

#### Basic mode




### EDR mode




## Channel 2

### Basic mode




### EDR mode




### Channel 3

#### Basic mode



#### EDR mode



### 3.2.6 Band Edge

## Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10~30 MHz      Detector function = peak



**Measurement Data: Complies**

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Band – edgeLower edgeUpper edge


**Band-edges in the restricted band 2310-2390 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]	Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]		
			Antenna	Amp. Gain	Cable							
2376.0	46.8	57.1	H	25.4	37.1	4.0	54.0	74.0	39.1	49.4	15.0	24.7


**Band-edges in the restricted band 2483.5-2500 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]	Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]		
			Antenna	Amp. Gain	Cable							
2483.5	50.8	63.8	H	25.4	37.1	4.0	54.0	74.0	43.1	56.1	11.0	18.0


**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**

Unwanted Emission – Low channelFrequency Range = 30 MHz ~ 26.5 GHz

**Unwanted Emission – Middle channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



Unwanted Emission – High channel  
Frequency Range = 30 MHz ~ 26.5 GHz



### 3.2.7 Field Strength of Harmonics - Transmitter

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions. In case of the air temperature of the test site is out of the range is 10 to 40°C before the testing proceeds the warm-up time of EUT maintain adequately

#### The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

Peak:VBW ≥ RBW

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Average:VBW=10Hz

Span = 100 MHz

Detector function = Peak and Average

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data:**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			D.C.F	Limits [dBuV/m] AV/Peak		Result [dBuV/m] AV/Peak		Margin [dB] AV / Peak	
				Antenna	Amp.Gain	Cable							
4804.0	53.3	60.3	H	31.4	36.5	5.7	-30.33	54.0	74.0	23.7	30.6	30.3	43.4
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			D.C.F	Limits [dBuV/m] AV/Peak		Result [dBuV/m] AV/Peak		Margin [dB] AV / Peak	
				Antenna	Amp.Gain	Cable							
4882.2	49.7	59.2	H	31.4	36.5	5.7	-30.33	54.0	74.0	20.0	29.5	34.0	44.5
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			D.C.F	Limits [dBuV/m] AV/Peak		Result [dBuV/m] AV/Peak		Margin [dB] AV / Peak	
				Antenna	Amp.Gain	Cable							
4960.2	48.4	59.6	H	31.4	36.5	5.7	-30.33	54.0	74.0	18.7	29.9	35.3	44.1

- No other emissions were detected at a level greater than 20dB below limit.

- D.C.F ( Duty Cycle Correction Factor) =  $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(3.043\text{ms}/100\text{ms}) = -30.33$$

Radiated Emissions – Charging + BT


243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT/Model No.: SENA / SPH10

TEST MODE: USB Cahrgeing + BT

Temp Humi : 26°C / 41%

Tested by: PARK.H.W



Freq MHz	Reading dBuV/m	C.F dB/m	Result dBuV/m	Limit QP		Margin dB	Height cm	Angle deg	Polarity
				Limit dBuV/m	Margin dB				
1 106.66	45.94	-13.03	32.90	43.50	10.60	123	249	VERTICAL	
2 117.33	48.07	-12.49	35.57	43.50	7.93	133	153	VERTICAL	
3 179.76	43.00	-9.93	33.07	43.50	10.43	100	256	HORIZONTAL	
4 309.33	51.36	-7.00	44.36	46.00	1.64	100	268	HORIZONTAL	
5 314.67	44.16	-6.86	37.30	46.00	8.70	100	255	HORIZONTAL	
6 320.00	48.46	-6.74	41.72	46.00	4.28	100	276	HORIZONTAL	

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.8 Field Strength of Harmonics - Receivers

#### Definition:

The field strength of emissions from intentional radiators was measured. In case of the air temperature of the test site is out of the range is 10 to 40°C before the testing proceeds the warm-up time of EUT maintain adequately

Test method	: FCC Part 15.209
Frequency Range	: 30 MHz ~ 10 <sup>th</sup> harmonic.
Bandwidth	: 120 kHz (F < 1GHz) 1 MHz (F > 1GHz)
Distance of antenna	: 3 meters
Test mode	: Rx mode
Result	: <b>Complies</b>

#### Measurement Data:

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit
- It gave the worse case emissions.


#### Field Strength Limit

##### Part 15.209 LIMIT:


Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100**
88 ~ 216	150**
216 ~ 960	200**
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.


**Conducted Emission – Low channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



Conducted Emission – Middle channel  
Frequency Range = 30 MHz ~ 26.5 GHz



**Conducted Emission – High channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



**Measurement Data:**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp.Gain	Cable						
AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak
1497.0	41.4	56.7	H	25.7	38.4	1.6	54.0	74.0	30.3	45.6	23.7	28.4
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
AV / Peak	AV / Peak	AV / Peak	Pol.	Antenna	Amp.Gain	Cable	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak
1495.5	44.7	57.6	H	25.7	38.4	1.6	54.0	74.0	33.6	46.5	20.4	27.5
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
AV / Peak	AV / Peak	AV / Peak	Pol.	Antenna	Amp.Gain	Cable	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak	AV / Peak
1494.80	45.6	57.8	H	25.7	38.4	1.6	54.0	74.0	34.5	46.7	19.5	27.3

No other emissions were detected at a level greater than 20dB below limit.

### 3.2.9 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: **Complies**

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit
- It gave the worse case emissions

#### Minimum Standard: FCC Part 15.207(a)/EN 55022


Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Radiated Emissions – Charging + BT LINE

243 Jibug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax :+82-31-3236010

EUT / Model No. : SPH10 Phase : LINE  
-----  
Test Mode : Charging mode + BT Test Power : 120 / 60  
Temp./Humi. : 23 / 56 Test Engineer : PARK.H.W  
-----




Freq MHz	RD QP		RD AV		C. F dB	Result dBuV	Result QP		Result AV		Limit QP	Limit dBuV	Margin dB	Margin dB						
	dBuV	dBuV	dBuV	dBuV			dBuV	dBuV	dBuV	dBuV										
0.150	33.34	11.44	9.66	43.00	43.00	21.10	66.00	56.00	56.00	23.00	34.90									
0.193	39.54	24.34	9.64	49.18	49.18	33.98	63.91	53.91	53.91	14.72	19.92									
0.252	30.23	18.63	9.64	39.87	39.87	28.27	61.69	51.69	51.69	21.82	23.42									
0.324	30.93	19.63	9.66	40.59	40.59	29.29	59.60	49.60	49.60	19.02	20.32									
0.469	23.32	13.12	9.67	32.99	32.99	22.79	56.53	46.53	46.53	23.54	23.74									
0.537	21.52	12.22	9.67	31.19	31.19	21.89	56.00	46.00	46.00	24.81	24.11									

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

Radiated Emissions – Charging + BT NEUTRAL

243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax :+82-31-3236010

EUT / Model No. : SPH10 Phase : NEUTRAL  
-----  
Test Mode : Charging mode + BT Test Power : 120 / 60  
Temp./Humi. : 23 / 56 Test Engineer : PARK.H.W  
-----



Freq MHz	RD QP dBuV	RD AV dBuV	C. F dB	Result		Result		Limit		Margin	
				QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.151	34.14	12.44	9.67	43.81	22.11	65.94	55.94	22.14	33.84		
0.192	38.24	24.54	9.64	47.88	34.18	63.95	53.95	16.07	19.77		
0.257	29.63	18.63	9.65	39.28	28.28	61.53	51.53	22.25	23.25		
0.321	30.23	19.13	9.65	39.88	28.78	59.68	49.68	19.80	20.90		
0.391	21.43	12.33	9.65	31.08	21.98	58.04	48.04	26.96	26.06		
0.448	23.02	11.42	9.66	32.69	21.09	56.91	46.91	24.23	25.83		

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Spectrum Analyzer (~30GHz)	FSV-30	100757	R&S	1 year	2011-01-24
2	Spectrum Analyzer (~2.9GHz)	8594E	3710A04074	HP	2 year	2009-10-12
3	Signal Generator (~3.2GHz)	8648C	3623A02597	HP	1 year	2011-03-30
4	Signal Generator (1~20GHz)	83711B	US34490456	HP	1 year	2011-03-30
5	Attenuator (3dB)	8491A	37822	HP	2 year	2010-10-08
6	Attenuator (10dB)	8491A	63196	HP	2 year	2010-10-08
7	Attenuator (30dB)	8498A	3318A10929	HP	2 year	2011-01-05
8	Test Receiver (~30MHz)	ESHS10	828404/009	R&S	1 year	2011-03-30
9	EMI Test Receiver (~1GHz)	ESCI7	100722	R&S	1 year	2010-10-08
10	RF Amplifier (~1.3GHz)	8447D	2439A09058	HP	2 year	2010-10-08
11	RF Amplifier (1~18GHz)	8449B	3008A02126	HP	2 year	2010-03-29
12	Horn Antenna (1~18GHz)	BBHA 9120D	9120D122	SCHWARZBECK	2 year	2010-12-24
13	Horn Antenna (18 ~ 40GHz)	SAS-574	154	Schwarzbeck	2 year	2010-11-25
14	Horn Antenna (18 ~ 40GHz)	SAS-574	155	Schwarzbeck	2 year	2010-11-25
15	TRILOG Antenna	VULB 9160	9160-3172	SCHWARZBECK	2 year	2010-10-07
16	Dipole Antenna	VHA9103	2116	SCHWARZBECK	2 year	2010-11-25
17	Dipole Antenna	VHA9103	2117	SCHWARZBECK	2 year	2010-11-25
18	Dipole Antenna	VHA9105	2261	SCHWARZBECK	2 year	2010-11-25
19	Dipole Antenna	VHA9105	2262	SCHWARZBECK	2 year	2010-11-25
20	Hygro-Thermograph	THB-36	0041557-01	ISUZU	2 year	2010-04-12
21	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
22	Power Divider	11636A	6243	HP	2 year	2010-10-08
23	DC Power Supply	6622A	3448A03079	HP	-	-
24	Frequency Counter	5342A	2826A12411	HP	1 year	2011-03-30
25	Power Meter	EPM-441A	GB32481702	HP	1 year	2011-03-30
26	Power Sensor	8481A	US41030291	HP	1 year	2010-10-08
27	Audio Analyzer	8903B	3729A18901	HP	1 year	2010-10-08
28	Modulation Analyzer	8901B	3749A05878	HP	1 year	2010-10-08
29	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2010-10-08
30	Stop Watch	HS-3	601Q09R	CASIO	2 year	2010-03-31
31	LISN	ENV216	100408	R&S	1 year	2010-10-08
32	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	2 year	2010-05-13
33	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	-	-
34	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	-	-