

FCC PART 15.247

TEST REPORT

For

Coby Communications Ltd.

Unit C-E, 8/F, PO Shau Centre, 115 How Ming Street,
Kwun Tong Kowloon, Hong Kong

FCC ID: S7IMID7120

Report Type: Original Report	Product Type: Mobile Internet Device
Test Engineer: Jim Huang	<i>Jim Huang</i>
Report Number: RDG110927003-00-15.247	
Report Date: 2011-12-02	
Reviewed By: Alvin Huang EMC Engineer	<i>Alvin Huang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
EXTERNAL I/O CABLING LIST AND DETAILS.....	6
CONFIGURATION OF TEST SETUP	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
§15.247 (i) and §1.1307 (b) (1), §2.1093 – RF EXPOSURE	9
STANDARD APPLICABLE	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	27
FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER	33
APPLICABLE STANDARD	33

TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	40
FCC §15.247(e) - POWER SPECTRAL DENSITY	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	45

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Coby Communications Ltd.*'s product, model number: *MID7120 (FCC ID: S7IMID7120)* (the "EUT") in this report is a *Mobile Internet Device*, which was measured approximately: 19.9 cm (L) x 12.1 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7V battery and DC 5V adapter for charging.

Adapter Information: SWITCHING ADAPTER

Model: ADS-18C-06 0512GPCU;

Input: 100-240V~50/60Hz max. 0.6A;

Output: 5V 2.4A

** All measurement and test data in this report was gathered from production sample serial number: 1108102 (Assigned by BACL, Shenzhen). The EUT was received on 2011-09-27*

Objective

This report is prepared on behalf of *Coby Communications Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B submissions with FCC ID: S7IMID7120

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.96 dB, the uncertainty of any radiation on emissions measurement is ± 4.0 dB

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g & 802.11n-20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

EUT was tested with Channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the average power and PSD across all data rates bandwidths, and modulations.

EUT Exercise Software

Software was provided by client.

Command: # athtestcmd -i wlan0 --tx tx99 --txfreq A* --txpwr B* --txrate C*

Note: A* contain 1,2,3,4,5,6,7,8,9,10,11,stand for channel.

Note: B* stand for power control level. 802.11 b is 14, 802.1 g is 9, 802.11n20 is 5.

Note: C* stand for TX rate, 802.11 b is 1,802.11 g is 6,802.11 n20 is 6.5.

Equipment Modifications


Modification was made to the unit tested.

Detail information please refers to the EUT internal photo.


External I/O Cabling List and Details

Cable Description	Length (m)	From	To
Shielded Detachable USB Cable with a core	1.0	Laptop	EUT

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

§15.247 (i) and §1.1307 (b) (1), §2.1093 – RF EXPOSURE

Standard Applicable

According to FCC §15.247 (i) & §2.1093

Result: Compliant

Please refer to the SAR report, report No.: RDG110927003-20.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The antennas was build on board which complied to section 15.203, the maximum gain is 2 dBi; please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard


FCC §15.207

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is ± 2.4 dB ($k=2$, 95% level of confidence).

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<u>Frequency Range</u>	<u>IF B/W</u>
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

15.41 dB at 0.160 MHz in the Neutral conducted mode

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Jim Huang on 2011-10-11.

Test Mode: Transmitting

120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/QP/Ave.)
0.165	49.77	10.10	65.57	15.80	QP
0.165	37.07	10.10	55.57	18.50	Ave
29.295	29.65	10.10	50.00	20.35	Ave
2.545	22.94	10.10	46.00	23.06	Ave
0.280	38.24	10.10	62.29	24.05	QP
0.190	40.69	10.10	64.86	24.17	QP
29.400	35.34	10.10	60.00	24.66	QP
2.545	31.08	10.10	56.00	24.92	QP
0.375	33.31	10.10	59.57	26.26	QP
0.190	17.48	10.10	54.86	37.38	Ave
0.280	14.56	10.10	52.29	37.73	Ave
0.375	10.34	10.10	49.57	39.23	Ave

120V, 60 Hz, Neutral:

Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Result (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK /QP/Ave.)
0.160	50.30	10.10	65.71	15.41	QP
0.160	38.78	10.10	55.71	16.93	Ave
0.205	44.18	10.10	64.43	20.25	QP
0.180	43.53	10.10	65.14	21.61	QP
28.045	27.89	10.10	50.00	22.11	Ave
2.420	23.62	10.10	46.00	22.38	Ave
0.275	29.37	10.10	52.43	23.06	Ave
2.420	30.96	10.10	56.00	25.04	QP
0.275	36.31	10.10	62.43	26.12	QP
27.920	32.61	10.10	60.00	27.39	QP
0.205	20.98	10.10	54.43	33.45	Ave
0.180	19.54	10.10	55.14	35.60	Ave

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB(k=2, 95% level of confidence) .

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-03-11	2012-03-10
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:


2.65 dB at 4924 MHz in the **Vertical** polarization for high channel (2462MHz) 801.11b mode.

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Jim Huang on 2011-10-19 to 2011-11-08.

1) Below 1 GHz:*Test Mode: Transmitting*

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Ant. Height (cm)	Ant. Polarity (H/V)	Turntable Position (degree)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
362.513000	42.9	148.0	V	228.0	-6.8	46.0	3.1*
249.999500	41.6	103.0	V	275.0	-7.4	46.0	4.4
366.606750	41.2	104.0	V	314.0	-3.6	46.0	4.8
183.987500	35.0	101.0	H	156.0	-10.3	43.0	8.0
104.679750	33.0	102.0	V	233.0	-14.1	43.0	10.0
102.263500	31.2	103.0	H	84.0	-15.6	43.0	11.8

*Within measurement uncertainty.

2) Above 1 GHz

802.11b Mode:

Indicated		Detector (PK/Ave.)	Table Angle Degree	Antenna		Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	S.A. Reading (dBμV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel (2412 MHz)												
4824	37.83	Ave	320	1.1	H	36.3	4.30	27.51	50.92	54	3.08*	harmonic
4824	38.21	Ave	210	1.0	V	35.0	4.30	27.51	50.00	54	4.00*	harmonic
2386.64	36.48	Ave	145	1.0	H	30.9	3.03	26.85	43.56	54	10.44	spurious
2389.64	36.91	Ave	334	1.0	V	30.3	3.03	26.85	43.39	54	10.61	spurious
4824	40.95	PK	320	1.1	H	36.3	4.30	27.51	54.04	74	19.96	harmonic
4824	41.78	PK	210	1.0	V	35.0	4.30	27.51	53.57	74	20.43	harmonic
2386.64	46.36	PK	145	1.0	H	30.9	3.03	26.85	53.44	74	20.56	spurious
2389.64	43.9	PK	334	1.0	V	30.3	3.03	26.85	50.38	74	23.62	spurious
Middle Channel (2437 MHz)												
4874	37.95	Ave	125	1.2	H	36.3	4.30	27.51	51.04	54	2.96*	harmonic
4874	38.25	Ave	356	1.5	V	35.0	4.30	27.49	50.06	54	3.94*	harmonic
4874	41.26	PK	125	1.2	H	36.3	4.30	27.51	54.35	74	19.65	harmonic
4874	41.93	PK	356	1.5	V	35.0	4.30	27.49	53.74	74	20.26	harmonic
High Channel (2462 MHz)												
4924	39.56	Ave	35	1.3	V	35.0	4.30	27.51	51.35	54	2.65*	harmonic
4924	38.15	Ave	253	1.4	H	36.3	4.30	27.51	51.24	54	2.76*	harmonic
2487.69	36.21	Ave	130	1.0	H	30.9	3.03	26.85	43.29	54	10.71	spurious
2487.69	35.2	Ave	145	1.0	V	30.3	3.03	26.85	41.68	54	12.32	spurious
4924	42.77	PK	35	1.3	V	35.0	4.30	27.51	54.56	74	19.44	harmonic
4924	41.32	PK	253	1.4	H	36.3	4.30	27.51	54.41	74	19.59	harmonic
2487.69	45.08	PK	130	1.0	H	30.9	3.03	26.85	52.16	74	21.84	spurious
2487.69	44.97	PK	145	1.0	V	30.3	3.03	26.85	51.45	74	22.55	spurious

*Within measurement uncertainty.

802.11g Mode:


Indicated		Detector (PK/Ave)	Table Angle Degree	Antenna		Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	S.A. Reading (dBμV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel (2412 MHz)												
4824	30.25	Ave	320	1.1	H	36.3	4.30	27.51	43.34	54	10.66	harmonic
4824	30.82	Ave	210	1.0	V	35.0	4.30	27.51	42.61	54	11.39	harmonic
2388.15	28.05	Ave	145	1.0	H	30.9	3.03	26.85	35.13	54	18.87	spurious
2389.34	28.13	Ave	334	1.0	V	30.3	3.03	26.85	34.61	54	19.39	spurious
2388.15	45.2	PK	145	1.0	H	30.9	3.03	26.85	52.28	74	21.72	spurious
2389.34	44.1	PK	334	1.0	V	30.3	3.03	26.85	50.58	74	23.42	spurious
4824	36.36	PK	320	1.1	H	36.3	4.30	27.51	49.45	74	24.55	harmonic
4824	37.38	PK	210	1.0	V	35.0	4.30	27.51	49.17	74	24.83	harmonic
Middle Channel (2437 MHz)												
4874	30.26	Ave	65	1.1	H	36.3	4.30	27.51	43.35	54	10.65	harmonic
4874	30.98	Ave	235	1.1	V	35.0	4.30	27.49	42.79	54	11.21	harmonic
4874	36.83	PK	65	1.1	H	36.3	4.30	27.51	49.92	74	24.08	harmonic
4874	37.58	PK	235	1.1	V	35.0	4.30	27.49	49.39	74	24.61	harmonic
High Channel (2462 MHz)												
4924	30.82	Ave	253	1.4	H	36.3	4.30	27.51	43.91	54	10.09	harmonic
4924	30.15	Ave	35	1.3	V	35.0	4.30	27.51	41.94	54	12.06	harmonic
2485.63	28.67	Ave	130	1.0	H	30.9	3.03	26.85	35.75	54	18.25	spurious
2489.34	29.23	Ave	145	1.0	V	30.3	3.03	26.85	35.71	54	18.29	spurious
2485.63	46.25	PK	130	1.0	H	30.9	3.03	26.85	53.33	74	20.67	spurious
2489.34	45.18	PK	145	1.0	V	30.3	3.03	26.85	51.66	74	22.34	spurious
4924	37.45	PK	253	1.4	H	36.3	4.30	27.51	50.54	74	23.46	harmonic
4924	37.97	PK	35	1.3	V	35.0	4.30	27.51	49.76	74	24.24	harmonic

802.11n-20 Mode:


Indicated		Detector (PK/Ave)	Table Angle Degree	Antenna		Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	S.A. Reading (dBμV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel (2412 MHz)												
4824	23.82	Ave	210	1.0	V	35.0	4.30	27.51	35.61	54	18.39	harmonic
4824	22.25	Ave	320	1.1	H	36.3	4.30	27.51	35.34	54	18.66	harmonic
2389.34	26.3	Ave	334	1.0	V	30.3	3.03	26.85	32.78	54	21.22	spurious
2389.34	46.1	PK	334	1.0	V	30.3	3.03	26.85	52.58	74	21.42	spurious
2388.15	45.2	PK	145	1.0	H	30.9	3.03	26.85	52.28	74	21.72	spurious
2388.15	25.05	Ave	145	1.0	H	30.9	3.03	26.85	32.13	54	21.87	spurious
4824	33.36	PK	320	1.1	H	36.3	4.30	27.51	46.45	74	27.55	harmonic
4824	34.38	PK	210	1.0	V	35.0	4.30	27.51	46.17	74	27.83	harmonic
Middle Channel (2437 MHz)												
4874	21.46	Ave	65	1.1	H	36.3	4.30	27.51	34.55	54	19.45	harmonic
4874	22.06	Ave	235	1.1	V	35.0	4.30	27.49	33.87	54	20.13	harmonic
4874	33.83	PK	65	1.1	H	36.3	4.30	27.51	46.92	74	27.08	harmonic
4874	34.58	PK	235	1.1	V	35.0	4.30	27.49	46.39	74	27.61	harmonic
High Channel (2462 MHz)												
4924	21.82	Ave	253	1.4	H	36.3	4.30	27.51	34.91	54	19.09	harmonic
4924	22.45	Ave	35	1.3	V	35.0	4.30	27.51	34.24	54	19.76	harmonic
2489.34	47.16	PK	145	1.0	V	30.3	3.03	26.85	53.64	74	20.36	spurious
2485.63	46.48	PK	130	1.0	H	30.9	3.03	26.85	53.56	74	20.44	spurious
2485.63	25.67	Ave	130	1.0	H	30.9	3.03	26.85	32.75	54	21.25	spurious
2489.34	26.23	Ave	145	1.0	V	30.3	3.03	26.85	32.71	54	21.29	spurious
4924	34.45	PK	253	1.4	H	36.3	4.30	27.51	47.54	74	26.46	harmonic
4924	34.77	PK	35	1.3	V	35.0	4.30	27.51	46.56	74	27.44	harmonic

Antenna Port Conducted Spurious Emissions:


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n-20 Low Channel



802.11n-20 Middle Channel



802.11n-20 High Channel




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa


The testing was performed by Jim Huang on 2011-10-17.

Test Result: Pass.


Please refer to the following tables and plots.

Channel	Channel Frequency (MHz)	Data Rate (Mbps)	6dB Bandwidth (MHz)	FCC Part 15.247 Limit (kHz)
802.11b Mode				
Low	2412	1	10.16	>500
Middle	2437	1	10.16	>500
High	2462	1	10.16	>500
802.11g Mode				
Low	2412	6	16.40	>500
Middle	2437	6	16.40	>500
High	2462	6	16.40	>500
802.11n-20 Mode				
Low	2412	6.5	17.20	>500
Middle	2437	6.5	17.12	>500
High	2462	6.5	17.12	>500


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel


Date: 17.OCT.2011 10:55:28

802.11g Middle Channel

Date: 17.OCT.2011 10:23:46


802.11g High Channel

Date: 17.OCT.2011 09:58:00

802.11n-20 Low Channel


Date: 17.OCT.2011 11:17:03

802.11n-20 Middle Channel



Date: 17.OCT.2011 11:36:53

802.11n-20 High Channel



Date: 17.OCT.2011 13:31:42


FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Jim Huang from 2011-11-16 to 2011-12-01

Test Mode: Transmitting


Channel	Frequency (MHz)	Data Rate (Mbps)	Reading Power (dBm)	Limit (dBm)	Result
802.11b Mode					
Low	2412	1	12.69	30	Pass
Middle	2437	1	12.95	30	Pass
High	2462	1	13.58	30	Pass
802.11g Mode					
Low	2412	6	12.21	30	Pass
Middle	2437	6	12.59	30	Pass
High	2462	6	13.29	30	Pass
802.11n-20 Mode					
Low	2412	6.5	11.57	30	Pass
Middle	2437	6.5	11.71	30	Pass
High	2462	6.5	11.61	30	Pass

802.11b RF Output Power, Low Channel




Date: 16.NOV.2011 15:20:40

802.11b RF Output Power, Middle Channel




Date: 16.NOV.2011 15:09:54

802.11b RF Output Power, High Channel




Date: 16.NOV.2011 15:10:17

802.11g RF Output Power, Low Channel




Date: 16.NOV.2011 15:20:16

802.11g RF Output Power, Middle Channel




Date: 16.NOV.2011 15:11:54


802.11g RF Output Power, High Channel



Date: 16.NOV.2011 15:11:15


802.11n-20 RF Output Power, Low Channel

Date: 1.DEC.2011 16:48:41

802.11n-20 RF Output Power, Middle Channel

Date: 1.DEC.2011 16:49:32

802.11n-20 RF Output Power, High Channel



Date: 1.DEC.2011 16:50:16

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 1 MHz and VBW of spectrum analyzer to 1 MHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Jim Huang on 2011-10-19.

Test Result: *Compliance*


Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
802.11b mode				
Low	2397.12	45.11	20	Pass
High	2486.30	51.29	20	Pass
802.11g mode				
Low	2399.93	35.28	20	Pass
High	2483.90	45.25	20	Pass
802.11n-20 mode				
Low	2399.93	32.54	20	Pass
High	2483.91	48.17	20	Pass

Please refer to following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side



802.11n-20: Band Edge, Left Side



802.11n-20: Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to 1.5MHz span mode. And then, set RBW and VBW of spectrum analyzer to proper value. (DTS)
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Jim Huang on 2011-10-17.

Test Mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	Data Rate (Mbps)	Reading Power Spectral Density (dBm)	Limit (dBm)	Result
802.11b mode					
Low	2412	1	-13.69	8	Pass
Middle	2437	1	-12.93	8	Pass
High	2462	1	-12.43	8	Pass
802.11g mode					
Low	2412	6	-14.50	8	Pass
Middle	2437	6	-13.35	8	Pass
High	2462	6	-13.23	8	Pass
802.11n-20 mode					
Low	2412	6.5	-13.98	8	Pass
Middle	2437	6.5	-13.50	8	Pass
High	2462	6.5	-13.93	8	Pass


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel





Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Date: 17.OCT.2011 10:50:19

Power Spectral Density, 802.11g Middle Channel**Power Spectral Density, 802.11g High Channel**

Date: 17.OCT.2011 10:19:59


Power Spectral Density, 802.11n-20 Low Channel

Date: 17.OCT.2011 12:06:39

Power Spectral Density, 802.11n-20 Middle Channel

Date: 17.OCT.2011 11:57:12

Power Spectral Density, 802.11n-20 High Channel



Date: 17.OCT.2011 12:17:18

***** END OF REPORT *****