

FCC ID: S7JNX16A11264XD

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz ;

Power and distance are rounded to the nearest mW and mm before calculation ;

The result is rounded to one decimal place for comparison ;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

802.11b/g/n HT20/n HT40:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.412	11b	9.33	7.6dBm-9.6dBm	2.83	3.0
2.437	11b	9.56	7.6dBm-9.6dBm	2.83	3.0
2.462	11b	9.59	7.6dBm-9.6dBm	2.83	3.0
2.412	11g	8.99	7.6dBm-9.6dBm	2.83	3.0
2.437	11g	8.86	7.6dBm-9.6dBm	2.83	3.0
2.462	11g	8.83	7.6dBm-9.6dBm	2.83	3.0
2.412	11n HT20	8.55	7.6dBm-9.6dBm	2.83	3.0
2.437	11n HT20	8.54	7.6dBm-9.6dBm	2.83	3.0
2.462	11n HT20	8.38	7.6dBm-9.6dBm	2.83	3.0
2.422	11n HT40	8.01	7.6dBm-9.6dBm	2.83	3.0
2.437	11n HT40	7.96	7.6dBm-9.6dBm	2.83	3.0
2.452	11n HT40	8.05	7.6dBm-9.6dBm	2.83	3.0

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	-0.612	-1dBm- 1 dBm	0.39	3.0
2.441	GFSK	-0.291	-1dBm- 1 dBm	0.39	3.0
2.480	GFSK	-0.210	-1dBm- 1 dBm	0.39	3.0
2.402	$\pi/4$ -DQPSK	-0.479	-1dBm- 1 dBm	0.39	3.0
2.441	$\pi/4$ -DQPSK	-0.168	-1dBm- 1 dBm	0.39	3.0
2.480	$\pi/4$ -DQPSK	-0.183	-1dBm- 1 dBm	0.39	3.0
2.402	8DPSK	-0.001	-1dBm- 1 dBm	0.39	3.0
2.441	8DPSK	0.398	-1dBm- 1 dBm	0.39	3.0
2.480	8DPSK	0.382	-1dBm- 1 dBm	0.39	3.0

BT DTS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	2.505	2.5dBm-4.5dBm	0.87	3.0
2.440	GFSK	4.116	2.5dBm-4.5dBm	0.87	3.0
2.480	GFSK	4.116	2.5dBm-4.5dBm	0.87	3.0

Conclusion:

For the max result : $2.83 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature: 

Date: 2016-03-15

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China