

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

nextbook

Model No.: NXA8LTE116

FCC ID: S7JNXA8LTE116

Trademark: N/A

REPORT NO.: ES150110111E3

ISSUE DATE: March 14, 2015

Prepared for

SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD.

Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan,
Shenzhen518108, China

Prepared by

SHENZHEN EMTEK CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	6
4	TEST METHODOLOGY.....	7
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
4.2	MEASUREMENT EQUIPMENT USED	7
4.3	DESCRIPTION OF TEST MODES.....	8
5	FACILITIES AND ACCREDITATIONS.....	9
5.1	FACILITIES	9
5.2	LABORATORY ACCREDITATIONS AND LISTINGS	9
6	TEST SYSTEM UNCERTAINTY	10
7	SETUP OF EQUIPMENT UNDER TEST	11
7.1	RADIO FREQUENCY TEST SETUP 1	11
7.2	RADIO FREQUENCY TEST SETUP 2	11
7.3	CONDUCTED EMISSION TEST SETUP	12
7.4	SUPPORT EQUIPMENT	12
8	TEST REQUIREMENTS.....	13
8.1	DTS (6DB) BANDWIDTH	13
8.2	MAXIMUM PEAK CONDUCTED OUTPUT POWER	20
8.3	MAXIMUM POWER SPECTRAL DENSITY	21
8.4	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS	28
8.5	RADIATED SPURIOUS EMISSION.....	33
8.6	CONDUCTED EMISSION TEST	58
8.7	ANTENNA APPLICATION	63

1 TEST RESULT CERTIFICATION

Applicant: SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD.
Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan, Shenzhen518108, China

Manufacturer: SHENZHEN YIFANG DIGITAL TECHNOLOGY CO., LTD.
Building NO.22,23, Fifth Region, Baiwangxin Industrial Park, Songbai Rd., Nanshan, Shenzhen518108, China

Product Description: nextbook

Model Number: NXA8LTE116

File Number: ES150210111E3

Date of Test: February 11, 2015 to March 13, 2015

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2014) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : February 11, 2015 to March 13, 2015

Jack Li

Prepared by : Jack Li /Editor

Joe Xia

Reviewer : Joe Xia/Supervisor

[Signature]

Approve & Authorized Signer : Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
IEEE 802.11 WLAN Mode Supported:	☒ 802.11b(20MHz channel bandwidth) ☒ 802.11g(20MHz channel bandwidth) ☒ 802.11n(20MHz channel bandwidth) ☒ 802.11n(40MHz channel bandwidth)
Data Rate:	802.11 b:1,2,5.5,11Mbps; 802.11 g:6,9,12,18,24,36,48,54Mbps; 802.11n(HT20):MCS0-MCS7; 802.11n(HT40):MCS0-MCS7;
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range:	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels:	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Transmit Power Max:	9.34dBm for 802.11b; 9.24dBm for 802.11g; 9.19dBm for 802.11n(HT20); 9.13dBm for 802.11n(HT40);
Antenna Type:	☒ integral antenna; ☐ antenna connector
Antenna Port:	☒ Ant1 ; ☐ Ant2 ;
Smart system:	☒ SISO for 802.11b/g/n ☐ MIMO for 802.11n
Antenna Gain:	2dBi
Power supply:	☒ DC supply: DC 3.7V internal rechargeable lithium battery or DC 5V from AC Adapter
	☒ Adapter supply: Model: ACDC-10BAU Input: 100-240V, 50-60Hz, 0.5A Output: DC 5V, 2A
Temperature Range:	-10°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.

Modified Information

[illegible]

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/17/2014
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/17/2014
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/17/2014
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/17/2014
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/17/2014

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/17/2014
Pre-Amplifier	HP	8447D	2944A07999	05/17/2014
Bilog Antenna	Schwarzbeck	VULB9163	142	05/17/2014
Loop Antenna	ARA	PLA-1030/B	1029	05/17/2014
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/17/2014
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/17/2014
Cable	Schwarzbeck	AK9513	ACRX1	05/17/2014
Cable	Rosenberger	N/A	FP2RX2	05/17/2014
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2014
Cable	Schwarzbeck	AK9513	CRRX2	05/17/2014

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/17/2014
Power meter	Anritsu	ML2495A	0824006	05/17/2014
Power sensor	Anritsu	MA2411B	0738172	05/17/2014

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

- : Accredited by CNAS, 2013.10.29
The certificate is valid until 2016.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291
- : Accredited by TUV Rheinland Shenzhen, 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025.
- : Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.
- : Accredited by FCC, February 28, 2013
The Certificate Registration Number is 709623.
- : Accredited by Industry Canada, May 24, 2008
The Certificate Registration Number is 4480A-2

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.




7.2 RADIO FREQUENCY TEST SETUP 2


The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.4-2014 and CAN/CSA-CEI/IEC CISPR 22.

The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (nextbook) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.4-2014 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS (6DB) BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.


8.1.5 Test Results

Temperature: 24°C
Humidity: 53 %


Test Date: February 13, 2015
Test By: KING KONG

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
802.11b	1	2412	10.027	500	PASS
	6	2437	9.600	500	PASS
	11	2462	9.620	500	PASS
802.11g	1	2412	16.642	500	PASS
	6	2437	16.657	500	PASS
	11	2462	16.613	500	PASS
802.11n (HT20)	1	2412	17.883	500	PASS
	6	2437	17.826	500	PASS
	11	2462	17.761	500	PASS
802.11n (HT40)	3	2422	36.580	500	PASS
	6	2437	36.583	500	PASS
	9	2452	34.533	500	PASS


Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 11: 2462MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 11: 2462MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 11: 2462MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 3: 2422MHz



Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 6: 2437MHz



Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 9: 2452MHz



8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The testing follows FCC public Notice DA 00-705 Measurement Guidelines.

The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2.5 Test Results

Temperature: 24°C
Humidity: 53 %

Test Date: February 13, 2015
Test By: KING KONG

Operation Mode	Channel Number	Channel Frequency (MHz)	Power Setting	Measurement Level (dBm)	Limit (dBm)	Verdict
802.11b	1	2412	32	9.34	30	PASS
	6	2437	33	9.05	30	PASS
	11	2462	35	9.04	30	PASS
802.11g	1	2412	38	9.24	30	PASS
	6	2437	39	8.60	30	PASS
	11	2462	41	9.22	30	PASS
802.11n (HT20)	1	2412	38	9.19	30	PASS
	6	2437	39	8.86	30	PASS
	11	2462	41	8.42	30	PASS
802.11n (HT40)	3	2422	42	9.13	30	PASS
	6	2437	43	9.08	30	PASS
	9	2452	45	8.81	30	PASS
Note: N/A						

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.


8.3.5 Test Results

Temperature: 24°C
Humidity: 53 %


Test Date: February 13, 2015
Test By: KING KONG

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	1	2412	-17.200	8	PASS
	6	2437	-15.660	8	PASS
	11	2462	-16.030	8	PASS
802.11g	1	2412	-20.150	8	PASS
	6	2437	-20.180	8	PASS
	11	2462	-18.320	8	PASS
802.11n (HT20)	1	2412	-21.450	8	PASS
	6	2437	-20.290	8	PASS
	11	2462	-21.130	8	PASS
802.11n (HT40)	3	2422	-24.240	8	PASS
	6	2437	-22.080	8	PASS
	9	2452	-22.540	8	PASS
Note: N/A					


Test Model	Power Spectral Density
	802.11b
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11b
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11b
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11g
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11g
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11g
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 3: 2422MHz



Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 6: 2437MHz



Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 9: 2452MHz



8.4 UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.



Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.



8.4.5 Test Results


All the modulation modes were tested, the data of the worst mode(802.11b) are described in the following table

Test Model	Unwanted Emissions in non-restricted frequency bands
	802.11b
	Channel 1: 2412MHz




Test Model	Unwanted Emissions in non-restricted frequency bands
	802.11b
	Channel 6: 2437MHz






Test Model	Band edge
	802.11b
	Channel 1: 2412MHz



Test Model	Band edge
	802.11b
	Channel 11: 2462MHz



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v03r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remark:1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz)

VBW $\geq$ RBW for peak measurement

VBW = 10Hz for average measurement

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4-1992 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results


■ Spurious Emission below 30MHz (9KHz to 30MHz)

Test mode: TX Mode

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

■ Spurious Emission Below 1GHz (30MHz to GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 53 %


Mode:802.11b TX CH1

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	81.4100	51.05	-18.59	32.46	40.00	-7.54	QP		
2		207.5100	45.47	-15.64	29.83	43.50	-13.67	QP		
3		415.0900	31.77	-8.11	23.66	46.00	-22.34	QP		
4		526.6400	29.75	-6.04	23.71	46.00	-22.29	QP		
5		646.9200	30.34	-5.02	25.32	46.00	-20.68	QP		
6		787.5700	30.30	-2.87	27.43	46.00	-18.57	QP		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	39.7000	47.83	-12.60	35.23	40.00	-4.77	QP		
2	*	82.3800	55.06	-18.36	36.70	40.00	-3.30	QP		
3		194.9000	38.60	-15.35	23.25	43.50	-20.25	QP		
4		415.0900	31.00	-8.11	22.89	46.00	-23.11	QP		
5		527.6100	30.79	-6.01	24.78	46.00	-21.22	QP		
6		680.8700	30.20	-5.52	24.68	46.00	-21.32	QP		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table
		MHz	Level	Factor	ment			Height	Degree
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	81.4100	49.47	-18.59	30.88	40.00	-9.12	QP	
2		207.5100	43.05	-15.64	27.41	43.50	-16.09	QP	
3		415.0900	31.05	-8.11	22.94	46.00	-23.06	QP	
4		533.4300	30.38	-6.22	24.16	46.00	-21.84	QP	
5		622.6700	32.10	-5.54	26.56	46.00	-19.44	QP	
6		910.7600	33.37	-0.90	32.47	46.00	-13.53	QP	

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	32.9100	50.60	-13.82	36.78	40.00	-3.22	QP		
2	!	83.3500	54.52	-18.12	36.40	40.00	-3.60	QP		
3		207.5100	37.27	-15.64	21.63	43.50	-21.87	QP		
4		415.0900	31.34	-8.11	23.23	46.00	-22.77	QP		
5		523.7300	30.20	-6.16	24.04	46.00	-21.96	QP		
6		788.5400	30.49	-2.89	27.60	46.00	-18.40	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 53 %


Mode:802.11b TX CH11

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	81.4100	48.33	-18.59	29.74	40.00	-10.26	QP		
2		207.5100	39.33	-15.64	23.69	43.50	-19.81	QP		
3		415.0900	31.80	-8.11	23.69	46.00	-22.31	QP		
4		515.0000	30.05	-6.45	23.60	46.00	-22.40	QP		
5		658.5600	30.12	-4.76	25.36	46.00	-20.64	QP		
6		830.2500	31.02	-3.24	27.78	46.00	-18.22	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11b TX CH11
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	32.9100	49.59	-13.82	35.77	40.00	-4.23	QP		
2	*	82.3800	54.80	-18.36	36.44	40.00	-3.56	QP		
3		207.5100	36.06	-15.64	20.42	43.50	-23.08	QP		
4		415.0900	29.50	-8.11	21.39	46.00	-24.61	QP		
5		520.8200	30.45	-6.28	24.17	46.00	-21.83	QP		
6		658.5600	30.76	-4.76	26.00	46.00	-20.00	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature:	24℃	Test Date:	February 13, 2015
Humidity:	53 %	Test By:	KING KONG
Test mode:	802.11b	Frequency:	Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9313.00	V	45.28	42.29	74.00	54.00	-28.72	-11.71
11506.00	V	45.59	42.16	74.00	54.00	-28.41	-11.84
15943.00	V	48.90	40.33	74.00	54.00	-25.10	-13.67
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
9636.00	H	48.39	42.39	74.00	54.00	-25.61	-11.61
13478.00	H	46.94	42.31	74.00	54.00	-27.06	-11.69
15110.00	H	47.59	41.08	74.00	54.00	-26.41	-12.92

Test mode:	802.11b	Frequency:	Channel 6: 2437MHz
------------	---------	------------	--------------------

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9619.00	V	48.79	42.38	74.00	54.00	-25.21	-11.62
12118.00	V	47.80	42.27	74.00	54.00	-26.20	-11.73
15977.00	V	49.63	41.08	74.00	54.00	-24.37	-12.92
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
9449.00	H	47.41	42.73	74.00	54.00	-26.59	-11.27
11591.00	H	47.28	42.35	74.00	54.00	-26.72	-11.65
14991.00	H	49.21	40.77	74.00	54.00	-24.79	-13.23

Test mode:	802.11b	Frequency:	Channel 11: 2462MHz
------------	---------	------------	---------------------


Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
9500.00	V	48.84	42.52	74.00	54.00	-25.16	-11.48
11200.00	V	48.60	42.31	74.00	54.00	-25.40	-11.69
13733.00	V	48.01	41.12	74.00	54.00	-25.99	-12.88
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
9653.00	H	49.41	42.67	74.00	54.00	-24.59	-11.33
12152.00	H	50.09	42.59	74.00	54.00	-23.91	-11.41
15705.00	H	49.40	40.94	74.00	54.00	-24.60	-13.06

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 24 C
Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
Mode:802.11b TX CH1
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2388.960	49.53	-8.27	41.26	74.00	-32.74	peak		
2	*	2388.960	35.07	-8.27	26.80	54.00	-27.20	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11b TX CH1
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2386.400	51.84	-8.29	43.55	74.00	-30.45	peak		
2	*	2386.400	34.99	-8.29	26.70	54.00	-27.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11b TX CH11
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2484.671	49.84	-7.89	41.95	74.00	-32.05	peak		
2	*	2484.671	34.39	-7.89	26.50	54.00	-27.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11b TX CH11
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2485.166	54.80	-7.88	46.92	74.00	-27.08	peak		
2		2485.166	34.38	-7.88	26.50	54.00	-27.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11g TX CH1
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2389.680	50.94	-8.27	42.67	74.00	-31.33	peak		
2	*	2389.680	34.17	-8.27	25.90	54.00	-28.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11g TX CH1
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2390.000	52.43	-8.27	44.16	74.00	-29.84	peak		
2	*	2390.000	34.97	-8.27	26.70	54.00	-27.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11g TX CH11
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2484.292	50.87	-7.89	42.98	74.00	-31.02	peak		
2	*	2484.292	32.69	-7.89	24.80	54.00	-29.20	AVG		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.517	51.80	-7.89	43.91	74.00	-30.09	peak		
2	*	2483.517	33.59	-7.89	25.70	54.00	-28.30	AVG		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2389.840	52.25	-8.27	43.98	74.00	-30.02			peak
2	*	2389.840	35.67	-8.27	27.40	54.00	-26.60			AVG

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11n HT20 TX CH1
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2389.920	55.49	-8.27	47.22	74.00	-26.78	peak		
2	*	2389.920	35.77	-8.27	27.50	54.00	-26.50	AVG		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.648	51.58	-7.89	43.69	74.00	-30.31			peak
2	*	2483.648	34.79	-7.89	26.90	54.00	-27.10			AVG

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	52.81	-7.89	44.92	74.00	-29.08	peak		
2	*	2483.500	36.29	-7.89	28.40	54.00	-25.60	AVG		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2388.800	51.16	-8.27	42.89	74.00	-31.11	peak		
2	*	2388.800	35.17	-8.27	26.90	54.00	-27.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11n HT40 TX CH3
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2386.080	53.55	-8.29	45.26	74.00	-28.74	peak		
2	*	2386.080	36.69	-8.29	28.40	54.00	-25.60	AVG		

*:Maximum data x:Over limit !:over margin


Operator: CSL



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.830	50.91	-7.89	43.02	74.00	-30.98	peak		
2	*	2483.830	34.39	-7.89	26.50	54.00	-27.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 Mode:802.11n HT40 TX CH9
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.550	52.65	-7.89	44.76	74.00	-29.24	peak		
2	*	2483.550	33.99	-7.89	26.10	54.00	-27.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: CSL

8.6 CONDUCTED EMISSION TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure


The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results


PASS.



Site Conduction #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 53 %
 Mode: ON
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1700	50.00	0.00	50.00	64.96	-14.96	QP	
2		0.1700	28.68	0.00	28.68	54.96	-26.28	AVG	
3		0.2100	45.83	0.00	45.83	63.21	-17.38	QP	
4		0.2100	26.72	0.00	26.72	53.21	-26.49	AVG	
5		0.2550	27.06	0.00	27.06	51.59	-24.53	AVG	
6		0.2550	42.00	0.00	42.00	61.59	-19.59	QP	
7		0.2950	43.05	0.00	43.05	60.38	-17.33	QP	
8		0.2950	26.14	0.00	26.14	50.38	-24.24	AVG	
9		0.4250	26.86	0.00	26.86	47.35	-20.49	AVG	
10		0.4250	40.37	0.00	40.37	57.35	-16.98	QP	
11		11.9500	45.23	0.00	45.23	60.00	-14.77	QP	
12	*	11.9500	36.41	0.00	36.41	50.00	-13.59	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XY



Site: Conduction #1

Phase: **N**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz


Humidity: 53 %

Mode: ON

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1800	45.99	0.00	45.99	64.49	-18.50	QP	
2		0.1800	22.71	0.00	22.71	54.49	-31.78	AVG	
3		0.2300	40.08	0.00	40.08	62.45	-22.37	QP	
4		0.2300	21.73	0.00	21.73	52.45	-30.72	AVG	
5		0.3050	37.99	0.00	37.99	60.11	-22.12	QP	
6		0.3050	22.08	0.00	22.08	50.11	-28.03	AVG	
7		0.3850	34.36	0.00	34.36	58.17	-23.81	QP	
8		0.3850	20.20	0.00	20.20	48.17	-27.97	AVG	
9	*	11.7250	47.03	0.00	47.03	60.00	-12.97	QP	
10		11.7250	36.39	0.00	36.39	50.00	-13.61	AVG	
11		18.9750	31.89	0.00	31.89	60.00	-28.11	QP	
12		18.9750	22.19	0.00	22.19	50.00	-27.81	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XY



Site Conduction #1

Phase: **L1**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 240V/50Hz


Humidity: 53 %

Mode: ON

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.1800	47.63	0.00	47.63	64.49	-16.86	QP	
2		0.1800	35.26	0.00	35.26	54.49	-19.23	AVG	
3		0.2250	44.96	0.00	44.96	62.63	-17.67	QP	
4		0.2250	33.56	0.00	33.56	52.63	-19.07	AVG	
5		0.2750	42.78	0.00	42.78	60.97	-18.19	QP	
6		0.2750	33.67	0.00	33.67	50.97	-17.30	AVG	
7		0.7250	41.09	0.00	41.09	56.00	-14.91	QP	
8		0.7250	26.41	0.00	26.41	46.00	-19.59	AVG	
9		3.9100	43.89	0.00	43.89	56.00	-12.11	QP	
10		3.9100	25.65	0.00	25.65	46.00	-20.35	AVG	
11		11.6500	45.70	0.00	45.70	60.00	-14.30	QP	
12	*	11.6500	39.55	0.00	39.55	50.00	-10.45	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XY



Site Conduction #1

Phase: **N**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 240V/50Hz

Humidity: 53 %

Mode: ON

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1800	46.43	0.00	46.43	64.49	-18.06	QP	
2		0.1800	27.45	0.00	27.45	54.49	-27.04	AVG	
3		0.2150	41.02	0.00	41.02	63.01	-21.99	QP	
4		0.2150	24.62	0.00	24.62	53.01	-28.39	AVG	
5		0.2701	36.65	0.00	36.65	61.11	-24.46	QP	
6		0.2701	25.70	0.00	25.70	51.11	-25.41	AVG	
7		0.4100	33.88	0.00	33.88	57.65	-23.77	QP	
8		0.4100	23.16	0.00	23.16	47.65	-24.49	AVG	
9		4.5950	41.07	0.00	41.07	56.00	-14.93	QP	
10		4.5950	28.20	0.00	28.20	46.00	-17.80	AVG	
11		11.6750	47.84	0.00	47.84	60.00	-12.16	QP	
12	*	11.6750	38.01	0.00	38.01	50.00	-11.99	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: XY

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

For intentional device, according to IC RSS-Gen 8.3, testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.9 When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

The EUT'S antenna is PIFA antenna, and the antenna can't be replaced by the user, which in accordance to section 15.203, please refer to the internal photos. The antenna's gain is 2dBi and meets the requirement.

8.7.2 Result

PASS.

END OF REPORT