



## **REGULATORY COMPLIANCE TEST REPORT**

**FCC CFR 47 Part 1.1310**

**Report No.: TAGG05-U3\_MPE Rev A**

**Company:** Taggle Systems Pty Ltd

**Model:** Parakeet

## MPE/RF EXPOSURE EVALUATION REPORT

**Company:** Taggle Systems Pty Ltd

**Model:** Parakeet

**Standard:** RSS-102 Issue 5

**Test Report Serial No.:** TAGG05-U3\_MPE Rev A

This report supersedes: NONE

**Applicant:** Taggle Systems Pty Ltd  
Level 1, 101 Sussex Street  
Sydney, New South Wales 2000  
Australia

**Issue Date:** 14<sup>th</sup> October 2019

**This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



TESTING CERT #2381.01

**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**

## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

Power Density =  $P_d$  (mW/cm<sup>2</sup>) =  $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

$P$  = Peak output power (mW)

$G$  = Antenna numeric gain (numeric)

$d$  = Separation distance (cm)

Numeric Gain =  $10^{(G \text{ (dBi)}/10)}$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

| Freq. Band (MHz) | Ant Gain (dBi) | Numeric Gain (numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm | Power Density Limit (mW/cm <sup>2</sup> ) | Min Calculated 20 cm distance (@ Limit) |
|------------------|----------------|------------------------|-------------------------|------------------------|-------------------------------------------------------|-------------------------------------------|-----------------------------------------|
| 902.0 - 928.0    | 0.00           | 1.00                   | 17.23                   | 52.84                  | 0.01                                                  | 0.61                                      | 2.63                                    |

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)