

|  |   |  |                    |   |                           |
|--|---|--|--------------------|---|---------------------------|
| Prüfbericht - Nr.:   | 14009192 003  |  | Seite 1 von 13     |   |                           |
| Test Report No.  |   |  |                    |   |                           |
| Auftraggeber:<br>Applicant   | <b>Sure Win Technologies Ltd.</b><br>Flat C & A, 17/F.<br>International Industry Centre<br>2-8 Kwei Tei Street, Fotan, N.T.<br>Hong Kong                          |  |                    |   |                           |
| Gegenstand der Prüfung:<br>Test item   | Low Power Transmitter   |  |                    |   |                           |
| Bezeichnung:<br>Identification   | DB-2133, DB-2132, DB-3133,<br>DB-3132, DB-3131, DB-2131   | Serien-Nr.:<br>Serial No.  | Engineering sample |   |                           |
| Wareneingangs-Nr.:   | 050518023-<br>050518024   | Eingangsdatum:<br>Date of receipt  | 18.05.2005         |   |                           |
| Prüfort:<br>Testing location   | <b>TÜV Rheinland Hong Kong Ltd.</b><br>Unit 8, 25 <sup>th</sup> Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay<br>Kowloon, Hong Kong                       |  |                    |   |                           |
|  | <b>Hong Kong Productivity Council</b><br>HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong  |  |                    |   |                           |
| Prüfgrundlage:<br>Test specification   | FCC Part 15, Subpart C  |  |                    |   |                           |
| Prüfergebnis:<br>Test Result   | <b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b><br>The above mentioned product was tested and <b>passed</b> . |  |                    |   |                           |
| geprüft / tested by:   | kontrolliert / reviewed by:   |  |                    |   |                           |
| 03.06.2005   | Hugo Wan  | <br>03.06.2005 Thomas Berns |                    |   |                           |
| Datum<br>Date  | Name<br>Name  | Unterschrift<br>Signature  | Datum<br>Date      | Name<br>Name  | Unterschrift<br>Signature |
| Sonstiges:<br>Other Aspects  | FCC ID S8ABDAFF   |  |                    |   |                           |
| Abkürzungen:<br>OK, Pass, P<br>Fail, F<br>N/A<br>NT  | = entspricht Prüfgrundlage<br>= entspricht nicht Prüfgrundlage<br>= nicht anwendbar<br>= nicht getestet   |  | Abbreviations:     | OK, Pass, P = passed<br>Fail, F = failed<br>N/A = not applicable<br>NT = not tested |                           |
| Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.<br>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products. |   |  |                    |   |                           |

## Test Summary

### Radiated Emission of Carrier Frequency

*Result: Pass*

### Spurious Radiated Emissions

*Result: Pass*

### Bandwidth Measurement

*Result: Pass*

## Contents

|  |                        |    |
|--|------------------------|----|
| <b>General Remarks .....</b>                         | <b>4</b>               |    |
| Complementary Materials.....                         | 4                      |    |
| <b>List of Test and Measurement Instruments.....</b> | <b>5</b>               |    |
| <b>General Product Information .....</b>             | <b>6</b>               |    |
| Product Function and Intended Use.....               | 6                      |    |
| Ratings and System Details .....                     | 6                      |    |
| Independent Operation Modes.....                     | 7                      |    |
| Submitted Documents .....                            | 7                      |    |
| Related Submittal(s) Grants .....                    | 7                      |    |
| <b>Test Set-up and Operation Mode.....</b>           | <b>8</b>               |    |
| Principle of Configuration Selection .....           | 8                      |    |
| Test Operation and Test Software .....               | 8                      |    |
| Special Accessories and Auxiliary Equipment .....    | 8                      |    |
| Countermeasures to achieve EMC Compliance.....       | 8                      |    |
| <b>Test Methodology .....</b>                        | <b>9</b>               |    |
| Radiated Emission .....                              | 9                      |    |
| Field Strength Calculation.....                      | 9                      |    |
| <b>Test Results .....</b>                            | <b>10</b>              |    |
| Radiated Emission of Carrier Frequency               | Section 15.231(b)..... | 10 |
| Spurious Radiated Emissions                          | Section 15.231(b)..... | 11 |
| Bandwidth Measurement                                | Section 15.231(c)..... | 13 |

## General Remarks

### Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix 1: Test Results

Appendix 2: Test Setup

Appendix 3: EUT External Photo

Appendix 4: EUT Internal Photo

Appendix 5: FCCID Label, Block Diagram, Schematics and User manual.

## List of Test and Measurement Instruments

| Kind of Equipment         | Manufacturer    | Type   | S/N          |
|---------------------------|-----------------|--------|--------------|
| Test Receiver             | Rohde & Schwarz | ESVS30 | 842807/009   |
| Biconical Antenna         | Rohde & Schwarz | HK116  | 841489/015   |
| Log.-Periodic Antenna     | Rohde & Schwarz | HL223  | 841516/017   |
| Double Ridge Horn Antenna | EMCO            | 3115   | 9002-3351    |
| Double Ridge Horn Antenna | EMCO            | 3115   | 9002-3347    |
| Signal Generator          | Rohde & Schwarz | SMY 01 | 844146/024   |
| Signal Generator          | Rohde & Schwarz | SMY 01 | 844146/023   |
| Spectrum Analyzer         | Rohde & Schwarz | FSP30  | 1093.4495K30 |

## General Product Information

### Product Function and Intended Use

The equipment under test (EUT) is a remote door chime transmitter operating at 315 MHz. The EUT transmits a signal to the corresponding receiver when the button is pressed.

The transmitter is operated manually. It ceases transmitting signal once the button is released. It was verified by an engineer and a data graph is attached in the Appendix 1 page 1 as a reference.

#### FCC ID S8ABDAFF

| Models   | Product description |
|--|---------------------|
| DB-2133, DB-2132,<br>DB-3133, DB-3132,<br>DB-3131, DB-2131 | Wireless Doorbell   |

Each model number mentioned above consists of one transmitter and one receiver. This test report and the FCCID are issued to the transmitter only. The transmitter is used with the receiver of models DB-2133, DB-2132, DB-3133, DB-3132, DB-3131 and DB-2131. Hence the difference between the six model numbers is only the receiver difference only.

### Ratings and System Details

|                    | Transmitter                            |
|--------------------|--|
| Operated Frequency | : 315 MHz                              |
| Number of channels | : 1                                    |
| Type of antenna    | : Integral antenna                     |
| Power supply       | : Battery operated 12.0V, type 23A X 1 |
| Ports              | : none                                 |
| Protection Class   | : III                                  |
| Equipment Class    | : B                                    |

## Independent Operation Modes

The basic operation modes are:

- Switch on the door bell by pressing a button.

For further information refer to User Manual

## Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- FCC ID label

## Related Submittal(s) Grants

This is a single application for certification of the transmitter.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

## Test Methodology

### Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in section 7.1.1 and 7.1.2 of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

$$\text{System Factor} = CF + FA - PA.$$

Where FS = Peak Value of Field Strength in dBuV/m at 3 meters.

R = Peak Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Average value of FS = FS - Average factor.

Average Factor =  $20 \log \text{duty cycle}$ .

## Test Results

### Radiated Emission of Carrier Frequency

### Section 15.231(b)

#### RESULT:

**Pass**

|                      |   |                                       |
|----------------------|---|---------------------------------------|
| Test Specification   | : | FCC Part 15 Section 15.231(b1 and b2) |
| Test Method          | : | ANSI 63.4-2003                        |
| Measurement Location | : | Semi Anechoic Chamber                 |
| Measurement Distance | : | 3m                                    |
| Detector Function    | : | Peak                                  |
| Measurement BW       | : | 100 kHz                               |
| Supply Voltage       | : | DC 12.0V                              |
| Channel under test   | : | ---                                   |

#### Polarization: Vertical

| Value   | Frequency<br>(MHz) | System Factor<br>(dB) | Measured Field strength at 3m (peak)<br>(dB $\mu$ V/m) | Average Factor<br>(dB) | Net Field strength at 3m<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Delta to Limit<br>(dB) |
|---------|--------------------|-----------------------|--|------------------------|--|-------------------------|------------------------|
| Peak    | 314.771            | 15.10                 | 63.00  | -                      | 63.00                                      | 95.60                   | -32.62                 |
| Average | 314.771            | 15.10                 | 63.00  | -3.53                  | 59.47                                      | 75.60                   | -16.13                 |

#### Polarization: Horizontal

| Value   | Frequency<br>(MHz) | System Factor<br>(dB) | Measured Field strength at 3m (peak)<br>(dB $\mu$ V/m) | Average Factor<br>(dB) | Net Field strength at 3m<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Delta to Limit<br>(dB) |
|---------|--------------------|-----------------------|--|------------------------|--|-------------------------|------------------------|
| Peak    | 314.824            | 15.10                 | 71.60  | -                      | 71.60                                      | 95.60                   | -24.00                 |
| Average | 314.824            | 15.10                 | 71.60  | -3.53                  | 68.07                                      | 75.60                   | -7.53                  |

Remark; The calculation of average factor is shown in appendix 1 page 4.

#### Limit

#### Section 15.231(b2)

| Frequency within the band<br>(MHz) | Peak Emission     |              | Average Emission  |              |
|------------------------------------|-------------------|--------------|-------------------|--------------|
|                                    | (microvolt/meter) | dB $\mu$ V/m | (microvolt/meter) | dB $\mu$ V/m |
| 315                                | 60,256            | 95.6         | 6,025             | 75.6         |

According to section 15.35(b), When average radiated emission measurements are specified, including emission measurement below 1000MHz, there also is limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated.

**Spurious Radiated Emissions****Section 15.231(b)****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.231(b1 and b3)  
 Test Method : ANSI 63.4-2003  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 Detector Function : Peak  
 Measurement BW : 100 kHz  
 Supply Voltage : DC 12.0V  
 Measuring Frequency Range : 30-4500MHz

Polarization: Vertical

| Frequency<br>(MHz) | Reading<br>(pk)<br>(dBuV/m) | Antenna<br>Factor<br>(dBuV/m) | System<br>Factor<br>(dB) | Field<br>strength<br>at 3m<br>(pk)<br>(dBuV/m) | Average<br>Factor<br>(dB) | Field<br>strength<br>at 3m<br>(av)<br>(dBuV/m) | Limit<br>at 3m<br>(dBuV/m) | Delta<br>to Limit<br>(dB) |
|--------------------|-----------------------------|-------------------------------|--------------------------|--|---------------------------|--|----------------------------|---------------------------|
| 629.563            | 17.20                       | 19.30                         | 2.10                     | 38.60  | -3.53                     | 35.07  | 55.62                      | -20.55                    |
| 944.391            | 9.20                        | 22.40                         | 2.70                     | 34.30  | -3.53                     | 30.77  | 55.62                      | -24.85                    |
| 1260.020           | 45.80                       | 25.40                         | -33.68                   | 37.52  | -3.53                     | 33.99  | 55.62                      | -21.63                    |
| *1575.030          | 45.84                       | 25.40                         | -33.68                   | 37.56  | -3.53                     | 34.03  | 54.00                      | -19.97                    |
| 1890.720           | 34.34                       | 27.60                         | -32.85                   | 29.09  | -3.53                     | 25.56  | 55.62                      | -30.06                    |
| *2205.290          | 31.91                       | 27.60                         | -32.85                   | 26.66  | -3.53                     | 23.13  | 54.00                      | -30.87                    |
| 2519.920           | 30.49                       | 28.60                         | -31.51                   | 27.58  | -3.53                     | 24.05  | 55.62                      | -31.57                    |
| *2835.550          | 29.57                       | 30.00                         | -29.73                   | 29.84  | -3.53                     | 26.31  | 54.00                      | -27.69                    |
| 314.990            | 34.29                       | 30.00                         | -29.73                   | 34.56  | -3.53                     | 31.03  | 55.62                      | -24.59                    |

Polarization: Horizontal

| Frequency<br>(MHz) | Reading<br>(pk)<br>(dBuV/m) | Antenna<br>Factor<br>(dBuV/m) | System<br>Factor<br>(dB) | Field<br>strength<br>at 3m<br>(pk)<br>(dBuV/m) | Average<br>Factor<br>(dB) | Field<br>strength<br>at 3m<br>(av)<br>(dBuV/m) | Limit<br>at 3m<br>(dBuV/m) | Delta<br>to Limit<br>(dB) |
|--------------------|-----------------------------|-------------------------------|--------------------------|--|---------------------------|--|----------------------------|---------------------------|
| 629.661            | 30.10                       | 19.30                         | 2.10                     | 51.50  | -3.53                     | 47.97  | 55.62                      | -7.65                     |
| 944.531            | 21.40                       | 22.40                         | 2.70                     | 46.50  | -3.53                     | 42.97  | 55.62                      | -12.65                    |
| 1260.100           | 46.43                       | 25.40                         | -33.68                   | 38.15  | -3.53                     | 34.62  | 55.62                      | -21                       |
| *1575.150          | 43.10                       | 25.40                         | -33.68                   | 51.38  | -3.53                     | 47.85  | 54.00                      | -6.15                     |
| 1890.040           | 38.87                       | 27.60                         | -32.85                   | 33.62  | -3.53                     | 30.09  | 55.62                      | -25.53                    |
| *2205.630          | 32.68                       | 27.60                         | -32.85                   | 27.43  | -3.53                     | 23.9   | 54.00                      | -30.1                     |
| 2520.320           | 32.83                       | 28.60                         | -31.51                   | 29.92  | -3.53                     | 26.39  | 55.62                      | -29.23                    |
| *2835.510          | 32.29                       | 30.00                         | -29.73                   | 32.56  | -3.53                     | 29.03  | 54.00                      | -24.97                    |
| 3149.860           | 34.12                       | 30.00                         | -29.73                   | 34.39  | -3.53                     | 30.86  | 55.62                      | -24.76                    |

Remark: '\*' indicates the frequency of the emissions fall into the restricted band.

#### Limit

#### Section 15.231(b3)

| Fundamental<br>Frequency<br>(MHz) | Field strength of<br>spurious emission<br>(microvolt/meter) | Field strength of<br>spurious emission<br>(dB $\mu$ V/m) | Measurement distance<br>(meters) |
|-----------------------------------|---|--|----------------------------------|
| 260-470                           | 604   | 20*log(604) = 55.62                                      | 3                                |

#### Section 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

#### Limit for Radiated Emission under Section 15.209:

| Frequency (MHz) | Field strength<br>(microvolt/meter) | Field strength<br>(dBuV/m) | Measurement distance<br>(meters) |
|-----------------|-------------------------------------|----------------------------|----------------------------------|
| 30-88           | 100                                 | 20*log(100) = 40.0         | 3                                |
| 88-216          | 150                                 | 20*log(150) = 43.5         | 3                                |
| 216-960         | 200                                 | 20*log(200) = 46.0         | 3                                |
| 960-2500        | 500                                 | 20*log(500) = 54.0         | 3                                |

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

**Bandwidth Measurement****Section 15.231(c)****RESULT:****Pass**

Test Specification : FCC Part 15 section 15.231(c)  
Port of Testing : Antenna port  
Detector Function : Peak  
Supply Voltage : DC 12.0V

Refer to the data graph, the 20dB points at lower edge and at higher edge are 13.2kHz and 18.8kHz respectively apart from the centre modulated carrier, the bandwidth of the emission is 0.010 % of the centre frequency. Therefore, the EUT meets the requirement of section 15.231(c).

For test results refer to Appendix 1, page 1.

**Limit****Section 15.231(c)**

The bandwidth of the emission shall be no wider than 0.25% if the center frequency for devices operating above 70MHz and below 900MHz.