

Report No.14016428 001

Appendix 10


Use Manual

Manual of Wireless Transmitter

AM6003


Replacing battery:

- Please open the cabinet at the location of arrow with screwdriver. Then, follow the diagram to insert the A23 alkaline battery with positive side on the top.




Code Setting

- The code is set by manufacture, and there are combinations of codes up to 256. In order to avoid the interference, you can set the code by adding or removing jumpers of the alarm. Please make sure that the code setting of the transmitter must match with that of the receiver.
Eg. If the code of the receiver is 6,7,8; the code of the transmitter must also be 6,7,8. If the interference continues, please re-set the code and do the same procedure for both transmitter and receiver.




Mounting on the window

- Please remove the back of the case by pushing in the tab on the bottom by screwdrivers. Mount the back of the case on the wall and snap the front case back on. In case of using double side tapes, please ensure the wall is dry and clean.



Aligning the position for alarm and magnet

- Ensure that the arrow sign on the alarm must be opposite to the arrow on the magnet.



Warning: Changes or modifications not expressly approved by the party responsible for compliance would void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and , if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encourage to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.**
- Increase the separation between the equipment and receiver.**
- Connect the equipment into an outlet on a circuit different from that to which the receiver is needed.**
- Consult the dealer or an experienced radio/TV technician for help.**