

MAXIMUM PERMISSIBLE EXPOSURE EVALUATION REPORT

Applicant: Sinocastel Co., Ltd.

Address: 501, Building 11, Shenzhen Software Park (Phase 2), NO.1,
Kejizhong 2 Road, Gaoxin Middle District, Nanshan District,
Shenzhen, China

Product Name: Asset GPS Tracker

FCC ID: S8U-T-235M

Standard(s): 47 CFR §1.1310, 47 CFR §2.1091,
47 CFR §15.247(i)

Report Number: 2502T59407E-RF-00C

Report Date: 2025/7/22

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Reviewed By: Alice Tan
Title: RF Engineer

Pedro Yun

Approved By: Pedro Yun
Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	3
1. GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST.....	4
2.RF EXPOSURE EVALUATION (MPE).....	5
2.1. RF EXPOSURE EVALUATION.....	5
2.1.1 Applicable Standard.....	5
2.1.2 Calculation formula	5
2.1.3 Calculated Data:.....	6
EXHIBIT A - EUT PHOTOGRAPHS.....	7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502T59407E-RF-00C	Original Report	2025/7/22

1. GENERAL INFORMATION

1.1 General Description Of Equipment under Test

EUT Name:	Asset GPS Tracker
EUT Model:	T-235M
Rated Input Voltage:	9-36Vdc
EUT Received Date:	2025/5/16
EUT Received Status:	Good

Output Power And Antenna Gain Information:

Operation Modes	Frequency (MHz)	Antenna Gain [▲] (dBi)	Conducted output power including Tune-up Tolerance [▲] (dBm)	EIRP/ERP (dBm)	Limit (dBm)
GSM 850	824.2-848.8	-1.00	30.35	27.2	38.45
GSM 1900	1850.2-1909.8	-0.14	31.00	30.86	33.0
CAT-M LTE B2	1850.7-1909.3	-0.14	24.00	23.86	33.0
CAT-M LTE B4	1710.7-1754.3	1.54	24.00	25.54	30.0
CAT-M LTE B12	699.7-715.3	-3.99	25.00	18.86	44.77
CAT-M LTE B13	779.5-784.5	-1.45	24.00	20.4	44.77
CAT-M LTE B25	1850.7-1914.3	-0.14	24.00	23.86	33.0
CAT-M LTE B26	814.7-823.3	-1.00	25.00	21.85	50.0
CAT-M LTE B26	824.7-848.3	-1.00	25.00	21.85	38.45
NB-IOT LTE B2	1850.7-1909.3	-0.14	22.00	21.86	33.0
NB-IOT LTE B4	1710.7-1754.3	1.54	22.00	23.54	30.0
NB-IOT LTE B5	824.7-848.3	-1.00	24.00	20.85	38.45
NB-IOT LTE B12	699.7-715.3	-3.99	23.00	16.86	44.77
NB-IOT LTE B13	779.5-784.5	-1.45	22.00	18.4	44.77
NB-IOT LTE B71	663.7-697.3	-7.03	24.00	14.82	34.77

Note: ERP is for operation below 1 GHz and EIRP for above 1 GHz.

2.RF EXPOSURE EVALUATION (MPE)

2.1. RF Exposure Evaluation

2.1.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

2.1.2 Calculation formula

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

2.1.3 Calculated Data:

Operation Modes	Frequency (MHz)	Antenna Gain [▲]		Conducted output power including Tune-up Tolerance [▲]		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	1.83	1.52	-6.0	0.25	20.00	0.0001	1.0
GSM 850	824.2-848.8	-1.00	0.79	30.35	1083.93	20.00	0.171	0.55
GSM 1900	1850.2-1909.8	-0.14	0.97	31.00	1258.93	20.00	0.243	1.0
CAT-M LTE B2	1850.7-1909.3	-0.14	0.97	24.00	251.19	20.00	0.048	1.0
CAT-M LTE B4	1710.7-1754.3	1.54	1.43	24.00	251.19	20.00	0.071	1.0
CAT-M LTE B12	699.7-715.3	-3.99	0.40	25.00	316.23	20.00	0.025	0.47
CAT-M LTE B13	779.5-784.5	-1.45	0.72	24.00	251.19	20.00	0.036	0.52
CAT-M LTE B25	1850.7-1914.3	-0.14	0.97	24.00	251.19	20.00	0.048	1.0
CAT-M LTE B26	814.7-823.3	-1.00	0.79	25.00	316.23	20.00	0.050	0.54
CAT-M LTE B26	824.7-848.3	-1.00	0.79	25.00	316.23	20.00	0.050	0.55
NB-IOT LTE B2	1850.7-1909.3	-0.14	0.97	22.00	158.49	20.00	0.031	1.0
NB-IOT LTE B4	1710.7-1754.3	1.54	1.43	22.00	158.49	20.00	0.045	1.0
NB-IOT LTE B5	824.7-848.3	-1.00	0.79	24.00	251.19	20.00	0.040	0.55
NB-IOT LTE B12	699.7-715.3	-3.99	0.40	23.00	199.53	20.00	0.016	0.47
NB-IOT LTE B13	779.5-784.5	-1.45	0.72	22.00	158.49	20.00	0.023	0.52
NB-IOT LTE B71	663.7-697.3	-7.03	0.20	24.00	251.19	20.00	0.010	0.44
Note: The device contains a certified WWAN module, FCC ID:2AJYU-8VC0001, certified on 02/17/2020								

Note:

The Conducted output power including Tune-up Tolerance provided by manufacturer.

Simultaneous transmission:

BLE can transmit simultaneously with WWAN:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$S_{BLE}/S_{limit-BLE} + S_{WWAN}/S_{limit-WWAN}$$

$$= 0.0001/1.0 + 0.171/0.55$$

$$= 0.31$$

$$< 1.0$$

Result: Compliant. The device compliant Simultaneous transmission at 20cm distances.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2502T59407E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2502T59407E-RF-INP EUT INTERNAL PHOTOGRAPHS.

******* END OF REPORT *******