



RF Exposure Evaluation Report

Equipment : WAM2
Brand Name : Whistle
Model No. : AM2A
FCC ID : S8W-AM2A
Standard : 47 CFR Part 2.1091
Applicant / : Whistle Labs, Inc
Manufacturer : 1355 Market Street Suite 210 San Francisco,
CA 94103, USA

The product sample received on Aug. 16, 2017 and completely tested on Oct. 11, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Kevin Liang/ Assistant Manager
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

1	GENERAL DESCRIPTION	4
1.1	EUT General Information	4
1.2	Testing Location	4
2	MAXIMUM PERMISSIBLE EXPOSURE	5
2.1	Limit of Maximum Permissible Exposure	5
2.2	MPE Calculation Method	5
2.3	Calculated Result and Limit.....	6
PHOTOGRAPHS OF EUT V01		

REVISION HISTORY

[illegible]

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.2 Testing Location

Testing Location			
☒	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
☐	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D	-2.05	16.50	14.45	0.02786	20	0.00554	1.00000
2.4G;D1D	-2.05	14.90	12.85	0.01928	20	0.00384	1.00000
2.4G;BT-LE	-2.05	-0.89	-2.94	0.00051	20	0.00010	1.00000