

Prüfbericht-Nr.: Test report no.:	CN24IPWU 004	Auftrags-Nr.: Order no.:	168477868	Seite 1 von 10 Page 1 of 10
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2024-01-05	
Auftraggeber: Client:	Xiamen Intretech Inc. No. 100, Dongfu West Road, Haicang District, Xiamen, Fujian, China			
Prüfgegenstand: Test item:	M4GM			
Bezeichnung / Typ-Nr.: Identification / Type no.:	M4GM-GL-01 (Trademark: )			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR47 FCC Part 2.1091 RSS-102 Issue 5 February 2021			
Wareneingangsdatum: Date of sample receipt:	2024-04-02	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A003680014-001~014			
Prüfzeitraum: Testing period:	2024-04-10 - 2024-05-13			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2024-06-10	Ausstellungsdatum: Issue date:		2024-06-10
Signed by: Jonathan Li		Signed by: Bell Hu		
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: S96M4GMG			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

Prüfbericht-Nr.: CN24IPWU 004
Test report no.:

Seite 2 von 10
Page 2 of 10

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN24IPWU 004
Test Report No.:

Seite 3 von 10
Page 3 of 10

TEST SUMMARY

3.1.1 RF EXPOSURE COMPLIANCE

RESULT: Pass

Prüfbericht - Nr.: CN24IPWU 004

Test Report No.:

Seite 4 von 10

Page 4 of 10

CONTENTS

1.	TEST SITES.....	5
1.1	TEST FACILITIES	5
1.2	TRACEABILITY	5
1.3	CALIBRATION.....	5
1.4	LOCATION OF ORIGINAL DATA	5
1.5	STATUS OF FACILITY USED FOR TESTING	5
2.	GENERAL PRODUCT INFORMATION	6
2.1	GENERAL DESCRIPTION	6
2.2	RATING AND SYSTEM DETAILS	6
3.	TEST RESULTS	8
3.1	TRANSMITTER REQUIREMENTS & TEST SUITES.....	8
3.1.1	RF Exposure Compliance.....	8
3.1.1.1	FCC Part 1.1310, Part 2.1091	9

1. TEST SITES

1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China.

FCC Accreditation Designation No.: CN1260

ISED Wireless Device Testing Laboratory: 25069

1.2 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.3 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.4 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.5 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China. is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. GENERAL PRODUCT INFORMATION

2.1 GENERAL DESCRIPTION

The EUT is wireless module which supports GPRS/EGPRS, LTE-CAT1 wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 RATING AND SYSTEM DETAILS

Table 1: Technical Specification of EUT

General Information of EUT	Value
Product Name:	M4GM
Test Model No.:	M4GM-GL-01
Trademark:	
FCC ID:	S96M4GMG
Operating Voltage:	DC 8V~30V
Testing Voltage:	DC 24V
Operation Temperature:	0°C to +60°C
Technical Specification of GPRS, EGPRS	
Operated Modes:	GPRS, EGPRS
Operational Frequency Band(s):	GSM 850, PCS 1900
Nominal RF Output Power:	GSM 850: 33 dBm $\pm$ 2dB PCS 1900: 30 dBm $\pm$ 2dB
Power Class:	GSM 850: Class 4 PCS 1900: Class 1
Modulation Type:	GMSK(GPRS/EGPRS), 8PSK(EGPRS)
Antenna Type:	External Antenna
Max Antenna Gain:	3.4 dBi for 1900 band 5.4 dBi for 850 band
Technical Specification of WCDMA	
Operational Frequency:	Band 2, Band 4, Band 5
Type of Modulation:	BPSK/QPSK/16QAM
Antenna Type:	External Antenna
Antenna Number:	1
Max Antenna Gain:	3.4 dBi for WCDMA Band 2 2.8 dBi for WCDMA Band 4 5.4 dBi for WCDMA Band 5 (Provided by the Client)
Technical Specification of LTE	
Operational Frequency:	Band 2, Band 4, Band 12, Band13, Band 25, Band26, Band 41, Band 66

Prüfbericht - Nr.: CN24IPWU 004
Test Report No.:**Seite 7 von 10**
Page 7 of 10

Type of Modulation:	QPSK, 16QAM
Power Class:	Class 3
TX and RX Antenna Ports:	1 * TRX, 1 * RX-only
Device Category:	CAT1
Antenna Type:	External Antenna
Antenna Number:	1
Max Antenna Gain:	3.4 dBi for LTE Band 2 2.8 dBi for LTE Band 4 5.4 dBi for LTE Band 5 4.5 dBi for LTE Band 12 4.6 dBi for LTE Band 13 3.1 dBi for LTE Band 25 5.1 dBi for LTE Band 26 5.1 dBi for LTE Band 41 2.9 dBi for LTE Band 66 (Provided by the Client)

3. Test Results

3.1 Transmitter Requirements & Test Suites

3.1.1 RF Exposure Compliance

RESULT:**Pass**

Test standard : 47 CFR FCC Part 2.1091

Limit : Table 1 of 47 CFR FCC Part 1.1310

Kind of test site : Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modeling should be used to determine compliance.

Radio Frequency Exposure Calculation Formula:

MPE Calculation is based on the conducted power and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$Pd = \frac{P_{out} * G}{4R^2\pi}$$

Where,

 P_d = power density in mW/cm² or W/m² P_{out} = output power to antenna in mW or W G_{num} = Antenna gain in numeric π = 3.14159

R = Distance between observation point and the center of radiator in cm or m

3.1.1.1 FCC Part 1.1310, Part 2.1091

Radio Frequency Exposure of FCC Limit

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Table 2: RF Exposure Calculations for FCC, stand-alone mode

Operating Mode	Maximum Conducted Output Power		Antenna Gain (dBi)	Max. E.R.P./E.I.R.P. (dBm)	Min. Distance (cm)	Calculation (mW/cm ²)	FCC Limit (mW/cm ²)	Result
	Measured Power (dBm)	Max. Power incl. tune-up (dBm)						
WCDMA band 2	23.01	25	3.4	28.4	20	0.1199	1.000	PASS
WCDMA band 4	23.81	25	2.8	27.8	20	0.2182	1.000	PASS
WCDMA band 5	23.09	25	5.4	30.4	20	0.1377	0.549	PASS
LTE band 2	23.49	25	3.4	28.4	20	0.1199	1.000	PASS
LTE band 4	23.12	25	2.8	27.8	20	0.2182	1.000	PASS
LTE band 5	22.96	25	5.4	30.4	20	0.1774	0.549	PASS
LTE band 12	22.95	25	4.5	29.5	20	0.1815	0.466	PASS
LTE band 13	21.98	25	4.6	29.6	20	0.1285	0.518	PASS
LTE band 25	22.94	25	3.1	28.1	20	0.2037	1.000	PASS
LTE band 26	23.50	25	5.1	30.1	20	0.2037	0.543	PASS
LTE band 41	23.71	25	5.1	30.1	20	0.1227	1.000	PASS
LTE band 66	22.97	25	2.9	27.9	20	0.1199	1.000	PASS

Operating Mode	Band	Maximum Conducted Output Power		Division factors (dB)	Antenna Gain (dBi)	Max. time-averaged E.R.P./ E.I.R.P. (dBm)	Min. Distance (cm)	Calculation (mW/cm ²)	FCC Limit (mW/cm ²)	Result
		Measured Power (dBm)	Max. Power incl. tune-up (dBm)							
GPRS	850(1slot)	32.39	35	-9.03	5.4	31.37	20	0.2729	0.549	PASS
	850(2slots)	30.02	32	-6.02	5.4	31.38	20	0.2734	0.549	PASS
	850(3slots)	28.8	30	-4.26	5.4	31.14	20	0.2587	0.549	PASS
	850(4slots)	27.66	29	-3.01	5.4	31.39	20	0.2740	0.549	PASS
	1900(1slot)	29.24	32	-9.03	3.4	26.37	20	0.0862	1.000	PASS
	1900(2slots)	28.16	30	-6.02	3.4	27.38	20	0.1088	1.000	PASS
	1900(3slots)	26.62	29	-4.26	3.4	28.14	20	0.1296	1.000	PASS
	1900(4slots)	25.36	28	-3.01	3.4	28.39	20	0.1373	1.000	PASS
EGPRS	850(1slot)	29.72	35	-9.03	5.4	31.37	20	0.2729	0.549	PASS
	850(2slots)	28.49	32	-6.02	5.4	31.38	20	0.2734	0.549	PASS
	850(3slots)	26.91	30	-4.26	5.4	31.14	20	0.2587	0.549	PASS
	850(4slots)	25.66	29	-3.01	5.4	31.39	20	0.2740	0.549	PASS
	1900(1slot)	29.23	32	-9.03	3.4	26.37	20	0.0862	1.000	PASS
	1900(2slots)	28.61	30	-6.02	3.4	27.38	20	0.1088	1.000	PASS
	1900(3slots)	27.4	29	-4.26	3.4	28.14	20	0.1296	1.000	PASS
	1900(4slots)	26.13	28	-3.01	3.4	28.39	20	0.1373	1.000	PASS

Note: Division factors, 1Tx slot = 1 transmit time slot out of 8 time slots= -9.03dB; 2Tx slots = 2 transmit time slots out of 8 time slots= -6.02dB; 3Tx slots = 3 transmit time slots out of 8 time slots= -4.26dB; 4Tx slots = 4 transmit time slots out of 8 time slots= -3.01dB

Note1: The GPRS/EGPRSWCDMA and LTE modes cannot transmit simultaneously.

➤ **Conclusion**

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.