

Prüfbericht-Nr.: Test report no.:	CN24IPWU 001	Auftrags-Nr.: Order no.:	168477868	Seite 1 von 24 Page 1 of 24
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2024-01-05	
Auftraggeber: Client:	Xiamen Intretech Inc. No. 100, Dongfu West Road, Haicang District, Xiamen, Fujian, China			
Prüfgegenstand: Test item:	M4GM			
Bezeichnung / Typ-Nr.: Identification / Type no.:	M4GM-GL-01 (Trademark:  SDATAWAY)			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2 KDB 971168 D01 ANSI C63.26			
Wareneingangsdatum: Date of sample receipt:	2024-04-02	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A003680014-001~014			
Prüfzeitraum: Testing period:	2024-04-10 - 2024-05-13			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	 Jonat han Li		genehmigt von: authorized by:	 Bell Hu
Datum: Date:	2024-06-10		Ausstellungsdatum: Issue date:	2024-06-10
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: S96M4GMG			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN24IPWU 001
Test report no.:

Seite 2 von 24
Page 2 of 24

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Test Summary

5.1.1. RF POWER OUTPUT

RESULT: Pass

5.1.2. MODULATION CHARACTERISTICS

RESULT: Pass

5.1.3. OCCUPIED BANDWIDTH AND 26dB BANDWIDTH

RESULT: Pass

5.1.4. SPURIOUS EMISSIONS AT ANTENNA TERMINALS

RESULT: Pass

5.1.5. SPURIOUS EMISSIONS AT ANTENNA TERMINALS – BAND EDGE

RESULT: Pass

5.1.6. FIELD STRENGTH OF SPURIOUS RADIATION

RESULT: Pass

5.1.7. FREQUENCY STABILITY

RESULT: Pass

5.1.8. PEAK TO AVERAGE RATIO

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
1.2	TEST STANDARD(S)	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	8
2.7	STATUS OF FACILITY USED FOR TESTING.....	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	11
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	11
3.5	SUBMITTED DOCUMENTS.....	11
4	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE.....	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	13
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	13
4.5	TEST SETUP DIAGRAM	14
5.	TEST RESULTS	16
5.1.	ESSENTIAL REQUIREMENTS OF STANDARD	16
5.1.1.	RF POWER OUTPUT	16
5.1.2.	MODULATION CHARACTERISTICS.....	17
5.1.3.	OCCUPIED BANDWIDTH AND 26dB BANDWIDTH	18
5.1.4.	SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	19
5.1.5.	SPURIOUS EMISSIONS AT ANTENNA TERMINALS – BAND EDGE	20
5.1.6.	FIELD STRENGTH OF SPURIOUS RADIATION.....	21
5.1.7.	FREQUENCY STABILITY.....	22
5.1.8.	PEAK TO AVERAGE RATIO.....	23
6.	SYSTEM MEASUREMENT UNCERTAINTY	24
7.	LIST OF TABLES.....	24

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results for LTE operation Band 2

Appendix B: Test Results for LTE operation Band 4

Appendix C: Test Results for LTE operation Band 5

Appendix D: Test Results for LTE operation Band 12

Appendix E: Test Results for LTE operation Band 13

Appendix F: Test Results for LTE operation Band 25

Appendix G: Test Results for LTE operation Band 26L

Appendix H: Test Results for LTE operation Band 26U

Appendix I: Test Results for LTE operation Band 41

Appendix J: Test Results for LTE operation Band 66

Appendix K Test Results of Field Strength of Spurious Radiation

Appendix L: Photographs of the Test Set-Up

1.2 Test Standard(s)

Applied Rules:	Error! Reference source not found. Error! Reference source not found. Error! Reference source not found. Error! Reference source not found. Error! Reference source not found.
Test Method:	KDB 971168 D01 ANSI C63.26

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China.

FCC Accreditation Designation No.: CN1260

ISED Wireless Device Testing Laboratory: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (CTE6000)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Shielding Room 6#	Albatross	SR6	APC17151-SR6	2021-06-22	2024-06-22
Wideband Radio Communication Tester	R&S	CMW500	166305	2023-07-25	2024-07-25
Signal Analyzer	R&S	FSV 40	101475	2023-07-25	2024-07-25
Vector Signal Generator	R&S	SMBV100A	263466	2023-09-21	2024-09-21
Signal Generator	R&S	SMB100A	181041	2023-11-06	2024-11-05
High Speed Power Supply	KEITHLEY	2303	4080052	2023-11-06	2024-11-05
RF Control Unit	Tonscend	JS0806-1	19H8060192	N/A	N/A
Band Reject Filter Group	Tonscend	JS0806-F	19I8060194	2023-11-14	2025-11-13
Radio Spectrum Testing (LRD2)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Shielding Room 6#	Albatross	SR6	APC17151-SR6	2021-06-22	2024-06-22
Signal Analyzer	R&S	FSV 40	101475	2023-07-25	2024-07-25
Signal and spectrum analyzer	Rohde & Schwarz	FSV3030	101576	2023-11-06	2024-11-05
Vector signal generator	Rohde & Schwarz	SMBV100B	102642	2023-11-06	2024-11-05
Vector signal generator	Rohde & Schwarz	SMB100A	182690	2023-11-06	2024-11-05
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	170345	2023-11-06	2024-11-05
1 channel power supply	Rohde & Schwarz	HMC8041	101712	2023-11-06	2024-11-05
Band Reject Filter	Tonscend	JS0806-F	21I8060483	2023-11-14	2025-11-13

Group					
RF Control Unit	Tonscend	JS0806-1	21H8060472	N/A	N/A
Test Software	Tonscend	JS1120	N/A	N/A	N/A
Control PC	Lenovo	TianYi510S-07IMB	2018AP3073	N/A	N/A
Unwanted Emission Testing (TS8996)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2023-07-26	2024-07-25
Signal Analyzer	R&S	FSV 40	101439	2023-07-26	2024-07-25
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2023-07-26	2024-07-25
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2023-07-26	2024-07-25
Amplifier	R&S	SCU-18F	180070	2023-07-26	2024-07-25
Amplifier	R&S	SCU40A	100475	2023-07-26	2024-07-25
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2022-08-07	2024-08-06
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2022-08-07	2024-08-06
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2022-08-28	2024-08-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2022-08-07	2024-08-06
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2021-06-22	2024-06-22

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	±4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A to Appemdox L of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. File for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China. is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a 4G module, which support EDGE, WCDMA and LTE wireless technologies.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Product Name:	M4GM
Test Model No.:	M4GM-GL-01
Trademark:	
FCC ID:	S96M4GMG
Operating Voltage:	DC 8V~30V
Testing Voltage:	DC 24V
Operation Temperature:	0°C to +60°C
Technical Specification of LTE	
Operational Frequency:	Band 2, Band 4, Band 12, Band13, Band 25, Band26, Band 41, Band 66
Type of Modulation:	QPSK, 16QAM
Power Class:	Class 3
TX and RX Antenna Ports:	1 * TRX, 1 * RX-only
Device Category:	CAT1
Antenna Type:	External Antenna
Antenna Number:	1
Max Antenna Gain:	3.4 dBi for LTE Band 2 2.8 dBi for LTE Band 4 5.4 dBi for LTE Band 5 4.5 dBi for LTE Band 12 4.6 dBi for LTE Band 13 3.1 dBi for LTE Band 25 5.1 dBi for LTE Band 26 5.1 dBi for LTE Band 41 2.9 dBi for LTE Band 66 (Provided by the Client)

Prüfbericht - Nr.: CN24IPWU 001
Test Report No.:

Seite 10 von 24
 Page 10 of 24

Table 4: Operating Frequency Range of EUT

Frequency Band(s)	Frequency Range		Channel Bandwidth (MHz)
	Transmitting f_{UL} (MHz)	Receiving f_{DL} (MHz)	
Band 2	1850 ~ 1910	1930 ~ 1990	1.4, 3, 5, 10, 15, 20
Band 4	1710 ~ 1755	2110 ~ 2155	1.4, 3, 5, 10, 15, 20
Band 5	824 ~ 849	869 ~ 894	1.4, 3, 5, 10
Band 12	699 ~ 716	729 ~ 746	1.4, 3, 5, 10
Band 13	777 ~ 787	746 ~ 756	5, 10
Band 25	1850 ~ 1915	1930 ~ 1995	1.4, 3, 5, 10, 15, 20
Band 26	814 ~ 849	859 ~ 894	1.4, 3, 5, 10, 15
Band 41	2496 ~ 2690	2496 ~ 2690	5, 10, 15, 20
Band 66	1710 ~ 1780	2110 ~ 2200	1.4, 3, 5, 10, 15, 20

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, communication link established, Transmitting
 - 1) LTE operating
 - i. Low channel
 - ii. Middle channel
 - iii. High channel
- B. On, communication link established, Receiving
 - 1) LTE operating
- C. Idle
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|------------------------------|-------------------------|
| - Application Form | - Operation Description |
| - ID Label and Location Info | - Block Diagram |
| - Schematics | - PCB Layout |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in KDB 971168 D01 and ANSI C63.26.

According to clause 3.1, all tests were performed on model M4GM-GL-01 in this report.

Table 5: List of Frequencies under Test

Operation bands	Mode	Frequencies under Test					
		Uplink			Downlink		
		Range	EARFCN	Frequencies (MHz)	Range	EARFCN	Frequencies (MHz)
2	Standalone	Low	18601	1850.1000	Low	601	1930.1000
		Mid	18900	1880.0000	Mid	900	1960.0000
		High	19199	1909.9000	High	1199	1989.9000
4	Standalone	Low	19951	1710.1000	Low	1951	2110.1000
		Mid	20175	1732.5000	Mid	2175	2132.5000
		High	20399	1754.9000	High	2399	2154.9000
5	Standalone	Low	20401	824.1000	Low	2401	869.1000
		Mid	20525	836.5000	Mid	2525	881.5000
		High	20649	848.9000	High	2649	893.9000
12	Standalone	Low	23011	699.1000	Low	5011	729.1000
		Mid	23095	707.5000	Mid	5095	737.5000
		High	23179	715.9000	High	5179	745.9000
13	Standalone	Low	23181	777.1000	Low	5181	746.1000
		Mid	23230	782.0000	Mid	5230	751.0000
		High	23279	786.9000	High	5279	755.9000
25	Standalone	Low	26041	1850.1000	Low	8041	1930.1000
		Mid	26365	1882.5000	Mid	8365	1962.5000
		High	26689	1914.9000	High	8689	1994.9000
26_Lower Band (814-824 MHz)	Standalone	Low	26691	814.1000	Low	8691	859.1000
		Mid	26740	819.0000	Mid	8740	864.0000
		High	26789	823.9000	High	8789	868.9000
26_Upper Band (824-	Standalone	Low	26791	824.1000	Low	8791	869.1000
		Mid	26915	836.5000	Mid	8915	881.5000

849 MHz)		High	27039	848.9000	High	9039	893.9000
41	Standalone	Low	39675	2498.500	Low	39675	2498.500
		Mid	40620	2593.000	Mid	40620	2593.000
		High	41565	2687.500	High	41565	2687.500
66	Standalone	Low	131973	1710.1000	Low	66437	2110.1000
		Mid	132322	1745.0000	Mid	66786	2145.0000
		High	132671	1779.9000	High	67135	2179.9000

Table 6: Test Environments

Environment Parameter	Values During Tests			
	Temperature	Voltage (Radio Module)	Voltage (EUT)	Relative Humidity
NTNV	25°C±2°C	3.3Vdc	24Vdc	Ambient
LTLV	0 °C	3.0Vdc	---	---
LTHV	0 °C	3.6Vdc	---	---
HTLV	+60 °C	3.0Vdc	---	---
HTHV	+60 °C	3.6Vdc	---	---

Table 7: Test Configurations

Frequency Bands	Bandwidths (MHz)						Modulation	
	1.4	3	5	10	15	20	QPSK	16QAM
2	Δ	Δ	Δ	Δ	Δ	Δ	Δ	Δ
4	Δ	Δ	Δ	Δ	Δ	Δ	Δ	Δ
5	Δ	Δ	Δ	Δ	-	-	Δ	Δ
12	Δ	Δ	Δ	Δ	-	-	Δ	Δ
13	-	-	Δ	Δ	-	-	Δ	Δ
25	Δ	Δ	Δ	Δ	Δ	Δ	Δ	Δ
26	Δ	Δ	Δ	Δ	Δ	-	Δ	Δ
41	-	-	Δ	Δ	Δ	Δ	Δ	Δ
66	Δ	Δ	Δ	Δ	Δ	Δ	Δ	Δ

4.3 Special Accessories and Auxiliary Equipment

Table 8: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	N/A	IVP0330-2000	N/A	DC 3.3V, 2.0A
Adapter	N/A	IVP2400-2000	N/A	DC 24V, 2.0A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5. TEST RESULTS

5.1. ESSENTIAL REQUIREMENTS OF STANDARD

5.1.1. RF POWER OUTPUT

RESULT:

Pass

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2
Limits	:	Operating band FCC Limit Band 2 EIRP 2 watts Band 4 EIRP 1 watts Band 5 ERP 7 watts Band 12 ERP 3 watts Band 13 ERP 3 watts Band 25 EIRP 2 watts Band 26 Lower Band ERP 100 watts Band 26 Upper Band ERP 7 watts Band 41 ERP 3 watts Band 66 EIRP 1 watts
Test procedure	:	Clause 5.2.4.2 of ANSI C63.26
Kind of test site	:	Shielding Room

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☐ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	23 °C
Relative humidity	:	50%
Atmospheric pressure	:	101.0 kPa
ERP or EIRP = $P_{\text{Meas}} + G_T$		

where

ERP or EIRP: effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g. dBm) P_{Meas} : measured transmitter output power, in dBm G_T : gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

Refer to attached Appendix A to Appendix J for details of test results.

5.1.2. MODULATION CHARACTERISTICS**RESULT:****Pass**

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2
Limits	:	"Other types of equipment", the use of higher order modulations such as OFDM or LTE or other modulation are acceptable for use
Test procedure	:	Clause 5.2.3 of ANSI C63.26
Kind of test site	:	Shielding Room
2024-04-10 - 2024-05-13 DC 3.3V		

Note:

The device implement digital modulation such as BPSK and QPSK, hence the EUT is deemed to comply with this requirement without additional testing.

5.1.3. OCCUPIED BANDWIDTH AND 26dB BANDWIDTH**RESULT:****Pass**

Test standard : 47 CFR FCC Part 22
47 CFR FCC Part 24
47 CFR FCC Part 27
47 CFR FCC Part 90
47 CFR FCC Part 2

Test requirement : Section 2.1049 of 47 CFR FCC Part 2

Limits : No limit

Test procedure : Section 5.4.3 of ANSI C63.26
☒ Conducted measurements
☐ Radiated measurements

Kind of test site : Shielding Room

Test Setup

Date of testing : 2024-04-10 - 2024-05-13

Input voltage : DC 3.3V

Test environment : ☒ Normal test conditions
☐ Extreme test conditions

Operation mode : A.1

Ambient temperature : 24 °C

Relative humidity : 50%

Atmospheric pressure : 101.0 kPa

Refer to attached Appendix A to Appendix J for details of test results.

5.1.4. SPURIOUS EMISSIONS AT ANTENNA TERMINALS

RESULT:

Pass

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2																										
Limits	:	<table><tr><td>Operating band</td><td>FCC Limit</td></tr><tr><td>Band 2</td><td>< - 13 dBm /1MHz</td></tr><tr><td>Band 4</td><td>< - 13 dBm /1MHz</td></tr><tr><td></td><td>< - 13 dBm /100kHz</td></tr><tr><td>Band 5</td><td>@ < 1GHz < - 13 dBm /1MHz @ > 1GHz</td></tr><tr><td>Band 12</td><td>< - 13 dBm /100kHz</td></tr><tr><td>Band 13</td><td>< - 13 dBm /100kHz</td></tr><tr><td>Band 25</td><td>< - 13 dBm /1MHz</td></tr><tr><td>Band 26 Lower Band</td><td>< - 13 dBm /100kHz</td></tr><tr><td></td><td>< - 13 dBm /100kHz</td></tr><tr><td>Band 26 Upper Band</td><td>@ < 1GHz < - 13 dBm /1MHz @ > 1GHz</td></tr><tr><td>Band 41</td><td>< - 13 dBm /1MHz</td></tr><tr><td>Band 66</td><td>< - 13 dBm /1MHz</td></tr></table>	Operating band	FCC Limit	Band 2	< - 13 dBm /1MHz	Band 4	< - 13 dBm /1MHz		< - 13 dBm /100kHz	Band 5	@ < 1GHz < - 13 dBm /1MHz @ > 1GHz	Band 12	< - 13 dBm /100kHz	Band 13	< - 13 dBm /100kHz	Band 25	< - 13 dBm /1MHz	Band 26 Lower Band	< - 13 dBm /100kHz		< - 13 dBm /100kHz	Band 26 Upper Band	@ < 1GHz < - 13 dBm /1MHz @ > 1GHz	Band 41	< - 13 dBm /1MHz	Band 66	< - 13 dBm /1MHz
Operating band	FCC Limit																											
Band 2	< - 13 dBm /1MHz																											
Band 4	< - 13 dBm /1MHz																											
	< - 13 dBm /100kHz																											
Band 5	@ < 1GHz < - 13 dBm /1MHz @ > 1GHz																											
Band 12	< - 13 dBm /100kHz																											
Band 13	< - 13 dBm /100kHz																											
Band 25	< - 13 dBm /1MHz																											
Band 26 Lower Band	< - 13 dBm /100kHz																											
	< - 13 dBm /100kHz																											
Band 26 Upper Band	@ < 1GHz < - 13 dBm /1MHz @ > 1GHz																											
Band 41	< - 13 dBm /1MHz																											
Band 66	< - 13 dBm /1MHz																											
Test procedure	:	Clause 5.7.4 of ANSI C63.26																										
Kind of test site	:	Shielding Room																										

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☐ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	24 °C
Relative humidity	:	51%
Atmospheric pressure	:	101.0 kPa

The limit calculation:
 $\text{Limit} = P_{\text{Meas}} \text{ (dBm)} - [43 + 10 \log(P_{\text{Meas}})] = -13 \text{ dBm}$

Refer to attached Appendix A to Appendix J for details of test results.

**5.1.5. SPURIOUS EMISSIONS AT ANTENNA TERMINALS – BAND
EDGE****RESULT:****Pass**

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2																						
Limits	:	<table><tr><td>Operating band</td><td>FCC Limit</td></tr><tr><td>Band 2</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 4</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 5</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 12</td><td>< - 13 dBm /30kHz</td></tr><tr><td>Band 13</td><td>< - 13 dBm /30kHz</td></tr><tr><td>Band 25</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 26 Lower Band</td><td>< - 20 dBm /1%EBW</td></tr><tr><td>Band 26 Upper Band</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 41</td><td>< - 13 dBm /1%EBW</td></tr><tr><td>Band 66</td><td>< - 13 dBm /1%EBW</td></tr></table>	Operating band	FCC Limit	Band 2	< - 13 dBm /1%EBW	Band 4	< - 13 dBm /1%EBW	Band 5	< - 13 dBm /1%EBW	Band 12	< - 13 dBm /30kHz	Band 13	< - 13 dBm /30kHz	Band 25	< - 13 dBm /1%EBW	Band 26 Lower Band	< - 20 dBm /1%EBW	Band 26 Upper Band	< - 13 dBm /1%EBW	Band 41	< - 13 dBm /1%EBW	Band 66	< - 13 dBm /1%EBW
Operating band	FCC Limit																							
Band 2	< - 13 dBm /1%EBW																							
Band 4	< - 13 dBm /1%EBW																							
Band 5	< - 13 dBm /1%EBW																							
Band 12	< - 13 dBm /30kHz																							
Band 13	< - 13 dBm /30kHz																							
Band 25	< - 13 dBm /1%EBW																							
Band 26 Lower Band	< - 20 dBm /1%EBW																							
Band 26 Upper Band	< - 13 dBm /1%EBW																							
Band 41	< - 13 dBm /1%EBW																							
Band 66	< - 13 dBm /1%EBW																							
Test procedure	:	Clause 5.7.3 of ANSI C63.26																						
Kind of test site	:	Shielding Room																						

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☐ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	24 °C
Relative humidity	:	51%
Atmospheric pressure	:	101.0 kPa

The limit calculation:

$$\text{Limit} = P_{\text{Meas}} \text{ (dBm)} - [43 + 10 \log(P_{\text{Meas}})] = -13 \text{ dBm}$$

Refer to attached Appendix A to Appendix J for details of test results.

5.1.6. FIELD STRENGTH OF SPURIOUS RADIATION**RESULT:****Pass**

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2
Limits	:	Operating band FCC Limit Band 2 < - 13 dBm /1MHz Band 4 < - 13 dBm /1MHz Band 5 < - 13 dBm /100kHz @ < 1GHz < - 13 dBm /1MHz @ > 1GHz Band 12 < - 13 dBm /100kHz Band 13 < - 13 dBm /100kHz Band 25 < - 13 dBm /1MHz Band 26 < - 13 dBm /100kHz Lower Band Band 26 < - 13 dBm /100kHz @ < 1GHz Upper Band < - 13 dBm /1MHz @ > 1GHz Band 41 < - 13 dBm /1MHz Band 66 < - 13 dBm /1MHz
Test procedure	:	Clause 5.5 of ANSI C63.26
Kind of test site	:	3m Semi Anechoic Room

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☐ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	23 °C
Relative humidity	:	47%
Atmospheric pressure	:	101.0 kPa

The limit calculation:

$$\text{Limit} = P_{\text{Meas}} (\text{dBm}) - [43 + 10 \log(P_{\text{Meas}})] = -13 \text{ dBm}$$

Sweep the whole frequency band through the range from 9 kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in this report. The measurement is performed for all operational modes and both antenna polarization, only the data of the worst mode is recorded in this report.

Refer to attached Appendix K for details of test results.

5.1.7. FREQUENCY STABILITY**RESULT:****Pass**

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2
Limits	:	Operating band FCC Limit Band 2 Within authorized bands Band 4 Within authorized bands Band 5 2.5 ppm Band 12 Within authorized bands Band 13 Within authorized bands Band 25 Within authorized bands Band 26 Lower Band 2.5 ppm Band 26 Upper Band 2.5 ppm Band 41 Within authorized bands Band 66 Within authorized bands
Test procedure	:	Clause 5.6.3 of ANSI C63.26
Kind of test site	:	Shielding Room

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☒ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	24 °C
Relative humidity	:	51%
Atmospheric pressure	:	101.0 kPa

Refer to attached Appendix A to Appendix J for details of test results.

5.1.8. PEAK TO AVERAGE RATIO**RESULT:****Pass**

Test standard	:	47 CFR FCC Part 22 47 CFR FCC Part 24 47 CFR FCC Part 27 47 CFR FCC Part 90 47 CFR FCC Part 2																						
Limits	:	<table><tr><th>Operating band</th><th>FCC Limit</th></tr><tr><td>Band 2</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 4</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 5</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 12</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 13</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 25</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 26 Lower Band</td><td>N/A</td></tr><tr><td>Band 26 Upper Band</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 41</td><td>PAR ≤ 13 dB</td></tr><tr><td>Band 66</td><td>PAR ≤ 13 dB</td></tr></table>	Operating band	FCC Limit	Band 2	PAR ≤ 13 dB	Band 4	PAR ≤ 13 dB	Band 5	PAR ≤ 13 dB	Band 12	PAR ≤ 13 dB	Band 13	PAR ≤ 13 dB	Band 25	PAR ≤ 13 dB	Band 26 Lower Band	N/A	Band 26 Upper Band	PAR ≤ 13 dB	Band 41	PAR ≤ 13 dB	Band 66	PAR ≤ 13 dB
Operating band	FCC Limit																							
Band 2	PAR ≤ 13 dB																							
Band 4	PAR ≤ 13 dB																							
Band 5	PAR ≤ 13 dB																							
Band 12	PAR ≤ 13 dB																							
Band 13	PAR ≤ 13 dB																							
Band 25	PAR ≤ 13 dB																							
Band 26 Lower Band	N/A																							
Band 26 Upper Band	PAR ≤ 13 dB																							
Band 41	PAR ≤ 13 dB																							
Band 66	PAR ≤ 13 dB																							
Test procedure	:	Clause 5.2.6 of ANSI C63.26																						
Kind of test site	:	Shielding Room																						

Test Setup

Date of testing	:	2024-04-10 - 2024-05-13
Input voltage	:	DC 3.3V
Test environment	:	☒ Normal test conditions ☐ Extreme test conditions
Operation mode	:	A.1
Ambient temperature	:	24 °C
Relative humidity	:	51%
Atmospheric pressure	:	101.0 kPa

Refer to attached Appendix A to Appendix J for details of test results.

6. SYSTEM MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Table 9: System Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

7. LIST OF TABLES

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty	8
Table 3: Technical Specification of EUT	9
Table 4: Operating Frequency Range of EUT	10
Table 5: List of Frequencies under Test.....	12
Table 6: Test Environments.....	13
Table 7: Test Configurations.....	13
Table 8: List of Accessories and Auxiliary Equipment.....	13
Table 9: System Measurement Uncertainty	24