

Manufacturer: Trimble Inc., 4450 Gibson Drive, Tipp City, Ohio 45371, USA
Model / HVIN: TR400900
FCC ID: S9E123130
ISED ID: 5817A-123130

Test Laboratory: SGS Fimko Oy
Address: Karakaarenkuja 4, FI-02610 Espoo, FINLAND
Accreditation Body: FINAS
CAB Identifier: T004
ISED Company Number: 8708A

REFERENCE DOCUMENTS

KDB447498 D01 General RF Exposure Guidance v06, 23 October 2015
FCC CFR 47 §1.1310, Radio frequency exposure limits
FCC CFR 47 §2.1091, Radio frequency exposure evaluation: mobile devices
RSS-102 Issue 5, 2015

EUT SPECIFICATION

RF module, 410 MHz to 430 MHz; 450 MHz to 470 MHz, 1W
Using the maximum power (including tune-up tolerances), the power density was calculated. Maximum antenna gain was assumed (6 dBi).

RF EXPOSURE RESULT

FCC

Test Description	Standard	Compliance distance
RF Exposure (General Public)	FCC CFR 47 §1.1310	=> 0.34 m when 6 dBi antenna used

ISED

Test Description	Standard	Compliance distance
RF Exposure (General Public)	RSS-102	=> 0.45 m when 6 dBi antenna used

RF EXPOSURE ASSESSMENT

FCC: Exposure Limits for Uncontrolled / Controlled Environment

Frequency Range /MHz	RF power density, occupational/controlled [mW/cm ²]	RF power density, general population/uncontrolled [mW/cm ²]
300 – 1500 MHz	f/300	f/1500

f = frequency in MHz

ISED: Exposure Limits for Uncontrolled Environment

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

Note: f is frequency in MHz.

* Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).

ISED: Exposure Limits for Controlled Environment

Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²³	170	180	-	Instantaneous*
0.1-10	-	1.6/ f	-	6**
1.29-10	193/ f ^{0.5}	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ f ^{0.25}	0.3444/ f ^{0.25}	44.72/ f ^{0.5}	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 f ^{0.25}	0.04138 f ^{0.25}	0.6455 f ^{0.5}	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ f ^{1.2}
150000-300000	0.354 f ^{0.5}	9.40 x 10 ⁻⁴ f ^{0.5}	3.33 x 10 ⁻⁴ f	616000/f ^{1.2}

Note: f is frequency in MHz.

* Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).

Single transmission RF Exposure Levels (mW/cm²)

FCC

Lowest frequency (410 MHz)

EUT		Antenna		General Public		Controlled Environment	
Freq.	Power	Gain		Level	Safe D	Level	Safe D
MHz	W	dBi	G	mW/cm ²	cm	mW/cm ²	cm
410	1.0	0	1.0	0.27	17,172	1.37	7,623
		4	2.5		27,151		12,054
		6	4.0		34,344		15,247

Highest frequency (470 MHz)

EUT		Antenna		General Public		Controlled Environment	
Freq.	Power	Gain		Level	Safe D	Level	Safe D
MHz	W	dBi	G	mW/cm ²	cm	mW/cm ²	cm
470	1.0	0	1.0	0.31	16,026	1.57	7,121
		4	2.5		25,339		11,260
		6	4.0		32,052		14,242

Single transmission RF Exposure Levels (W/m²)

ISED

Lowest frequency (410 MHz)

EUT		Antenna		General Public		Controlled Environment	
Freq.	Power	Gain		Level	Safe D	Level	Safe D
MHz	W	dBi	G	W/m ²	m	W/m ²	m
410	1.0	0	1.0	1.60	0,223	13.07	0,078
		4	2.5		0,353		0,123
		6	4.0		0,446		0,156

Highest frequency (470 MHz)

EUT		Antenna		General Public		Controlled Environment	
Freq.	Power	Gain		Level	Safe D	Level	Safe D
MHz	W	dBi	G	W/m ²	m	W/m ²	m
470	1.0	0	1.0	1.75	0,213	13.99	0,075
		4	2.5		0,337		0,119
		6	4.0		0,427		0,151

Report Issue Date: March 4, 2022



Henri Mäki
Test Engineer

Disclaimer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.