


SK TECH CO., LTD.

Page 1 of 25

Certificate of Compliance

Test Report No.:	SKTFCE-040623-057		
NVLAP CODE :	200220-0		
Applicant:	Nextier Inc.		
Applicant Address:	#821-3, Byucksan Digit. Valley II 153-023, 481-10, Gasan-dong, Geumcheon-Gu, Seoul, Korea		
Manufacturer:	Nextier Inc.		
Manufacturer Address:	#821-3, Byucksan Digit. Valley II 153-023, 481-10, Gasan-dong, Geumcheon-Gu, Seoul, Korea		
Product:	Plasma Display Panel Television		
FCC ID:	SADNP-42SEI	Model No.:	NP-42SEI
Multi-listing M/N:	PDP42NESI, NP42SI-DWI, HPTN-4200, MTPO42		
Receipt No.:	SKTEU04-0148	Date of receipt:	Mar. 09, 2004
Date of Issue:	June 23, 2004		
Testing location:	SK TECH CO., LTD. 820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea		
Test Standards:	ANSI C63.4 / 2001		
Rule Parts:	FCC part 15 Subpart B		
Equipment Class :	Class B Digital Device Peripheral		

This device has shown compliance with the conducted emissions limits in 15.107, 15.207 or 18.307 adopted under FCC 02-157(ET Docket 98-80). The device may be marketed after July 11, 2005, and is not affected by the 15.37(j) or 18.123 transition provisions.

Test Result: The above mentioned product has been tested and passed.

Prepared by: Y.H.Kang

Tested by: S. Y. Yoon/Engineer

Approved by: C.H.Jeong
/Manager & Chief Engineer

Signature

Date

Signature

Date

Signature

Date

Other Aspects :

Abbreviations : · OK, Pass = passed · Fail = failed · N/A = not applicable

- ☒ • This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.

NVLAP Lab. Code: 200220-0



» » Contents « «

Contents	2
List of Tables	2
List of Figures	2
1. General	3
2. Test Site	3
2.1 Location	3
2.2 List of Test and Measurement Instruments	4
2.3 Test Date	4
2.4 Test Environment	4
3. Description of the tested samples	5
3.1 Rating and Physical Characteristics	5
3.2 Submitted Documents	5
4. Measurement Conditions	6
4.1 Modes of Operation	6
4.2 List of Peripherals	6
4.3 Type of Used cables	7
4.4 Test Setup	7
4.5 Uncertainty	8
5. EMISSION Test	11
5.1 Conducted Emissions	11
5.2 Radiated Emissions	24

» List of Tables

Table 1	List of test and measurement Equipment	4
Table 2	Test Data, Conducted Emissions, TV Mode(Ground)	14
Table 3	Test Data, Conducted Emissions, TV Mode(non-Ground)	17
Table 4	Test Data, Conducted Emissions, VGA Mode(Line-PE)	20
Table 5	Test Data, Conducted Emissions, VGA Mode(Neutral-PE)	23
Table 6	Test Data, Radiated Emissions	25

» List of Figures

Figure 1	Spectral Diagram, LINE-PE, TV Mode(Ground)	12
Figure 2	Spectral Diagram, Neutral-PE, TV Mode(Ground)	13
Figure 3	Spectral Diagram, LINE-PE, TV Mode(Non-Ground)	15
Figure 4	Spectral Diagram, Neutral-PE, TV Mode(Non-Ground)	16
Figure 5	Spectral Diagram, LINE-PE, VGA Mode, Q.P	18
Figure 6	Spectral Diagram, LINE-PE, VGA Mode, A.V	19
Figure 7	Spectral Diagram, Neutral-PE, VGA Mode, Q.P	21
Figure 8	Spectral Diagram, Neutral-PE, VGA Mode, A.V	22

**SK TECH CO., LTD.***Page 3 of 25*

1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by SK Tech Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

SK TECH Co., Ltd.

2.1 Location

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

The test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200220-0 and DATech for DAR-Registration No.:DAT-P-076/97-01



2.2 List of Test and Measurement Instruments

Table 1 : List of Test and Measurement Equipment

- Conducted Disturbance

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESHS10	862970/019	07.2004
Artificial Mains Network	ESH2-Z5	834549/011	08.2004
EMI Receiver	ESHS10	835871/002	10.2004
Artificial Mains Network	ESH3-Z5	836679/018	08.2004

- Radiated Disturbance

Kind of Equipment	Type	S/N	Calibrated until
EMI Receiver	ESVS 10	825120/013	10.2004
EMI Receiver	ESVS 10	834468/008	10.2004
Spectrum Analyzer	R3361A	11730187	10.2004
Amplifier	8447F	3113A05153	08.2004
Log Periodic Antenna	UHALP9107	1819	10.2004
Biconical Antenna	BBA9106	91031626	10.2004
Open Site Cable	N/A	N/A	N/A
Antenna Turntable Driver	5907	N/A	N/A
Antenna Turntable controller	5906	N/A	N/A
Amp & Receiver connection cable	N/A	N/A	N/A
Amp & Spectrum connection cable	N/A	N/A	N/A
50Ω Switcher	MP59B	6100214538	N/A

2.3 Test Date

Date of Application : Mar. 09, 2004

Date of Test : June 16, 2004 ~ June 22, 2004

2.4 Test Environment

See each test item's description.



3. Description of the tested samples

The EUT is the Plasma Display Panel Television.

Model No. General Description.

Basic Model No : NP-42SEI

Model PDP42NESI, NP42SI-DWI, HPTN-4200 and MTPO42 are similar to basic model, except for model designation and trademark.

3.1 Rating and Physical Characteristics

Power Supply	AC 100V ~ 240V, 50/60Hz
Power Consumption(Typical)	290W
Dimensions (W x H x D)	Without stand : 1028mm x 625mm x 89.8mm With stand : 1028mm x 692.5mm x 270mm
Weight	Without stand : 35kg With stand : 40.5kg
Temperature	Operational : 0 ~ 40 Storage : -5 ~ 50
Humidity	Operational : 20 ~ 70% (without condensation) Storage : 20 ~ 75% (without condensation)
Pressure	Operational/Storage : 800 ~ 1114 hPa (Altitude : 0 ~ 2,000m)
Screen Size (Active area)	42" (932.94mm(H) x 532.80mm(V))
Aspect ratio	16:9
Number of Pixels	852 (H) x 480(V)
Pixel Pitch	1.095mm(H) x 1.110mm(V)
Displayable Colors	16.77 million colors
Brightness	1000 cd/m ²
Contrast Ratio	3000:1
Color Temperature	9500K
Viewing Angle	Over 160 degrees

3.2 Submitted Documents

N/A



4. Measurement Conditions

The operating Input voltage : AC 120V, 60Hz.

4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

The EUT is connected to Notebook PC.

Tested in mode of displaying "H" on the screen.

4.2 List of Peripherals

Description	Manufacturer	Model Name	Serial No.	FCC ID
Plasma Display Panel Television (EUT)	Nextier Inc.	NP-42SEI	N/A	
Notebook PC	LG IBM	2681	FX-P2816	-
Adaptor (for Notebook)	ASTEC Electronics Co., Ltd.	08K8202	11S08K8202Z1Z 6LR38F053	-
Pattern Generator	Leader	401YB	0100064	




4.3 Type of Used Cables

Description	Length	Type of shield	Manufacturer	Remark
VGA Cable	1.2m	Shield	None	For EUT
A/V Cable (x20)	1.5m	Non-Shield	None	For EUT (Termination)
S-Video Cable (x2)	1.2m	Non-Shield	None	For EUT (Termination)
Scart Cable (x2)	1.0m	Non-Shield	None	For EUT (Termination)
Power cable	1.2m	Non-Shield	None	For EUT
AC Adaptor power cable	1.2m	Non-Shield	None	For Notebook PC

4.4 Test Setup

The test setup photographs showed the external supply connections and interfaces.



[System Block Diagram of Test Configuration]



4.5 Uncertainty

1) Radiated disturbance

- ◎ Horizontally polarized radiated disturbances from 30MHz to 1000MHz at a distance of 3m

Input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ci _u (xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver reading	±0.1	K =1	0.1	1	0.1	0.10
2) Attenuation: antenna-receiver	±0.18	K=2	0.09	1	0.09	0.05
3) Antenna factor	±1.5	K=2	0.75	1	0.75	1.00
RECEIVER CORRECTIONS:						
4) Sine wave voltage	±0.56	K=2	0.28	1	0.50	0.50
5) Pulse amplitude response	±1.5	Rectangular (1/3)	0.87	1	0.87	0.87
6) Pulse repetition rate response	±1.5	Rectangular (1/3)	0.87	1	0.87	0.87
7) Noise floor proximity	±0.5	K=2	0.25	1	0.25	0.25
8) AF frequency interpolation	±0.3	Rectangular (1/3)	0.17	1	0.17	0.17
9) Balance	±0.3	Rectangular (1/3)	0.17	1	0.17	0.53
10) AF height deviations	±0.5	Rectangular (1/3)	0.29	1	0.29	0.29
11) Phase center location	±0.3	Rectangular (1/3)	0.17	1	0.17	0.17
12) Directive difference	+1.0	Rectangular (1/3)	0.29	1	0.29	0.29
13) Cross polarization	±0.9	Rectangular (1/3)	0.52	1	0.52	0.52
14) Site corrections	±2.6	Rectangular (1/3)	1.5	1	1.5	1.63
15) Mismatch (ant-receiver)	±1.06	U-shaped (1/2)	0.75	1	0.75	0.67

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2 + (9)^2 + (10)^2 + (11)^2 + (12)^2 + (13)^2 + (14)^2 + (15)^2} = 2.37$$

Expanded Uncertainty

$$U = k * U_c(x_i) = 2 * 2.37 = 4.74 \text{dB} \quad (\text{The coverage factor } k = 2 \text{ yields approximately a 95% level of confidence})$$


SK TECH CO., LTD.

Page 9 of 25

◎ Vertically polarized radiated disturbances from 30MHz to 1000MHz at a distance of 3m

Input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ci _u (xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver reading	±0.1	K=1	0.1	1	0.1	0.10
2) Attenuation: antenna-receiver	±0.18	K=2	0.09	1	0.09	0.05
3) Antenna factor	±1.5	K=2	0.75	1	0.75	1.00
RECEIVER CORRECTIONS:						
4) Sine wave voltage	±0.56	K=2	0.28	1	0.50	0.50
5) Pulse amplitude response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
6) Pulse repetition rate response	±1.5	Rectangular (√3)	0.87	1	0.87	0.87
7) Noise floor proximity	±0.5	K=2	0.25	1	0.25	0.25
8) AF frequency interpolation	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
9) Balance	±0.9	Rectangular (√3)	0.52	1	0.52	0.52
10) AF height deviations	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
11) phase center location	±0.3	Rectangular (√3)	0.17	1	0.17	0.17
12) directive difference	+1.0	Rectangular (√3)	0.29	1	0.29	0.29
13) cross polarization	±0.9	Rectangular (√3)	0.52	1	0.52	0.52
14) site corrections	±2.6	Rectangular (√3)	1.5	1	1.5	1.63
15) Mismatch (ant-receiver)	±1.06	U-shaped (√2)	0.75	1	0.75	0.67

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2 + (9)^2 + (10)^2 + (11)^2 + (12)^2 + (13)^2 + (14)^2 + (15)^2} = 2.43$$

Expanded Uncertainty

$$U = k * U_c(x_i) = 2 * 2.43 = 4.86 \text{ dB}$$

(The coverage factor k =2 yields approximately a 95% level of confidence)



2) Conducted disturbance

◎ Conducted disturbance from 150KHz to 30MHz using a 50Ω/50uH AMN

input quantity	Uncertainty of Xi		U(Xi) dB	Ci	Ciu(xi)	CISPR 16-4
	dB	Probability distribution function				
1) Receiver Readeing	±0.1	K=1	0.1	1	0.1	0.10
2) Attenuation:AMN-receiver	±0.36	Triangular ($\sqrt{6}$)	0.15	1	0.15	0.05
RECEIVER CORRECTIONS:						
3) Sine wave voltage	±0.5	K=2	0.25	1	0.25	0.50
4) Pulse amplitude response	±1.5	Rectangular ($\sqrt{3}$)	0.87	1	0.87	0.87
5) Pulse repetition rate response	±1.5	Rectangular ($\sqrt{3}$)	0.87	1	0.87	0.87
6) AMN voltage division factor	±0.07	K=2	0.04	1	0.04	0.1
7) Mismatch : AMN-receiver	±0.55	U-shaped ($\sqrt{2}$)	0.39	1	0.39	0.53
8) AMN impedance	±1.52	Triangular ($\sqrt{6}$)	0.62	1	0.62	1.08

- 1)~8) For numbered comments, refer to following articles

Combined Uncertainty

$$U_c(x_i) = \sqrt{(1)^2 + (2)^2 + (3)^2 + (4)^2 + (5)^2 + (6)^2 + (7)^2 + (8)^2} = 1.47$$

Expanded uncertainty

$$U = k * U_c(x_i) = 2 * 1.47 = 2.94 \text{ dB}$$

The coverage factor $k = 2$ yields approximately a 95% level of confidence

◎ Refer

- 1) receiver's resolution capacity
- 2) refer to the sub clause 11. of a calibration report
- 3) quoted from CISPR 16-4
- 4) refer to a calibration report
- 5) refer to CISPR 16-4 article 5. 7)
- 6) refer to a calibration report and a measured AMN impedance data



5. EMISSION Test

5.1 Conducted Emissions

Result:**Pass**

The line-conducted facility is located inside a 2.0M x 3.6M x 7.2M shielded enclosure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 604-05.

A 1m x 1.5m wooden table 80cm high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room. ROHDE & SCHWARZ Model ESH3-Z5 (10kHz-30MHz) 50ohm/50 uH Line-Impedance Stabilization Networks(LISNs) are bonded to the shielded room.

The EUT is powered from the ROHDE & SCHWARZ LISN and the support equipment is powered from the ROHDE & SCHWARZ LISN. Power to the LISNs are filtered by a high-current high-insertion loss Lindgren enclosures power line filters (100dB 14kHz-10GHz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the ROHDE & SCHWARZ LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150kHz to 30MHz with 100msec. sweep time.

The frequency producing the maximum level was reexamined using EMI/field Intensity Meter (ESHS 10) and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.

**SK TECH CO., LTD.**

Page 12 of 25

Figure 1 : Spectral Diagram, LINE – PE, TV Mode (Ground)


22 Jun 2004 17:25

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: LINE-PE
color bar / ground
Result File: 42sei I1.dat : NP-42SEI / color bar / ground

Scan Settings (1 Range) Frequencies Receiver Settings
Start 150kHz Stop 30MHz Step 10kHz IF BW 10kHz Detector PK M-Time 100msec Atten Auto Preamp OFF OpRge 60dB

Final Measurement: Detector: X AV
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB



**SK TECH CO., LTD.**

Page 13 of 25

Figure 2 : Spectral Diagram, NEUTRAL – PE, TV Mode (Ground)


22 Jun 2004 17:36

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: NEUTRAL-PE
color bar / ground
Result File: 42sei n1.dat : NP-42SEI / color bar / ground

Scan Settings (1 Range)		Receiver Settings						
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB

Final Measurement: Detector: X AV
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB



**Table 2: Test Data, Conducted Emissions, TV Mode (Ground)**

► LINE-PE

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
2.09	26.44	0.13	0.3	56.00	29.13
2.56	26.53	0.13	0.3	56.00	29.04
3.72	28.56	0.13	0.3	56.00	27.01
4.42	27.07	0.23	0.4	56.00	28.30
4.88	28.76	0.23	0.4	56.00	26.61

► NEUTRAL-PE

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
1.63	28.63	0.17	0.3	56.00	26.90
2.56	28.81	0.17	0.3	56.00	26.72
3.72	29.27	0.17	0.3	56.00	26.26
4.42	29.24	0.24	0.4	56.00	26.12
4.88	31.10	0.24	0.4	56.00	24.26

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emissions are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. C/F = Correction Factor
6. C/L = Cable Loss

♦ Margin Calculation

$$(6) \text{Margin} = (5)\text{Limit} - (4)\text{Actual}$$

$$[(4)\text{Actual} = (1)\text{Reading} + (2)\text{C/F} + (3)\text{C/L}]$$

**SK TECH CO., LTD.**

Page 15 of 25


Figure 3 : Spectral Diagram, LINE – PE, TV Mode (Non-Ground)

22 Jun 2004 17:05

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: LINE-PE
Color bar / non ground
Result File: 42sei.l.dat : NP-42SEI / color bar / non ground

Scan Settings	(1 Range)				Receiver Settings				
	Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
	150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB
Final Measurement:		Detector:	X QP						
		Meas Time:	1sec						
		Peaks:	8						
		Acc Margin:	35 dB						



**SK TECH CO., LTD.**

Page 16 of 25

Figure 4 : Spectral Diagram, Neutral – PE, TV Mode (Non-Ground)


22 Jun 2004 16:48

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: NEUTRAL-PE
Color bar/non ground
Result File: 42sei.n.dat : NP-42SEI / color bar / non ground

Scan Settings	(1 Range)				Receiver Settings				
	Frequencies								
Start	150kHz	Stop	30MHz	Step	10kHz	IF BW	10kHz	Detector	PK
								M-Time	100msec
								Atten	Auto
								Preamp	OFF
								OpRge	60dB

Final Measurement: Detector: X AV
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB



**Table 3: Test Data, Conducted Emissions, TV Mode (Non-Ground)**

► LINE-PE

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
0.23	47.40	0.08	0.1	62.45	14.87
4.42	40.78	0.23	0.4	56.00	14.59
10.93	46.58	0.39	0.5	60.00	12.53
11.86	47.42	0.39	0.5	60.00	11.69
14.65	47.48	0.67	0.6	60.00	11.25

► NEUTRAL-PE

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
0.23	32.71	0.13	0.1	62.45	29.51
11.86	33.78	0.33	0.5	60.00	25.39
13.72	33.85	0.50	0.6	60.00	25.05
14.65	36.15	0.50	0.6	60.00	22.75
15.58	32.85	0.50	0.6	60.00	26.05

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emissions are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. C/F = Correction Factor
6. C/L = Cable Loss

♦ Margin Calculation

$$(6) \text{Margin} = (5)\text{Limit} - (4)\text{Actual}$$

$$[(4)\text{Actual} = (1)\text{Reading} + (2)\text{C/F} + (3)\text{C/L}]$$

**SK TECH CO., LTD.**

Page 18 of 25

Figure 5 : Spectral Diagram, LINE – PE, VGA Mode, Q.P

21 Jun 2004 17:29

CONDUCTED DISTURBANCE

EUT: NP-42SEI

Manuf:

Op Cond:

Operator:


Test Spec:

Comment: LINE-PE

Result File: NP-42SEIL.dat ; nextier monitor

Scan Settings	(1 Range)				Receiver Settings				
	Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
	150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB

Final Measurement: Detector: X QP
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB



**SK TECH CO., LTD.**

Page 19 of 25


Figure 6 : Spectral Diagram, LINE – PE, VGA Mode, A.V

21 Jun 2004 17:40

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: LINE-PE
AV
Result File: NP-42SEIL2.dat : nextier monitor

Scan Settings	(1 Range)				Receiver Settings				
	Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
	150kHz	30MHz	10kHz	10kHz	PK	100msec	Auto	OFF	60dB
Final Measurement:					Detector: X AV				
					Meas Time: 1sec				
					Peaks: 8				
					Acc Margin: 35 dB				



**Table 4: Test Data, Conducted Emissions, VGA Mode**► **LINE-PE (Q.P)**

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
1.63	41.29	0.13	0.3	56.00	14.28
2.09	42.84	0.13	0.3	56.00	12.73
11.86	46.60	0.39	0.5	60.00	12.51
14.65	49.91	0.67	0.6	60.00	8.82
15.58	48.28	0.67	0.6	60.00	10.45

► **LINE-PE (A.V)**

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
1.63	28.63	0.13	0.3	56.00	26.94
2.09	41.27	0.13	0.3	56.00	14.30
11.86	38.75	0.39	0.5	60.00	20.36
13.72	37.06	0.67	0.6	60.00	21.67
14.65	40.51	0.67	0.6	60.00	18.22

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emissions are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. C/F = Correction Factor
6. C/L = Cable Loss

◆ Margin Calculation

$$(6) \text{Margin} = (5)\text{Limit} - (4)\text{Actual}$$

$$[(4)\text{Actual} = (1)\text{Reading} + (2)\text{C/F} + (3)\text{C/L}]$$

**SK TECH CO., LTD.**

Page 21 of 25

Figure 7 : Spectral Diagram, Neutral – PE, VGA Mode, Q.P

21 Jun 2004 18:05

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: NEUTRAL-PE
QUASI
Result File: 42sein.dat : nextier monitor

Scan Settings (1 Range) Frequencies Receiver Settings
Start 150kHz Stop 30MHz Step 10kHz IF BW 10kHz Detector PK M-Time 100msec Atten Auto Preamp OFF OpRge 60dB

Final Measurement: Detector: X QP
Meas Time: 1sec
Peaks: 8
Acc Margin: 35 dB







Figure 8 : Spectral Diagram, Neutral – PE, VGA Mode, A.V

21 Jun 2004 18:08

CONDUCTED DISTURBANCE

EUT: NP-42SEI
Manuf:
Op Cond:
Operator:
Test Spec:
Comment: NEUTRAL-PE
AVERAGE
Result File: 42sein2.dat : nextier monitor

Scan Settings	(1 Range)	Frequencies			Receiver Settings			
Start		Start		IF BW	Detector	M-Time	Atten	Preamp
150kHz	30MHz	Stop	10kHz	10kHz	PK	100msec	Auto	OFF
Final Measurement:					Detector:	X AV		
					Meas Time:	1sec		
					Peaks:	8		
					Acc Margin:	35 dB		



**Table 5: Test Data, Conducted Emissions, VGA Mode**► **Neutral-PE (Q.P)**

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
2.09	47.34	0.17	0.3	56.00	8.19
11.86	49.83	0.33	0.5	60.00	9.34
13.95	49.95	0.50	0.6	60.00	8.95
14.65	52.05	0.50	0.6	60.00	6.85
15.58	51.34	0.50	0.6	60.00	7.56

► **Neutral-PE (A.V)**

Frequency (MHz)	Reading (dBuV)	C/F (dB)	CL (dB)	Limit (dBuV)	Margin (dB)
2.09	42.90	0.17	0.3	56.00	12.63
11.86	39.34	0.33	0.5	60.00	19.83
14.65	41.66	0.50	0.6	60.00	17.24
15.58	41.20	0.50	0.6	60.00	17.70

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emissions are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. C/F = Correction Factor
6. C/L = Cable Loss

♦ Margin Calculation

$$(6) \text{Margin} = (5) \text{Limit} - (4) \text{Actual}$$

$$[(4) \text{Actual} = (1) \text{Reading} + (2) \text{C/F} + (3) \text{C/L}]$$



5.2 Radiated Emissions

Result :**Pass**

Preliminary measurements were made indoors at 3 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME.

Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found.

The spectrum was scanned from 30 to 300 MHz using biconical antenna and from 300 to 1000 MHz using log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using SCHWARZBECK dipole antennas. The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with FRP.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter(ESVS 10) and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test.

Each EME reported was calibrated using self-calibrating mode.

**Table 6 : Test Data, Radiated Emissions**

Frequency (MHz)	Pol.	Height [m]	Angle [°]	(1) Reading (dB μ V)	(2) AFCL (dB/m)	(3) Actual (dB μ V/m)	(4) Limit (dB μ V/m)	(5) Margin (dB)
77.00	H	1.8	56	25.0	7.1	32.1	40.0	7.9
160.89	H	1.0	250	20.8	17.3	38.1	43.5	5.4
250.56	V	1.0	126	21.0	20.4	41.4	46.0	4.6
302.00	H	1.0	100	19.1	19.4	38.5	46.0	7.5
366.48	V	1.0	132	17.3	21.0	38.3	46.0	7.7

Table. Radiated Measurements at 3-meters

NOTES:

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emission are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. Measurements using CISPR quasi-peak mode.
5. AFCL = Antenna factor and cable loss
6. H = Horizontal, V = Vertical Polarization

♦ Margin Calculation

$$(5) \text{Margin} = (4) \text{Limit} - (3) \text{Actual}$$

$$[(3) \text{Actual} = (1) \text{Reading} + (2) \text{AFCL}]$$