

REVISION RECORD				
REV	ECO	DESCRIPTION	APVD	DATE
A	CW67	RELEASED	YAEL H.	6.3.03

SHEET	43	44	45	46	47	48	49	50	51	52	53	54	55	56
REV														
SHEET	29	30	31	32	33	34	35	36	37	38	39	40	41	42
REV														
SHEET	15	16	17	18	19	20	21	22	23	24	25	26	27	28
REV														
SHEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14
REV	A	A	A											

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PROPRIETARY AND CONFIDENTIAL TO MTI. NO PERSON IS ALLOWED TO COPY REPRINT REPRODUCE OR PUBLISH ANY PART OF THIS DOCUMENT NOR, DISCLOSE ITS CONTENTS TO OTHERS, NOR MAKE ANY USE OF IT NOR ALLOW OR ASSIST OTHERS TO MAKE ANY USE OF IT, - UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF MTI AND THEN ONLY TO THE EXTENT AUTHORIZED.
 (C) COPYRIGHT – MTI WIRELESS EDGE LTD.

PRODUCT STATUS: <input type="checkbox"/> PROPOSAL, <input checked="" type="checkbox"/> INDEVELOPMENT <input type="checkbox"/> PREPRODUCTION, <input type="checkbox"/> PRODUCTION							
ACTION	NAME	SIGN	DATE				
PREP	Y.HARASH	Y.H	25.12.02	TITLE SPECIFICATION FOR MT – 486004/N SUBSCRIBER ANTENNA 5.15 - 5.875 GHz ,26 dBi			
CHKD	D.FAINER	D.F	3.3.03				
DSGN	A.HVIV	A.H	28.2.03				
PROJ	M.ROSTMY	M.R	25.2.03				
MFG							
SIZE		CLASSIFICATION		DWG NO			

QA	M.MOTOVICH	MOTI	25.2.03	A	NONE	RD41262600C
MARK.	D.SHANI	D.S	3.3.03	SCALE NONE		SHEET 1 OF 3

961-7/96

SIZE A	MTI WIRELESS EDGE	DWG NO RD41262600C	REV A
SCALE NONE			SHEET 2 OF 3

SPECIFICATION

FLAT PANEL SUBSCRIBER ANTENNA

MTI PART NUMBER	MT – 486004/N
REGULATORY COMPLIANCE	ETSI EN 302 085 V1.1.2,(2001-02) Range 1
<u>1. ELECTRICAL</u>	
FREQUENCY RANGE	5.15 - 5.875 GHz
GAIN	26 dBi (min)
VSWR	1.7:1 (max),1.5:1 (typ)
3 dB BEAMWIDTH	6° (typ)
POLARIZATION	Linear (Vertical or Horizontal)
SIDELOBES LEVEL	ETSI EN 302 085 V1.1.2, TS1-TS5
CROSS POLARIZATION	ETSI EN 302 085 V1.1.2, TS1-TS5 -20 db (max)
F/B RATIO	ETSI EN 302 085 V1.1.2, TS1-TS5 -30 db (max)
INPUT IMPEDANCE	50 (ohm)
INPUT POWER	6W (max)
LIGHTNING PROTECTION	DC Grounded
<u>2. MECHANICAL</u>	
DIMENSIONS (LxWxD)	450 x 450 x 30mm (max)
WEIGHT	3 (kg) (max)
CONNECTOR	N-TYPE Female
RADOME	Plastic
BASE PLATE	Aluminum with chemical conversion coating
OUTLINE DRAWING	RD41262700C
<u>3. MOUNTING KIT</u>	
	See RD41191800C

SIZE A	MTI WIRELESS EDGE	DWG NO RD41262600C	REV A
SCALE NONE		SHEET 3 OF 3	

4. ENVIRONMENTAL				
TEST	STANDARD	DURATION	TEMPERTURE	NOTES
LOW TEMPERATURE	IEC 68-2-1	72 h	-55°C	-
HIGH TEMPERATURE	IEC 68-2-2	72 h	+71°C	-
TEMP. CYCLING	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
VIBRATION	IEC 60721-3-4	30 min/axis	-	Random 4M5
SHOCK MECHANICAL	IEC 60721-3-4	-	-	4M5
HUMIDITY	ETSI EN300-2-4 T4.1E	144 h	-	95%
WATER TIGHTNESS	IEC 529	-	-	IP67
SOLAR RADIATION	ASTM G53	1000 h	-	-
SALT SPRAY	IEC 68-2-11 Ka	500 h	-	-
ICE AND SNOW	-	-	-	25mm Radial
WIND SPEED SURVIVAL OPERATION	- -	- -	- -	220 Km/h 160 Km/h
WIND LOAD (SURVIVAL): FRONT THRUST SIDE THRUST	- -	- -	- -	58.3 kg 3.9 kg

SIZE A	MTI WIRELESS EDGE	DWG NO RD41262600C	REV A
SCALE NONE		SHEET 4 OF 3	