

RF Exposure / SAR Statement

No. : 30CE0195-SH-02-A

Applicant : BRIDGESTONE CORPORATION
Type of Equipment : TPMS(Tire Pressure Monitoring System)
Model No. : E612
FCC ID : SBDE612

BRIDGESTONE CORPORATION declares that Model : TPMS(Tire Pressure Monitoring System) complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "E612(ECU)" has 19.14 mW of conducted Peak Output power and 19.14 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "E612(ECU)" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 19.14 mW (Maximum peak output power)
G = 1.00 Numerical Antenna gain; equal 0.00 dBi
r = 20.0 cm

For: E612(ECU)

S = 0.00381 mW/cm²

**UL Japan, Inc.
Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400
Facsimile: +81 463 50 6401