



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>



Dates of Tests: August 09 ~ 16, 2007
 Test Report S/N: LR500190709E
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

SWBVK160

APPLICANT

VK Corporation

Classification	:	Licensed Portable Transmitter Held to Ear (PCE)
Manufacturing Description	:	Quad-Band GPRS Terminal Equipment with Bluetooth
Manufacturer	:	VK Corporation
Model name	:	VK160
Test Device Serial No.:	:	Identification
FCC Rule Part(s)	:	§24(E), §22(H), §2
TX Frequency Range	:	824.2 ~ 848.8 MHz (GSM850) / 1850.2 ~ 1909.8 MHz (PCS1900)
RX Frequency Range	:	869.2 ~ 893.8 MHz (GSM850) / 1930.2 ~ 1989.8 MHz (PCS1900)
Max. RF Output Power	:	1.13 W ERP GSM850 (30.54dBm) 0.78 W EIRP PCS1900 (28.94dBm)
Max. SAR Measurement	:	0.273W/kg GSM850 Head SAR / 0.302W/kg GSM850 Body SAR 0.343W/kg PCS1900 Head SAR / 0.439W/kg PCS1900 Body SAR
Emission Designators:	:	255KGXW (GSM850) / 250KGXW (PCS1900)
Data of issue	:	August 27, 2007

This test report is issued under the authority of:

Dong-Min JUNG, Technical Manager

The test was supervised by:

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.

NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION'S -----	3
2. INFORMATION'S ABOUT TEST ITEM -----	4
3. TEST REPORT	
3.1 SUMMARY OF TESTS -----	5
3.2 DESCRIPTION OF TESTS -----	6
3.2.1 EQUIVALENT ISOTROPIC RADIATED POWER -----	6
3.2.2 FIELD STRENGTH OF SPURIOUS RADIATION -----	6
3.2.3 OCCUPIED BANDWIDTH -----	7
3.2.4 SPURIOUS EMISSION AT ANTENNA TERMINAL -----	7
3.2.5 OCCUPIED BANDWIDTH EMISSION LIMITS -----	7
3.2.6 FREQUENCY STABILITY -----	8
3.3 TEST DATA -----	9
3.3.1 EFFECTIVE RADIATED POWER OUTPUT -----	9
3.3.2 FIELD STRENGTH OF SPURIOUS RADIATION -----	13
3.3.3 FREQUENCY STABILITY -----	19
3.4 CNNCLUSION -----	21
3.5 TEST PLOTS -----	22
APPENDIX	
APPENDIX 1 TEST EQUIPMENT USED FOR TESTS -----	35
APPENDIX 2 LABEL AND USER'S MANUAL INFORMATION -----	37

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2007-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2009-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2008-03-28	FCC filing
VCCI	JAPAN	R2133, C2307	2008-06-22	VCCI registration
IC	CANADA	IC5799	2008-04-23	IC filing

2. Information's about test item

2-1 Client & Manufacturer

Company name : VK Corporation
 Address : VK B/D, 548-6, Anyang 8dong, Manan-gu, Anyang City, Kyonggi-Do
 Korea 430-716
 Tel / Fax : +82-31-470-8531 / +82-31-470-8902

2-2 Equipment Under Test (EUT)

Classification : Quad-Band GPRS Terminal Equipment with Bluetooth
 Trade name : SBWVK160
 Model name : VK160
 Serial number : Identification
 Date of receipt : August 03, 2007
 EUT condition : Pre-production, not damaged
 Antenna type / Gain : Intenna / Max. 0.35dBi(GSM850) / Max. 0.74dBi(PCS1900)
 Tx Frequency Range : 824.2 ~ 848.8 MHz (GSM850) / 1850.2 ~ 1909.8 MHz (PCS1900)
 Rx Frequency Range : 869.2 ~ 893.8 MHz (GSM850) / 1930.2 ~ 1989.8 MHz (PCS1900)
 RF output power Range : 1.13 W ERP GSM850 (30.54dBm)
 0.78 W EIRP PCS1900 (28.94dBm)
 Max. SAR Measurement : 0.273W/kg GSM850 Head SAR / 0.302W/kg GSM850 Body SAR
 0.343W/kg PCS1900 Head SAR / 0.439W/kg PCS1900 Body SAR
 Frequency Tolerance : $\pm 0.00025\%$ (2.5ppm)
 Modulation(s) : GMSK
 Emission Designators : 255KGXW(GSM850) / 250KGXW(PCS1900)
 Power Source : 3.7V (Polymer Lithium-Ion Battery)

2-3 Tested frequency

	GSM 850		PCS 1900	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)
LOW	128	824.2	512	1850.2
MID	190	836.6	661	1880.0
HIGH	251	848.8	810	1909.8

3. Test Report

3.1 Summary of tests

Parameter	Status
Transmitter Requirements	
Output Power	C
Occupied Bandwidth	C
Field Strength of Spurious Radiation	C
Spurious Radiation at Antenna Terminal	C
Frequency Stability	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Emission Designator: - GSM850

EMISSION Designator = 255KGXW

GSM BW = 255KHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

Emission Designator: - PCS1900

EMISSION Designator = 250KGXW

GSM BW = 250KHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

3.2 DESCRIPTION OF TESTS

3.2.1 Effective Radiated Power Output

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For GSM signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

3.2.2 Radiation Spurious and Harmonic Emissions

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used. With RBW=VBW=1MHz. The value that we could measure was only reported. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

3.2.3 Occupied Bandwidth

The 99% power bandwidth was measured with a calibrated spectrum analyzer.

3.2.4 Spurious Emission at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz.

3.2.5 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

3.2.6 Frequency Stability/Temperature Variation

The frequency stability of the transmitter is measured by:

- a) **Temperature** :The temperature is varied from -30°C to + 60°C using an environmental chamber.
- b) **Primary Supply Voltage** :The primary supply voltage is varied from 85% to 115% of the voltage Normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification –The minimum frequency stability shall be +/- 0.00025% at any time during normal operation.

Specification — The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 ($\pm 2.5\text{ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27 °C to provide a reference)
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight ”soak” at -30°C(usually 14-16 hours),the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency to the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements is made at 10°C interval up to room temperature. At least a period of one and one half hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency were made at 10intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

Note: The EUT is tested down to the battery endpoint.

3.3 DESCRIPTION OF TESTS

3.3.1 Output Power

Measurement Procedure:

- During the process of testing, the EUT was controlled via Radio Communication tester to ensure max. Power transmission and proper modulation.
- Power output was measured at the RF output terminals when the transmitter is adjusted in accordance with Communication tester (or the tune-up procedure).

Measurement Data:


GSM850

Channel	Frequency (MHz)	TEST CONDITIONS	Power Step: 5
		(dBm)	
128	824.2		31.75
190	836.6		31.63
251	848.8		31.39


PCS1900

Channel	Frequency (MHz)	TEST CONDITIONS	Power Step: 0
		(dBm)	
512	1850.2		29.95
661	1880.0		30.14
810	1909.8		30.53


POWER OUT. GSM850 Ch.128




POWER OUT. GSM850 Ch.190




POWER OUT. GSM850 Ch.251




POWER OUT. PCS1900 Ch.512



POWER OUT. PCS1900 Ch.661



POWER OUT. PCS1900 Ch.810



Effective Radiated Power Output (GSM850)**Measurement Data:****GSM850**

Channel	Frequency (MHz)	TEST CONDITIONS			Power Step: 5	
		Ref. level (dBm)	Pol. (H/V)	ERP (dBm)	ERP (W)	Battery
128	824.2	-9.83	V	30.41	1.10	Standard
190	836.6	-9.62	V	30.54	1.13	Standard
251	848.8	-9.17	V	30.32	1.08	Standard

Note 1: Radiated measurements at 3 meters by Substitution Method.

Equivalent Isotropic Radiated Power (PCS1900)**Measurement Data:****PCS1900**

Channel	Frequency (MHz)	TEST CONDITIONS			Power Step: 0	
		Ref. level (dBm)	Pol. (H/V)	EIRP (dBm)	EIRP (W)	Battery
512	1850.2	-12.15	V	28.09	0.64	Standard
661	1880.0	-11.88	V	28.94	0.78	Standard
810	1909.8	-11.91	V	28.54	0.71	Standard

Note 2: Radiated measurements at 3 meters by Substitution Method.

3.3.2 Field Strength of spurious Radiation

OPERATING FREQUENCY : 824.2 MHz
 CHANNEL : 128(Low)
 MEASURED OUTPUT POWER : 30.54 dBm = 1.13 W
 MODULATION : GSM(Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W)$ = 43.54 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.2 Field Strength of spurious Radiation**--- Continue**

OPERATING FREQUENCY : 836.6 MHz

CHANNEL : 190(Mid)

MEASURED OUTPUT POWER : 30.54 dBm = 1.13 W

MODULATION : GSM(Internal)

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W) = 43.54$ dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.2 Field Strength of spurious Radiation**--- Continue**

OPERATING FREQUENCY : 848.8 MHz

CHANNEL : 251(High)

MEASURED OUTPUT POWER : 30.54 dBm = 1.13 W

MODULATION : GSM(Internal)

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W)$ = 43.54 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.2 Field Strength of spurious Radiation**--- Continue**

OPERATING FREQUENCY : 1850.2 MHz

CHANNEL : 512(Low)

MEASURED OUTPUT POWER : 28.94 dBm = 0.78 W

MODULATION : GSM(Internal)

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W)$ = 41.94 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.2 Field Strength of spurious Radiation**--- Continue**

OPERATING FREQUENCY : 1880.0 MHz

CHANNEL : 661(Mid)

MEASURED OUTPUT POWER : 28.94 dBm = 0.78 W

MODULATION : GSM(Internal)

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W)$ = 41.94 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.2 Field Strength of spurious Radiation**--- Continue**

OPERATING FREQUENCY : 1909.8 MHz

CHANNEL : 810(High)

MEASURED OUTPUT POWER : 28.94 dBm = 0.78 W

MODULATION : GSM(Internal)

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W)$ = 41.94 dBc

Freq. (MHz)	LEVEL@ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
-	-	-	-	-	-
No emissions were detected are a level greater than 20dB below limit.					
-	-	-	-	-	-


Note1: Radiated measurements at 3 meters by Substitution Method.

--- Blank ---

3.3.3 Frequency Stability

OPERATING FREQUENCY : 836,599,972 Hz
 CHANNEL : 190(Mid)
 REFERENCE VOLTAGE : 3.7 VDC
 DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (dB)	FREQ (Hz)	Deviation (%)
100%	3.7	+20(Ref)	836,599,972	0.000000
100%		-30	836,600,090	-0.000014
100%		-20	836,600,067	-0.000011
100%		-10	836,600,029	-0.000007
100%		0	836,599,984	-0.000001
100%		+10	836,600,005	-0.000004
100%		+20	836,599,972	0.000000
100%		+25	836,599,937	0.000004
100%		+30	836,599,951	0.000003
100%		+40	836,599,899	0.000009
100%		+50	836,599,880	0.000011
100%		+60	836,599,891	0.000010
85%	3.2	+20	836,599,939	0.000004
115%	4.3	+20	836,599,953	0.000002
BATT.ENDPOINT	2.97	+20	836,599,990	-0.000002




3.3.3 Frequency Stability

- Continues

OPERATING FREQUENCY : 1,879,999,982 Hz
 CHANNEL : 0661(Mid)
 REFERENCE VOLTAGE : 3.7 VDC
 DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VAC)	TEMP (dB)	FREQ (Hz)	Deviation (%)
100%	3.7	+20(Ref)	1,879,999,982	0.000000
100%		-30	1,879,999,831	-0.000008
100%		-20	1,879,999,838	-0.000008
100%		-10	1,879,999,919	-0.000003
100%		0	1,879,999,849	-0.000007
100%		+10	1,879,999,940	-0.000002
100%		+20	1,879,999,982	0.000000
100%		+25	1,879,999,982	0.000000
100%		+30	1,880,000,048	0.000004
100%		+40	1,880,000,088	0.000006
100%		+50	1,880,000,131	0.000008
100%		+60	1,880,000,174	0.000010
85%	3.2	+20	1,879,999,960	-0.000001
115%	4.3	+20	1,879,999,960	-0.000001
BATT.ENDPOINT	2.97	+20	1,879,999,967	-0.000001



3.4 CONCLUSION


The data collected shows that the **VK Corp. Quad-Band GPRS Terminal with Bluetooth Equipment FCC ID: SBWVK160** complies with all the requirements of Parts 2, 22, 24 of the FCC Rules.

--- Blank ---


3.5 TEST PLOTS

--- Blank ---


GSM850 99 % Bandwidth Ch. 128



GSM850 99 % Bandwidth Ch. 190




GSM850 99 % Bandwidth Ch. 251




PCS1900

99 % Bandwidth Ch. 512




PCS1900

99 % Bandwidth Ch. 661




PCS1900

99 % Bandwidth Ch. 810




GSM850

-26dBc Bandwidth Ch. 128




GSM850

-26dBc Bandwidth Ch. 190




GSM850


-26dBc Bandwidth Ch. 251




PCS1900

-26dBc Bandwidth Ch. 512

PCS1900


-26dBc Bandwidth Ch. 661

PCS1900

-26dBc Bandwidth Ch. 810


GSM850

Band Edge Ch. 128




GSM850

Band Edge Ch. 251




PCS1900

Band Edge Ch. 512



PCS1900


Band Edge Ch. 810



GSM850

Spurious Emissions at Antenna Terminal / Ch.128 -1


ATTEN 40dB MKR -36.00dBm
RL 35.00dBm 10dB/ 1.874GHz



GSM850

Spurious Emissions at Antenna Terminal / Ch.128 -2


ATTEN 40dB MKR -35, 83dBm
RL 35.0dBm 10dB/ 7.875GHz



GSM850

Spurious Emissions at Antenna Terminal / Ch.190 -1


ATTEN 40dB MKR -35.67dBm
RL 35.0dBm 10dB/ 1.677GHz



GSM850

Spurious Emissions at Antenna Terminal / Ch.190 -2


ATTEN 40dB MKR -35, 83dBm
RL 35.0dBm 10dB/ 7.775GHz



GSM850

Spurious Emissions at Antenna Terminal / Ch.251 -1


ATTEN 40dB MKR -34.17dBm
RL 35.0dBm 10dB/ 1.701GHz



GSM850


Spurious Emissions at Antenna Terminal / Ch.251-2

ATTEN 40dB MKR -36, 33dBm
RL 35.0dBm 10dB/ 7.425GHz




PCS1900

Spurious Emissions at Antenna Terminal / Ch.512 -1




PCS1900

Spurious Emissions at Antenna Terminal / Ch.512 -2




PCS1900

Spurious Emissions at Antenna Terminal / Ch.661 -1




PCS1900

Spurious Emissions at Antenna Terminal / Ch.661 -2




PCS1900

Spurious Emissions at Antenna Terminal / Ch.810 -1



PCS1900

Spurious Emissions at Antenna Terminal / Ch.810 -2



APPENDIX 1

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Apr-08
2	Signal Generator	8648C	3623A02597	HP	Apr-08
3	Attenuator (3dB)	8491A	37822	HP	Nov-07
4	Attenuator (10dB)	8491A	63196	HP	Nov-07
5	EMI Test Receiver	ESVD	843748/001	R&S	Jan-08
6	LISN	KNW-407	8-1430-1	Kyoritsu	Jan-08
7	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Jan-08
8	RF Amplifier	8447D	2949A02670	HP	Jan-08
9	RF Amplifier	8447D	2439A09058	HP	Jan-08
10	RF Amplifier	8449B	3008A02126	HP	Apr-09
11	Test Receiver	ESHS10	828404009	R&S	Jan-08
12	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Jul-08
13	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-09
14	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-09
15	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-09
16	Dipole Antenna	VHA9103	2116	Schwarzbeck	Nov-07
17	Dipole Antenna	VHA9103	2117	Schwarzbeck	Nov-07
18	Dipole Antenna	UHA9105	2261	Schwarzbeck	Nov-07
19	Dipole Antenna	UHA9105	2262	Schwarzbeck	Nov-07
20	Spectrum Analyzer	8591E	3649A05888	HP	Jan-08
21	Spectrum Analyzer	8563E	3425A02505	HP	Apr-08
22	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Feb-08
23	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	Jun-08
24	RF Switch	MP59B	6200414971	ANRITSU	Jun-08
25	RF Switch	MP59B	6200438565	ANRITSU	Jun-08
26	Power Divider	11636A	6243	HP	Nov-07
27	DC Power Supply	6622A	3448A03079	HP	Oct-07
28	Attenuator (30dB)	11636A	6243	HP	Nov-07
29	Frequency Counter	5342A	2826A12411	HP	Apr-08
30	Power Meter	EPM-441A	GB32481702	HP	Apr-08
31	Power Sensor	8481A	2702A64048	HP	Apr-08
32	Audio Analyzer	8903B	3729A18901	HP	Nov-07
33	Modulation Analyzer	8901B	3749A05878	HP	Nov-07
34	TEMP & HUMIDITY Chamber	YJ-500	L05022	JinYoung Tech	Oct-07
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-09

APPENDIX 2

Label and User's Manual Information

Certification Labeling Requirements

§ 15.19 Labeling requirements.

(a) In addition to the requirements in part 2 of this chapter, a device subject to **certification, or verification** shall be labeled as follows:

(1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under part 73 of this chapter, land mobile operation under part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

(2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with part 15 of the FCC Rules for use with cable television service.

(3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

(4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

(5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

User's Manual Information

§ 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B - Unintentional Radiators:

§ 15.105 Information to the user.

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.