



683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080
 Tel: +82-31-321-2664 Fax: +82-31-321-1664
<http://www.digitalemc.com>

**CERTIFICATE OF COMPLIANCE
 FCC Part 22, 24 Certification**

Dates of Tests: June. 1 ~ 4, 2005
 Test Report S/N: DR50110506B
 Test Site: DIGITAL EMC CO., LTD.

Model No.

SBWVK650C

APPLICANT

VK Corporation

| | | |
|------------------------------|----------|---|
| Classification | : | Licensed Portable Transmitter Held to Ear (PCE) |
| FCC Rule Part(s) | : | §22(H), §24(E), §2 |
| EUT Type | : | Dual-Band CDMA Phone |
| Model name | : | VK650C |
| Serial number | : | Identical prototype |
| TX Frequency Range | : | 824.70 ~848.31 MHz (CDMA) 1851.25 ~ 1908.75 MHz (PCS) |
| RX Frequency Range | : | 869.70 ~893.31 MHz (CDMA) 1931.25 ~ 1988.75 MHz (PCS) |
| Max. RF Output Power | : | 0.256W ERP CDMA (24.08dBm) 0.239W EIRP PCS (23.78dBm) |
| Max. SAR Measurement | : | 0.594W/kg CDMA Head SAR 0.585W/kg PCS Head SAR |
| Max. SAR Measurement | : | 0.919W/kg CDMA Body SAR 0.676W/kg PCS Body SAR |
| Emission Designators: | : | 1M25F9W |
| Date of Issue | : | JUNE 10, 2005 |

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



NVLAP LAB CODE 200559-0

TABLE OF CONTENTS

| | |
|---|--------------------------------------|
| ATTACHMENT | A: COVER LETTER(S) |
| ATTACHMENT | B: ATTESTATION STATEMENT(S) |
| ATTACHMENT | C: TEST REPORT |
| 1.1 SCOPE | 3 |
| 2.1 INTRODUCTION | 4 |
| 3.1 INSERTS | 5 |
| 4.1 DESCRIPTION OF TESTS | 6-9 |
| 5.1 EFFECTIVE RADIATED POWER OUTPUT | 10 |
| 6.1 EQUIVALENT ISOTROPIC RADIATED POWER | 11 |
| 7.1 RADIATED MEASUREMENTS | 12-17 |
| 8.1 FREQUENCY STABILITY | 18-19 |
| 9.1 PLOTS OF EMISSIONS | 20 |
| 10.1 LIST OF TEST EQUIPMENT | 21-22 |
| 11.1 SAMPLE CALCULATIONS | 23 |
| 12.1 CONCLUSION | 24 |
| ATTACHMENT | D: TEST PLOTS |
| ATTACHMENT | E: FCC ID LABEL & LOCATION |
| ATTACHMENT | F: TEST SETUP PHOTOGRAPHS |
| ATTACHMENT | G: EXTERNAL PHOTOGRAPHS |
| ATTACHMENT | H: INTERNAL PHOTOGRAPHS |
| ATTACHMENT | I: BLOCK DIAGRAM(S) |
| ATTACHMENT | J: SCHEMATIC DIAGRAM(S) |
| ATTACHMENT | K: OPERATIONAL / CIRCUIT DESCRIPTION |
| ATTACHMENT | L: PARTS LIST/TUNE UP PROCEDURE |
| ATTACHMENT | M: USER'S MANUAL |
| ATTACHMENT | N: SAR MEASUREMENTS REPORT |
| ATTACHMENT | O: SAR TEST PLOTS |
| ATTACHMENT | P: SAR TEST SETUP PHOTOGRAPHS |
| ATTACHMENT | Q: DIPOLE VALIDATION (S) |
| ATTACHMENT | R: PROBE CALIBRATION |

MEASUREMENT REPORT

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant: VK Corporation

Address: VK B/D, 548-6, Anyang 8dong, Manan-gu, Anyang City, Kyonggi do, 430-716, Korea

Attention: Seung-Bok Won (Manager)

- FCC ID: SBWVK650C
- Quantity: Identical Prototype
- Tx Freq. Range: 824.70 ~848.31 MHz (CDMA)
1851.25 ~ 1908.75 MHz (PCS CDMA)
- Rx Freq. Range: 869.70 - 893.31 MHz (CDMA)
1931.25 ~ 1988.75 MHz (PCS CDMA)
- Max. Power Rating: 0.256W ERP CDMA (24.08dBm)
0.239W EIRP PCS (23.78dBm)
- FCC Classification(s): Licensed Portable Transmitter Held to Ear (PCE)
- Equipment (EUT) Type: Dual-Band CDMA Phone
- Modulation(s): CDMA
- Frequency Tolerance: $\pm 0.00025\%$ (2.5ppm)
- FCC Rule Part(s): §22(H), §24(E), §2
- Dates of Tests: June 1 ~ 4, 2005
- Place of Tests: DIGITAL EMC
- Test Report S/N: DR50110506B

2.1. General information

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

<http://www.digitalemc.com> E-mail : demc@unitel.co.kr

Tel: +82-31-321-2664 Fax: +82-31-321-1664

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the
“General requirements for the competent of calibration and testing laboratory”.

This laboratory is accredited by NVLAP. NVLAP Lab. Code is 200559-0.

Test operator: engineer



June 10, 2005

Won-Jung Lee

Data

Name

Signature

Report Reviewed By: manager



June 10, 2005

Harvey Sung

Data

Name

Signature

Ordering party:

| | | |
|---------------|---|---|
| Company name | : | VK Corporation |
| Address | : | 6F, Vk B/D, 548-6, Anyang 8dong, Manan-gu |
| Zipcode | : | 430-716 |
| City/town | : | Anyang City, Kyonggi do |
| Country | : | KOREA |
| Date of order | : | May 25, 2005 |

3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting

Modulation, and Harmonic Supresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.

4.1 DESCRIPTION OF TESTS

4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100-5000Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequency, the audio signal generator is varied from 100 to 50kHz.

4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

4.4 Modulation Limiting

The audio signal generator is connected to the audio put circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies(300Hz, 1000Hz and 3000Hz), and the input voltage is varied form 30% modulation ($\pm 3.6\text{kHz}$ deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein . Measurements were performed for ST, SAT and wide-band data modulations. The corresponding results are shown herein.

Note: ST, SAT and wide-band data were internally generated by the EUT.




Fig.3. Transmitter Audio Frequency & Tone Test Setup.

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.5 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (c) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

4.6 Occupied Bandwidth

The 99% power bandwidth was measured with a calibrated spectrum analyzer.

4.7 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10th Harmonics.

4.8 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.9 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range.

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.10 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a) **Temperature** :The temperature is varied from -30°C to + 60°C using an environmental chamber.
- b) **Primary Supply Voltage** :The primary supply voltage is varied from 85% to 115% of the voltage Normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification –The minimum frequency stability shall be +/- 0.00025% at any time during normal operation.

Specification — The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 ($\pm 2.5\text{ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27 °C to provide a reference)
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight ”soak” at -30°C(usually 14-16 hours),the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency to the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements is made at 10°C interval up to room temperature. At least a period of one and one half hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency were made at 10intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.11 Radiated Emission

Final test was performed according to ANSI C63.4-2003 at the open field test site. There are no deviations from the standard.

The EUT was placed in a 0.8m high table along with the peripherals. The turn table was separated from the antenna distance 3meters. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum.

The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. Reported are maximized emission levels.

These tests were performed at 120kHz of 6dB bandwidth.

4.12 Conducted Emission

The power line conducted interference measurements were performed according to ANSI C63.4-2003 in a shielded enclosure with peripherals placed on a table, 0.8m high over a metal floor. It was located more than required distance away from the shielded enclosure wall. There are no deviations from the standard.

The EUT was plugged into the LISN and the frequency range of interest scanned.

Reported are maximized emission levels.

These tests were performed at 9kHz of 6dB bandwidth.

5.1 TEST DATA

5.2 Effective Radiated Power Output

A. POWER: High (CDMA Mode/ Swing Down)

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | Supplied Power |
|----------------------|------------------------|--------------|--------------|--------------|-------------------|
| 824.70 | -15.50 | H | 0.146 | 21.64 | Standard |
| 836.52 | -16.67 | H | 0.129 | 21.09 | Standard |
| 848.31 | -14.00 | H | 0.256 | 24.08 | Standard |

Note: Standard battery is options for this phone.

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

6.1 TEST DATA

6.2 Equivalent Isotropic Radiated Power (E.I.R.P)

A. POWER: High (PCS Mode / Swing Up)

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | EIRP (W) | EIRP (dBm) | Supplied Power |
|----------------------|------------------------|--------------|--------------|---------------|-------------------|
| 1851.25 | -14.67 | H | 0.239 | 23.78 | Standard |
| 1880.00 | -14.83 | H | 0.222 | 23.46 | Standard |
| 1908.75 | -15.00 | H | 0.227 | 23.56 | Standard |

Note: Standard battery is options for this phone.

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

7.1 TEST DATA

7.2 CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 824.7 MHz
 CHANNEL : 1013(Low)
 MEASURED OUTPUT POWER : 21.64 dBm = 0.146 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) = 34.64$ dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 1649.4 | -39.99 | 8.2 | -31.79 | H | 53.43 |
| 2474.1 | -45.75 | 9.4 | -36.35 | H | 57.99 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 TEST DATA (CONTINUED)**7.3 CDMA Radiated Measurements**Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 836.52 MHz
 CHANNEL : 0384(Mid)
 MEASURED OUTPUT POWER : 21.09 dBm = 0.129 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) = 34.10$ dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 1673.04 | -38.51 | 8.2 | -30.31 | H | 52.40 |
| 2509.56 | -45.25 | 9.4 | -35.85 | H | 56.94 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 TEST DATA (CONTINUED)**7.4 CDMA Radiated Measurements**Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 848.31 MHz
 CHANNEL : 0777(High)
 MEASURED OUTPUT POWER : 24.08 dBm = 0.256 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 37.08 dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 1696.62 | -38.51 | 8.2 | -30.31 | H | 54.39 |
| 2544.93 | -45.25 | 9.4 | -35.85 | H | 59.93 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 TEST DATA**(CONTINUED)****7.5 PCS Radiated Measurements**Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1851.25 MHz
 CHANNEL : 0025(Low)
 MEASURED OUTPUT POWER : 23.78 dBm = 0.239 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) = 36.78$ dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 3702.50 | -42.47 | 9.3 | -33.17 | H | 56.95 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 TEST DATA (CONTINUED)**7.6 PCS Radiated Measurements**Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1880.00 MHz
 CHANNEL : 0600(Mid)
 MEASURED OUTPUT POWER : 23.46 dBm = 0.222 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) = 36.46$ dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 3760.00 | -40.54 | 9.3 | -31.24 | V | 54.70 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 TEST DATA (CONTINUED)**7.7 PCS Radiated Measurements**Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY : 1908.75 MHz
 CHANNEL : 1175(High)
 MEASURED OUTPUT POWER : 23.56 dBm = 0.227 W
 MODULATION SIGNAL : CDMA (Internal)
 DISTANCE : 3 meters
 LIMIT : $43 + 10 \log_{10} (W) =$ 36.56 dBc

| Freq. (MHz) | LEVEL@ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|---|--|--|--------------|-------|
| 3817.50 | -39.57 | 9.3 | -30.27 | V | 53.83 |
| - | - | - | - | - | - |
| - | - | - | - | - | - |
| - | - | - | - | - | - |

NOTE

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:


The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

8.1 TEST DATA

8.2 Frequency Stability (CDMA)

OPERATING FREQUENCY : 836,520,006 Hz
 CHANNEL : 0384(Mid)
 REFERENCE VOLTAGE : 3.7 VDC
 DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm


| VOLTAGE (%) | POWER (VDC) | TEMP (dB) | FREQ (Hz) | Deviation (%) |
|----------------|----------------|--------------|--------------|------------------|
| 100% | 3.7 | +20(Ref) | 836520006 | 0.000000 |
| 100% | | -30 | 836519984 | -0.000003 |
| 100% | | -20 | 836519997 | -0.000001 |
| 100% | | -10 | 836519993 | -0.000002 |
| 100% | | 0 | 836520019 | 0.000002 |
| 100% | | +10 | 836520008 | 0.000000 |
| 100% | | +20 | 836520006 | 0.000000 |
| 100% | | +25 | 836519992 | -0.000002 |
| 100% | | +30 | 836520006 | 0.000000 |
| 100% | | +40 | 836519988 | -0.000002 |
| 100% | | +50 | 836519976 | -0.000004 |
| 100% | | +60 | 836519969 | -0.000004 |
| 85% | 3.3 | +20 | 836519963 | -0.000005 |
| 115% | 4.2 | +20 | 836519994 | -0.000001 |
| BATT.ENDPOINT | 3.3 | +20 | 836519963 | -0.000005 |



8.1 TEST DATA (CONTINUED)**8.3 Frequency Stability (PCS)**

OPERATING FREQUENCY : 1879.999,984 Hz
 CHANNEL : 0600(Mid)
 REFERENCE VOLTAGE : 3.7 VDC
 DEVIATION LIMIT : ± 0.00025 % or 2.5 ppm

| VOLTAGE (%) | POWER (VDC) | TEMP (dB) | FREQ (Hz) | Deviation (%) |
|---------------|-------------|-----------|------------|---------------|
| 100% | 3.7 | +20(Ref) | 1879999984 | 0.000000 |
| 100% | | -30 | 1879999939 | -0.000002 |
| 100% | | -20 | 1879999947 | -0.000002 |
| 100% | | -10 | 1880000065 | -0.000005 |
| 100% | | 0 | 1880000048 | 0.000004 |
| 100% | | +10 | 1880000083 | 0.000006 |
| 100% | | +20 | 1879999984 | 0.000000 |
| 100% | | +25 | 1879999890 | -0.000005 |
| 100% | | +30 | 1879999839 | -0.000007 |
| 100% | | +40 | 1879999869 | -0.000006 |
| 100% | | +50 | 1879999905 | -0.000004 |
| 100% | | +60 | 1879999826 | -0.000008 |
| 85% | 3.3 | +20 | 1880000187 | 0.000011 |
| 115% | 4.2 | +20 | 1879999859 | -0.000006 |
| BATT.ENDPOINT | 3.3 | +20 | 1880000187 | 0.000011 |



9.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT D)

10.1 TEST EQUIPMENT

| | Type | Manufacturer | Model | Cal.Due.Date (dd/mm/yy) | S/N |
|----|------------------------------|----------------------------|----------|----------------------------|---------------|
| 01 | Spectrum Analyzer | Agilent | E4404B | 19/11/05 | US41061134 |
| 02 | Spectrum Analyzer | H.P | 8563E | 25/09/05 | 3551A04634 |
| 03 | Power Meter | H.P | EPM-442A | 15/07/05 | GB37170413 |
| 04 | Power Sensor | H.P | 8481A | 15/07/05 | 3318A96332 |
| 05 | Frequency Counter | H.P | 5342A | 07/10/05 | 2119A04450 |
| 06 | Multifunction Synthesizer | H.P | 8904A | 07/10/05 | 3633A08404 |
| 07 | Signal Generator | H.P | 8673D | 26/09/05 | 2844A00753 |
| 08 | Signal Generator | H.P | E4421A | 15/07/05 | US37230529 |
| 09 | Signal Generator | R/S | SMR20 | 24/05/06 | 101251 |
| 10 | Audio Analyzer | H.P | 8903B | 21/07/05 | 3011A0944B |
| 11 | Modulation Analyzer | H.P | 8901B | 15/07/05 | 3028A03029 |
| 12 | Sensor Module | H.P | 11722A | 15/07/05 | 3111A04665 |
| 13 | Oscilloscope | LeCroy | 9314A | 10/10/05 | 93144390 |
| 14 | CDMA Mobile Station Test Set | H.P | 8924C | 07/10/05 | US35360688 |
| 15 | Power Splitter | WEINSCHEL | 1593 | 07/10/05 | 332 |
| 16 | BAND Reject Filter | Microwave circuits INC. | NO308372 | 07/10/05 | 3125-01DC0312 |
| 17 | BAND Reject Filter | Wainwright | WRG1750 | 07/10/05 | SN2 |
| 18 | AC Power supply | DAEKWANG | 5KVA | 18/04/06 | N/A |
| 19 | DC Power Supply | H.P | 6622A | 18/04/06 | 465487 |
| 20 | Attenuator (30dB) | H.P | 8498A | 07/10/05 | 50101 |
| 21 | Attenuator (10dB) | WEINSCHEL | 23-10-34 | 07/10/05 | BP4387 |
| 22 | HORN ANT | EMCO | 3115 | 06/03/07 | 6419 |
| 23 | HORN ANT | EMCO | 3115 | 01/10/05 | 21097 |
| 24 | HORN ANT | A.H.Systems | SAS-574 | 09/11/06 | 154 |
| 25 | HORN ANT | A.H.Systems | SAS-574 | 09/11/06 | 155 |
| 26 | Dipole Antenna | Schwarzbeck | VHA9103 | 29/10/05 | 2116 |

11.1 TEST EQUIPMENT**(CONTINUED)**

| | Type | Manufacturer | Model | Cal.Due.Date (dd/mm/yy) | S/N |
|----|---------------------------------|--------------|-------------|----------------------------|-------------|
| 27 | Dipole Antenna | Schwarzbeck | VHA9103 | 04/10/06 | 2117 |
| 28 | Dipole Antenna | Schwarzbeck | UHA9105 | 04/10/06 | 2261 |
| 29 | Dipole Antenna | Schwarzbeck | UHA9105 | 04/10/06 | 2262 |
| 30 | RFI/FIELD Iintensity Meter | Kyorits | KNM-504D | 07/07/05 | SN-161-4 |
| 31 | Frequency Converter | Kyorits | KCV-604C | 07/07/05 | 4-230-3 |
| 32 | TEMP & HUMIDITY Chamber | JISCO | J-RHC2 | 14/09/05 | 021031 |
| 33 | Log Periodic Antenna | Schwarzbeck | UHALP9108A1 | 29/10/05 | 1098 |
| 34 | Biconical Antenna | Schwarzbeck | VHA9103 | 29/10/05 | VHA91031946 |
| 35 | Digital Multimeter | H.P | 34401A | 18/04/06 | 3146A13475 |
| 36 | Attenuator (10dB) | WEINSCHEL | 23-10-34 | 07/10/05 | BP4386 |
| 37 | High-Pass Filter | ANRITSU | MP526 | 12/06/05 | M27756 |
| 38 | Attenuator (3dB) | Agilent | 8491B | 15/09/05 | 58177 |
| 39 | Wireless communication test set | Agilent | 8960 | 07/07/05 | GB41321167 |
| 40 | RFI/FIELD Intensity Meter | Kyorits | KNW-2402 | 16/08/05 | 4N-170-3 |

11.1 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

12.1 CONCLUSION

The data collected shows that the **VK Corporation. Dual-Band(CDMA / PCS) Phone FCC ID: SBWVK650C** complies with all the requirements of Parts 2, 22 and 24 of the FCC rules.